

Stacked and Nested If Structures

CSC 100 - Lyon College - Spring 2025

Marcus Birkenkrahe

March 14, 2025

Contents

1	Introduction	1
2	Sequential if structures	2
3	Stacked if (ladder) structures	3
3.1	Explanation	3
3.2	Example	3
3.3	Practice: Loot by Difficulty	4
4	Nested if Structures	6
4.1	Explanation	6
4.2	Example	6
4.3	Practice: Boss Fight (Bonus Assignment)	7
5	Example with stacked and nested conditional statements	8
6	What about curly brackets?	9
7	Conclusion	10

1 Introduction

- Objectives:

- Sequential if structures
- Stacked if structures
- Nested if structures

- **Theme:** Text-based adventure game—dungeon exploration and decision-making.
- **Objective:** Learn sequential, stacked and nested `if` structures for complex decisions in pseudocode and C source code.

2 Sequential if structures

- Sequential `if` structures are evaluated independently and sequentially from the top. Multiple conditions can be true, and all matching blocks will execute. The outcome of one does not affect the others.
- Simple sequential `if` statements:

```
if ( i == 1 ) {
    // do one thing
}
if ( i == 2 ) {
    // do another thing
}
```

- An illustration in BPMN:




Figure 1: Single IF statements

- Example:
 1. If you have enough gold (> 100), buy a sword.
 2. If you have too little health (< 100), drink a potion.

```
IF gold > 100
  PRINT "Buying a sword!"
```

```

END IF

IF health < 100
    PRINT "Drinking a potion!"
END IF

```

3 Stacked if (ladder) structures

3.1 Explanation

- Stacked if structures test a sequence of conditions, but only one block executes. Once a condition is true, the rest are skipped.
- Simple stacked if statements:

```

if ( i == 1 ) {
    // do one thing
}
else if ( i == 2 ) {
    // do another thing
}

```

- An illustration in BPMN:

3.2 Example

- Game Context: After defeating an enemy, the player's reward depends on their health.
- Pseudocode:

```

SET health = 60

IF health > 75 THEN
    PRINT "You're in top form! You find a golden shield."
ELSE IF health > 50 THEN
    PRINT "You're scratched but standing. You find a rusty sword."
ELSE IF health > 25 THEN
    PRINT "You're wounded but alive. You find a healing potion."
ELSE
    PRINT "You collapse but grab a small coin."
END IF

```




Figure 2: Single IF statements

- Source code: Run this in onecompiler.com/c/43bteavtn

```

int health = 10; // SET health = 60

if (health > 75) // IF health > 75 THEN
    puts("You're in top form! You find a golden shield.");
else if (health > 50) // ELSE IF health > 50 THEN
    puts("You're scratched but standing. You find a rusty sword.");
else if (health > 25) // ELSE IF health > 25 THEN
    puts("You're wounded but alive. You find a healing potion.");
else
    puts("You collapse but grab a small coin.");
  
```

You collapse but grab a small coin.

3.3 Practice: Loot by Difficulty

- **Task:** Write pseudocode for loot based on enemy difficulty (1-10). Use a stacked if structure.

- **Starter Code:**

```
SET enemy_difficulty = 6
PRINT "You defeat a monster!"

// Add stacked if structure here
```

- **Guidance:**

- enemy_difficulty 8-10: print "You find a gold coin"
- enemy_difficulty 5-7: print "You find an iron ring"
- enemy_difficulty 1-4: print "You find a stick"
- enemy_difficulty not a number > 0: print "Something went wrong - nothing found."

- **Example Output:** "You defeat a monster! You find an iron ring!"

- **Time:** 10 minutes to write and test.

- **Sample solution:** <https://onecompiler.com/c/43bsst2mg>

```
SET enemy_difficulty = 6
PRINT "You defeat a monster!"

IF enemy_difficulty >= 8
    PRINT "You find a gold coin!"
ELSE IF enemy_difficulty >= 5
    PRINT "You find an iron ring!"
ELSE IF enemy_difficulty >= 1
    PRINT "You find a stick!"
ELSE
    PRINT "Something went wrong - nothing found."
END IF
```

- **Sample source code:**

onecompiler.com/c/43brbdw4f

```

int enemy_difficulty = 6; // SET enemy_difficulty = 6
printf("You defeat a monster! "); // PRINT "You defeat a monster!"

if (enemy_difficulty >= 8) // 8-10: "gold coin"
    printf("You find a gold coin!");
else if (enemy_difficulty >= 5) // 5-7: "iron ring"
    printf("You find an iron ring!");
else if (enemy_difficulty >= 1) // 1-4: "stick"
    printf("You find a stick!");
else
    puts("Something went wrong - nothing found.");

You defeat a monster! You find an iron ring!

```

4 Nested if Structures

4.1 Explanation

- Nested if structures place one or more if statements inside another if statement, creating layered conditions. The inner if is only evaluated if the outer condition is true, allowing for decisions that depend on multiple criteria.

4.2 Example

- Game Context: Opening a vault requires a key AND enough strength.
- Example:

```

SET has_key = true
SET strength = 40

IF has_key THEN
    IF strength >= 50 THEN
        PRINT "You unlock and open the vault!"
    ELSE
        PRINT "You unlock it but can't open it."
    END IF
ELSE
    PRINT "You need a key."
END IF

```

- Key Point: Inner condition (`strength`) depends on outer condition (`has_key`) being true.
- Source code: onecompiler.com/c/43brdaaj4

```
int has_key = 1; // SET has_key = true
int strength = 40; // SET strength = 40

if (has_key) { // IF has_key THEN
    if (strength >= 50) // IF strength >= 50 THEN
        puts("You unlock and open the vault!");
    else
        puts("You unlock it but can't open it.");
} else {
    puts("You need a key.");
}
```

You unlock it but can't open it.

4.3 Practice: Boss Fight (Bonus Assignment)

- **Task:** Write pseudocode for a boss fight. Success requires a sword AND high skill. Use a nested if structure. Write C source code and test it.
- **Starter Code:**

```
SET has_sword = true
SET skill = 70
PRINT "You face the boss!"

// Add nested if structure here
```

- **Guidance:**

- Sword + skill 80: "You win!"
- Else: "You lose."

- **Example Output:** "You face the boss! You lose!"

5 Example with stacked and nested conditional statements

- Game Context: After defeating an enemy, the player's reward depends on their health. This includes both stacked and nested statements.
- Pseudocode:

```
SET health = 60
SET enemy_defeated = true

IF enemy_defeated THEN
    IF health > 75 THEN
        PRINT "You're in top form! You find a golden shield."
    ELSE IF health > 50 THEN
        PRINT "You're scratched but standing. You find a rusty sword."
    ELSE IF health > 25 THEN
        PRINT "You're wounded but alive. You find a healing potion."
    ELSE
        PRINT "You collapse but grab a small coin."
    END IF
ELSE
    PRINT "You flee with nothing."
END IF
```

- Source code: Run this in onecompiler.com/c/43br7x7b4

```
int health = 10; // SET health = 60
int enemy_defeated = 1; // SET enemy_defeated = 1 (true))

if (enemy_defeated) { // IF enemy_defeated THEN
    if (health > 75) // IF health > 75 THEN
        puts("You're in top form! You find a golden shield.");
    else if (health > 50) // ELSE IF health > 50 THEN
        puts("You're scratched but standing. You find a rusty sword.");
    else if (health > 25) // ELSE IF health > 25 THEN
        puts("You're wounded but alive. You find a healing potion.");
    else
        puts("You collapse but grab a small coin.");
} else {
```



```
puts("You flee with nothing.");  
}
```

You collapse but grab a small coin.

6 What about curly brackets?

- When should you use curly brackets after the `if`, `else`, and `else if` statements?

Curly brackets define a **block of code** that belongs to that `if`, `else if` or `else` condition. You should always use them because they make debugging (and writing code) vastly easier!

They are **mandatory** when the block contains more than one statement.

They are **optional** when the block contains only one statement.

- Code example:

```
int health = 10;  
  
if (health > 75) {  
    puts("You're in top form! You find a golden shield.");  
} else if (health > 50) {  
    puts("You're scratched but standing. You find a rusty sword.");  
} else if (health > 25) {  
    puts("You're wounded but alive. You find a healing potion.");  
} else {  
    puts("You collapse but grab a small coin.");  
}
```

You collapse but grab a small coin.

You collapse but grab a small coin.

7 Conclusion

- **Summary:**

- **Sequential:** Independent checks that can all execute if true (e.g., buy a sword AND drink a potion based on gold and health).
 - **Stacked:** Mutually exclusive choices in a sequence (e.g., one reward based on health after a battle).
 - **Nested:** Layered conditions where inner checks depend on outer ones (e.g., needing a key AND strength to open a vault).
- **Next:** Switch control statement, and loops for repeated actions in the game (e.g., fighting multiple enemies).