

What is wrong with this code?

```
struct Point {                                     // 1
    int x;
    int y;
}
```

```
int main(void) {
    struct Point p = {3, 4};
    return 0;
}
```

```
struct Point {                                     // 2
    int x;
    int y;
};
```

```
int main(void) {
    Point p = {3, 4};
    printf("(%d,%d)\n", p.x, p.y);
    return 0;
}
```

```
struct Point {                                     // 3
    int x;
    int y;
};
```

```
int main(void) {
    struct Point p = {3, 4};
    printf("(%d,%d)\n", p->x, p->y);
    return 0;
}
```

```
struct Point {                                     // 4
    float x;
    float y;
};
```

```
void move_point(struct Point p, float dx, float dy) {
    p.x += dx;
    p.y += dy;
}
```

```
struct Point {                                     // 5
    float x;
    float y;
};
```

```
void move_point(struct Point *p, float dx, float dy) {
    p.x += dx;
    p.y += dy;
}
```

```
#include <stdio.h>
```

```
struct Point {                                     // 6
    int x;
    int y;
};
```

```
void move_point(struct Point *p) {
    p->x += 1;
    p->y += 1;
}
```

```
int main(void) {
    struct Point pt = {3,4};
    move_point(pt);
    printf("(%d,%d)\n", pt.x, pt.y);
    return 0;
}
```