

RODAS LINOL

MULTI

Rodas Linol is a water based and transpiring decorative paint with particular and beautiful satin, antique and classic effect, easy application and wide range of colors help to redecorate houses, villas, shops, flats into sophisticated and exceptional scenery of renaissance palaces. This product is created to give new decorative solutions for interiors in order to make your environment unique for the refine elegance.

Characteristics and Physical Properties

Color	Toner Pearl/Premeasured colorant to get required colors
Appearance	As per Catalogue
Specific Weight	1.0kg/liter
Method of Application	Brush, roller, spatula, leather cloth, trowel
Coverage	8-10 sqm/liter
Drying time	3-4 hours AT 20°C
Dilution	Ready to use (you can add 5% if needed)
Application Temperature	5°C-30°C
Resistance	Good Resistance for abrasion once hardened
Wash-ability	Good after hardened using water and normal detergent
Stability	Approximately one (1) year in to the packaging

Surface Preparation:

New concrete:

- Surface must be clean, structurally sound, and free from all contaminants including curing compounds, form release agent, dust, dirt, oil, old coatings and paint
- New concrete and masonry surfaces should be cured for least 28 days. Provide an absorptive surface on all substrates including smooth precast or formed concrete
- The moisture content of the concrete should be below 4% by weight
- All laitance must be removed prior to the next step in surface preparation
- Remove form marks and other protrusion. Ensure that the surface is fully dry prior to the application of corresponding primer and subsequent coating

Old Concrete

- Old concrete should be clean and in a good state. Cracks, holes and other irregularities should be filled in
- All blistered, cracks and peeled-off paints should be removed either by grit blasting, mechanical sanding or paint stripper
- Penetrated paint must be cleaned and treated with ammonia solution

- Glossy finish coat must be sanded
- Oils and greases are best removed by steam cleaning in conjunction with a detergent solution. Through scrubbing with hot caustic solutions will also removed mineral oils and greases

Method of Application:

- Ensure that the surface is properly prepared with the application of Rodas Masonry AR Primer as an impregnating sealer to protect the concrete from efflorescence, Rodas PVA Wall Filler (if necessary, to even up surface irregularities) and Nascryl (as specified) as an intermediate coat prior to the application of Rodas Linol Multi. It is imperative to ensure that the surface to be coated is free from other contaminants, grease and concrete laitance. [Download the technical datasheet for detailed information on website]

Storage:

Store below 250°C. Protect from frost. Protect from source sunlight and direct heat. Keep container sealed when not in use.

Cleaning of Tools:

All tools should be cleaned with water as soon as possible.

Packaging:

4kg and 20kg in a plastic bucket

Physiological Hazard:

Rodas Linol Multi is a water-based paint, nevertheless, good ventilation is recommended as well as the use of safety tools and equipment. Harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advice.