

Rodas SETA

General Description:

Rodas SETA is decorative is decorative trowel-coating with dramatic metallic effect. It provides silky polychromatic finish that enhances the beauty of indoor surfaces.

The product is given a high level of breathability, prevents mildew and fungi growth, UV resistant and environment friendly.

Characteristics and Physical Properties:

Viscosity	Pasty
Thinning / Cleaning	Water
Yield	100 – 125 g./m ² .
Touch Dry	1 – 2 hrs.
Appearance	Silky
Shelf Life	12 Months
Application by	Trowel
Dilution	Not recommended.
VOC	45 g/L

Surface Preparation:

- For the new concrete, it should be fully cured at least 28 days and the substrate must be free from any form of contaminants.
- If old concrete, all blistered, cracks and peeled off paint should be removed.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.

Typical Recommended System

- Apply 1 coat of MAS Masonry Primer.
- Level the surface with PVA Wall Filler if necessary and sand until smooth.
- Apply 1 – 2 coats of Masonry Primer tinted with desired color.
- Apply 1 – 2 coats of RODAS SETA tinted and diluted with 30% with water as a base coat.
- Apply the effect coat using the explained tools and technique.

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight, containers must be kept tightly closed.

Packing:

RODAS SETA is available in 4 kg and 20 kg

Physiological Hazards:

RODAS SETA is a water based paint and does not contain solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. RODAS SETA is harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advice.