

RODAS ALBA

General Description:

ALBA is a water – based wall decorative paint with special pearlescent pigment intended for internal application. It creates many different metallic finishes with deep surface elegance. It is odorless, non – toxic and washable.

Advantages:

- Easy application
- Low odor and low VOC level
- Ready to use
- Can be tinted with variety of desired colors.

Characteristics and Physical Properties:

Color	See Catalogues
Appearance	Metallic
Grades	Smooth, Fine, Medium, Coarse
Flash Point	Non – flammable
Sp. weight	1.0 kg./liter
Method of Application	Brush, roller, spatula, leather cloth, trowel
Coverage	8 – 12 m ² /kg. depending on the porosity of the surface and type of application.
Drying time	3 – 4 hours
Dilution	5 – 10% with fresh water
VOC	52 g/L

Surface Preparation:

New Concrete:

- It should be fully cured at least 28 days and the substrate must be free from any form of contaminants.
- Ensure that the surface to be coated is sound and clean.
- Substrate must be primed by Masonry AR Primer, Masonry Primer, PVA Wall filler, sanding and intermediate coat with cryl (any color) or decorative basecoat.

Old concrete:

- All blisters, cracks and peeled off paint should be removed.

- Remove any loose or flaking material back to a sound firm edge.
- Treat any organic growth with a fungicidal wash.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.

Method of Application:

- Surface to be coated must be prepared as ready for painting.
- Apply ALBA to the surface with a trowel both vertically and horizontally to achieve a consistent. Work in 1-2 m² sections at a time. For a smoother finish, lightly run a smoothing spatula across the surface to remove any stipple.
- At the edges (architrave, picture rail and skirting) or corners, apply the ALBA with a paint brush and smoothen with a trowel or spatula.
- Leave to dry for about 3-4 hours under drying condition and lightly sand the surface with sand not to the extent of destroying the effect of the paint.
- Apply the final layer of the paint to the surface with the desired design using either Brush, Roller, Trowel, Leather cloth as thin as possible and work with the chosen tools in a motion that will create a unique design.

Storage:

Shelf life 12 months minimum if stored below 25°C. Protect from frost. Protect from source of sunlight and direct heat. Keep container sealed when not in use.

Cleaning of Tools:

All tools should be cleaned with water as soon as possible.

Packing:

Available in 1liter, 4 Kg, 10 kg.

Physiological Hazards:

ALBA is nontoxic, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. It is harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advice.