

RODAS VELO

General Description:

RODAS VELO is based on special resin and fillers to provide an interesting decorative paint for external and internal surfaces. It is formulated to protect the substrate from efflorescence and aggressive agent present in the environment.

Advantages:

- For interior and exterior use.
- Good adhesion properties.
- Repels water vapor and humidity.
- Allows the release of any moisture coming up from the ground by capillary action.
- Protect the formation of fungus and algae.
- Inherent flexibility to accommodate hair cracks in the substrate.
- Ease of application.
- Environment friendly.

Characteristics and Physical Properties:

Color	As per catalogue
Gloss	Eggshell
Specific Gravity	1.10-1.20 kg./ lit.
Viscosity	14000 cps.
Coverage	14.5 m ² / lit.
Touch Dry	1 – 2 hrs.
Dry to recoat	3 - 4 hrs.
Shelf Life	12 months
Flash Point	65°C
Application	By brush or roller.
Thinning / cleaning	Water.
Water absorption coeff.	= 0.10 kg. /sq.m. h

Surface Preparation:

New Substrates:

- New concrete should be cured at least 28 days.
Substrate must be free from any form of contaminants.
- Apply 1 coat of RODAS Masonry AR Primer as impregnating sealer.
- Level the surface with RODAS PVA Wall filler and sand until smooth.

Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of RODAS Masonry AR Primer as impregnating sealer; apply 1 – 2 coats of MASCRYL # 1000
- Apply 2 coats of MAS VELO in any choice of application techniques.

Typical Recommended System:

RODAS Masonry AR Primer	1 Coat.
PVA Wall Filler (optional)	2 Coats.
RODAS VELO	2 Coats.

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Containers must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:

Available in 5kg. and 25 kg.

Precautions:



See Safety Indication Sheet.