Precise Control of Organic LED Emission Through Optically-Resonant Microcavity Confinement

Benjamin Isenhart[1],Ekraj Dahal[2], Karen Cianciulli[3], Matthew S. White[12]

[1]Department of Physics, The University of Vermont, Burlington VT
[2]Materials Science Pgrogram, The University of Vermont, Burlington VT
[3]Asheville School, Asheville NC

May 2, 2019

OLED Devices

- Electron-hole recombination in the emissive layer
- Use of TCO to maximize photon outcoupling
- Color determined only by the material in the emissive layer



Waveguides

- Conductors provide bounds to Maxwell's Equations
- General modes of propagation
  - TE Mode
  - TM Mode
  - TEM Mode



Magnetic flux lines appear as continuous loops
Electric flux lines appear with beginning and end points

https://www.allaboutcircuits.com/

The Fabry-Pérot Etalon



https://en.wikipedia.org/wiki/Fabry-Pérot_interferometer

$$T(\phi) = \frac{(1-R_1)(1-R_2)}{\left(1-\sqrt{R_1 R_2}\right)^2 + 4\sqrt{R_1 R_2}\sin^2(\phi)}$$

$$T_{\phi=0} = \frac{(1-R_1)(1-R_2)}{\left(1-\sqrt{R_1 R_2}\right)^2}$$

Microcavity-confined OLEDs

- Replace TCO with partially reflective metal film
- Fabry-Pérot etalon with emission source inside
- Resonant mode selected out of the broadband emission
- Standing wave resonance across multiple cavity stack



Device Fabrication





NPB hole transport material



Alq_3 emissive material



BPhen electron transport material

Angle-Resolved Electroluminescence Spectroscopy (ARES)

Peak Emission Wavelength

$$\lambda_0 = \frac{2nd}{q}$$

$n \rightarrow$ index of refraction

$d \rightarrow$ cavity thickness

$q \rightarrow$ resonant mode





Band Narrowing

$$Q = \frac{2nd}{\lambda_0}\left\{\frac{1-\sqrt{R_1R_2}}{\pi(R_1R_2)^{1/4}}\right\}$$

$$Q = q\left\{\frac{1-\sqrt{R_1R_2}}{\pi(R_1R_2)^{1/4}}\right\}$$





Effect of Bottom Electrode Material



Aluminum bottom electrode



Silver bottom electrode

Behavior at Large Angles

N=2 cavities



N=3 cavities



N=4 cavities



N=5 cavities



Number and Bandwidth of Resonant Modes

N=2 cavities



N=3 cavities



N=4 cavities



N=5 cavities



Conclusions and Future Work

- Control of peak emission wavelength with cavity thickness
- Control of bandwidth with cavity thickness and multi-cavity devices
- More research into controlling the multi-peak emission of multi-cavity devices
- Push towards the lasing threshold with devices of $N > 10$

References

[1] V. Bulovi. "Transform-Limited, Narrow-Linewidth Lasing Action in Organic Semiconductor Microcavities". In: *Science* 279.5350 (Jan. 1998), pp. 553–555. DOI: 10.1126/science.279.5350.553. URL: https://doi.org/10.1126/science.279.5350.553.

[2] D.J. Griffiths. *Introduction to Electrodynamics*. Prentice Hall, 1999. ISBN: 9780138053260. URL: https://books.google.com/books?id=M8XvAAAAMAAJ.

[3] Nur Ismail et al. "Fabry-Pérot resonator: spectral line shapes, generic and related Airy distributions, linewidths, finesses, and performance at low or frequency-dependent reflectivity". In: *Optics Express* 24.15 (July 2016), p. 16366. DOI: 10.1364/oe.24.016366. URL: https://doi.org/10.1364/oe.24.016366.

[4] Toshinori Matsushima, Guang-He Jin, and Hideyuki Murata. "Marked improvement in electroluminescence characteristics of organic light-emitting diodes using an ultrathin hole-injection layer of molybdenum oxide". In: *Journal of Applied Physics* 104.5 (Sept. 2008), p. 054501. DOI: 10.1063/1.2974089. URL: https://doi.org/10.1063/1.2974089.

[5] Joseph Shinar and Ruth Shinar. "Organic light-emitting devices (OLEDs) and OLED-based chemical and biological sensors: an overview". In: *Journal of Physics D: Applied Physics* 41.13 (June 2008), p. 133001. DOI: 10.1088/0022-3727/41/13/133001. URL: https://doi.org/10.1088/0022-3727/41/13/133001.

[6] P. N. Stavrinou et al. "Angular spectrum of visible resonant cavity light-emitting diodes". In: *Journal of Applied Physics* 86.6 (Sept. 1999), pp. 3475–3477. DOI: 10.1063/1.371233. URL: https://doi.org/10.1063/1.371233.

Acknowledgements

- Funding
  - UVM FOUR
  - UVM Clean Energy Fund
  - UVM Department of Physics
- Lab Group
- Committee Members
  - Dr. Frederic Sansoz
  - Dr. Madalina Furis
  - Dr. Matthew S. White

Questions?



THE BEST THESIS DEFENSE IS A GOOD THESIS OFFENSE.

https://xkcd.com/1403/