

# Permanent Monitoring Installation Report



<b>Field Ticket #</b>	RGS1807210131	<b>TD MD</b>	816.7 m MD
<b>Client</b>	Santos Ltd	<b>Tubing Size</b>	2-3/8in 4.7 lb/ft
<b>Well Name</b>	RM50-61-1	<b>Casing Size</b>	7in 23lb/ft
<b>Well Location</b>	Roma	<b>SHP</b>	0 psi
<b>Rig</b>	Wild Desert 4	<b>BHP</b>	1136 psi
<b>Customer Rep</b>	R.Mann	<b>SHT</b>	10 °C
<b>Service Eng</b>	G. Humphreys	<b>BHT</b>	45 °C

<b>Activity</b>	<b>Date</b>	<b>Time</b>	<b>Activity</b>	<b>Date</b>	<b>Time</b>
Depart Base	20/07/2018	17:30	Job End	21/07/2018	3:00
Job Start	20/07/2018	21:00	Return Base	21/07/2018	3:30

Gauge Use	Pump Control	Surface Card	Not required
Gauge Depth	790.17	Telemetry	Analogue
Gauge Type	4-20mA 0-1.5k psi, 105 DegC	Surface Output	4-20mA
Pres Range	0-1500 psia	Cable Splice Depth	N/A
Temp Range	N/A	Tubing Hanger	3/8in NPT - 1/4in Swagelok
Max Devi	0.0°	Wellhead Outlet	AnTech Type C S/N18-1566

<b>TEC Cable</b>	0.25" x 11mm Encap	Encapsulation	Square 11mm
Serial Number	0001509404	Manufacturer	Draka
Conductor	16 AWG Solid Copper	Material	Polypropylene
Tube OD	0.25"	Pres Rating	15 kpsi
Material	316L SS	Temp Rating	150 DegC

<b>Gauge</b>	Analogue	Pres Sensor	Piezoresistive
Serial Number	LC00070	Calibration Range	0 -1500 psia
Depth	790.17 m	Temp Sensor	N/A
OD	1"	Temp Range	N/A
Vibration	N/A	Vibration Range	N/A

Gauge Carrier	Cannon Clamp Type with Vibration Sleeve
Running OD	4.600"
Serial Number	N/A
Cross Coupling Protectors	2-3/8in - 3-1/2in Wiper Blade Style Stainless Steel
Running OD	4.000"
Qty Installed	84
Bands and Clips Material	0.25" x 0.75" w-7/8" Buckle 316SS
Qty Installed	170

Comments: Gauge Carrier installed 2 full joints above PCP. 4-20mA Analogue gauge installed. RIH installing 84 banded CCP. Installed 2 x 1/4in NPT fittings in the hanger and pressure tested. Nipped down and installed Rod lock and AnTech wellhead outlet.

# Permanent Monitoring Installation Report



Sequence of Events		
Date	Time	Description
20/07/2018	17:30	Depart Roma
	19:00	Arrive location
	19:15	Unload and spot equipment.
	21:00	Safety meeting with crew.
		Pick up Sheave and make up BHA
	21:30	Make up gauge carrier and gauge to completion.
		RIH first 4 joints then increase back tension on spooling unit.
21/07/2018		Installed 84 banded cross coupling protectors.
	0:30	Make up hanger.
		Strip encapsulation and pass cable through tubing hanger and tighten TEC seals.
		Land hanger and start pressure test to 3000 psi.
		Rig down floor.
		Nippled down.
	2:20	Land and nipple up rod-lock.
		Pressure test rod lock to 300/3000 psi.
		Install AnTech wellhead outlet.
	3:00	Final gauge reading 1136 psia.
		Prepare report.
	3:30	Depart location for Roma.