Activity Description	Permanent Gauge Installation	Assessment No:	GN010	Rev:	1.2		
& Location:	Onshore, Australia	Date:	2-Dec-2019				
References used:	 Huracan Permanent Gauge Installation SOP (GN013) Wellsite Permit to Work System 	Assessment Team: G. Humphreys, K. Rowbotham, J. Hollingworth					
(Inc. Legal	FROMM Pneumatic Combination Tool A480 (parts & troubleshooting)	Company / Dept.:	Huracan / Permanent Monitoring				
obligations)	Gauge Specific Installation Instructions	Frequency of Activity:					
	Wellhead Outlet Installation Instructions	Persons Affected:	Huracan Crew,	V			

OPERATION / EVENT	HAZARD	RISK	In	itial Ri	sk	CONTROLS		Residual Risk		Risk	
Steps	Energy source to cause harm / damage	Consequence of hazard – harm / damage to occur		Со	RS	Detail	Person to implement	Person to monitor	Pr	Со	RS
Arrival to site, Spotting Unit & Rigging Up	Interaction mobile plant & infrastructure (impact with) Unsuitable / Restricted worksite Lifting (equipment) Overhead loads Moving equipment Manual handling	 Equipment damage – Huracan &/or Client (impact, dropped object) Injury - Permanent disability (Slipping & Tripping, crush, dropped object) Environmental impact – spill to ground NPT – manoeuvring worksite 	Possible	Major	Med C4	 Rig Induction Check personnel and equipment certification Spotter for all interaction between mobile plant infrastructure Exclusion zone required around unit for authorised personnel only Exclusion zone between unit and rig floor Ensure guards in in place on unit Competent personnel (driver & spotter) Communication confirmed Visual inspection / hazard hunt of worksite To set-up unit for spooling operations, park truck 	Huracan Crew, Spotter	Supervisor	Remote	Major	Low E4



						Ensure immobile & turned off Ensure ongoing gas testing is performed and a Hot Work Permit open when test equipment is used inside 30m from the wellhead	
Install Gauge Carrier	 Lifting operations Moving / rotating equipment Manual Handling 	Injury - Permanent disability (Slipping & Tripping, crush, dropped object) Equipment damage — Huracan & / or Client (impact, dropped object)	Possible	Major	Med C3	 Pre-Job Safety Meeting, Review Resource Docs (JSA / SOP) Permit + confirm communication method & any other isolations / controls reqd. for job Competent personnel operating rig tong, pick up gauge carrier and install on completion string and torque Ensure personnel clear during torque procedure 	Low D3
Installing gauge and cable and suspending TEC cable through sheave and suspending above rig floor	 Lifting operations Moving / rotating equipment Manual handling Interaction with other operating plant 	 Injury, dropped object Damage to plant & equipment, dropped object) NPT - Delays to job 	Possible	Major	Med C4	Gloves for manual handling Install gauge into gauge carrier and tighten Connect TEC cable and cable head to gauge and mark and toque to 1-1/4 turns as per manufacturer's instructions Experienced competent personnel / supervision Ensure lifting equipment certified and current NEVER work under a suspended load Huracan Crew, Rig Crew All personnel	Low E4



Running In Hole with tubing and Gauge Cable	Moving / rotating equipment Manual handling Interaction with other operating plant	Damage to TEC cable Injury (Slipping & Tripping, crush, dropped object) Damage to plant & equipment (dropped object)	Possible	Major	MED C4	Good communication between driller, spool operator & man on floor. Controlled speed to help keep tubing away from potential snags Ensure no back tension on TEC cable while running in hole for first 4 joints Exclusion zone around spooler for authorised personnel only Slowly increase back tension on TEC cable as per SOP Ensure cable will not be crushed by rig slips Driller to have smooth operation on the brake while running in and out of hole Gloves for manual handling Experienced competent personnel / supervision Lifting equipment certified and current NEVER work under a suspended load Good communication between driller, spool operator & man on floor. Controlled speed to help keep tubing away from potential snags
Installing Cross Coupling Protectors	Moving / rotating equipmentManual handling	 Personnel injury from crushed fingers in cross coupling protectors Damage to TEC cable 	Likely	Major	High B4	Hold meeting with rig personnel and discus pre-job Huracan Crew, Rig Crew Crew Supervisor Logical Crew C



	Interaction with other operating plant	Dropped Objects in well				 Use correct hand tool for specific cross coupling installation Ensure mat is placed around tubing and slips so no objects are dropped in the hole Ensure TEC cable is pulled against tubing using open palms and open hands with manual operations for Cannon protector installation tool correctly adjusted prior to starting 	
Pass TEC cable through tubing hanger and landing of hanger, engaging torque anchor, termination of TEC cable	High pressure Manual Handling Crushed from rotating equipment	 Equipment Damage (Kinking TEC cable, TEC cable doesn't pass through hanger assembly,) Negative impact on reputation (Cannot seal from hanger to capillary tubing, Failure to inject) 	Possible	Minor	Low C2	 Use landing joint on tubing hanger Once tubing hanger installed in elevators and brought to a suitable height, perform gauge reading, Switch of surface monitoring equipment, Tape cable spool clear area and cut TEC cable ensuring both ends are held during cutting. Lower sheave Strip encapsulation from TEC cable Check TEC cable fitting in hanger and fit onto TEC cable. Pass TEC cable through hanger seal then install upper seal. Fill void between hanger seals and required and tighten upper seal 	Neg E2



Previous Review Date Rev 1.2, 2-Dec-19 Next Review Date 2-Dec-2021

							 Pressure test seal as per client procedure Land hanger and rotate to engage toque anchor 					
Tree Installation and Wellhead Outlet Installation and Pressure Test	High pressure Manual Handling Crushed from rotating equipment	 Equipment Damage tubing, Capillary doesn't pass throug assembly,) Negative impacreputation (Cannot Rod Lock to capilla or from ½" fitting to rod-lock body, Fainject) 	tubing the hanger of the conseal from the cast iron	Possible	Major	Med C4	ich that gauge cable will	Huracan Crew, Rig Crew	Huracan Installation Supervisor	Remote	Major	Low E4
Rigging down	 Lifting Overhead loads Moving equipment Manual handling 	 Injury, whipping cable Damage to pla equipment (sna tubing, blockage end of tubing, drobject) 	ant & agging of cut	Likely	Moderate	Med B3	 Follow operational procedures Experienced competent supervision Ensure permit is closed out Worksite is cleaned up, isolations removed (as reqd.) 	Huracan Crew	Supervisor	Remote	Major	Low E4
Approved By: J. Ho	llingworth		Signature:		Jon F	fossingwo	rth	Date	: 2-Dec-	19		



NOTE: Using the Risk Matrix below, identify the Consequence & Probability of each risk occurring and enter the risk score in the Inherent column. Review the consequence, probability and risk score after appropriate controls have been agreed upon. Remember, the consequence does not change unless you eliminate the hazard (only the probability may change!)

Consequence

. == >	HEALTH AND SAFETY	First Aid Injury (FAI)	Medical Treatment (MTI)	Lost time Injury (LTI)	Permanent Disability / Fatality	Fatalities (multiple)		
	FINANCIAL IMPACT	< \$20K	\$20K - \$200K	\$200K - \$2M	\$2M - \$20M	\$20M+		
	REPUTATION	Minimal impact on business reputation, land holder only	Some impact on business reputation, local community exposure	Moderate impact on business reputation, local media exposure	Significant impact on business reputation, national media exposure	Critical impact on reputation, international media exposure		
HURACAN	ENVIRO.	Incident. No breach of regulations / EA. Minimal and short term impact to any local environment.	Minor breach of regulations / EA resulting in notification to regulator. Localised, short term, recoverable minor impact on flora and fauna	Serious breach of regulations / EA resulting in reporting to regulator, investigation, environment notice or fines. Significant localised but short term environmental impact	Major breach of legislation resulting in prosecution or litigation and regulatory intervention. Serious and long term ecological impact and environmental harm. Emergency Management activated.	Significant compliance breach resulting in prosecution / class action or loss of licence. Severe environmental harm with widespread or permanent Impact Crisis Management activated.		
		1. Insignificant	2. Minor	3. Moderate	4. Major	5. Catastrophic		
A common event that is likely to occur in the industry many times per year	A. Highly Likely	Medium (A1)	Medium (A2)	High (A3)	Extreme (A4)	Extreme (A5)		
An event likely to occur more than once a year in the industry	B. Likely	Low (B1)	Medium (B2)	Medium (B3)	High (B4)	Extreme (B5)		
An event that may occur in the industry over 10 years	C. Possible	Low (C1)	Low (C2)	Medium (C3)	Medium (C4)	High (C5)		
An event not likely to occur in the industry over 10 years	D. Unlikely	Negligible (D1)	Low (D2)	Low (D3)	Medium (D4)	Medium (D5)		
An event that has not previously been experienced in the industry but may occur in exceptional circumstances	E. Remote	Negligible (E1)	Negligible (E2)	Low (E3)	Low (E4)	Medium (E5)		
Hierarchy of Con	trols	Level 1 – Eliminate the Hazard		Level 2 – Substitute, Isolate & E	ngineer Level 3 - A	Level 3 - Admin & PPE Controls		
Reporting Requirements		Report Only – All Negligi	ible Classifications	Investigate – All Low to Med	lium TapRoot – Hig	h or above, or any Hi-Po		

