

# Lab Assignment 10



Inspiring Excellence

<b>Course Code:</b>	CSE111
<b>Course Title:</b>	Programming Language II
<b>Topic:</b>	Review
<b>Number of Tasks:</b>	12

**[NO SUBMISSION]**

[You are not allowed to change the driver codes of any of the tasks]

### Task 1

We know that Nike has opened their official outlets in Bangladesh. So let's construct a **NikeBD** class so that they can keep track of their inventory and sales here.

[Hint: Only 3 types of products are available: “Jordan”, “Cortez” and “Kobe”]

Driver Code	Output
<pre>public class NikeTester {     public static void main(String[] args) {         System.out.println("=====1=====");         NikeBD.status();         NikeBD dhaka = new NikeBD("Dhaka Banani");         NikeBD chittagong = new NikeBD("Chittagong GEC");         System.out.println("=====2=====");         dhaka.details();         System.out.println("=====3=====");         chittagong.details();         System.out.println("=====4=====");         dhaka.restockProducts("Jordan", 200);         System.out.println("=====5=====");         String [] products = {"Jordan", "Cortez", "Kobe"};         int [] qty = {1200, 200, 200};         String [] products2 = {"Jordan", "Cortez", "Kobe"};         int [] qty2 = {1200, 250, 100};         dhaka.restockProducts(products, qty);         System.out.println("=====6=====");         chittagong.restockProducts(products2, qty2);         System.out.println("=====7=====");         NikeBD.status();         System.out.println("=====8=====");         dhaka.details();         System.out.println("=====9=====");         chittagong.details();         dhaka.productSold("Jordan", 760, "Cortez", 90);         chittagong.productSold("Jordan", 520, "Kobe", 70);         System.out.println("=====10=====");         NikeBD.status();         System.out.println("=====11=====");         chittagong.details();     } }</pre>	<pre>=====1===== Nike Bangladesh Status: Branches Opened: 0 Currently Stocked: Jordan: 0, Cortez: 0, Kobe: 0 Sold: 0 =====2===== Nike Dhaka Banani outlet: Products Currently Stocked: Jordan: 0, Cortez: 0, Kobe: 0 Sold: 0 =====3===== Nike Chittagong GEC outlet: Products Currently Stocked: Jordan: 0, Cortez: 0, Kobe: 0 Sold: 0 =====4===== =====5===== =====6===== =====7===== Nike Bangladesh Status: Branches Opened: 2 Currently Stocked: Jordan: 2600, Cortez: 450, Kobe: 300 Sold: 0 =====8===== Nike Dhaka Banani outlet: Products Currently Stocked: Jordan: 1400, Cortez: 200, Kobe: 200 Sold: 0 =====9===== Nike Chittagong GEC outlet: Products Currently Stocked: Jordan: 1200, Cortez: 250, Kobe: 100 Sold: 0 =====10===== Nike Bangladesh Status: Branches Opened: 2 Currently Stocked: Jordan: 1320, Cortez: 360, Kobe: 230 Sold: 1440 =====11===== Nike Chittagong GEC outlet: Products Currently Stocked: Jordan: 680, Cortez: 250, Kobe: 30 Sold: 590</pre>

## Task 2

Design the child class **Striker** and **Defender** that inherits from the Football class so that the given output matches with the output generated by the driver code.

Parent Class	
<pre>public class Football {     public String name;     public int age;     public int stamina;      public Football(String name, int age, int stamina) {         this.name = name;         this.age = age;         this.stamina = stamina;     }      public void display() {         System.out.println("Name: " + name);         System.out.println("Age: " + age);         System.out.println("Stamina: " + stamina);     }      public void calculatePerformance() {         System.out.println("Performance is not defined yet");     } }</pre>	
Driver Code	Output
<pre>public class FootballTester {     public static void main(String[] args) {         Striker ronaldo = new Striker("Ronaldo", 39, 90, 901, 1000);         Defender ramos = new Defender("Ramos", 38, 85, 1000, 100);          System.out.println("1=====");         ronaldo.display();         System.out.println("2=====");         ronaldo.calculatePerformance();         System.out.println("3=====");         ramos.display();         System.out.println("4=====");         ramos.calculatePerformance();     } }</pre>	<pre>1===== Name: Ronaldo Age: 39 Stamina: 90 Goals: 901 Shots on target: 1000 2===== Performance: 0.901 3===== Name: Ramos Age: 38 Stamina: 85 Tackles: 1000 Interceptions: 100 4===== Performance: 0.1</pre>

### Task 3

Design the **Nokia** class derived from the Mobile class so that the following output is produced.

#### Parent Class

```
class Mobile {
    public String model;
    public String IMEICode;
    public boolean simCardStatus;

    public Mobile(String model, String IMEICode, boolean simCardStatus) {
        this.model = model;
        this.IMEICode = IMEICode;
        this.simCardStatus = simCardStatus;
        System.out.println("Model " + model + " is manufactured.");
    }

    public String getCountryName(String countryCode) {
        if (countryCode.equals("880")) {
            return "Bangladesh";
        } else if (countryCode.equals("455")) {
            return "USA";
        }
        return null;
    }

    public void activateSimCard() {
        if (!simCardStatus) {
            simCardStatus = true;
            System.out.println("SIM card is activated successfully.");
        }
    }

    @Override
    public String toString() {
        return "Mobile Phone Detail:\nModel: " + model + "\nIMEICode: " + IMEICode + "\nSIM Card Status: " + simCardStatus;
    }
}
```

//Driver code below

Driver Code	Output
<pre> public class MobileTester {     public static void main(String[] args) {         Nokia N3110 = new Nokia("N3110", true, "IMEI-102", 0);         System.out.println(N3110);         System.out.println("1=====");         Nokia N1100 = new Nokia("N1100", false, "IMEI-124", 100);         System.out.println(N1100);         System.out.println("2=====");         System.out.println(N3110.dialCall("88017196xxxx"));         System.out.println("3=====");         N3110.rechargeSIMCard(200);         N1100.rechargeSIMCard(300);         System.out.println("4=====");         System.out.println(N3110.dialCall("88017196xxxx"));         System.out.println("5=====");         System.out.println(N1100.dialCall("45517196xxxx"));         System.out.println("6=====");         N1100.activateSimCard();         System.out.println("7=====");         System.out.println(N1100.dialCall("45517196xxxx"));         System.out.println("8=====");         System.out.println(N1100.dialCall("96617196xxxx"));     } } </pre>	<pre> Model N3110 is manufactured. Mobile Phone Detail: Model: N3110 IMEICode: IMEI-102 SIM Card Status: true Balance: 0.0 TK 1===== Model N1100 is manufactured. Mobile Phone Detail: Model: N1100 IMEICode: IMEI-124 SIM Card Status: false Balance: 100.0 TK 2===== Insufficient balance! Please recharge. 3===== Recharge successful! Current balance 200.0 TK. Recharge successful! Current balance 400.0 TK. 4===== Dialing the number 88017196xxxx to Bangladesh region. 5===== No SIM card available! Please check the SIM card connectivity. 6===== SIM card is activated successfully. 7===== Dialing the number 45517196xxxx to USA region. 8===== Dialing is not allowed in this region. </pre>

## Task 4

Design the **Dragon** class and **Phoenix** class derived from the **MagicalCreature** class so that the following output is produced.

Parent Class		
<pre>public class MagicalCreature {     public String name;     public int age;     public MagicalCreature(String name, int age) {         this.name = name;         this.age = age;     }     public void makeSound() {         System.out.println(name + " makes a magical sound.");     }     public void displayInfo() {         System.out.println("Name: " + name + "\nAge: " + age);     }     public void performMagic() {         System.out.println(name + " performs a generic magic.");     } }</pre>		
Driver Code	Output	
<pre>public class MagicalTester {     public static void main(String[] args) {         Dragon drake = new Dragon("Drake", 500, 75);         Phoenix fawkes = new Phoenix("Fawkes", 200, 5);         drake.displayInfo();         drake.makeSound();         drake.performMagic();         drake.fly();         System.out.println("=====");         fawkes.displayInfo();         fawkes.makeSound();         fawkes.performMagic();         fawkes.regenerate();     } }</pre>	<pre>Name: Drake Age: 500 Drake roars with a fiery breath! Drake breathes fire with power level: 75 Drake flies through the sky. ===== Name: Fawkes Age: 200 Fawkes sings an enchanting song. Fawkes is reborn with 5 rebirth cycles. Fawkes regenerates its body in a burst of flames.</pre>	

## Task 5

Design the **Bondhus** class derived from the **SocialMedia** class so that the following output is produced.

### Parent Class

```
public class SocialMedia{
    public String userName;
    public String email;

    public SocialMedia(String name, String mail){
        userName = name;
        email = mail;
    }
    @Override
    public String toString() {
        return userName + "'s profile:" + "\nUser Name: " + userName + "\nEmail:" + email;
    }
}
```

### Driver Code

```
public class SocialMediaTester{
    public static void main(String []args){
        Bondhus f1 = new Bondhus("Sheldon", "sheldon@gmail.com");
        Bondhus f2 = new Bondhus("Penny", "penny@gmail.com");
        Bondhus f3 = new Bondhus("Leonard", "leonard@gmail.com");
        System.out.println("1-----");
        f1.showSentbox();
        System.out.println("2-----");
        f2.showSentbox();
        System.out.println("3-----");
        f2.sendMessage("Hi");
        f2.sendMessage("Hello");
        f2.sendMessage("NiHao");
        f3.sendMessage("Hola");
        f3.sendMessage("Sheldon, please.");
        System.out.println("4-----");
        f2.showSentbox();
        System.out.println("5-----");
        f1.showSentbox();
        System.out.println("6-----");
        f1.sendMessage("Bazinga!");
        f2.sendMessage("Well, duh!");
        f3.showSentbox();
        System.out.println("7-----");
        f2.showSentbox();
        f2.sendMessage("Bye.");
        f2.sendMessage("Oh! No");
        System.out.println("8-----");
        f1.showSentbox();
        System.out.println("9-----");
        System.out.println(f1);
        System.out.println("10-----");
        System.out.println(f2);
    }
}
```

### Output

```
1-----
Sheldon's Sentbox:
No sent messages.
2-----
Penny's Sentbox:
No sent messages.
3-----
4-----
Penny's Sentbox:
Hi
Hello
NiHao
5-----
Sheldon's Sentbox:
No sent messages.
6-----
Leonard's Sentbox:
Hola
Sheldon, please.
7-----
Penny's Sentbox:
Hi
Hello
NiHao
Well, duh!
Sentbox is full.
8-----
Sheldon's Sentbox:
Bazinga!
9-----
Sheldon's profile:
User Name: Sheldon
Email:sheldon@gmail.com
Messages Sent: 1
10-----
Penny's profile:
User Name: Penny
Email:penny@gmail.com
Messages Sent: 5
```

## Task 6

Observe the following Tester class and outputs to design both the **Patient** class and **InPatient** class with appropriate elements.

Tester Class	Expected Output
<pre>public class PatientTester {     public static void main(String[] args) {         Patient p1 = new Patient("Robert", "Dr. Thomas");         System.out.println(p1);         System.out.println("1.....");         Patient.details();         System.out.println("2.....");         InPatient p2 = new InPatient("Christina", "Dr. Alex", "Oncology");         System.out.println(p2);         System.out.println("3.....");         InPatient.details();         System.out.println("4.....");         Patient p3 = new InPatient("Sofia", "Dr. Brawn", "Pediatrics");         Patient p4 = new Patient("Patrick", "Dr. Alex");         Patient.details();         System.out.println("5.....");         Patient[] allPatients = { p1, p2, p3, p4 };         Patient.details(allPatients);     } }</pre>	<pre>Patient ID: P01, Name: Robert Doctor: Dr. Thomas 1..... Total patients: 1. 2..... New patient admitted in Oncology. Patient ID: P02, Name: Christina Doctor: Dr. Alex Department: Oncology 3..... Total patients: 2. Admitted In-Patients: 1. Out-Patients: 1. 4..... New patient admitted in Pediatrics. Total patients: 4. 5..... Details of 4 selected patients: == == == == == Patient ID: P01, Name: Robert Doctor: Dr. Thomas == == == == == Patient ID: P02, Name: Christina Doctor: Dr. Alex Department: Oncology == == == == == Patient ID: P03, Name: Sofia Doctor: Dr. Brawn Department: Pediatrics == == == == == Patient ID: P04, Name: Patrick Doctor: Dr. Alex</pre>



## Task 7

1	public class Trace {
2	public int sum, temp;
3	public Trace(int sum, int temp){
4	this.sum = sum;
5	this.temp = temp;
6	}
7	}
8	class Quiz5{
9	public int sum = 12, x = 2, y = 6;
10	public Trace trace;
11	public Quiz5(Trace t){
12	trace = t;
13	int x = trace.temp + y;
14	sum = sum + (t.sum--) + y;
15	System.out.println(trace.sum + " " + sum + " " + x);
16	sum -= 10;
17	}
18	public void methodA(int sum, int temp){
19	sum = 3 + sum - trace.sum;
20	x = sum + 12 + y;
21	y = trace.temp + temp + sum;
22	this.sum = y + methodB(trace.temp, trace) + trace.temp;
23	System.out.println(sum + " " + y + " " + this.sum);
24	}
25	public int methodB(int x, Trace temp){
26	int sum = x + temp.sum + this.x;
27	temp.temp = sum + this.sum;
28	System.out.println(x + " " + temp.temp + " " + sum);
29	return sum;
30	}
31	}

<pre>Trace p = new Trace(3, 4); Quiz5 q = new Quiz5(p); q.methodA(4, 8); q.methodA(5, 10);</pre>	Output		

## Task 8

1	public class Test {
2	public static int a=3;
3	public int b=7, c;
4	public Test(){
5	methodA(a+4);
6	}
7	public void methodA(int a){
8	Tracing t = new Tracing(2,7);
9	a = Tracing.a+ Test.a;
10	c = b + a + t.methodB();
11	System.out.println(this.a+" "+this.b+" "+c);
12	}
13	}
14	class Tracing {
15	public static int a = 9, y = 5;
16	public int x, b;
17	public Tracing(int a, int b){
18	x += a;
19	y += b;
20	this.a = this.x;
21	this.b = this.y;
22	}
23	public int methodB(){
24	System.out.println(this.a+" "+this.b+" "+x);
25	b = y - this.b + Test.a;
26	x += this.b;
27	return this.b;
28	}
29	}

Tracing t2 = new Tracing(4, 3); Test ex = new Test(); t2.methodB(); ex.methodA(Test.a);	Output		

## Task 9

1	public class A {
2	public static int temp = 3;
3	public int sum;
4	public int y;
5	public A(int x) {
6	y = A.temp - 1 + x;
7	sum = this.temp + 2;
8	A.temp -= 2;
9	}
10	public void methodA(int y, int[] n) {
11	int x = 0;
12	n[0] += 1;
13	this.y = this.y + y + temp;
14	A.temp += 1;
15	x = x + 2 + n[0];
16	n[0] = sum + 2;
17	System.out.println(x + " " + this.y + " " + this.sum);
18	}
19	}
20	public class B extends A {
21	public static int x = 1;
22	public B() {
23	super(5);
24	sum = 2;
25	y = A.temp + 1;
26	B.x = 3 + temp + B.x;
27	A.temp -= 2;
28	}
29	public B(B b) {
30	super(2);
31	sum = 3;
32	this.sum = sum + this.sum%2 + 2;
33	B.x = b.x + B.x;
34	}
35	public void methodB(int m, int n) {
36	int[] y = {2, 3};
37	this.y = y[0] + this.y + m;
38	B.x = this.y + 2 + A.temp - n;
39	methodA(B.x, y);
40	this.sum = B.x + y[1] + this.sum;
41	System.out.println(B.x + " " + (y[0]+y[1]) + " " + this.sum);
42	}
43	}

Write the output of the following tester code:

<pre>int[] n = {23}; A a1 = new A(3); B b1 = new B(); B b2 = new B(b1); a1.methodA(1, n); b2.methodB(3, 2); a1.methodA(1, n);</pre>	Output		
	x	y	sum

### Task 10

1	<code>public class Bank {</code>
2	<code>    public static int rs = 3;</code>
3	<code>    public static int cd = -8;</code>
4	<code>    public int bl = 0;</code>
5	<code>    public int br = 0;</code>
6	<code>    public Bank() {</code>
7	<code>        br = rs - 2;</code>
8	<code>        bl = rs + 1;</code>
9	<code>        rs -= 2;</code>
10	<code>    }</code>
11	<code>    public void deposit(int a, int b) {</code>
12	<code>        int cd = 0;</code>
13	<code>        br = br + a + (rs++);</code>
14	<code>        cd = cd + 1 + b;</code>
15	<code>        bl = bl + cd + br;</code>
16	<code>        System.out.println(cd + " " + br + " " + bl);</code>
17	<code>    }</code>
18	<code>}</code>
19	<code>public class Account extends Bank {</code>
20	<code>    public static int cd = 1;</code>
21	<code>    public int bl = -4;</code>
22	<code>    public Account() {</code>
23	<code>        bl = 0;</code>
24	<code>        br = rs + 3;</code>
25	<code>        super.bl = 2 + rs + 3;</code>
26	<code>        rs -= 2;</code>
27	<code>    }</code>
28	<code>    public Account(Account acc) {</code>
29	<code>        bl = acc.bl + super.bl;</code>
30	<code>        cd = acc.cd;</code>
31	<code>        acc.withdraw(2, 3);</code>
32	<code>    }</code>

33	public void withdraw(int a, int b) {
34	int br = 0;
35	br = br + this.br;
36	cd = br + 2 + (++rs);
37	deposit(cd, br);
38	bl = cd + br + bl;
39	System.out.println(cd + " " + br + " " + bl);
40	}
41	}

Write the output of the following code:

<pre> public class Tester {     public static void main(String[] args) {         Bank b1 = new Bank();         Account a1 = new Account();         Account a2 = new Account(a1);         a1.deposit(3, 4);         a2.withdraw(1, 6);     } } </pre>	<b>Output:-</b>		

### Task 11

1	public class Device {
2	public void start() {
3	System.out.println("Device starting");
4	}
5	public void shutdown() {
6	System.out.println("Device shutting down");
7	start();
8	}
9	}
10	public class Laptop extends Device {
11	public void start() {
12	System.out.println("Laptop booting up");
13	}
14	}
15	public class Smartphone extends Device {
16	public void notifyUser() {
17	System.out.println("Smartphone notification");
18	}
19	}
20	public class GamingLaptop extends Laptop {
21	public void start() {

22	System.out.println("GamingLaptop powering on");
23	super.start();
24	}
26	public void notifyUser() {
27	System.out.println("GamingLaptop notification alert");
28	}
29	}

Assuming the following variables have been defined:

```
Device d1 = new GamingLaptop();
Device d2 = new Laptop();
Device d3 = new Device();
Object d4 = new Laptop();
Laptop d5 = new GamingLaptop();
Object d6 = new Smartphone();
```

In the table below,

- The output produced by the statement in the left-hand column, should be written in the right-hand column
- If the statement produces more than one line of output, indicate the line breaks with slashes as in "a/b/c" to indicate three lines of output with "a" followed by "b" followed by "c".
- If the statement causes an error, fill in the right-hand column with either the phrase "compiler error" or "runtime error" to indicate when the error would be Detected.

	Statement	Output
1	d1.start();	
2	d2.start();	
3	d4.start();	
4	d6.start();	
5	d1.shutdown();	
6	d3.shutdown();	
7	d4.shutdown();	
8	d5.shutdown();	
9	d6.shutdown();	
10	((GamingLaptop)d4).notifyUser();	
11	((GamingLaptop)d6).shutdown();	
12	((Smartphone)d1).notifyUser();	
13	((Smartphone) d6).start();	
14	((GamingLaptop) d5).start();	
15	((GamingLaptop)d5).notifyUser();	

## Task 12

1	public class Department{
2	public String chant = "I love my Department!";
3	public void task1(){
4	System.out.println(chant);
5	}
6	public void task2(){
7	task1();
8	System.out.println("Doing Task 2 "+ chant);
9	}
10	public void advising(){
11	System.out.println("Advising is Pain.");
12	}
13	public String toString(){
14	advising();
15	return chant;
16	}
17	}
18	public class CSEDept extends Department{
19	public String chant = "CSE is Love.";
20	public void task2(){
21	System.out.println("Doing Task 2 "+ chant);
22	}
23	public void advising(){
24	System.out.println("Advising is Pain.");
25	}
26	}
27	public class EEEDept extends Department{
28	public String chant = "Help.";
29	public void task1(){
30	System.out.println("Doing Task 1 "+ chant);
31	}
32	public void advising(){
33	super.advising();
34	System.out.println(chant);
35	}
36	public String toString(){
37	task2();
38	return chant;
39	}
40	}
41	public class SoftwareDept extends CSEDept{
42	public String chant = "Software is fun!";
43	public String toString(){

44	advising();
45	return chant;
46	}
47	public void task1(){
48	System.out.println("Doing Task 1 "+ chant);
49	task2();
50	}
51	}
53	public class RoboticsDept extends EEEDept{
54	public String chant = "New Department woohoo!";
55	public void task2(){
56	System.out.println("Doing Task 2 "+ chant);
57	}
58	public void advising(){
59	super.advising();
60	task1();
61	System.out.println(chant);
62	}
63	}

Assuming the following variables have been defined:

```

Department b1 = new Department();
Department b2 = new EEEDept();
Department b3 = new SoftwareDept();
CSEDept c1 = new SoftwareDept ();
CSEDept c2 = new CSEDept();
Object o1 = new EEEDept();
Department o2 = new RoboticsDept();

```

In the table below,

- The output produced by the statement in the left-hand column, should be written in the right-hand column
- If the statement produces more than one line of output, indicate the line breaks with slashes as in "a/b/c" to indicate three lines of output with "a" followed by "b" followed by "c".
- If the statement causes an error, fill in the right-hand column with either the phrase "compiler error" or "runtime error" to indicate when the error would be detected.

	Statement	Output
1	c2.task2();	
2	b3.task1();	
3	System.out.println(b3);	
4	((CSEDept)b1).task1();	
5	System.out.println(((Object)b2).chant);	



6	((Department)b2).advising();	
7	((CSEDept)b2).task2();	
8	((EEEDept)b2).task2();	
9	System.out.println((CSEDept)b3);	
10	System.out.println(((Department)c1).chant);	
11	((Object)c1).toString();	
12	System.out.println(((Department)c2));	
13	System.out.println(((Department)o1));	
14	((EEEDept)o2).advising();	
15	((SoftwareDept)o2).task1();	