

Summary report

Wellbore: 15/9-F-15 A

Period: 2009-01-02 00:00 - 2009-01-03 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	23
Days Ahead/Behind (+/-):	11.2
Operator:	StatoilHydro
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Mærsk Contractors
Spud Date:	2008-12-11 15:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (°):	
Pressure (°):	
Date Well Complete:	

Dist Drilled (m):	296
Penetration rate (m/h):	-999.99
Hole Dia (in):	8.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.56
Dia Last Casing (°):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	3385
Depth mTVD:	2870
Plug Back Depth mMD:	
Depth at formation strength mMD:	2562
Depth At Formation Strength mTVD:	2418
Depth At Last Casing mMD:	2561.8
Depth At Last Casing mTVD:	2416.2

Summary of activities (24 Hours)

RIH with 8½" BHA and drilled from 3181m to 3481m.

Summary of planned activities (24 Hours)

Continue drilling 8½" hole from 3481m to 3950m

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	03:00	2532	drilling – trip	ok	RIH with 8 1/2" BHA on 5" DP from 1077 m to 1726 m. Changed to 5 1/2" handling equipment and RIH with 8 1/2" BHA on 5 1/2" DP from 1726 m to 2532 m. Filled pipe every 15 strds.
03:00	04:45	2532	drilling – trip	ok	MU TDS and filled pipe. Staged up pumps and circulated btms up at 13 3/8" csg shoe at 2532 m. Parameters: 2150 lpm / bar.
04:45	06:00	2635	drilling – trip	ok	RIH with 8 1/2" BHA from 2532 m to 2594 m. Found obstruction at 2594 m. PU 1-2 m and washed down stand. Continued RIH with 8 1/2" BHA from 2594 m to 2630 m. Found obstruction at 2630 m. PU 1-2 m and washed down stand. Parameters : 1600 lpm / SPP 80 bar / 50 RPM / torque 9-11 kNm. Up weigh 150 MT / Rotational weight 137 MT / Down weight 128 MT.
06:00	09:30	3141	drilling – trip	ok	Continued RIH with 8½" BHA from 2636m to 3141m. Took weight at 2668m and 2696m. Reamed through with 2000 lpm and 50/60 rpm.
09:30	10:45	3181	drilling – trip	ok	Made up to TDS and washed down last stand from 3141m to 3180m, with 2000 lpm, 60 rpm. Drilled 1 meter to 3181m before taking connection.
10:45	21:00	3342	drilling – drill	ok	Continued drilling 8½" hole from 3181 m to 3342 m. Flow 2100 lpm / SPP 148 bars / String RPM 120 TQ 8-29 kNm / WOB 8-10 / ECD 1.36 EMW / MUD weight 1.32 SG / ROP 19-21mph. Up weight 170 MT / Down weight 132 MT / Free rotational weight 147 MT. Parallel activity: Made up 10-3/4" CSG in std and rack back in derrick.
21:00	00:00	3385	drilling – drill	ok	Continued drilling 8½" hole from 3342 m to 3385 m. Flow 2100 lpm / SPP 148-150 bars / String RPM 120 TQ 12-30 kNm / WOB 5-8 / ECD 1.36-1.38 EMW / MUD weight 1.32-1.34 SG / ROP 20 mph. Up weight 172 MT / Down weight 128 MT / Free rotational weight 147 MT. Weighted up mud to 1.34 SG. Parallel activity: Made up 10-3/4" CSG in std and rack back in derrick.

Drilling Fluid

Sample Time	03:30	10:00	21:00
Sample Point	Flowline	Flowline	Flowline
Sample Depth mMD	3149	3185	3351
Fluid Type	OBM-Standard	OBM-Standard	OBM-Standard
Fluid Density (g/cm3)	1.32	1.33	1.33
Funnel Visc (s)	-999.99	-999.99	-999.99
Mf ()			
Pm ()			
Pm filtrate ()			
Chloride ()			
Calcium ()			
Magnesium ()			
Ph			
Excess Lime ()			
Solids			
Sand ()			
Water ()			
Oil ()			
Solids ()			
Corrected solids ()			
High gravity solids ()			
Low gravity solids ()			
Viscometer tests			
Plastic visc. (mPa.s)	20	22	19
Yield point (Pa)	11.5	10	11.5
Filtration tests			
Pm filtrate ()			

Filtrate Lthp ()			
Filtrate Hthp ()			
Cake thickn API ()			
Cake thickn HPHT ()			
Test Temp HPHT (degC)	120	120	120
Comment			

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	3346		1.2	estimated
00:00	4118		1.16	estimated

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
3199.8	2825.5	61.42	272.26	
3241.7	2843.5	67.42	275.37	
3280.7	2856.2	74.58	277.8	
3321.4	2864.4	82.32	278.66	
3361.7	2868.8	85.13	279.03	
3401.3	2871.9	85.77	280.03	
3442.6	2875.5	84.22	280.17	

Stratigraphic Information

Depth to Top of Formation mMD	Depth to Top of Formation mTVD	Description
3392	2870	Hidra Fm

Lithology Information

Start Depth mMD	End Depth mMD	Start Depth mTVD	End Depth mTVD	Shows Description	Lithology Description
3180	3223	2815	2836		Marl w/minor claystones
3220	3450	2836	2876		Marl