

Summary report

Wellbore: 15/9-F-15 B

Period: 2009-01-13 00:00 - 2009-01-14 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	1
Days Ahead/Behind (+/-):	20.3
Operator:	StatoilHydro
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Mærsk Contractors
Spud Date:	2009-01-13 12:15
Wellbore type:	
Elevation RKB-MSL (m):	54
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (°):	
Pressure (°):	
Date Well Complete:	

Dist Drilled (m):	191
Penetration rate (m/h):	-999.99
Hole Dia (in):	8.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.56
Dia Last Casing (°):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	3401
Depth mTVD:	2949
Plug Back Depth mMD:	
Depth at formation strength mMD:	2562
Depth At Formation Strength mTVD:	2418
Depth At Last Casing mMD:	2560.9
Depth At Last Casing mTVD:	2415.3

Summary of activities (24 Hours)

Drilled 8½" hole from 3210m to 3473m. Took pressure points.

Summary of planned activities (24 Hours)

Continued drilling to TD. Take pressure points. Circulate hole clean. POOH with 8½" BHA.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
12:15	00:00	3401	drilling -- drill	ok	Drilled 8½" hole from 3210m to 3401m. Drilling parameters: Flow 2140 lpm / SPP 142-157 bars / String RPM 130 TQ 15-20 kNm / WOB 3-8,5 / ECD 1.42 EMW / M UD weight 1.34 SG / ROP 20-30 mph.

Drilling Fluid

Sample Time	10:00	16:00	22:30
Sample Point	Flowline	Flowline	Flowline
Sample Depth mMD	3185	3246	3366
Fluid Type	OBM-Standard	OBM-Standard	OBM-Standard
Fluid Density (g/cm3)	1.34	1.34	1.34
Funnel Visc (s)	-999.99	-999.99	-999.99
Mf (°)			
Pm (°)			
Pm filtrate (°)			
Chloride (°)			
Calcium (°)			
Magnesium (°)			
Ph			
Excess Lime (°)			
Solids			
Sand (°)			
Water (°)			
Oil (°)			
Solids (°)			
Corrected solids (°)			
High gravity solids (°)			
Low gravity solids (°)			
Viscometer tests			
Plastic visc. (mPa.s)	28	27	29
Yield point (Pa)	11	10.5	10.5
Filtration tests			
Pm filtrate (°)			
Filtrate Lthp (°)			
Filtrate Hthp (°)			
Cake thickn API (°)			
Cake thickn HPHT (°)			
Test Temp HPHT (degC)	120	120	120
Comment			

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	3480		.96	estimated

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
3149.4	2801.1	60.21	270.16	
3158.9	2805.9	59.52	269.88	
3194.8	2824.2	59.29	272.22	
3234.9	2846	54.92	274.74	
3274.5	2869.1	53.75	278.21	
3315	2893.8	51.13	279.7	
3355.8	2919.5	50.63	280.16	
3396.5	2946	48.09	281.46	
3436.4	2973.1	46.32	282.43	

Log Information

Run No	Service Company	Depth Top mMD	Depth Bottom mTVD	Tool	BHST (degC)
100	Schlumberger	3185	3480	ECOSCOPE - STETHSCOPE - TELESCOPE	-999.99

Stratigraphic Information

Depth to Top of Formation mMD	Depth to Top of Formation mTVD	Description
3144.7	2799.8	Blodøks Fm
3277.5	2871.3	Hidra Fm
3296.7	2882.8	Rødby Fm
3327	2901.6	Asgard Fm
3365	2925.9	Draupne Fm
3370	2929.3	Hugin Fm

Lithology Information

Start Depth mMD	End Depth mMD	Start Depth mTVD	End Depth mTVD	Shows Description	Lithology Description
3195	3280	2824	2824		Marl, Limestone & Claystone
3280	3300	2872	2872		Marly Limestone, Limestone & Claystone
3300	3330	2884	2903		Marly Limestone & Limestone
3330	3366	2903	2926		Limestone, Siltstone & Claystone
3366	3372	2926	2930		Claystone
3372	3414	2930	2957		Sandstone, Siltstone & Claystone

Gas Reading Information

Time	Class	Depth to Top mMD	Depth to Bottom MD	Depth to Top mTVD	Depth to Bottom TVD	Highest Gas (%)	Lowest Gas ()	C1 (ppm)	C2 (ppm)	C3 (ppm)	IC4 (ppm)	IC5 (ppm)
00:00	drilling gas peak	3376		2941		10.02		46985	3239	1238	79	42