

Summary report

Wellbore: 15/9-F-15 C

Period: 2013-10-21 00:00 - 2013-10-22 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	63
Days Ahead/Behind (+/-):	
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2009-01-19 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (°):	
Pressure (°):	
Date Well Complete:	2009-02-14

Dist Drilled (m):	-999.99
Penetration rate (m/h):	-999.99
Hole Dia (°):	
Pressure Test Type:	formation integrity test
Formation strength (°):	
Dia Last Casing (°):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMD:	3049
Depth mTVD:	
Plug Back Depth mMD:	
Depth at formation strength mMD:	
Depth At Formation Strength mTVD:	
Depth At Last Casing mMD:	2914.8
Depth At Last Casing mTVD:	

Summary of activities (24 Hours)

Waited on weather to pull production riser.
Meanwhile performed general rig maintenance, cleaning and housekeeping.

Summary of planned activities (24 Hours)

Waiting on weather to pull production riser.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	07:00	0	interruption -- waiting on weather	ok	Waited on weather to pull production riser. Meanwhile performed general rig maintenance: P/T contingency kill manifold in moonpool. Performed cleaning in pit- /pumproom. Performed housekeeping in drilling areas.
07:00	19:00	0	interruption -- waiting on weather	ok	Waited on weather to pull production riser. Meanwhile performed general rig maintenance: Weekly inspection on aft IRN. Performed high wind checks. Changed out fwd PRS wire, interrupted job due to wind speed above 45 knts. Performed cleaning and housekeeping in drilling areas.
19:00	00:00	0	interruption -- waiting on weather	ok	Waited on weather to pull production riser. Meanwhile performed general rig maintenance: Continued to change out fwd PRS wires. Performed cleaning and housekeeping in drilling areas.

Drilling Fluid

Sample Time	10:00	17:00
Sample Point	Reserve pit	Reserve pit
Sample Depth mMD	3231	3231
Fluid Type	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.21	1.21
Funnel Visc (s)	-999.99	-999.99
Mf (°)		
Pm (°)		
Pm filtrate (°)		
Chloride (°)		
Calcium (°)		
Magnesium (°)		
Ph		
Excess Lime (°)		
Solids		
Sand (°)		
Water (°)		
Oil (°)		
Solids (°)		
Corrected solids (°)		
High gravity solids (°)		
Low gravity solids (°)		
Viscometer tests		
Plastic visc. (mPa.s)	30	30
Yield point (Pa)	7	7
Filtration tests		
Pm filtrate (°)		
Filtrate Lthp (°)		
Filtrate Hthp (°)		
Cake thickn API (°)		
Cake thickn HPHT (°)		

Test Temp HPHT (degC)	120	120
Comment		