

Summary report

Wellbore: 15/9-F-15 C

Period: 2013-10-26 00:00 - 2013-10-27 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	68
Days Ahead/Behind (+/-):	
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2009-01-19 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2009-02-14

Dist Drilled (m):	-999.99
Penetration rate (m/h):	-999.99
Hole Dia (I):	
Pressure Test Type:	formation integrity test
Formation strength (I):	
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	2637
Depth mTVD:	
Plug Back Depth mMD:	
Depth at formation strength mMD:	
Depth At Formation Strength mTVD:	
Depth At Last Casing mMD:	2914.8
Depth At Last Casing mTVD:	

Summary of activities (24 Hours)

Pulled out of hole with 8 1/2" Clean-out bit to surface. Waiting on weather. Meanwhile: Performed general rig maintenance. Removed debris around template with ROV.

Summary of planned activities (24 Hours)

Waiting on weather. Meanwhile: Install 9 5/8" EZSV.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	00:30	1825	plug abandon -- cement plug	ok	POOH with 8 1/2" Clean-out bit from 1900 m to 1835 m. Engaged top-drive and broke circulation 2500 lpm, 96 bar, 80 RPM, 8 - 11 kNm. Circulated bottoms up while reciprocating string in 9 5/8" EZSVB setting area from 1825 m to 1835 m.
00:30	01:15	1817	plug abandon -- cement plug	ok	Pumped slug and Filled trip-tank.
01:15	04:30	0	plug abandon -- cement plug	ok	POOH with 8 1/2" Clean-out bit from 1817 m to surface on 5 1/2" DP and HWDP.
04:30	06:00	0	plug abandon -- cement plug	ok	Laid down 8 1/2" bit. Cleared and cleaned rig floor. Performed general rig maintenance.
06:00	00:00	0	interruption -- waiting on weather	ok	Performed general rig maintenance. Removed worn cement hose from cement manifold. ROV removed debris around template.

Drilling Fluid

Sample Time	10:00	22:00
Sample Point	Flowline	Active pit
Sample Depth mMD	0	0
Fluid Type	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.21	1.21
Funnel Visc (s)	-999.99	-999.99
Mf (I)		
Pm (I)		
Pm filtrate (I)		
Chloride (I)		
Calcium (I)		
Magnesium (I)		
Ph		
Excess Lime (I)		
Solids		
Sand (I)		
Water (I)		
Oil (I)		
Solids (I)		
Corrected solids (I)		
High gravity solids (I)		
Low gravity solids (I)		
Viscometer tests		
Plastic visc. (mPa.s)	40	35
Yield point (Pa)	9.5	7.5
Filtration tests		
Pm filtrate (I)		
Filtrate Lthp (I)		
Filtrate Hthp (I)		
Cake thickn API (I)		
Cake thickn HPHT (I)		
Test Temp HPHT (degC)	120	120
Comment		

