

Summary report

Wellbore: 15/9-F-15 D

Period: 2013-11-10 00:00 - 2013-11-11 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	1
Days Ahead/Behind (+/-):	
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2013-11-10 14:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (°):	
Pressure (°):	
Date Well Complete:	2013-12-02

Dist Drilled (m):	-999.99
Penetration rate (m/h):	-999.99
Hole Dia (in):	17.5
Pressure Test Type:	formation integrity test
Formation strength (°):	
Dia Last Casing (°):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	1484
Depth mTVD:	1448
Plug Back Depth mMD:	
Depth at formation strength mMD:	
Depth At Formation Strength mTVD:	
Depth At Last Casing mMD:	1368.4
Depth At Last Casing mTVD:	1340.4

Summary of activities (24 Hours)

RIH with 17 1/2" BHA.
Drilled cement and kicked off.
Drilled 17 1/2" hole.

Summary of planned activities (24 Hours)

Drill 17 1/2" hole.
Wait on weather.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
14:00	19:00	1403	drilling -- drill	ok	Drilled with reduced rate from 1373m to 1403m with 3000-4010 liter/min, 50 % return of formation at 1380m, 155-237 bar, 122 rpm, 6-12kNm, ROP 2-5 m/hr, WOB 3-5 ton, ECD 1,438 sg. Max gas 0,04% Obtained surveys as required
19:00	23:45	1484	drilling -- drill	ok	Drilled from 1403m to 1484m with 4000 liter/min, 235 bar, 80-120 rpm, 12-25 kNm, ROP 27-29 m/hr, WOB 2-10 ton, ECD 1,420 sg. Max gas 0,05 %. Obtained surveys as required
23:45	00:00	1484	drilling -- circulating conditioning	ok	Recorded SCR's.

Drilling Fluid

Sample Time	03:00	20:00
Sample Point	Flowline	Flowline
Sample Depth mMD	1539	1426
Fluid Type	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.4	1.4
Funnel Visc (s)	-999.99	-999.99
Mf (°)		
Pm (°)		
Pm filtrate (°)		
Chloride (°)		
Calcium (°)		
Magnesium (°)		
Ph		
Excess Lime (°)		
Solids		
Sand (°)		
Water (°)		
Oil (°)		
Solids (°)		
Corrected solids (°)		
High gravity solids (°)		
Low gravity solids (°)		
Viscometer tests		
Plastic visc. (mPa.s)	36	39
Yield point (Pa)	9	10
Filtration tests		
Pm filtrate (°)		
Filtrate Lthp (°)		
Filtrate Hthp (°)		
Cake thickn API (°)		
Cake thickn HPHT (°)		
Test Temp HPHT (degC)	120	120
Comment		

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	1368		1.03	estimated
00:00	1484		1.03	estimated

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
1389.4	1359.7	21.9	245.03	
1409.8	1378.6	21.44	249.87	
1469.5	1434.6	19.8	266.07	
1510	1472.8	18.52	273.32	
1551	1512	16.25	280.28	
1591	1550.5	15.05	294.29	
1631.1	1589.2	15.19	309.35	
1672.1	1628.7	15.54	316.07	

Lithology Information

Start Depth mMD	End Depth mMD	Start Depth TVD	End Depth TVD	Shows Description	Lithology Description
1390	1480				Claystone with traces of Limestone

Gas Reading Information

Time	Class	Depth to Top mMD	Depth to Bottom MD	Depth to Top mTVD	Depth to Bottom TVD	Highest Gas (%)	Lowest Gas ()	C1 (ppm)	C2 (ppm)	C3 (ppm)	IC4 (ppm)	IC5 (ppm)
00:00	drilling gas peak	1457		1421.6		.35		2847	0	0	0	0