

Summary report

Wellbore: 15/9-F-15 D

Period: 2013-11-13 00:00 - 2013-11-14 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	4
Days Ahead/Behind (+/-):	.6
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2013-11-10 14:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2013-12-02

Dist Drilled (m):	158
Penetration rate (m/h):	-999.99
Hole Dia (in):	17.5
Pressure Test Type:	formation integrity test
Formation strength (I):	
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	2190
Depth mTVD:	2094
Plug Back Depth mMD:	
Depth at formation strength mMD:	
Depth At Formation Strength mTVD:	
Depth At Last Casing mMD:	1368.4
Depth At Last Casing mTVD:	1340.4

Summary of activities (24 Hours)

Drilled 17 1/2" hole from 1929 m to 2190 m.
Waited on weather.

Summary of planned activities (24 Hours)

Circulate 17 1/2" hole clean and POOH into 20" shoe.
Wait on weather.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	02:45	1929	drilling -- circulating conditioning	ok	Circulated hole clean with 4500 liter/min, 280 bar. 3 x bottoms up. Racked back one stand each bottoms up.
02:45	03:00	1929	drilling -- pressure detection	ok	Performed flow check, ok.
03:00	04:30	1325	drilling -- trip	ok	POOH wet into 20" shoe with 17 1/2" BHA on 5 1/2" DP from 1929 m to 1325 m. Observed obstruction when passing 1378 meter with stabs, 10-15 Ton overpull. Ran back down to 1378 meter, sat down 15 Ton, not able to pass. Pulled back into shoe at 1325 meter.
04:30	06:45	1325	interruption -- waiting on weather	ok	Waited one weather, not able to discharge cuttings to vessel due to hard weather. Monitored well on triptank.
06:45	07:00	1380	drilling -- ream	ok	Washed down with 17 1/2" BHA from 1366 m to 1404 m at 3000 liter/min, 132 bar, 15 rpm, 8-25 kNm. Observed 25 Ton WOB when bit passes 1378 m, continued to wash down. Observed 5-10 Ton WOB when stabs passes 1378 meter.
07:00	07:15	1370	drilling -- trip	ok	Pulled back with 17 1/2" BHA on 5 1/2" DP from 1380 m to 1370 m. Observed obstruction when passing 1378 meter with stabs, 5-10 Ton overpull.
07:15	07:30	1384	drilling -- ream	ok	Slided down with 17 1/2" BHA from 1370 m to 1384 m at 3000 liter/min, 133 bar. Observed 20-21 Ton WOB when passes 1379-1382 m. Sat down 30 ton at 1395 meter, established rotation 15 rpm and attempted to wash down. No able to pass 1384 meter.
07:30	08:30	1325	drilling -- trip	ok	POOH wet into 20" shoe with 17 1/2" BHA on 5 1/2" DP from 1384 m to 1325 m.
08:30	13:45	1325	interruption -- waiting on weather	ok	Waited one weather, not able to discharge cuttings to vessel due to hard weather. Monitored well on triptank. Vessel came alongside at 12:00 hrs. Commenced cuttings discharge from rig ISO tanks.
13:45	14:30	1392	drilling -- trip	ok	RIH with 17 1/2" BHA from 1364 m to 1376m. Sat down 30 Ton at 1376 meter. Established circulation with 500 liter/min, 45 bar, 15 rpm, 5-28 kNm. Washed past 1376 meter with bit and stabilizers to 1392 m.
14:30	15:30	1444	drilling -- trip	ok	Washed down from 1392 m to 1444 m with 4450 liter/min, 267 bar, 30-60 rpm, 10-25 kNm.
15:30	16:45	2013	drilling -- trip	ok	RIH with 17 1/2" BHA from 1444 m to 2013 m.
16:45	17:30	2030	drilling -- trip	ok	Washed down from 2013 m to 2030 m with 4450 liter/min, 285 bar, 140 rpm, 10-19 kNm.
17:30	00:00	2190	drilling -- drill	ok	Drilled 17 1/2" hole from 2032 m to 2190 m with 4320 liter/min, 282-291 bar, 140 rpm, 15-22 kNm, ROP 32-36 m/hr, WOB 3-6 ton, ECD 1,42 sg. Ma x gas 0,2%.

Drilling Fluid

Sample Time	09:00	12:00	20:00
Sample Point	Flowline	Flowline	Flowline
Sample Depth mMD	1888	2035	2094
Fluid Type	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.4	1.4	1.4
Funnel Visc (s)	-999.99	-999.99	-999.99
Mf ()			
Pm ()			
Pm filtrate ()			
Chloride ()			
Calcium ()			
Magnesium ()			
Ph			
Excess Lime ()			
Solids			
Sand ()			

Water ()			
Oil ()			
Solids ()			
Corrected solids ()			
High gravity solids ()			
Low gravity solids ()			
Viscometer tests			
Plastic visc. (mPa.s)	33	35	33
Yield point (Pa)	10	10	9
Filtration tests			
Pm filtrate ()			
Filtrate Lthp ()			
Filtrate Hthp ()			
Cake thickn API ()			
Cake thickn HPHT ()			
Test Temp HPHT (degC)	120	120	120
Comment			

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	1380		1.03	estimated
00:00	2190.8		1.03	estimated

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
2035.6	1959.9	30.21	4.37	
2075.6	1994.4	30.3	4.6	
2116	2029.4	29.79	3.84	
2156.5	2064.6	29.75	3.56	

Lithology Information

Start Depth mMD	End Depth mMD	Start Depth TVD	End Depth TVD	Shows Description	Lithology Description
2000	2160				Claystone with minor dolomite and traces of Limestone and Sandstone