

Summary report

Wellbore: 15/9-F-15 D

Period: 2013-11-29 00:00 - 2013-11-30 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	20
Days Ahead/Behind (+/-):	10.3
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2013-11-10 14:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2013-12-02

Dist Drilled (m):	502
Penetration rate (m/h):	-999.99
Hole Dia (in):	8.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.6
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	3912
Depth mTVD:	3036.8
Plug Back Depth mMD:	
Depth at formation strength mMD:	3302
Depth At Formation Strength mTVD:	2848
Depth At Last Casing mMD:	3294.7
Depth At Last Casing mTVD:	

Summary of activities (24 Hours)

Drilling and geosteering 8 1/2" hole from 3410 m to 3912 m.

Summary of planned activities (24 Hours)

Drilling and geosteering 8 1/2" hole.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	05:45	3496	drilling -- drill	ok	Drilled 8 1/2" hole from 3370 m to 3496 m with 2400 lpm, 202 bar, 120 rpm, 16-23 kNm, 7 ton WOB. ROP 10 m/hr. ECD 1,51 SG. Max gas: 0,8 %. Reduced ROP to 10 m/hr @ 3471 m to 3496 m. Down link and take survey after connection.
05:45	06:00	3499	drilling -- drill	ok	Drilled 8 1/2" hole from 3496 m to 3499 m. with 2400 lpm, 211 bar, 120 rpm, 16-25 kNm, 5 ton WOB. ROP 25-30 m/hr. ECD 1,52 SG. Max gas: 2,77 %. Down link and take survey after connection.
06:00	07:15	3532	drilling -- drill	ok	Drilled 8 1/2" hole from 3499 m to 3532 m. with 2400 lpm, 212 bar, 120 rpm, 22-27 kNm, 4 ton WOB. ROP 25-30 m/hr. ECD 1,52 SG. Max gas: 1,9 %.
07:15	07:30	3532	drilling -- other	ok	Took SCR @ 3532 m, 1,32 SG. Pump 1. 20/30/40 stroke, 33/41/42 bar. Pump 2. 20/30/40 stroke, 22/32/44 bar.
07:30	16:00	3730	drilling -- drill	ok	Drilled 8 1/2" hole from 3532 m to 3730 m. with 2400 lpm, 218 bar, 120 rpm, 18-27 kNm, 3-5 ton WOB. ROP 25-30 m/hr. ECD 1,53 SG. Max gas: 2,16 % Down link and take survey after connection.
16:00	16:15	3730	drilling -- other	ok	Took SCR @ 3730 m, 1,32 SG. Pump 1. 20/30/40 stroke, 28/37/49 bar. Pump 2. 20/30/40 stroke, 27/38/50 bar.
16:15	00:00	3912	drilling -- drill	ok	Drilled 8 1/2" hole from 3499 m to 3532 m. with 2400 lpm, 228 bar, 120 rpm, 22-30 kNm, 4-9 ton WOB. ROP 25-30 m/hr. ECD 1,53 SG. Max gas: 2,51 % Down link and take survey after connection.

Drilling Fluid

Sample Time	03:00	09:00	14:00	21:45
Sample Point	Flowline	Active pit	Flowline	Flowline
Sample Depth mMD	3473	3299	3688	3858
Fluid Type	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.32	1.32	1.32	1.32
Funnel Visc (s)	-999.99	-999.99	-999.99	-999.99
Mf ()				
Pm ()				
Pm filtrate ()				
Chloride ()				
Calcium ()				
Magnesium ()				
Ph				
Excess Lime ()				
Solids				
Sand ()				
Water ()				
Oil ()				
Solids ()				
Corrected solids ()				
High gravity solids ()				
Low gravity solids ()				
Viscometer tests				
Plastic visc. (mPa.s)	37	41	37	36
Yield point (Pa)	12	11.5	11	10.5
Filtration tests				
Pm filtrate ()				
Filtrate Lthp ()				
Filtrate Hthp ()				
Cake thickn API ()				

Cake thickn HPHT ()				
Test Temp HPHT (degC)	120	120	120	120
Comment				

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	3300		1.14	estimated
00:00	3449		1.29	estimated
00:00	3914		1.18	estimated

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
3436.6	2898.1	69.87	96.73	
3477.6	2911.7	71.37	101.82	
3516.5	2923.1	74.54	106.98	
3556.8	2934.3	73.2	107.38	
3597.7	2944.9	76.6	107.41	
3637.6	2953.6	78.44	107.46	
3678.5	2961.4	79.55	108.18	
3718.3	2969	78.51	106.58	
3758.8	2978.7	73.62	104.51	
3798.6	2991.5	68.99	105.01	
3834.9	3005.4	65.9	107.78	
3878.4	3023.1	65.99	109.35	
3918.7	3039.5	65.98	109.47	

Log Information

Run No	Service Company	Depth Top mMD	Depth Bottom mTVD	Tool	BHST (degC)
104	Baker Hughes Inteq	3409	3912	ZoneTrak G - CoPilot - OnTrak - ORD - C C	-999.99

Lithology Information

Start Depth mMD	End Depth mMD	Start Depth mTVD	End Depth mTVD	Shows Description	Lithology Description
3409	3449	2888.5	2902		Interbedded Limestone and marl
3449	3483	2902	2913		Claystone
3483	3720	2913	2969.3		Sandstone with minor claystone beds
3720	3912	2969.3	3036.8		Sandstone with minor claystone beds

Gas Reading Information

Time	Class	Depth to Top mMD	Depth to Bottom MD	Depth to Top mTVD	Depth to Bottom TVD	Highest Gas (%)	Lowest Gas ()	C1 (ppm)	C2 (ppm)	C3 (ppm)	IC4 (ppm)	IC5 (ppm)
00:00	drilling gas peak	3458		2905.2		.86		8253	548	172	11	4
00:00	drilling gas peak	3484		2913.6		1.33		13234	896	350	26	12
00:00	drilling gas peak	3507		2920		2.73		26513	2367	1083	86	45
00:00	drilling gas peak	3527		2924.9		2.66		25782	2319	1077	87	46
00:00	drilling gas peak	3550		2932.1		3.35		32568	3039	1492	127	72
00:00	drilling gas peak	3557		2934.3		2.69		25362	2365	1167	100	57
00:00	drilling gas peak	3586		2941.6		2.22		19377	1946	1055	98	63
00:00	drilling gas peak	3604		2946.3		2.59		23814	2273	1165	105	65
00:00	drilling gas peak	3624		2950.4		3.05		28579	2675	1364	123	78
00:00	drilling gas peak	3729		2971.5		3.1		29836	2674	1289	112	71
00:00	drilling gas peak	3751		2976.6		3.46		33489	3064	1513	134	85
00:00	drilling gas peak	3791		2989		3.66		34386	3294	1703	155	101
00:00	drilling gas peak	3831		3003.5		3.65		33360	3272	1767	167	112
00:00	drilling gas peak	3857		3013.6		3.34		30603	2967	1569	148	100