

Summary report

Wellbore: 15/9-F-15 D

Period: 2013-12-20 00:00 - 2013-12-21 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	41
Days Ahead/Behind (+/-):	17
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2013-11-10 14:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (°):	
Pressure (°):	
Date Well Complete:	2013-12-02

Dist Drilled (m):	0
Penetration rate (m/h):	-999.99
Hole Dia (°):	
Pressure Test Type:	formation integrity test
Formation strength (°):	
Dia Last Casing (°):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	4685
Depth mTVD:	3212.3
Plug Back Depth mMD:	
Depth at formation strength mMD:	
Depth At Formation Strength mTVD:	
Depth At Last Casing mMD:	4683.6
Depth At Last Casing mTVD:	3212

Summary of activities (24 Hours)

POOH and L/O ME plug RT.
Cleaned and cleared rig floor.

*** Note ***

Further operations to supend F-15 D will be reported on F-1 B well intervention.

Summary of planned activities (24 Hours)

Well intervention on F-1 B

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	02:15	0	completion -- other	ok	POOH w/ ME plug RT on 3 1/2" DP from 850 m to surface. Avg. tripping speed 378 m/hr.
02:15	02:45	0	completion -- other	ok	Broke 3 1/2" DP stand and RT in foxhole. L/D plug RT.
02:45	03:30	0	completion -- other	ok	Changed handling equipment to 5 1/2". Cleaned and cleared rig floor. *** Note *** Further operations for suspending F-15 D will be reported on F-1B - well intervention.

Drilling Fluid

Sample Time	16:00
Sample Point	Active pit
Sample Depth mMD	4685
Fluid Type	Enviromul Yellow
Fluid Density (g/cm3)	1.32
Funnel Visc (s)	-999.99
Mf (°)	
Pm (°)	
Pm filtrate (°)	
Chloride (°)	
Calcium (°)	
Magnesium (°)	
Ph	
Excess Lime (°)	
Solids	
Sand (°)	
Water (°)	
Oil (°)	
Solids (°)	
Corrected solids (°)	
High gravity solids (°)	
Low gravity solids (°)	
Viscometer tests	
Plastic visc. (mPa.s)	38
Yield point (Pa)	12
Filtration tests	
Pm filtrate (°)	
Filtrate Lthp (°)	
Filtrate Hthp (°)	
Cake thickn API (°)	
Cake thickn HPHT (°)	
Test Temp HPHT (degC)	120
Comment	

