

Summary report

Wellbore: 15/9-F-1

Period: 2013-07-27 00:00 - 2013-07-28 00:00

Status:	normal
Report creation time:	2018-05-03 13:50
Report number:	11
Days Ahead/Behind (+/-):	
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2007-11-28 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2013-08-20

Dist Drilled (m):	-999.99
Penetration rate (m/h):	-999.99
Hole Dia (in):	26
Pressure Test Type:	
Formation strength (g/cm3):	0
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	1355
Depth mTVD:	1343
Plug Back Depth mMD:	
Depth at formation strength mMD:	0
Depth At Formation Strength mTVD:	0
Depth At Last Casing mMD:	220.9
Depth At Last Casing mTVD:	220.9

Summary of activities (24 Hours)

Pulled and lubricated out of hole with 26" bottom hole assembly from 1355m MD to 221m MD.
Performed viper trip to TD at 1355m MD.
Pulled out of hole with 26" bottom hole assembly from 1355m MD to 250m MD.

Summary of planned activities (24 Hours)

Lay down 26" bottom hole assembly to deck.
Rig up to run 20" casing.
Run 20" casing.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	01:30	1245	drilling -- trip	ok	Pulled out of hole with 26" bottom hole assembly from 1355m MD to 1245m MD. At 1245m MD took 10MT overpull. Attempted to get past restriction several times up to 30MT - no go. Attempted to pass restriction with 10 rpm - no go - string torqued up at 30 kNm.
01:30	02:00	1222	drilling -- trip	ok	Lubricated out of hole with 26" bottom hole assembly at 500 lpm seawater and 10 rpm from 1245m MD to 1222m MD. Pumped a total of one string volume. Attempted to pull s tring without circulation with up to 25MT - no go.
02:00	02:30	1182	drilling -- trip	ok	Lubricated out of hole with 26" bottom hole assembly at 1000 lpm and 10 rpm from 1222m MD to 1182m MD.
02:30	05:00	543	drilling -- trip	ok	Pulled out of hole with 26" bottom hole assembly from 1182m MD to 543m MD. At 543m MD, observed 30MT overpull.
05:00	05:45	506	drilling -- trip	ok	Lubricated out of hole with 26" bottom hole assembly from 543m MD to 506m MD with 1500 lpm and 30 rpm.
05:45	07:00	347	drilling -- trip	ok	Pulled out of hole with 26" bottom hole assembly from 506m MD to 347m MD. Observed tight spots at 505m MD, 488m MD, 479m MD and 440m MD with maximum 30MT ov erpull.
07:00	07:15	347	drilling -- trip	ok	Cleaned PS21 slips due to excessive clay on pipe body.
07:15	07:30	347	drilling -- drill	ok	Performed prejob meeting prior to perform wiper trip to TD.
07:30	08:45	221	drilling -- trip	ok	Pulled out of hole with 26" bottom hole assembly from 347m MD to 221m MD. Observed tight spots at 284m MD and 272m MD with maximum 20MT overpull.
08:45	09:00	221	drilling -- ream	ok	Established circulation at 4500 lpm and 128 bar to clean bottom hole assembly for clay.
09:00	17:15	1355	drilling -- ream	ok	Ran in hole with 26" bottom hole assembly from 221m MD to 1355m MD. Washed and reamed areas from 381m - 390m, 1317m - 1328m and 1328m - 1355m with 3000 lpm, 72-80 bar and 40 rpm.
17:15	18:15	1355	drilling -- circulatin g conditioning	ok	Pumped 20m3 hi-visc, 30m3 seawater, 30m3 hi-visc and 100m3 seawater at 3000 lpm, 72 bar and 40 rpm.
18:15	20:00	1355	drilling -- circulatin g conditioning	ok	Displaced hole to 1.35 sg KCl water based mud at 4600 lpm and 177 bar.
20:00	21:00	1287	drilling -- trip	ok	Pulled out of hole with 26" bottom hole assembly from 1355m MD to 1334m MD. At 1334m MD observed 20MT overpull. Attempted to pass restriction several times with up to 45MT overpull - no go. Lubricated past restriction with 300 lpm from 1334m MD to 1287m MD with 30MT overpull.
21:00	00:00	350	drilling -- trip	ok	Pulled out of hole with 26" bottom hole assembly from 1287m MD to 350m MD. Observed tight spots at 1040m MD, 635m MD and 556m MD with maximum 10MT overpull.
Meanwhile: While pulling out of hole, ROV jetted drillstring at seabed due to excessive clay on pipe body with good success.					

Drilling Fluid

Sample Time	00:30	01:00	06:00
Sample Point	Flowline	Reserve pit	Reserve pit
Sample Depth mMD	-999.99	-999.99	437
Fluid Type	Seawater	KCl/Polymer/GEM	Spud Mud
Fluid Density (g/cm3)	1.03	1.35	1.03
Funnel Visc (s)	-999.99	110	120
Mf ()			
Pm ()			
Pm filtrate ()			
Chloride ()			
Calcium ()			
Magnesium ()			
Ph			
Excess Lime ()			
Solids			
Sand ()			
Water ()			
Oil ()			
Solids ()			
Corrected solids ()			
High gravity solids ()			

Low gravity solids ()			
Viscometer tests			
Plastic visc. (mPa.s)	-999.99	28	-999.99
Yield point (Pa)	-999.99	11.5	-999.99
Filtration tests			
Pm filtrate ()			
Filtrate Lthp ()			
Filtrate Hthp ()			
Cake thickn API ()			
Cake thickn HPHT ()			
Test Temp HPHT ()			
Comment			

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
1355	1342.9	10	310	