

Summary report

Wellbore: 15/9-F-1

Period: 2013-08-08 00:00 - 2013-08-09 00:00

Status:	normal
Report creation time:	2018-05-03 13:50
Report number:	23
Days Ahead/Behind (+/-):	.9
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2007-11-28 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2013-08-20

Dist Drilled (m):	164
Penetration rate (m/h):	-999.99
Hole Dia (in):	17.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.55
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	2602
Depth mTVD:	2583
Plug Back Depth mMD:	
Depth at formation strength mMD:	1358
Depth At Formation Strength mTVD:	1345.9
Depth At Last Casing mMD:	1348.4
Depth At Last Casing mTVD:	1336.4

Summary of activities (24 Hours)

Drilled and orientated 17 1/2" hole from 2438 m MD to TD at 2602 m MD.
Circulated hole clean.

Summary of planned activities (24 Hours)

Circulate hole clean.
POOH with 17 1/2" BHA.
Retrieve wear bushing.
Rig up and run 13 3/8" casing.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	21:45	2602	drilling -- drill	ok	Drilled and oriented 17 1/2" hole from 2438 m MD to 2602 m MD with 4430 liter/min, 280 - 290 bar, 90-140 rpm, 16-27 kNm, WOB 15-20 Ton, ROP 3-18 m/h, 1,39 - 1,41 sg ECD. Average drilling ROP 7,5 m/hr Meanwhile picked up and racked back 13 3/8" casing in derrick.
21:45	00:00	2602	drilling -- circulating conditioning	ok	Reciprocated string while circulating hole clean with 4365 l/min, 275-280 bar, 120 rpm, 5-9 kNm, ECD 1,391 sg. Racked back 1 stand after 1 x bottoms up.

Drilling Fluid

Sample Time	04:00	11:00	16:00	21:40
Sample Point	Active pit	Flowline	Flowline	Flowline
Sample Depth mMD	2602	2526	2559	2597
Fluid Type	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.4	1.4	1.4	1.4
Funnel Visc (s)	-999.99	-999.99	-999.99	-999.99
Mf ()				
Pm ()				
Pm filtrate ()				
Chloride ()				
Calcium ()				
Magnesium ()				
Ph				
Excess Lime ()				
Solids				
Sand ()				
Water ()				
Oil ()				
Solids ()				
Corrected solids ()				
High gravity solids ()				
Low gravity solids ()				
Viscometer tests				
Plastic visc. (mPa.s)	33	33	34	33
Yield point (Pa)	10	9.5	9.5	10.5
Filtration tests				
Pm filtrate ()				
Filtrate Lthp ()				
Filtrate Hthp ()				
Cake thickn API ()				
Cake thickn HPHT ()				
Test Temp HPHT (degC)	120	120	120	120
Comment				

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	1355		.99	estimated
00:00	2602		1	estimated

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
2436.7	2313.8	30.19	35.59	
2470.8	2343.3	30.22	36.84	
2517.2	2383.4	30.25	36.59	
2557.9	2418.6	30.19	34.71	
2587	2443.7	30.19	33.06	

Log Information

Run No	Service Company	Depth Top mMD	Depth Bottom mTVD	Tool	BHST (degC)
101	Baker Hughes Inteq	1355	2602	ZoneTrak G - OnTrak	-999.99

Stratigraphic Information

Depth to Top of Formation mMD	Depth to Top of Formation mTVD	Description
2459	2333	Sele Fm
2527	2392	Lista Fm

Lithology Information

Start Depth mMD	End Depth mMD	Start Depth mTVD	End Depth mTVD	Shows Description	Lithology Description
2430	2440	2308	2316.7		Balder - tuffaceous Claystones
2450	2520	2325.3	2385.8		Sele - Claystones with traces of tuff
2530	2602	2394.4	2456.7		Lista - Claystones with limestone stringers