

Summary report

Wellbore: 15/9-F-1

Period: 2013-08-14 00:00 - 2013-08-15 00:00

Status:	normal
Report creation time:	2018-05-03 13:50
Report number:	29
Days Ahead/Behind (+/-):	5.2
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2007-11-28 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2013-08-20

Dist Drilled (m):	300
Penetration rate (m/h):	-999.99
Hole Dia (in):	8.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.55
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	2905
Depth mTVD:	2727.1
Plug Back Depth mMD:	
Depth at formation strength mMD:	2605
Depth At Formation Strength mTVD:	2459.2
Depth At Last Casing mMD:	2595.4
Depth At Last Casing mTVD:	2446.8

Summary of activities (24 Hours)

POOH and laid down 12 1/4" BHA.
Made up and RIH with 8 1/2" drilling BHA.
Drilled 8 1/2" hole to 2905 meter.

Summary of planned activities (24 Hours)

Drill 8 1/2" to TD.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	00:30	0	drilling -- drill	ok	Performed Pre-job Meeting prior to make up 8 1/2" BHA. Changed to 5" handling equipment.
00:30	06:00	151	drilling -- trip	ok	Picked up and made up 8 1/2" drilling BHA and RIH from surface to 151 meter.
06:00	07:15	1011	drilling -- trip	ok	RIH with 8 1/2" BHA on 5 1/2" HWDP / DP from 151 m to 1011 m. Average tripping speed 688 m/hr.
07:15	08:00	1011	drilling -- trip	ok	Tested MWD tools with 2000 liter/min, 118 bar.
08:00	10:00	2585	drilling -- trip	ok	RIH with 8 1/2" BHA on 5 1/2" HWDP / DP from 1011m to 2585 m. Average tripping speed 787 m/hr. Filled pipe every 1000 meter.
10:00	11:00	2605	drilling -- trip	ok	Washed down from 2585 m to 2605 m with 1800 liter/min, 111 bar, 60 rpm, 9-13 kNm.
11:00	18:45	2779	drilling -- drill	ok	Drilled and oriented 8 1/2" hole from 2605 m MD to 2779 m MD with 1990 - 2389 liter/min, 142 - 207 bar, 60-130 rpm, 11-19 kNm, WOB 5-10 Ton, ROP 37-42 m /h, 1,31 - 1,34 sg ECD. Average drilling ROP 23 m/hr Meanwhile picked up and racked back 10 3/4" casing in derrick.
18:45	00:00	2905	drilling -- drill	ok	Drilled and oriented 8 1/2" hole from 2779 m MD to 2905 m MD with 2400 - 2470 liter/min, 207 - 211 bar, 130-160 rpm, 17-21 kNm, WOB 5-12 Ton, ROP 39-18 m/h, 1,34 - 1,35 sg ECD. Average drilling ROP 24 m/hr Meanwhile picked up and racked back 10 3/4" casing in derrick.

Drilling Fluid

Sample Time	02:00	12:00	16:30	23:00
Sample Point	Flowline	Flowline	Flowline	Flowline
Sample Depth mMD	2946	2602	2704	2878
Fluid Type	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.28	1.28	1.28	1.28
Funnel Visc (s)	-999.99	-999.99	-999.99	-999.99
Mf ()				
Pm ()				
Pm filtrate ()				
Chloride ()				
Calcium ()				
Magnesium ()				
Ph				
Excess Lime ()				
Solids				
Sand ()				
Water ()				
Oil ()				
Solids ()				
Corrected solids ()				
High gravity solids ()				
Low gravity solids ()				
Viscometer tests				
Plastic visc. (mPa.s)	32	30	33	33
Yield point (Pa)	9.5	6	7.5	8.5
Filtration tests				

Pm filtrate ()				
Filtrate Lthp ()				
Filtrate Hthp ()				
Cake thickn API ()				
Cake thickn HPHT ()				
Test Temp HPHT (degC)	120	120	120	120
Comment				

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	2631		.85	estimated
00:00	2905		1.04	estimated

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
2653.2	2501.9	27.05	19.76	
2693.7	2538	26.44	14.67	
2733.9	2574	26.47	6.38	
2774.3	2610.2	26.45	356.36	
2814.8	2646.5	26.44	349.52	
2855.3	2682.7	26.84	342.3	
2895.1	2717.9	29.13	334.29	
2935.6	2753	30.82	327.98	

Stratigraphic Information

Depth to Top of Formation mMD	Depth to Top of Formation mTVD	Description
2631	2482.2	Ty Fm
2769	2605.5	Ekofisk Fm
2788	2622.5	Tor Fm

Lithology Information

Start Depth mMD	End Depth mMD	Start Depth mTVD	End Depth mTVD	Shows Description	Lithology Description
2605.3	2631	2459.6	2482.2		Lista - Claystones with limestone stringers
2631	2769	2482.2	2605.5		Ty - Sandstones and claystones
2769	2905	2605.5	2727.1		Shetland Limestones with traces of Dolomite