

Summary report

Wellbore: 15/9-F-1

Period: 2013-08-15 00:00 - 2013-08-16 00:00

Status:	normal
Report creation time:	2018-05-03 13:50
Report number:	30
Days Ahead/Behind (+/-):	7.1
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2007-11-28 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2013-08-20

Dist Drilled (m):	219
Penetration rate (m/h):	-999.99
Hole Dia (in):	8.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.55
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	3364
Depth mTVD:	3083
Plug Back Depth mMD:	
Depth at formation strength mMD:	2605
Depth At Formation Strength mTVD:	2459.2
Depth At Last Casing mMD:	2595.4
Depth At Last Casing mTVD:	2446.8

Summary of activities (24 Hours)

Drilled and orientated 8 1/2" hole from 3145 m MD to 3364 m MD.
Picked up and racked back casing offline.

Summary of planned activities (24 Hours)

Drill and orientate 8 1/2" hole to TD.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	11:15	3145	drilling -- drill	ok	Drilled and oriented 8 1/2" hole from 2905 m MD to 3145m MD with 2450 - 2570 liter/min, 202 - 216 bar, 160 rpm, 18-21 kNm, WOB 4-12 Ton, ROP 18-25 m/h, 1,35 - 1,37 sg ECD. Average drilling ROP 21 m/hr Meanwhile picked up and racked back 9 5/8" casing in derrick.
11:15	11:30	3145	drilling -- other	ok	Recorded SCR's
11:30	16:30	3253	drilling -- drill	ok	Drilled and oriented 8 1/2" hole from 3145 m MD to 3253 m MD with 2570 - 2707 liter/min, 205 - 214 bar, 160 rpm, 17-23 kNm, WOB 4-8 Ton, ROP 18-25 m/h, 1,37 - 1,39 sg ECD. Average drilling ROP 22 m/hr Increased MW from 1,28 sg to 1,32 sg while drilling. Meanwhile picked up and racked back 9 5/8" casing in derrick.
16:30	16:45	3253	drilling -- survey	ok	Pulled off bottom and trouble shoot Sonic tool failure. Sonic tool not fuctional.
16:45	00:00	3364	drilling -- drill	ok	Drilled and oriented 8 1/2" hole from 3253 m MD to 3364 MD with 2446 - 2570 liter/min, 205 - 213 bar, 160 rpm, 18-23 kNm, WOB 4-8 Ton, ROP 11-22 m/h, 1, 38 - 1,39 sg ECD. Average drilling ROP 15 m/hr Meanwhile picked up and racked back 9 5/8" casing in derrick. Total 44 stands racked back.

Drilling Fluid

Sample Time	01:00	11:00	17:00	20:00
Sample Point	Flowline	Flowline	Flowline	Flowline
Sample Depth mMD	3387	3148	3259	3308
Fluid Type	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.32	1.28	1.32	1.32
Funnel Visc (s)	-999.99	-999.99	-999.99	-999.99
Mf ()				
Pm ()				
Pm filtrate ()				
Chloride ()				
Calcium ()				
Magnesium ()				
Ph				
Excess Lime ()				
Solids				
Sand ()				
Water ()				
Oil ()				
Solids ()				
Corrected solids ()				
High gravity solids ()				
Low gravity solids ()				
Viscometer tests				
Plastic visc. (mPa.s)	31	31	32	29
Yield point (Pa)	8	8	8.5	8.5
Filtration tests				
Pm filtrate ()				

Filtrate Lthp ()				
Filtrate Hthp ()				
Cake thickn API ()				
Cake thickn HPHT ()				
Test Temp HPHT (degC)	120	120	120	120
Comment				

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	2631		.85	estimated
00:00	3364		1.28	estimated

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
2975.9	2787	33.73	322.9	
3016.3	2820	36.82	316.6	
3056.6	2852	38.42	310.99	
3097.1	2883.2	40.86	304.69	
3136.9	2912.2	45.54	301.79	
3177.3	2939.4	49.5	301.46	
3217.8	2967	44.85	301.22	
3257.9	2996.4	40.65	301.61	
3298.5	3028.1	36.47	301.87	
3338.7	3061.2	32.86	302.97	
3379	3095.9	28.3	302.94	

Stratigraphic Information

Depth to Top of Formation mMD	Depth to Top of Formation mTVD	Description
2971	2783	Hod Fm
3066	2859.3	Blodøks Fm
3111	2893	Hidra Fm
3147	2919	Rødby Fm
3216	2965	Åsgard Fm
3270	3006	Draupne Fm
3320	3045.6	Heather Fm.

Lithology Information

Start Depth mMD	End Depth mMD	Start Depth mTVD	End Depth mTVD	Shows Description	Lithology Description
2905	3111	2727.1	2893.5		Limestones
3111	3270	2893.5	3005.7		Marls and Limestones
3270	3320	3005.7	3045.4		Claystone, carbonaceous
3320	3364	3045.4	3082.8		Sandstones

Gas Reading Information

Time	Class	Depth to Top mMD	Depth to Bottom MD	Depth to Top mTVD	Depth to Bottom TVD	Highest Gas (%)	Lowest Gas ()	C1 (ppm)	C2 (ppm)	C3 (ppm)	IC4 (ppm)	IC5 (ppm)
00:00	drilling gas peak	3051		2846.7		.34		2395	103	58	8	5
00:00	drilling gas peak	3280		3013.7		.8		6301	312	110	8	4
00:00	drilling gas peak	3298		3027		.94		7377	369	133	9	5
00:00	drilling gas peak	3316		3042.5		.96		7410	538	200	14	8