

Summary report

Wellbore: 15/9-F-1

Period: 2013-08-19 00:00 - 2013-08-20 00:00

Status:	normal
Report creation time:	2018-05-03 13:50
Report number:	34
Days Ahead/Behind (+/-):	11.6
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2007-11-28 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2013-08-20

Dist Drilled (m):	-999.99
Penetration rate (m/h):	-999.99
Hole Dia (in):	8.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.55
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	3632
Depth mTVD:	3328
Plug Back Depth mMD:	
Depth at formation strength mMD:	2605
Depth At Formation Strength mTVD:	2459.2
Depth At Last Casing mMD:	2595.4
Depth At Last Casing mTVD:	2446.8

Summary of activities (24 Hours)

Re-logged open hole with Sonic tool.
POOH with 8 1/2" logging BHA.

Summary of planned activities (24 Hours)

POOH with 8 1/2" logging BHA.
Pick up and RIH with 3 1/2" cement stinger.
Set P&A plug 1+2.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	01:00	3347	interruption -- other	ok	Recorded pressure points.
01:00	01:30	3620	interruption -- other	ok	RIH with 8 1/2" BHA on 5 1/2" DP from 3347 m to 3620 m. Reduced speed due to hole condition.
01:30	07:45	3333	formation evaluation -- log	ok	Back reamed OOH while re-logging from 3620 m to 3333 m with 2540 liter/min, 170 bar, 100 rpm, 12-22 kNm.
07:45	09:15	3295	formation evaluation -- log	ok	Observed tight spot at 3333 meter, attempted to work through without rotation. Hole packed off. Pulled back to 3295 without flow. Ran back in to 3335 with 1650 liter/min, 87 bar. Re-logged stand from 3333 m to 3295 m.
09:15	10:30	3255	formation evaluation -- log	ok	Pumped OOH from 3295 m to 3257 m, experienced tight hole. Ran back in to 3273 m without circulation. Re-logged stand from 3273 m to 3255 m.
10:30	19:30	2652	formation evaluation -- log	ok	Back reamed OOH while re-logging from 3255 m to 2652 m with 2540 liter/min, 160-168 bar, 100-120 rpm, 11-21 kNm.
19:30	20:30	2584	formation evaluation -- log	ok	POOH while re-logging from 2652 m to 2584 m with 2540 liter/min, 160-168 bar.
20:30	21:45	2584	formation evaluation -- log	ok	Circulated bottoms up with 2430 liter/min, 218 bar, 130 rpm.
21:45	22:15	2584	formation evaluation -- log	ok	Flow checked well, OK.
22:15	22:30	2584	drilling -- bop activities	ok	Function tested BOP.
22:30	23:00	2584	drilling -- trip	ok	Pumped 4 m3 1,56 sg slug with 1000 liter/min, 22 bar.
23:00	00:00	1800	drilling -- trip	ok	POOH with 8 1/2" BHA on 5 1/2" DP from 2584 m to 1800 m. Average tripping speed 784 meter/hr.

Drilling Fluid

Sample Time	01:00	13:00
Sample Point	Active pit	Flowline
Sample Depth mMD	3632	3632
Fluid Type	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.32	1.32
Funnel Visc (s)	-999.99	-999.99
Mf ()		
Pm ()		
Pm filtrate ()		
Chloride ()		
Calcium ()		
Magnesium ()		
Ph		
Excess Lime ()		
Solids		
Sand ()		
Water ()		
Oil ()		
Solids ()		
Corrected solids ()		
High gravity solids ()		
Low gravity solids ()		
Viscometer tests		
Plastic visc. (mPa.s)	35	34
Yield point (Pa)	10	11
Filtration tests		

Pm filtrate ()		
Filtrate Lthp ()		
Filtrate Hthp ()		
Cake thickn API ()		
Cake thickn HPHT ()		
Test Temp HPHT (degC)	120	120
Comment		