

Summary report

Wellbore: 15/9-F-1 A

Period: 2013-08-23 00:00 - 2013-08-24 00:00

Status:	normal
Report creation time:	2018-05-03 13:50
Report number:	1
Days Ahead/Behind (+/-):	1.2
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2013-08-20 05:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2013-08-29

Dist Drilled (m):	384
Penetration rate (m/h):	-999.99
Hole Dia (in):	8.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.55
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	3004
Depth mTVD:	2801.4
Plug Back Depth mMD:	
Depth at formation strength mMD:	2605
Depth At Formation Strength mTVD:	2459.2
Depth At Last Casing mMD:	2595.4
Depth At Last Casing mTVD:	2446.8

Summary of activities (24 Hours)

Kicked off well from F-1
Drilled and steered 8 1/2" section to 3004 m MD.

Summary of planned activities (24 Hours)

Drilling and orienting 8 1/2" section

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
05:00	07:00	2632	drilling -- drill	ok	Drilled and oriented 8 1/2" hole from 2620 m to 2632 m, controlled ROP 10 m/hr. WOB 5 - 12 tonne. 2000 l/min/ bar. 80 rpm / 8 - 12 kNm. Started bleeding in LCM premix, 4m3 per stand for drilling Ty Fm.
07:00	09:00	2673	drilling -- drill	ok	Drilled and oriented 8 1/2" hole through Ty Fm. from 2632 m to 2673 m, average ROP 20 m/hr. WOB 5 - 12 tonne. 2000 - 2400 l/min/ 143 - 170 bar, ECD: 1,34. 80 - 140 rpm / 11 - 22 kNm. Increased rpm after top stab out of casing shoe. Bleed in LCM premix as per plan to maintain particle concentration.
09:00	12:30	2771	drilling -- drill	ok	Drilled and oriented 8 1/2" hole through Ty Fm. from 2673 m to 2771 m maintaining constant drilling parameters and bleeding in LCM premix, average ROP : 28 m/h. WOB 5 - 12 tonne. 2400 l/min/ 170 - 175 bar. 140 rpm / 12 - 20 kNm. ECD 1,36 SG
12:30	17:00	2857	drilling -- drill	ok	Drilled and oriented 8 1/2" hole in Shetland Gp. from 2771 m to 2857 m, average ROP: 19 m/hr. WOB 5 - 12 tonne. 2400 l/min/ 175 bar. 140-160 rpm / 12 - 25 kNm. ECD: 1,37. Increased rpm to 160 to combat high stick slip.
17:00	17:15	2857	drilling -- other	ok	Took SCR
17:15	19:00	2892	drilling -- drill	ok	Drilled and oriented 8 1/2" hole in Shetland Gp. from 2857 m to 2892 m, average ROP: 20 m/hr. WOB 10 - 12 tonne. 2400 l/min/ 175 bar. 160 rpm / 11 - 26 kNm. ECD 1,37. Added four sacks Baracarb 50/150 and Steelseal 100/400 per stand to maintain LCM background concentration.
19:00	00:00	3004	drilling -- drill	ok	Drilled and oriented 8 1/2" hole in Shetland Gp. from 2892 m to 3004 m, average ROP: 22 m/hr. WOB 10 - 14 tonne. 2400 l/min/ 175 - 178 bar. 160 rpm / 12 - 25 kNm. ECD 1,37 - 1,38 SG. Added four sacks Baracarb 50/150 and Steelseal 100/400 per stand to maintain LCM background concentration.

Drilling Fluid

Sample Time	02:00	09:00	15:00	20:45
Sample Point	Flowline	Flowline	Flowline	Flowline
Sample Depth mMD	3051	2667	2819	2934
Fluid Type	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.3	1.28	1.28	1.28
Funnel Visc (s)	-999.99	-999.99	-999.99	-999.99
Mf ()				
Pm ()				
Pm filtrate ()				
Chloride ()				
Calcium ()				
Magnesium ()				
Ph				
Excess Lime ()				
Solids				
Sand ()				
Water ()				
Oil ()				
Solids ()				
Corrected solids ()				
High gravity solids ()				
Low gravity solids ()				
Viscometer tests				
Plastic visc. (mPa.s)	34	30	31	35
Yield point (Pa)	13	9.5	8.5	9.5
Filtration tests				
Pm filtrate ()				
Filtrate Lthp ()				
Filtrate Hthp ()				

Cake thickn API ()				
Cake thickn HPHT ()				
Test Temp HPHT (degC)	120	120	120	120
Comment				

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	2620		.86	estimated
00:00	3004		1.04	estimated

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
2621.1	2473.2	29.93	25.32	
2647.4	2496.2	28.62	18.88	
2688.1	2532.2	27.17	11.08	
2727.5	2567.3	26.91	3.24	
2768.6	2603.9	26.81	353.59	
2809.1	2639.9	28.15	343.98	
2849.4	2675.1	30.2	333.38	
2889.6	2709.5	32.18	322.06	
2930.4	2743.6	34.72	315.89	
2970.7	2775.9	38.45	310.87	
3010.9	2806.6	42.29	305.91	

Stratigraphic Information

Depth to Top of Formation mMD	Depth to Top of Formation mTVD	Description
2628	2479.2	Ty Fm
2771	2606.1	Ekofisk Fm
2790	2623	Tor Fm
2987	2788.6	Hod Fm

Lithology Information

Start Depth mMD	End Depth mMD	Start Depth mTVD	End Depth mTVD	Shows Description	Lithology Description
2620	2632	2472.3	2482.7		Claystone (Lista)
2632	2771	2482.7	2606.1		Sandstone with occasional Claystone (Ty)
2771	2790	2606.1	2623		Limestone (Ekofisk)
2790	2987	2623	2788.6		Limestone (Tor)
2987	3004	2788.6	2801.4		Limestone (Hod)