

Summary report

Wellbore: 15/9-F-1 A

Period: 2013-08-24 00:00 - 2013-08-25 00:00

Status:	normal
Report creation time:	2018-05-03 13:50
Report number:	2
Days Ahead/Behind (+/-):	1.6
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2013-08-20 05:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2013-08-29

Dist Drilled (m):	422
Penetration rate (m/h):	-999.99
Hole Dia (in):	8.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.55
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	3426
Depth mTVD:	3055.6
Plug Back Depth mMD:	
Depth at formation strength mMD:	2605
Depth At Formation Strength mTVD:	2459.2
Depth At Last Casing mMD:	2595.4
Depth At Last Casing mTVD:	2446.8

Summary of activities (24 Hours)

Drilled and oriented 8 1/2" hole from 3004 m to 3426 m.

Summary of planned activities (24 Hours)

Drilling 8 1/2" hole to TD, circulating hole clean.
POOH and relogging reservoir, taking pressure points.
POOH.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	03:00	3070	drilling -- drill	ok	Drilled and oriented 8 1/2" hole from 3004 m to 3070 m, average ROP: 22 m/h WOB 5 - 12 tonne. 2400 l/min/ 175 - 180 bar. 160 rpm / 15 - 22 kNm. ECD 1,38 SG. Started to increase MW from 1,28 SG to 1,32 SG.
03:00	04:30	3094	drilling -- drill	ok	Drilled and oriented 8 1/2" hole from 3070 m to 3094 m, average ROP: 15 m/hr. WOB 5 - 8 tonne. 2400 l/min/ 183 bar. 160 rpm / 15 - 20 kNm. ECD 1,39 SG. Experienced problems in achieving required build rate, controlled ROP to 15 m/hr, set build force to 97%, reduced walk force Increased MW from 1,28 SG to 1,32 SG. Maintained LCM background concentration
04:30	08:00	3128	drilling -- drill	ok	Drilled and oriented 8 1/2" hole from 3094 m to 3128 m, average ROP: 9,7 m/hr. WOB 1 - 3 tonne. 2400 l/min/ 183 bar. 160 rpm / 12 - 17 kNm. ECD 1,40 SG. Controlled ROP to 10 m/hr to improve steering capability. MW in - out: 1,32 SG. Maintained LCM background concentration
08:00	19:00	3317	drilling -- drill	ok	Drilled and oriented 8 1/2" hole from 3128 m to 3317 m, average ROP: 17,2 m/hr. WOB 2 - 14 tonne. 2400 l/min/ 183 - 189 bar. 160 rpm / 12 - 24 kNm. ECD 1,40 SG. Took SCR's at 3303 m Maintained LCM background concentration
19:00	00:00	3426	drilling -- drill	ok	Drilled and oriented 8 1/2" hole from 3317 m to 3426 m, average ROP: 22 m/hr. WOB 5 - 12 tonne. 2400 l/min/ 188 - 195 bar. 160 rpm / 14 - 25 kNm. ECD 1,42 SG. Maintained LCM background concentration

Drilling Fluid

Sample Time	02:00	09:00	15:00	19:30
Sample Point	Flowline	Flowline	Flowline	Flowline
Sample Depth mMD	3474	3154	3255	3337
Fluid Type	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.32	1.32	1.32	1.32
Funnel Visc (s)	-999.99	-999.99	-999.99	-999.99
Mf ()				
Pm ()				
Pm filtrate ()				
Chloride ()				
Calcium ()				
Magnesium ()				
Ph				
Excess Lime ()				
Solids				
Sand ()				
Water ()				
Oil ()				
Solids ()				
Corrected solids ()				
High gravity solids ()				
Low gravity solids ()				
Viscometer tests				
Plastic visc. (mPa.s)	34	37	38	38
Yield point (Pa)	13	10.5	10.5	13.5

Filtration tests				
Pm filtrate ()				
Filtrate Lthp ()				
Filtrate Hthp ()				
Cake thickn API ()				
Cake thickn HPHT ()				
Test Temp HPHT (degC)	120	120	120	120
Comment				

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	2620		.86	estimated
00:00	3358		1.29	estimated
00:00	3426		1.28	estimated

Stratigraphic Information

Depth to Top of Formation mMD	Depth to Top of Formation mTVD	Description
3104	2871.5	Blodøks Fm
3193	2922.3	Rødby Fm
3279	2962.8	Åsgard Fm
3358	3008.3	Draupne Fm

Lithology Information

Start Depth mMD	End Depth mMD	Start Depth mTVD	End Depth mTVD	Shows Description	Lithology Description
3004	3104	2801.4	2871		Limestone (Hod)
3104	3153	2871.7	2900		Limestone (Blodøks)
3153	3193	2900	2922.3		Limestone (Hidra)
3193	3279	2922.3	2961.5		Limestone (Rødby)
3279	3358	2691.5	3008.3		Marl (Åsgard)
3358	3429	3008.3	3058		Claystone (Draupne)

Gas Reading Information

Time	Class	Depth to Top mMD	Depth to Bottom MD	Depth to Top mTVD	Depth to Bottom TVD	Highest Gas (%)	Lowest Gas ()	C1 (ppm)	C2 (ppm)	C3 (ppm)	IC4 (ppm)	IC5 (ppm)
00:00	drilling gas peak	3074		2851.3		.66		4686	210	123	15	10