

Summary report

Wellbore: 15/9-F-1 A

Period: 2013-08-25 00:00 - 2013-08-26 00:00

|                          |                  |
|--------------------------|------------------|
| Status:                  | normal           |
| Report creation time:    | 2018-05-03 13:50 |
| Report number:           | 3                |
| Days Ahead/Behind (+/-): | 1.9              |
| Operator:                | Statoil          |
| Rig Name:                | MÆRSK INSPIRER   |
| Drilling contractor:     | Maersk Drilling  |
| Spud Date:               | 2013-08-20 05:00 |
| Wellbore type:           |                  |
| Elevation RKB-MSL (m):   | 54.9             |
| Water depth MSL (m):     | 91               |
| Tight well:              | Y                |
| HPHT:                    | Y                |
| Temperature (I):         |                  |
| Pressure (I):            |                  |
| Date Well Complete:      | 2013-08-29       |

|                             |                          |
|-----------------------------|--------------------------|
| Dist Drilled (m):           | 256                      |
| Penetration rate (m/h):     | -999.99                  |
| Hole Dia (in):              | 8.5                      |
| Pressure Test Type:         | formation integrity test |
| Formation strength (g/cm3): | 1.55                     |
| Dia Last Casing (I):        |                          |

|                                   |        |
|-----------------------------------|--------|
| Depth at Kick Off mMD:            |        |
| Depth at Kick Off mTVD:           |        |
| Depth mMd:                        | 3682   |
| Depth mTVD:                       | 3239.7 |
| Plug Back Depth mMD:              |        |
| Depth at formation strength mMD:  | 2605   |
| Depth At Formation Strength mTVD: | 2459.2 |
| Depth At Last Casing mMD:         | 2595.4 |
| Depth At Last Casing mTVD:        | 2446.8 |

Summary of activities (24 Hours)

Drilled 8 1/2" hole to TD at 3682 m.  
Circulated hole clean.  
Re-logged interval and commenced taking pressure points.

Summary of planned activities (24 Hours)

Drop gyro.  
POOH with 8 1/2" drilling BHA, L/D same.  
P/U and RIH with 3 1/2" cement stinger.

Operations

| Start time | End time | End Depth mMD | Main - Sub Activity                  | State | Remark                                                                                                                                                                                                                                                                                               |
|------------|----------|---------------|--------------------------------------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 00:00      | 05:30    | 3546          | drilling -- drill                    | ok    | Drilled 8 1/2" hole from 3426 m to 3546 m, average ROP: 22 m/hr.<br>WOB 7 - 14 tonne. 2450 l/min/ 190 - 195 bar. 160 rpm / 18 - 22 kNm. ECD 1,42 SG.<br><br>Maintained LCM background concentration<br>Controlled ROP to 25 m/hr                                                                     |
| 05:30      | 05:45    | 3546          | drilling -- other                    | ok    | Took SCR                                                                                                                                                                                                                                                                                             |
| 05:45      | 07:45    | 3576          | drilling -- drill                    | ok    | Drilled 8 1/2" hole from 3546 m to 3576 m, average ROP: 15 m/hr.<br>WOB 7 - 14 tonne. 2450 l/min/ 190 - 195 bar. 160 rpm / 18 - 22 kNm. ECD 1,42 SG.<br><br>Maintained LCM background concentration<br>Controlled ROP to 25 m/hr                                                                     |
| 07:45      | 08:30    | 3576          | interruption -- other                | ok    | Circulated and reciprocated string while Baker logging unit re-booted computer system                                                                                                                                                                                                                |
| 08:30      | 15:15    | 3682          | drilling -- drill                    | ok    | Drilled 8 1/2" hole from 3576 m to TD at 3682 m, average ROP: 15,7 m/hr.<br>WOB 2 - 14 tonne. 2450 l/min/ 195 - 199 bar. 160 rpm / 11 - 26 kNm. ECD 1,42 SG.<br><br>TD: 3682 m MD.<br>Controlled ROP from 3626 - 3640 m: 15 m/hr / 3640 - 3682 m: 10 m/hr<br>Maintained LCM background concentration |
| 15:15      | 15:30    | 3682          | drilling -- survey                   | ok    | Took final survey and downlinked                                                                                                                                                                                                                                                                     |
| 15:30      | 17:00    | 3682          | drilling -- circulating conditioning | ok    | Circulated hole clean w/ 2450 l/min/ 197 - 194 bar, 140 RPM / 12 - 20 kNm, ECD 1,41 SG.<br><br>Circulated first B/U<br>Reciprocated string from 3682 - 3662 m                                                                                                                                        |
| 17:00      | 17:15    | 3682          | drilling -- circulating conditioning | ok    | Racked back one stand                                                                                                                                                                                                                                                                                |
| 17:15      | 20:30    | 3682          | drilling -- circulating conditioning | ok    | Circulated hole clean w/ 2450 l/min/ 192 bar, 140 RPM / 21 - 20 kNm, ECD 1,40 SG, total 3 x B/U<br>Reciprocated string from 3662 - 3327 m.<br>Hold TBT for taking pressure points and re-logging                                                                                                     |
| 20:30      | 21:00    | 3505          | formation evaluation -- log          | ok    | POOH 5 1/2" stands from 3665 m to 3505 m. Limited pulling speed to 2-3 min/stand. Made up TDS.                                                                                                                                                                                                       |
| 21:00      | 21:45    | 3491          | formation evaluation -- log          | ok    | Re-logged section from 3503,3 to 3491 m w/ 2000 lpm, 135 bar, 60 rpm, 12 - 17 kNm.                                                                                                                                                                                                                   |
| 21:45      | 22:00    | 3544          | formation evaluation -- log          | ok    | RIH from 3491 m to 3544 m.                                                                                                                                                                                                                                                                           |
| 22:00      | 23:45    | 3544          | formation evaluation -- log          | ok    | Made up TDS and re-logged section from 3544 to 3506 m w/ 2000 lpm, 135 bar, 60 rpm, 12 - 17 kN m.                                                                                                                                                                                                    |
| 23:45      | 00:00    | 3521          | formation evaluation -- log          | ok    | RIH to 3534 m. Took weights: 188 t up, 144 t down, 157 t rot.<br>Performed 10 min. sticky test                                                                                                                                                                                                       |

Drilling Fluid

|                       |                  |                  |                  |
|-----------------------|------------------|------------------|------------------|
| Sample Time           | 09:00            | 15:30            | 22:00            |
| Sample Point          | Flowline         | Flowline         | Flowline         |
| Sample Depth mMD      | 3618             | 3682             | 3682             |
| Fluid Type            | Enviromul Yellow | Enviromul Yellow | Enviromul Yellow |
| Fluid Density (g/cm3) | 1.32             | 1.32             | 1.32             |
| Funnel Visc (s)       | -999.99          | -999.99          | -999.99          |
| Mf ( )                |                  |                  |                  |
| Pm ( )                |                  |                  |                  |
| Pm filtrate ( )       |                  |                  |                  |
| Chloride ( )          |                  |                  |                  |
| Calcium ( )           |                  |                  |                  |
| Magnesium ( )         |                  |                  |                  |
| Ph                    |                  |                  |                  |
| Excess Lime ( )       |                  |                  |                  |
| Solids                |                  |                  |                  |
| Sand ( )              |                  |                  |                  |

|                        |      |     |     |
|------------------------|------|-----|-----|
| Water ()               |      |     |     |
| Oil ()                 |      |     |     |
| Solids ()              |      |     |     |
| Corrected solids ()    |      |     |     |
| High gravity solids () |      |     |     |
| Low gravity solids ()  |      |     |     |
| Viscometer tests       |      |     |     |
| Plastic visc. (mPa.s)  | 35   | 35  | 34  |
| Yield point (Pa)       | 11.5 | 12  | 13  |
| Filtration tests       |      |     |     |
| Pm filtrate ()         |      |     |     |
| Filtrate Lthp ()       |      |     |     |
| Filtrate Hthp ()       |      |     |     |
| Cake thickn API ()     |      |     |     |
| Cake thickn HPHT ()    |      |     |     |
| Test Temp HPHT (degC)  | 120  | 120 | 120 |
| Comment                |      |     |     |

### Pore Pressure

| Time  | Depth mMD | Depth TVD | Equ Mud Weight (g/cm3) | Reading   |
|-------|-----------|-----------|------------------------|-----------|
| 00:00 | 2620      |           | .86                    | estimated |
| 00:00 | 3358      |           | 1.29                   | estimated |
| 00:00 | 3682      |           | 1.14                   | estimated |

### Survey Station

| Depth mMD | Depth mTVD | Inclination (dega) | Azimuth (dega) | Comment |
|-----------|------------|--------------------|----------------|---------|
| 3051      | 2835.6     | 45.11              | 300.16         |         |
| 3091.4    | 2863.3     | 48.2               | 296.12         |         |
| 3130.5    | 2888       | 53.44              | 294.14         |         |
| 3171.2    | 2911.1     | 57.55              | 289.29         |         |
| 3212.1    | 2931.6     | 62.02              | 285.32         |         |
| 3251.6    | 2949.8     | 63.21              | 281.36         |         |
| 3292      | 2969.5     | 58.32              | 281.29         |         |
| 3333.1    | 2992.7     | 53.03              | 282.89         |         |
| 3373.4    | 3018.6     | 46.91              | 287.36         |         |
| 3413.8    | 3046.9     | 44.3               | 285.04         |         |
| 3454.1    | 3075.9     | 43.58              | 283.54         |         |
| 3494.3    | 3104.9     | 44.11              | 283.07         |         |
| 3534.6    | 3133.8     | 44.1               | 283.1          |         |
| 3574.3    | 3162.3     | 44.13              | 283.44         |         |
| 3615.2    | 3191.7     | 44.05              | 284.07         |         |
| 3655.4    | 3220.6     | 44.08              | 285.06         |         |
| 3671.1    | 3231.9     | 44.05              | 285.44         |         |
| 3682      | 3239.7     | 44.05              | 285.44         |         |

### Stratigraphic Information

| Depth to Top of Formation mMD | Depth to Top of Formation mTVD | Description |
|-------------------------------|--------------------------------|-------------|
| 3429                          | 3057.8                         | Heather Fm  |
| 3435                          | 3062.1                         | Hugin Fm    |
| 3500                          | 3109                           | Sleipner Fm |

### Lithology Information

| Start Depth mMD | End Depth mMD | Start Depth mTVD | End Depth mTVD | Shows Description | Lithology Description         |
|-----------------|---------------|------------------|----------------|-------------------|-------------------------------|
| 3429            | 3435          | 3058             | 3062           |                   | Sandstone/Claystone (Heather) |
| 3435            | 3500          | 3062             | 3109           |                   | Sandstone (Hugin)             |
| 3500            | 3682          | 3109             | 3240           |                   | Sandstone (Slepiner)          |