

Summary report

Wellbore: 15/9-F-1 B

Period: 2013-08-29 00:00 - 2013-08-30 00:00

Status:	normal
Report creation time:	2018-05-03 13:51
Report number:	1
Days Ahead/Behind (+/-):	.7
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2013-08-29 15:30
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2013-09-07

Dist Drilled (m):	146
Penetration rate (m/h):	-999.99
Hole Dia (in):	12.25
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.55
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	2763
Depth mTVD:	2600.2
Plug Back Depth mMD:	
Depth at formation strength mMD:	2605
Depth At Formation Strength mTVD:	2459.2
Depth At Last Casing mMD:	2595.4
Depth At Last Casing mTVD:	2446.8

Summary of activities (24 Hours)

Kicked off well from F-1 A.
Drilled 12 1/4" hole through Ty Fm. to 2763 m.

Summary of planned activities (24 Hours)

Continue drilling 12 1/4" hole to TD at app. 3093 m MD.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
15:30	17:00	2627	drilling – drill	ok	Continued to kick off from F-1 A. Drilled 12 1/4" hole from 2617 m to 2627 m as per Baker DD instructions. WOB 2 - 5 tonne. 2800 l/min/ 153 bar. 40 rpm / 13 - 17 kNm. Started bleeding in LCM premix, 4m3 per stand for drilling Ty Fm.
17:00	19:00	2650	drilling – drill	ok	Drilled and oriented 12 1/4" hole from 2627 m to 2650 m. Average ROP 11,5 m/hr. WOB 3 - 6 tonne. 3500 l/min/ 215 - 220 bar. 80 rpm / 15 -18 kNm. ECD 1,32 SG. Bleed in LCM premix as per plan to maintain particle concentration. Initially controlled ROP to 10 m/hr.
19:00	00:00	2763	drilling – drill	ok	Drilled and oriented 12 1/4" hole from 2650 m to 2763 m. Average ROP: 22,6 m/hr, WOB 2 - 6 tonne. 3500 l/min/ 215 - 220 bar. 80 rpm / 17 - 21 kNm. ECD 1,32 SG. Bleed in LCM premix as per plan to maintain particle concentration.

Drilling Fluid

Sample Time	03:00	09:00	15:00	21:00
Sample Point	Active pit	Flowline	Flowline	Flowline
Sample Depth mMD	2831	2545	2620	2707
Fluid Type	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.28	1.32	1.28	1.28
Funnel Visc (s)	-999.99	-999.99	-999.99	-999.99
Mf (I)				
Pm (I)				
Pm filtrate (I)				
Chloride (I)				
Calcium (I)				
Magnesium (I)				
Ph				
Excess Lime (I)				
Solids				
Sand (I)				
Water (I)				
Oil (I)				
Solids (I)				
Corrected solids (I)				
High gravity solids (I)				
Low gravity solids (I)				
Viscometer tests				
Plastic visc. (mPa.s)	38	35	38	38
Yield point (Pa)	11.5	12	8	8
Filtration tests				
Pm filtrate (I)				
Filtrate Lthp (I)				
Filtrate Hthp (I)				
Cake thickn API (I)				
Cake thickn HPHT (I)				
Test Temp HPHT (degC)	120	120	120	120
Comment				

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
2620.5	2472.8	28.92	35.26	
2644.1	2493.6	27.75	38.27	
2684.7	2529.8	26.12	44.21	
2725.1	2566.1	26.09	51.43	
2764.9	2601.9	26.08	54.07	

Stratigraphic Information

Depth to Top of Formation mMD	Depth to Top of Formation mTVD	Description
2628	2479	Ty Fm