

Summary report

Wellbore: 15/9-F-1 C

Period: 2014-03-04 00:00 - 2014-03-05 00:00

Status:	normal
Report creation time:	2018-05-03 13:51
Report number:	12
Days Ahead/Behind (+/-):	2.6
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Maersk Drilling
Spud Date:	2014-02-21 14:30
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2014-03-15

Dist Drilled (m):	410
Penetration rate (m/h):	-999.99
Hole Dia (in):	12.25
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.55
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	3056
Depth mTVD:	2873.1
Plug Back Depth mMD:	
Depth at formation strength mMD:	1358
Depth At Formation Strength mTVD:	1345.9
Depth At Last Casing mMD:	2507.7
Depth At Last Casing mTVD:	2445.8

Summary of activities (24 Hours)

Drilled 12 1/4" hole from 2646 m to 3056 m. Circulated bottoms up and hole clean.

Summary of planned activities (24 Hours)

POOH with 12 1/4" BHA on 5 1/2" DP. and R/B BHA in derrick. Pull wear bushing. R/U Casing equipment. RIH 9 5/8" x 103/4" casing.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	01:45	2674	drilling -- drill	ok	Drilled 12 1/4" hole from 2646 m to 2674 m with 3850 lpm, 250 bar, 120 rpm, 12-16 kNm, 6-12 WOB. ROP 30 m/hr ECD 1,32 SG. Max gas 0,2 %. Obtained surveys as required. Bled in 4 m3 LCM in activ system for each stand drilled. Take cuttings into iso tanks.
01:45	06:00	2755	drilling -- drill	ok	Drilled 12 1/4" hole from 2674 m to 2755 m with 3850 lpm, 250 bar, 120 rpm, 15-20 kNm, 16 WOB. ROP 30 m/hr ECD 1,32 SG. Max gas 0,2 %. Obtained surveys as required. Added 4 sacks LCM in activ system for each stand drilled. Not able to discharge cuttings to cutting vessel due to bad weather. Take cuttings into iso tanks.
06:00	07:15	2775	drilling -- drill	ok	Drilled 12 1/4" hole from 2755 m to 2775 m with 3850 lpm, 253 bar, 120 rpm, 12-16 kNm, 5-13 WOB. ROP 20 m/hr ECD 1,31 SG. Max gas 0 %. Obtained surveys as required. Added 4 sacks LCM in activ system for each stand drilled
07:15	07:30	2775	drilling -- other	ok	Took SCR @ 2775 m, MW 1,28 SG, 30/40/50 stroks MP # 2, 8/14/22 bar, MP # 3, 9/15/21 bar.
07:30	22:00	3056	drilling -- drill	ok	Drilled 12 1/4" hole from 2775 m to 3056 m with 3850 lpm, 260 bar, 120 rpm, 12-16 kNm, 12-14 WOB. ROP 20-30 m/hr ECD 1,31 SG. Max gas 0, 15 %. Obtained surveys as required. Added 4 sacks LCM in activ system for each stand drilled. Take cuttings into iso tanks from 12:30 hrs. Section TD at 3056 m
22:00	22:30	3056	drilling -- survey	ok	Worked torque out of string. Took survey and sent downlink.
22:30	00:00	3056	drilling -- circulating conditioning	ok	Circulated hole clean with 3880 lpm, 242 bar, 140 rpm, 11-16 kNm, ECD 1,31 SG. Max gas 0,1%. Circulated total 2 B/U, 409 m3. Take cuttings into iso tanks.

Drilling Fluid

Sample Time	04:00	09:30	15:15	21:45
Sample Point	Flowline	Flowline	Flowline	Flowline
Sample Depth mMD	2724	2817	2927	3051
Fluid Type	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow	Enviromul Yellow
Fluid Density (g/cm3)	1.28	1.28	1.28	1.28
Funnel Visc (s)	-999.99	-999.99	-999.99	-999.99
Mf ()				
Pm ()				
Pm filtrate ()				
Chloride ()				
Calcium ()				
Magnesium ()				
Ph				
Excess Lime ()				
Solids				
Sand ()				
Water ()				
Oil ()				
Solids ()				
Corrected solids ()				
High gravity solids ()				
Low gravity solids ()				
Viscometer tests				
Plastic visc. (mPa.s)	31	28	32	33
Yield point (Pa)	8.5	10.5	9.5	10
Filtration tests				
Pm filtrate ()				

Filtrate Lthp ()				
Filtrate Hthp ()				
Cake thickn API ()				
Cake thickn HPHT ()				
Test Temp HPHT (degC)	120	120	120	120
Comment				

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	2572		.87	estimated
00:00	3056		1.13	estimated

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
2668.7	2596.2	27.32	36.53	
2710.3	2632.6	30.65	36.83	
2750.7	2666.8	33.66	37.05	
2790.8	2699.4	37.42	37.39	
2830.9	2730.4	41.45	37.47	
2870.8	2759.6	44.47	38.12	
2911.1	2787.4	48.27	38.95	
2951.3	2813.4	51.13	39.44	
2991.7	2837.9	54.11	39.39	
3032.1	2860.6	57.64	40.25	
3056	2873.1	59.49	40.51	

Stratigraphic Information

Depth to Top of Formation mMD	Depth to Top of Formation mTVD	Description
2668.2	2595.8	Ekofisk Fm
2685	2610.7	Tor Fm
2875	2762.5	Hod Fm
2980	2831	Blodøks Fm