

Summary report

Wellbore: 15/9-F-4

Period: 2007-10-31 00:00 - 2007-11-01 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	25
Days Ahead/Behind (+/-):	13.6
Operator:	StatoilHydro
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Mærsk Contractors
Spud Date:	2007-03-10 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2008-02-28

Dist Drilled (m):	-999.99
Penetration rate (m/h):	-999.99
Hole Dia (in):	12.25
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.53
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	2770
Depth mTVD:	2607.6
Plug Back Depth mMD:	
Depth at formation strength mMD:	1363
Depth At Formation Strength mTVD:	1336.5
Depth At Last Casing mMD:	2760.5
Depth At Last Casing mTVD:	2598.7

Summary of activities (24 Hours)

MU and RIH with 10 3/4" x 9 5/8" csg from 587 to 1858 m MD.

Summary of planned activities (24 Hours)

RIH with 10 3/4" x 9 5/8" csg from 1858 to 2618 m MD. RIH and land 10 3/4" x 9 5/8" csg. Circulate, pump and displace cement. Set seal assy. Release PADRT and POOH.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	02:15	416	drilling -- casing	ok	RIH with 9 5/8" csg from 276 to 416 m MD. Filled every joint with 1.40 sg mud using FAC tool.
02:15	03:00	393	interruption -- other	ok	Changed proximity switch on PDM.
03:00	06:00	587	drilling -- casing	ok	RIH with 9 5/8" csg from 416 to 587 m MD. Filled every joint with 1.40 sg mud using FAC tool.
06:00	00:00	1550	drilling -- casing	ok	RIH with 9 5/8" csg from 587 to 1550 m MD. Filled every joint with 1.40 sg mud using FAC tool. LO 3 jnts. Running speed 4-7 jnts/hr .

Drilling Fluid

Sample Time	15:00	23:00
Sample Point	Active pit	Active pit
Sample Depth mMD	2770	2770
Fluid Type	OBM-Standard	OBM-Standard
Fluid Density (g/cm3)	1.4	1.4
Funnel Visc (s)	-999.99	-999.99
Mf (I)		
Pm (I)		
Pm filtrate (I)		
Chloride (I)		
Calcium (I)		
Magnesium (I)		
Ph		
Excess Lime (I)		
Solids		
Sand (I)		
Water (I)		
Oil (I)		
Solids (I)		
Corrected solids (I)		
High gravity solids (I)		
Low gravity solids (I)		
Viscometer tests		
Plastic visc. (mPa.s)	30	29
Yield point (Pa)	11.5	12
Filtration tests		
Pm filtrate (I)		
Filtrate Lthp (I)		
Filtrate Hthp (I)		
Cake thickn API (I)		
Cake thickn HPHT (I)		
Test Temp HPHT (degC)	120	120
Comment		

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	2770		1.03	estimated

