

Summary report

Wellbore: 15/9-F-4

Period: 2008-02-09 00:00 - 2008-02-10 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	36
Days Ahead/Behind (+/-):	11.4
Operator:	StatoilHydro
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Mærsk Contractors
Spud Date:	2007-03-10 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2008-02-28

Dist Drilled (m):	147
Penetration rate (m/h):	-999.99
Hole Dia (in):	8.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.65
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	2917
Depth mTVD:	2732
Plug Back Depth mMD:	
Depth at formation strength mMD:	2760
Depth At Formation Strength mTVD:	2599
Depth At Last Casing mMD:	2760.5
Depth At Last Casing mTVD:	2598.7

Summary of activities (24 Hours)

Drilled out shoe track and shoe. Performed FIT to 1.65 SG. Drilled 8½" hole from 2774m to 2993m. Took survey at 2993 m MD equivalent to 2795 m TVD. Cleaned out the well reciprocating the pipe.

Summary of planned activities (24 Hours)

Clean out the well reciprocating the pipe. POOH to the shoe. Await for further instruction in conjunction F12 start up.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	01:30	2733	drilling -- drill	ok	Continued washing down from 2670m to 2733m. Washing parameters : Flow 1500 lpm / SPP 140 bar / String RPM 30 / Bit RPM 146. ROP 30-40 m/hr.
01:30	04:30	2734	drilling -- drill	ok	Drilled out float. From 2733m to 2734m. Drilling parameters : Flow 1500 lpm / SPP 140 bar / String RPM 10-30 / Bit RPM 125-145. ROP 1-40 m/hr, WOB 1-9 MT. Recovered rubber at the shakers.
04:30	06:00	2751	drilling -- drill	ok	Drilled shoe track from 2734m to 2751m. Drilling parameters : Flow 1500 lpm / SPP 140 bar / String RPM 30 / Bit RPM 146 / ROP 30-40 m/hr / WOB 1 MT / TQ 10-12 kNm. MUD weight 1.4 SG. Back reamed to float with 1500 lpm, RIH and made connection at 2751m, volume pumped prior to connection 26m³.
06:00	06:30	2760	drilling -- drill	ok	Drilled shoe track from 2751m to 2760m. Drilling parameters: Flow 1500 lpm / SPP 140 bar / String RPM 30 / Bit RPM 145 / ROP 30-40 m/hr / WOB 1-4 MT / TQ 10-12 kNm. MUD weight 1.4 SG.
06:30	06:45	2761	drilling -- drill	ok	Drilled shoe from 2760m to 2761m. Drilling parameters: Flow 1500 lpm / SPP 140 bar / String RPM 30 / Bit RPM 145 / WOB 1-6 MT / TQ 10-12 kNm.
06:45	07:15	2771	drilling -- drill	ok	Cleaned out rat hole from 2765m to 2771m. Cleaning parameters: Flow 1500 lpm / SPP 140 bar / String RPM 30 / Bit RPM 145 / WOB 1-3 MT.
07:15	08:00	2774	drilling -- drill	ok	Drilled new formation from 2771m to 2774m. Drilling parameters: Flow 1500 lpm / SPP 140 bar / String RPM 30 / Bit RPM 145 / WOB 5-7 MT / TQ 12-14 kNm. MUD weight 1.4 SG.
08:00	09:00	2760	formation evaluation -- rft/fit	ok	Pulled back into the shoe. Racked back one std. Installed side entry sub and CMT hose. Confirmed line up from CMT unit to drill floor. Leak tested line to 100 bars 10 min.
09:00	10:00	2760	formation evaluation -- rft/fit	ok	Performed FIT test. Closed annular. Applied 64 bars down DP and ANN equivalent to 1.65 SG. Rigged down CMT hose and side entry sub.
10:00	19:00	2854	drilling -- drill	ok	Linked down the Power Drive. Drilled new formation from 2774m to 2854m. Drilling parameters: Flow 2070 lpm / SPP 250 bar / String RPM 30 / Bit RPM 190 / WOB 7-9 MT / TQ 1 6-19 kNm. ECD 1.51 SG. MUD weight 1.4 SG. Took survey before connection.
19:00	00:00	2917	drilling -- drill	ok	Drilled new formation from 2854m to 2917m. Drilling parameters : Flow 2070-2090 lpm / SPP 245-250 bar / String RPM 40 / Bit RPM 203 / ROP 16-20 m/hr / WOB 7-9 MT / TQ 18-19 kNm. ECD 1.51 SG MUD weight 1.4 SG. Took survey before connection.

Equipment Failure Information

Start time	Depth mMD	Depth mTVD	Sub Equip - Syst Class	Operation Downtime (min)	Equipment Repaired	Remark
00:00	2632		hoisting equ -- top drive	0	00:00	-

Drilling Fluid

Sample Time	02:00	11:00	16:00	22:30
Sample Point	Active pit	Flowline	Active pit	Active pit
Sample Depth mMD	2770	2775	2831	2905
Fluid Type	OBM-Standard	OBM-Standard	OBM-Standard	OBM-Standard
Fluid Density (g/cm3)	1.4	1.4	1.4	1.4
Funnel Visc (s)	-999.99	-999.99	-999.99	-999.99
Mf ()				
Pm ()				
Pm filtrate ()				
Chloride ()				
Calcium ()				
Magnesium ()				
Ph				
Excess Lime ()				
Solids				
Sand ()				
Water ()				
Oil ()				
Solids ()				
Corrected solids ()				
High gravity solids ()				
Low gravity solids ()				

Viscometer tests				
Plastic visc. (mPa.s)	23	28	29	30
Yield point (Pa)	7.5	9.5	10.5	7.5
Filtration tests				
Pm filtrate ()				
Filtrate Lthp ()				
Filtrate Hthp ()				
Cake thickn API ()				
Cake thickn HPHT ()				
Test Temp HPHT (degC)		120	120	120
Comment				

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	2770		1.03	estimated

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
2773.9	2610.2	31.22	140.01	
2800.7	2633	31.75	145.84	
2840.3	2666.7	31.62	150.5	
2879.9	2700.3	32.11	155.23	
2920.1	2734.3	32.76	160.49	
2959.1	2766.8	34.44	162.51	