

Summary report

Wellbore: 15/9-F-4

Period: 2008-02-10 00:00 - 2008-02-11 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	37
Days Ahead/Behind (+/-):	11.9
Operator:	StatoilHydro
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Mærsk Contractors
Spud Date:	2007-03-10 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2008-02-28

Dist Drilled (m):	147
Penetration rate (m/h):	-999.99
Hole Dia (in):	8.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.65
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	2917
Depth mTVD:	2732
Plug Back Depth mMD:	
Depth at formation strength mMD:	2760
Depth At Formation Strength mTVD:	2599
Depth At Last Casing mMD:	2760.5
Depth At Last Casing mTVD:	2598.7

Summary of activities (24 Hours)

None

Summary of planned activities (24 Hours)

None

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	04:15	2993	drilling -- drill	ok	Drilled new formation from 2917m to 2993m. Drilling parameters : Flow 2070 lpm / SPP 245-255 bar / String RPM 40 / Bit RPM 203 / ROP 21-23 m/hr / WOB 6-11 MT / TQ 18-21 kNm. ECD 1.51 SG MUD weight 1.4 SG.
04:15	04:30	2993	drilling -- survey	ok	Took survey at 2993 m MD equivalent to 2795 m TVD. Stopped drilling for further instruction in conjunction with F12 perforation and start production.
04:30	06:00	2992	drilling -- circulating conditioning	ok	Cleaned out well reciprocating the pipe, flow 2090 lpm / SPP 215 bar / String RPM 50 / Bit RPM 213. Operations transferred to F-99.

Bit Record

Run No.	Bit Size	Bit Type	IADC Code	Manufacturer	Hrs Drilled	Start mMD	End mMD	Hole Made (last 24H)	Hours Drilled (last 24H)	Form ROP	Total ROP	Total Hole Made	Total Hrs Drilled
5	8.5 in	MDI616LHABP X	M222	Smith International	11.6	2770	2770			19.2	19.2	223	11.6

Drilling Fluid

Sample Time	03:15
Sample Point	Flowline
Sample Depth mMD	2977
Fluid Type	OBM-Standard
Fluid Density (g/cm3)	1.4
Funnel Visc (s)	-999.99
Mf (I)	
Pm (I)	
Pm filtrate (I)	
Chloride (I)	
Calcium (I)	
Magnesium (I)	
Ph	
Excess Lime (I)	
Solids	
Sand (I)	
Water (I)	
Oil (I)	
Solids (I)	
Corrected solids (I)	
High gravity solids (I)	
Low gravity solids (I)	
Viscometer tests	
Plastic visc. (mPa.s)	29
Yield point (Pa)	8
Filtration tests	
Pm filtrate (I)	
Filtrate Lthp (I)	
Filtrate Hthp (I)	
Cake thickn API (I)	
Cake thickn HPHT (I)	
Test Temp HPHT (degC)	120

Comment	
---------	--