

Summary report

Wellbore: 15/9-F-4

Period: 2008-02-13 00:00 - 2008-02-14 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	38
Days Ahead/Behind (+/-):	12.3
Operator:	StatoilHydro
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Mærsk Contractors
Spud Date:	2007-03-10 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2008-02-28

Dist Drilled (m):	42
Penetration rate (m/h):	-999.99
Hole Dia (in):	8.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.65
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	3035
Depth mTVD:	2836
Plug Back Depth mMD:	
Depth at formation strength mMD:	2760
Depth At Formation Strength mTVD:	2599
Depth At Last Casing mMD:	2760.5
Depth At Last Casing mTVD:	2598.7

Summary of activities (24 Hours)

Tagged bottom at 2993m. Drilled from 2993m to 3064m. Drilling parameters: Flow 2090-2225 lpm / SPP 200-220 bar / String RPM 180 / ROP 2.5-8,5 m/hr / WOB 4-6 MT / TQ 15-20 kNm / ECD 1.59 SG. Had heavy stick slip with 10 MT WOB to start with, reduced WOB to 5 MT. Hidra started at 3040m.

Summary of planned activities (24 Hours)

Continue drilling from 3064m to TD.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
16:00	00:00	3035	drilling -- drilling	ok	Tagged bottom at 2993m. Drilled from 2993m to 3035m. Increased mudweight from 1.40 sg to 1.45 sg . Drilling parameters: Flow 2090-2225 lpm / SPP 200-220 bar / String RPM 180 / ROP 2.5-8,5 m/hr / WOB 4-6 MT / TQ 15-20 kNm / ECD 1.59 SG. Had heavy stick slip with 10 MT WOB to start with, reduced WOB to 5 MT.

Drilling Fluid

Sample Time	17:00	22:00
Sample Point	Active pit	Flowline
Sample Depth mMD	3005	3025
Fluid Type	OBM-Standard	OBM-Standard
Fluid Density (g/cm3)	1.45	1.45
Funnel Visc (s)	-999.99	-999.99
Mf (I)		
Pm (I)		
Pm filtrate (I)		
Chloride (I)		
Calcium (I)		
Magnesium (I)		
Ph		
Excess Lime (I)		
Solids		
Sand (I)		
Water (I)		
Oil (I)		
Solids (I)		
Corrected solids (I)		
High gravity solids (I)		
Low gravity solids (I)		
Viscometer tests		
Plastic visc. (mPa.s)	28	28
Yield point (Pa)	9.5	11.5
Filtration tests		
Pm filtrate (I)		
Filtrate Lthp (I)		
Filtrate Hthp (I)		
Cake thickn API (I)		
Cake thickn HPHT (I)		
Test Temp HPHT (degC)	120	120
Comment		

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	3064		1.2	estimated

Survey Station

Depth mMD	Depth mTVD	Inclination (dega)	Azimuth (dega)	Comment
3001.1	2801.3	35.31	165.32	
3041.5	2833.9	36.6	171.51	

Stratigraphic Information

Depth to Top of Formation mMD	Depth to Top of Formation mTVD	Description
3005	2805	Blodeks Fm
3040	2833	Hidra Fm

Lithology Information

Start Depth mMD	End Depth mMD	Start Depth TVD	End Depth TVD	Shows Description	Lithology Description
2993	3050				Marl and Limestone