

Summary report

Wellbore: 15/9-F-4

Period: 2008-02-17 00:00 - 2008-02-18 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	42
Days Ahead/Behind (+/-):	14.3
Operator:	StatoilHydro
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Mærsk Contractors
Spud Date:	2007-03-10 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2008-02-28

Dist Drilled (m):	0
Penetration rate (m/h):	-999.99
Hole Dia (in):	8.5
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.65
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	3510
Depth mTVD:	3138.8
Plug Back Depth mMD:	
Depth at formation strength mMD:	2760
Depth At Formation Strength mTVD:	2599
Depth At Last Casing mMD:	2760.5
Depth At Last Casing mTVD:	2598.7

Summary of activities (24 Hours)

Rigged up WL for running MDT. RIH with MDT on WL to station #1. Attempted to activate probe - negative. Pulled in to 9 5/8" shoe and troubleshoot situation -negative. POOH with MDT toolstring. Checked surface equipment - ok. Checked toolstring and found 2 x MRPO pumps damaged. Re-configured toolstring with 1 back-up MRPO pump. RIH with simplified MDT toolstring on WL.

Summary of planned activities (24 Hours)

Perform pressure point sampling and fluid sampling. POOH with toolstring and rig down WL.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	01:00	0	interruption -- other	ok	Repaired rotational dragchain in AFT PRS upper drive. Meanwhile tested MDT tools
01:00	02:15	0	interruption -- other	ok	Repaired rotational dragchain in AFT PRS upper drive. Temporarily halted testing of MDT tools due to loading of drillpipe onto cantilever/pipe-deck.
02:15	03:15	0	interruption -- other	ok	Repaired rotational dragchain in AFT PRS upper drive. Meanwhile tested MDT tools.
03:15	06:00	0	formation evaluation -- log	ok	Tested MDT tools. Calibrated weight sensor. Brought WL rigging equipment to drillfloor.
06:00	08:45	0	formation evaluation -- log	ok	Rigged up sheaves and cable. Brought logging tools to drillfloor.
08:45	09:00	0	formation evaluation -- log	ok	Held toolbox talk prior to making up logging string.
09:00	10:00	0	formation evaluation -- log	ok	Made up MDT toolstring.
10:00	10:30	0	formation evaluation -- log	ok	Tested MDT tools on surface prior to RIH.
10:30	10:45	0	formation evaluation -- log	ok	Re-positioned lower sheave due to unfavorable cable alignment.
10:45	11:15	0	formation evaluation -- log	ok	RIH with MDT logging string on 7/48 cable. Performed shallow test - negative.
11:15	11:45	0	formation evaluation -- log	ok	POOH with MDT logging tools. Performed checks on surface - ok.
11:45	16:30	3245	formation evaluation -- log	ok	RIH with MDT logging string on 7/48 cable from surface to station #1 at 3245 m MD. Correlated MDT tool. Attempted to activate MDT probe - negative.
16:30	17:45	2671	interruption -- repair	ok	Pulled MDT tool from 3245 m to 2671 m MD inside 9 5/8" casing shoe. Troubleshoot tool failure - negative.
17:45	19:30	0	interruption -- repair	ok	POOH with MDT logging string on 7/48 cable from 2671 m MD to surface.
19:30	23:00	0	interruption -- repair	ok	Checked cable, cable head and surface cables - ok.
23:00	00:00	0	interruption -- repair	ok	Isolated and checked MDT string components as required.

Equipment Failure Information

Start time	Depth mMD	Depth mTVD	Sub Equip - Syst Class	Operation Downtime (min)	Equipment Repaired	Remark
00:00	0		pipe handling equ syst -- vertical pipe handling equ syst	0	00:00	Found loose beam in upper drive hoses on AFT PRS. Potetial falling object. Not able to use PRS for breaking pipe. Halted operation for inspection and repair of AFT PRS.

Drilling Fluid

Sample Time	15:00	22:45
Sample Point	Active pit	Reserve pit
Sample Depth mMD	3510	3510
Fluid Type	OBM-Standard	OBM-Standard
Fluid Density (g/cm3)	1.45	1.45
Funnel Visc (s)	-999.99	-999.99
Mf ()		
Pm ()		
Pm filtrate ()		
Chloride ()		
Calcium ()		
Magnesium ()		
Ph		
Excess Lime ()		
Solids		

Sand ()		
Water ()		
Oil ()		
Solids ()		
Corrected solids ()		
High gravity solids ()		
Low gravity solids ()		
Viscometer tests		
Plastic visc. (mPa.s)	28	27
Yield point (Pa)	9.5	10.5
Filtration tests		
Pm filtrate ()		
Filtrate Lthp ()		
Filtrate Hthp ()		
Cake thickn API ()		
Cake thickn HPHT ()		
Test Temp HPHT (degC)	120	120
Comment		

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	3195		1.28	estimated