

Summary report

Wellbore: 15/9-F-4

Period: 2008-03-12 00:00 - 2008-03-13 00:00

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	66
Days Ahead/Behind (+/-):	
Operator:	StatoilHydro
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Mærsk Contractors
Spud Date:	2007-03-10 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2008-02-28

Dist Drilled (m):	-999.99
Penetration rate (m/h):	-999.99
Hole Dia (I):	
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.65
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	3510
Depth mTVD:	3138.8
Plug Back Depth mMD:	
Depth at formation strength mMD:	2760
Depth At Formation Strength mTVD:	2599
Depth At Last Casing mMD:	3508
Depth At Last Casing mTVD:	3136.9

Summary of activities (24 Hours)

RIH with 6" PDC bit and scraper assy from 1977 m to 3458 m MD. Scraped plug setting area 3440-3450 m. POOH with 6" PDC bit and scraper assy from 3458 m to OOH. LD 6" PDC bit and scraper assemblies.

Summary of planned activities (24 Hours)

MU and RIH with 7" EZSV bridge plug from surface to 3448. Set bridge plug at 3448 m. POOH with running tool from 3448 m to OOH.

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	02:00	804	drilling -- drill	ok	RIH with 6" PDC bit and scraper assembly on 3 1/2" DP from 550 m to 804 m. Max running speed was 13 joints/hr.
02:00	03:45	804	drilling -- other	ok	Changed from 3 1/2" handling equipment to 5 1/2" handling equipment.
03:45	06:00	1977	drilling -- drill	ok	RIH with 6" PDC bit and scraper assembly on 5 1/2" DP from 804 m to 1977 m.
06:00	08:00	2650	drilling -- drill	ok	RIH with 6" PDC bit and scraper assembly on 5 1/2" DP from 1977 m to 2650 m.
08:00	09:30	2650	drilling -- circulating conditioning	ok	Broke circulation with rotation and circulated btms up, 1824 lpm / 290 bar, 20 rpm / 7 kNm. Up weight 141 MT / down weight 122 MT / rotating weight 130 MT.
09:30	13:00	3430	drilling -- drill	ok	Entered 7" liner PBR with reduced flow, 400 lpm / 45 bar. Observed no drag. Continued RIH with 6" PDC bit and scraper assembly on 5 1/2" DP from 2650 m to 3430 m.
13:00	15:30	3430	completion -- circulating conditioning	ok	MU TDS and washed down with scraper string from 3430 m to 3460 m, 1110 lpm / 143 bar. Up weight 159 MT. Pulled back and scraped liner interval 3440-3450 m, 1790 lpm / 300 bar, 60 rpm / 10 kNm. Circulated 1 1/2" btms up at 1790 lpm / 300 bar. RB one std and flow checked well static. Ok.
15:30	16:30	3228	drilling -- drill	ok	POOH with 6" PDC bit and scraper assembly on 5 stds of 5 1/2" DP wet from 3430 m to 3228 m. Flow checked well static. Ok.
16:30	21:15	807	drilling -- drill	ok	Pumped slug and continued to POOH with 6" PDC bit and scraper assembly on 5 1/2" DP from 3228 m to 807 m.
21:15	23:00	807	drilling -- other	ok	Changed from 5 1/2" handling equipment to 3 1/2" handling equipment. Serviced foldable fingerboard.
					Meanwhile flow checked well static. Ok.
23:00	00:00	685	drilling -- drill	ok	POOH with 6" PDC bit and scraper assembly on 3 1/2" DP from 807 m to 685 m.

Equipment Failure Information

Start time	Depth mMD	Depth mTVD	Sub Equip - Syst Class	Operation Downtime (min)	Equipment Repaired	Remark
00:00	13		pipe handling equ syst -- other	0	00:00	Not able to make up quick connections on HTS rollers due to trapped pressure.

Drilling Fluid

Sample Time	10:00	14:00	22:00
Sample Point	Active pit	Active pit	Active pit
Sample Depth mMD	3508	3510	780
Fluid Type	OBM-Standard	OBM-Standard	OBM-Standard
Fluid Density (g/cm3)	1.43	1.44	1.45
Funnel Visc (s)	-999.99	-999.99	-999.99
Mf (I)			
Pm (I)			
Pm filtrate (I)			
Chloride (I)			
Calcium (I)			
Magnesium (I)			
Ph			
Excess Lime (I)			
Solids			
Sand (I)			
Water (I)			
Oil (I)			
Solids (I)			
Corrected solids (I)			
High gravity solids (I)			
Low gravity solids (I)			
Viscometer tests			
Plastic visc. (mPa.s)	28	32	30

Yield point (Pa)	6.5	9	9
Filtration tests			
Pm filtrate ()			
Filtrate Lthp ()			
Filtrate Hthp ()			
Cake thickn API ()			
Cake thickn HPHT ()			
Test Temp HPHT (degC)	120	120	120
Comment			

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	3195		1.28	estimated
00:00	3417.5		1.08	measured