

Wellbore: 15/9-F-4

Status:	normal
Report creation time:	2018-05-03 13:52
Report number:	76
Days Ahead/Behind (+/-):	
Operator:	StatoilHydro
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Mærsk Contractors
Spud Date:	2007-03-10 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	2008-02-28

Dist Drilled (m):	-999.99
Penetration rate (m/h):	-999.99
Hole Dia (i):	
Pressure Test Type:	formation integrity test
Formation strength (g/cm3):	1.65
Dia Last Casing (i):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMD:	3510
Depth mTVD:	3138.8
Plug Back Depth mMD:	
Depth at formation strength mMD:	2760
Depth At Formation Strength mTVD:	2599
Depth At Last Casing mMD:	3508
Depth At Last Casing mTVD:	3136.9

WOW prior to retrieve the HP riser. Performed general maintenance and PM's. Commenced changing out the seal assy of BOP door. Installed flood light in derrick. Cleaned pit # 6,8,9,10 & 11.

WOW to be able to nipple down Diverter and BOP. Nipple down the Diverter, BOP and the HPDR.

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark																																								
00:00	06:00	0	interruption -- waiting on weather	ok	WOW prior to retrieve the HP drilling riser. Continued installation of flood light in derrick. <table border="1"> <thead> <tr> <th>Time</th><th>Wind speed Knots</th><th>Wind direction deg</th><th>Sea m</th><th>Wave direction deg</th></tr> </thead> <tbody> <tr><td>00:30</td><td>40/45</td><td>30°</td><td>6.4/10.1</td><td>360°</td></tr> <tr><td>02:00</td><td>42/47</td><td>30°</td><td>6.1/9.6</td><td>10°</td></tr> <tr><td>03:00</td><td>39/43</td><td>30°</td><td>6.0/9.6</td><td>10°</td></tr> <tr><td>04:30</td><td>37/41</td><td>20°</td><td>5.6/8.8</td><td>360°</td></tr> <tr><td>05:00</td><td>35/41</td><td>30°</td><td>5.3/8.4</td><td>10°</td></tr> <tr><td>06:00</td><td>34/38</td><td>20°</td><td>4.9/7.9</td><td>10°</td></tr> </tbody> </table>	Time	Wind speed Knots	Wind direction deg	Sea m	Wave direction deg	00:30	40/45	30°	6.4/10.1	360°	02:00	42/47	30°	6.1/9.6	10°	03:00	39/43	30°	6.0/9.6	10°	04:30	37/41	20°	5.6/8.8	360°	05:00	35/41	30°	5.3/8.4	10°	06:00	34/38	20°	4.9/7.9	10°					
Time	Wind speed Knots	Wind direction deg	Sea m	Wave direction deg																																									
00:30	40/45	30°	6.4/10.1	360°																																									
02:00	42/47	30°	6.1/9.6	10°																																									
03:00	39/43	30°	6.0/9.6	10°																																									
04:30	37/41	20°	5.6/8.8	360°																																									
05:00	35/41	30°	5.3/8.4	10°																																									
06:00	34/38	20°	4.9/7.9	10°																																									
06:00	19:00	0	interruption -- waiting on weather	ok	WOW prior to retrieve the HP riser. Meanwhile installed flood light in derrick. Commenced changing out the seal assy of BOP door. Cleaned pit # 9 & 11. Performed general maintenance and PM's. Moved CTS funnel from F-9 to F-1. Installed cover in CTS funnel. <table border="1"> <thead> <tr> <th>Time</th><th>Wind speed Knots</th><th>Wind direction deg</th><th>Sea m</th><th>Wave direction deg</th></tr> </thead> <tbody> <tr><td>07:00</td><td>24/30</td><td>30°</td><td>4.4/10</td><td>10°</td></tr> <tr><td>09:00</td><td>18/26</td><td>28°</td><td>4/10.4</td><td>30°</td></tr> <tr><td>11:00</td><td>14/20</td><td>24°</td><td>3.7/7.8</td><td>40°</td></tr> <tr><td>13:00</td><td>9/15</td><td>7°</td><td>3/9.4</td><td>340°</td></tr> <tr><td>15:00</td><td>15/21</td><td>300°</td><td>2.8/9.8</td><td>225°</td></tr> <tr><td>17:00</td><td>20/23</td><td>315°</td><td>2.9/8.9</td><td>250°</td></tr> <tr><td>19:00</td><td>19/22</td><td>320°</td><td>2.6/4.1</td><td>340°</td></tr> </tbody> </table>	Time	Wind speed Knots	Wind direction deg	Sea m	Wave direction deg	07:00	24/30	30°	4.4/10	10°	09:00	18/26	28°	4/10.4	30°	11:00	14/20	24°	3.7/7.8	40°	13:00	9/15	7°	3/9.4	340°	15:00	15/21	300°	2.8/9.8	225°	17:00	20/23	315°	2.9/8.9	250°	19:00	19/22	320°	2.6/4.1	340°
Time	Wind speed Knots	Wind direction deg	Sea m	Wave direction deg																																									
07:00	24/30	30°	4.4/10	10°																																									
09:00	18/26	28°	4/10.4	30°																																									
11:00	14/20	24°	3.7/7.8	40°																																									
13:00	9/15	7°	3/9.4	340°																																									
15:00	15/21	300°	2.8/9.8	225°																																									
17:00	20/23	315°	2.9/8.9	250°																																									
19:00	19/22	320°	2.6/4.1	340°																																									
19:00	00:00	0	interruption -- waiting on weather	ok	WOW prior to retrieve the HP riser. Installed flood light in derrick. Cleaned pit # 6,8 & 10. <table border="1"> <thead> <tr> <th>Time</th><th>Wind speed Knots</th><th>Wind direction deg</th><th>Sea m</th><th>Wave direction deg</th></tr> </thead> <tbody> <tr><td>21:00</td><td>18/22</td><td>320°</td><td>2.6/4.2</td><td>320°</td></tr> <tr><td>23:00</td><td>20/23</td><td>340°</td><td>2.5/4</td><td>340°</td></tr> </tbody> </table>	Time	Wind speed Knots	Wind direction deg	Sea m	Wave direction deg	21:00	18/22	320°	2.6/4.2	320°	23:00	20/23	340°	2.5/4	340°																									
Time	Wind speed Knots	Wind direction deg	Sea m	Wave direction deg																																									
21:00	18/22	320°	2.6/4.2	320°																																									
23:00	20/23	340°	2.5/4	340°																																									

Sample Time	15:00
Sample Point	Active pit
Sample Depth mMD	3508
Fluid Type	Packer fluid
Fluid Density (g/cm3)	1.03
Funnel Visc (s)	-999.99
Mf ()	
Pm ()	
Pm filtrate ()	
Chloride ()	
Calcium ()	
Magnesium ()	
Ph	
Excess Lime ()	
Solids	
Sand ()	
Water ()	
Oil ()	
Solids ()	
Corrected solids ()	
High gravity solids ()	
Low gravity solids ()	
Viscometer tests	
Plastic visc. (mPa.s)	-999.99

Yield point (Pa)	-999.99
Filtration tests	
Pm filtrate ()	
Filtrate Lthp ()	
Filtrate Hthp ()	
Cake thickn API ()	
Cake thickn HPHT ()	
Test Temp HPHT ()	
Comment	

Pore Pressure

Time	Depth mMD	Depth TVD	Equ Mud Weight (g/cm3)	Reading
00:00	3510		1.08	measured