

Summary report

Wellbore: 15/9-F-7

Period: 2007-09-14 00:00 - 2007-09-15 00:00

Status:	normal
Report creation time:	2018-05-03 13:53
Report number:	1
Days Ahead/Behind (+/-):	
Operator:	Statoil
Rig Name:	MÆRSK INSPIRER
Drilling contractor:	Mærsk Contractors
Spud Date:	2007-05-01 00:00
Wellbore type:	
Elevation RKB-MSL (m):	54.9
Water depth MSL (m):	91
Tight well:	Y
HPHT:	Y
Temperature ():	
Pressure ():	
Date Well Complete:	2007-10-04

Dist Drilled (m):	-999.99
Penetration rate (m/h):	-999.99
Hole Dia ():	
Pressure Test Type:	
Formation strength (g/cm3):	0
Dia Last Casing ():	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	0
Depth mTVD:	0
Plug Back Depth mMD:	
Depth at formation strength mMD:	0
Depth At Formation Strength mTVD:	0
Depth At Last Casing mMD:	
Depth At Last Casing mTVD:	

Summary of activities (24 Hours)

WOW to skid rig to F-7. Skidded to F-7. Started to skid out to remove riser tie-in winch.

Summary of planned activities (24 Hours)

Skid rig to slot number 7 (including skidding for removing riser tie-in winch). MU and run in with 36" BHA and "drill centralizing bushing".

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
21:00	00:00	0	interruption -- waiting on weather	ok	WOW to skid rig to F-7. Wind 41-53 kt.

Drilling Fluid

Sample Time	14:00
Sample Point	Active pit
Sample Depth mMD	0
Fluid Type	Seawater
Fluid Density (g/cm3)	1.01
Funnel Visc (s)	-999.99
Mf ()	
Pm ()	
Pm filtrate ()	
Chloride ()	
Calcium ()	
Magnesium ()	
Ph	
Excess Lime ()	
Solids	
Sand ()	
Water ()	
Oil ()	
Solids ()	
Corrected solids ()	
High gravity solids ()	
Low gravity solids ()	
Viscometer tests	
Plastic visc. (mPa.s)	-999.99
Yield point (Pa)	-999.99
Filtration tests	
Pm filtrate ()	
Filtrate Lthp ()	
Filtrate Hthp ()	
Cake thickn API ()	
Cake thickn HPHT ()	
Test Temp HPHT ()	
Comment	