

Agents SDK Quiz Preparation - Questions

Agents, Hooks, Output Schemas, Runners, all Tool types, Handoffs, Guardrails, Tracing/Spans, Streaming Events, Exceptions, etc.

Here are 17 MCQs that hit those areas at an expert level:

1. **AgentHooks Callback**

Which `AgentHooks` method is called **after** the agent's reasoning completes but **before** any tool is invoked?

- A. `on_agent_start`
- B. `on_agent_action`
- C. `on_tool_start`
- D. `on_agent_end`
- E. None of the above

2. **AgentOutputSchemaBase**

Which two methods **must** any `AgentOutputSchemaBase` subclass implement?

- A. `is_plain_text()` and `name()`
- B. `name()` and `execute_tool()`
- C. `json_schema()` and `is_plain_text()`
- D. `format_output()` and `parse_input()`
- E. `to_dict()` and `from_json()`

3. **Runner Variants**

What's the key difference between `run_sync()` and `run_streamed()`?

- A. `run_sync` blocks until complete and returns `RunResult`; `run_streamed` yields `RunItemStreamEvent` chunks as they arrive
- B. `run_sync` only uses the Responses API; `run_streamed` only uses Chat Completions
- C. `run_sync` cannot invoke tools; `run_streamed` can
- D. They behave identically under the hood
- E. None of the above

4. **WebSearchTool vs. FileSearchTool**

When would you use a `FileSearchTool` instead of a `WebSearchTool`?

- A. To search public APIs
- B. To scrape live web pages
- C. To call a local shell command for searching

- D. To search within user-uploaded files stored in a Vector Store
- E. None of the above

5. **HandoffInputFilter**

The `input_filter` parameter in a `handoff(...)` call controls:

- A. Which messages from history are passed to the next agent
- B. How many times a handoff can occur
- C. Whether to log the handoff event
- D. The tool schema used for the handoff
- E. None of the above

6. **Input Guardrail Trigger**

A tripwire in an `input_guardrail` raises which exception?

- A. `AgentsException`
- B. `InputGuardrailTripwireTriggered`
- C. `UserError`
- D. `ModelBehaviorError`
- E. None of the above

7. **Span Types**

Which span type logs the execution of a function-tool call?

- A. `GenerationSpanData`
- B. `HandoffSpanData`
- C. `FunctionSpanData`
- D. `GuardrailSpanData`
- E. `FunctionSpanDataOutput`

8. **trace() Usage**

To group several runs under the same trace ID for observability, you should:

- A. Call `with_trace("MyTrace")` around each `Runner.run()`
- B. Pass `trace="MyTrace"` to each `Agent` constructor
- C. Use `add_trace_processor()` only once at startup
- D. Use `group_id` in `RunConfig`
- E. All of them

9. **RunErrorDetails Contents**

Which field **isn't** part of `RunErrorDetails`?

- A. `message` (the error text)
- B. `error_type` (the exception class name)
- C. `stack_trace` (call stack)
- D. `final_output` (the last successful result)

E. None of the above

10. ModelProvider vs. ModelSettings

Which holds the **credentials** (e.g. API key) for calling an LLM?

- A. `ModelSettings`
- B. `ModelProvider`
- C. `OpenAIChatCompletionsModel` directly
- D. `RunConfig`
- E. None of the above

11. StreamEvent Subclass

Which event type carries the raw chunk from the LLM before it's parsed?

- A. `AgentUpdatedStreamEvent`
- B. `RawResponsesStreamEvent`
- C. `ToolCallOutputItem`
- D. `ReasoningItem`
- E. None of the above

12. Exception Hierarchy

If an LLM returns output that fails the declared `output_type` schema, the SDK raises:

- A. `InvalidSchemaError`
- B. `UserError`
- C. `ModelBehaviorError`
- D. `AgentsException`
- E. None of the above

13. Output Item Validity

Which of the following is NOT a valid output item class in the Agents SDK?

- A. `ToolCallOutputItem`
- B. `MessageOutputItem`
- C. `FunctionToolCallItem`
- D. `ReasoningItem`
- E. All of the above are valid

14. Valid Output Item

Which of these is a valid output item in the SDK?

- A. AgentReplyItem
- B. ReasoningItem
- C. ToolOutputResponseItem
- D. ResultItem
- E. None of the above

15. Tool Schema Validation Timing

When does the SDK enforce input schema validation for tools?

- A. When the tool is invoked at runtime
- B. During agent initialization
- C. During tool registration
- D. After all tools finish running
- E. Both A and B

16. Agent Output Logging

Which output item shows what the agent is thinking?

- A. MessageOutputItem
- B. ReasoningItem
- C. ThinkingItem
- D. DebugItem
- E. None of the above

17. Number of Tools

How many tools can you register in one agent?

- A. 10
 - B. 20
 - C. 64
 - D. No fixed limit
 - E. None of the above
-

Scroll down for Answer Keys

Answer Key

1. E
2. A, C
3. A
4. D
5. A
6. B
7. C
8. A
9. D
10. A B
11. B
12. C
13. C
14. B
15. A

16. B

17. D