

```
mininet> net
h1 h1-eth0:s1-eth1
h2 h2-eth0:s2-eth1
h3 h3-eth0:s3-eth1
h4 h4-eth0:s4-eth1
h5 h5-eth0:s5-eth1
h6 h6-eth0:s6-eth1
h7 h7-eth0:s7-eth1
h8 h8-eth0:s8-eth1
s1 lo: s1-eth1:h1-eth0 s1-eth2:s2-eth2
s2 lo: s2-eth1:h2-eth0 s2-eth2:s1-eth2 s2-eth3:s3-eth2
s3 lo: s3-eth1:h3-eth0 s3-eth2:s2-eth3 s3-eth3:s4-eth2
s4 lo: s4-eth1:h4-eth0 s4-eth2:s3-eth3 s4-eth3:s5-eth2
s5 lo: s5-eth1:h5-eth0 s5-eth2:s4-eth3 s5-eth3:s6-eth2
s6 lo: s6-eth1:h6-eth0 s6-eth2:s5-eth3 s6-eth3:s7-eth2
s7 lo: s7-eth1:h7-eth0 s7-eth2:s6-eth3 s7-eth3:s8-eth2
s8 lo: s8-eth1:h8-eth0 s8-eth2:s7-eth3
c0
mininet> nodes
available nodes are:
c0 h1 h2 h3 h4 h5 h6 h7 h8 s1 s2 s3 s4 s5 s6 s7 s8
```

```
mininet> dump
<Host h1: h1-eth0:10.0.0.1 pid=927>
<Host h2: h2-eth0:10.0.0.2 pid=931>
<Host h3: h3-eth0:10.0.0.3 pid=933>
<Host h4: h4-eth0:10.0.0.4 pid=935>
<Host h5: h5-eth0:10.0.0.5 pid=937>
<Host h6: h6-eth0:10.0.0.6 pid=939>
<Host h7: h7-eth0:10.0.0.7 pid=941>
<Host h8: h8-eth0:10.0.0.8 pid=943>
<OVSSwitch s1: lo:127.0.0.1,s1-eth1:None,s1-eth2:None pid=948>
<OVSSwitch s2: lo:127.0.0.1,s2-eth1:None,s2-eth2:None,s2-eth3:None pid=951>
<OVSSwitch s3: lo:127.0.0.1,s3-eth1:None,s3-eth2:None,s3-eth3:None pid=954>
<OVSSwitch s4: lo:127.0.0.1,s4-eth1:None,s4-eth2:None,s4-eth3:None pid=957>
<OVSSwitch s5: lo:127.0.0.1,s5-eth1:None,s5-eth2:None,s5-eth3:None pid=960>
<OVSSwitch s6: lo:127.0.0.1,s6-eth1:None,s6-eth2:None,s6-eth3:None pid=963>
<OVSSwitch s7: lo:127.0.0.1,s7-eth1:None,s7-eth2:None,s7-eth3:None pid=966>
<OVSSwitch s8: lo:127.0.0.1,s8-eth1:None,s8-eth2:None pid=969>
<Controller c0: 127.0.0.1:6653 pid=920>
```

```
mininet> h1 ifconfig
h1-eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.0.0.1 netmask 255.0.0.0 broadcast 10.255.255.255
    ether 00:00:00:00:00:01 txqueuelen 1000 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    loop txqueuelen 1000 (Local Loopback)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

mininet> h2 ifconfig
h2-eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.0.0.2 netmask 255.0.0.0 broadcast 10.255.255.255
    ether 00:00:00:00:00:02 txqueuelen 1000 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    loop txqueuelen 1000 (Local Loopback)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

```
    Port s7-eth2
      Interface s7-eth2
    Port s7-eth3
      Interface s7-eth3
    Port s7
      Interface s7
        type: internal
    Port s7-eth1
      Interface s7-eth1
  Bridge s1
    Controller "tcp:127.0.0.1:6653"
      is_connected: true
    Controller "ptcp:6654"
    fail_mode: secure
    Port s1-eth2
      Interface s1-eth2
    Port s1-eth1
      Interface s1-eth1
    Port s1
      Interface s1
        type: internal
  Bridge s2
    Controller "tcp:127.0.0.1:6653"
      is_connected: true
    Controller "ptcp:6655"
    fail_mode: secure
    Port s2-eth2
      Interface s2-eth2
    Port s2-eth3
      Interface s2-eth3
    Port s2-eth1
      Interface s2-eth1
    Port s2
      Interface s2
        type: internal
  ovs_version: "2.13.1"
```