

27-04-2024


What is machine learning?

- Extract (learn) meaningful information from the examples (training) and answer the query for unseen examples
- Specific task
- How can we allow computer to extract meaningful information from the examples?
 - Design general rules
 - Development of algorithms
- Automate the process of inductive inference

Inductive bias

- Garcia effect, Garcia et. al. 1960
 - Rat has an inductive bias

Group-1



Group-2



Sweet water



drinking normal water



drinking sweet water

Sweet and normal water

Empirical risk minimization (ERM)

- Given $X_1, X_2, \dots, X_n, X_i \in \mathcal{X}$ are n data points and $Y_1, Y_2, \dots, Y_n, Y_i \in \mathcal{Y}$ are their corresponding outputs
- If we know the data distribution, then we can use Bayes decision rule?
- But in most of the cases we don't know the data distribution!

► We can compute ERM as: $R_n(f) := \frac{1}{n} \sum_{i=1}^n l(X_i, Y_i, f(X_i))$

► Consider a set of functions $\mathcal{F} : \mathcal{X} \rightarrow \mathcal{Y}$

– $f_n := \arg \min_{f \in \mathcal{F}} R_n(f)$

Estimation Vs Approximation error

- Let's consider an example: least square regression problem
- Let \hat{f} be the true best in \mathcal{F} :
 - $\hat{f} := \arg \min_{f \in \mathcal{F}} R(f)$
- Estimation error: $R(f_n) - R(\hat{f})$
 - Its a random variables. Why?
 - Depends on n
- Approximation error: $R(\hat{f}) - R(f^*)$
 - f^* is the Bayes/best over all functions (measurable)
- Size of the function class \mathcal{F}
 - Small ?
 - Undercutting
 - Large ?
 - Overfitting

