

## 12. JWT Summary

### 1. User Authentication (Login):

- **Endpoint:** `/login`
- **Process:**
  - User submits credentials (username/password) via POST request.
  - Credentials are verified using `AuthenticationManager` with a `UsernamePasswordAuthenticationToken`.
  - On successful authentication, a **JWT token** is generated.

### 2. JWT Token Generation:

- **Class:** `JwtService`
- **Token Construction:**
  - Claims (e.g., `username`, `roles`) are added using `setClaims(Map<String, Object>)`.
  - The token includes metadata such as `subject`, `issuedAt`, and `expiration`.
  - The token is signed using a **HMAC-SHA256** algorithm with a secret key.
  - Output: A compact, self-contained token string.

### 3. Token Issuance:

- The token is returned to the client in the login response.
- **Client Responsibility:** Store the token securely (e.g., in `localStorage` or as an HTTP-only cookie).

### 4. Request with Token:

- For protected endpoints, the client includes the JWT in the `Authorization` header using the format:  
`Authorization: Bearer <JWT>`.

### 5. JWT Validation on API Requests:

- **Filter:** `JwtFilter` (extends `OncePerRequestFilter`)
- **Flow:**
  - Extract the `Authorization` header.

- Validate the token signature using the secret key (**Key** object via **Keys.hmacShaKeyFor()**).
- Decode claims using **Jwts.parserBuilder().parseClaimsJws(token).getBody()**.
- Check token validity:
  - **Signature**: Ensures the token hasn't been tampered with.
  - **Expiration**: Confirms the token is not expired using **Claims.getExpiration()**.

## 6.Authentication Context Update:

- If the token is valid:
  - Extract the **username** via **extractUserName()**.
  - Load **UserDetails** from the user store (via **UserDetailsService**).
  - Create a **UsernamePasswordAuthenticationToken** and set it in **SecurityContextHolder**.
- If invalid:
  - Deny access or return an unauthorized response.

## 7.Security Filter Chain Configuration:

- **Session Policy**: **SessionCreationPolicy.STATELESS** (No server-side sessions).
- **CSRF**: Disabled for token-based security.
- **Filters**: Custom **JwtFilter** added before the **UsernamePasswordAuthenticationFilter**.

## 8.Token Claims and Validation:

- Claims extracted (e.g., **username**, **roles**) using functional interfaces like **Claims::getSubject**.
- Token is validated to ensure:
  - Subject matches authenticated user.
  - Token is not expired (using **extractExpiration()**).

## 9.JWT Libraries and Key Management:

- **Library**: **io.jsonwebtoken** (JJWT).
- **Key Management**:
  - Secret key dynamically generated or securely configured using environment variables.

- Base64 encoding for portability, decoded for cryptographic operations.

## **10.Post-Validation Request Flow:**

- Once authenticated, the request proceeds to the controller.
- Authorization checks are performed based on roles or permissions included in the token.

## **End-to-End Lifecycle**

1. **Login** → User authenticated → JWT issued.
2. **Request** → JWT provided → Validated → User authenticated.
3. **Protected Resource Access** → Authorization ensured via claims.

This flow enables stateless, secure, and scalable API authentication using JWT.