


## 5. Project Setup For JWT

### Project Structure



**Make changes in that method that are in SecurityConfig:**

```
@Bean
public SecurityFilterChain securityFilterChain(HttpSecurity http) throws Exception {

    http.csrf(customizer -> customizer.disable())
        .authorizeHttpRequests(request -> request
            .requestMatchers("register")
            .permitAll()
            .anyRequest().authenticated())
        .sessionManagement(session ->
    session.sessionCreationPolicy(SessionCreationPolicy.STATELESS));
    return http.build();
}
```

**Add @GeneratedValue(strategy=GenerationType.IDENTITY) in this model**

```
package com.telusko.springsecdemo.model;

import jakarta.persistence.*;
import lombok.AllArgsConstructor;
import lombok.Data;
import lombok.NoArgsConstructor;

@Data
@Table(name = "users")
@Entity
public class User {

    @Id
    @GeneratedValue(strategy = GenerationType.IDENTITY)
    private int id;
    private String username;
    private String password;

}
```

POST http://localhost:8081/register

Params Authorization Headers (9) Body Pre-request Script Tests Settings

none form-data x-www-form-urlencoded raw binary JSON

```
1
2   "username": "navin",
3   "password": "n@123"
4
```

## Output:

Data Output Messages Notifications

	<b>id</b> [PK] integer	<b>password</b> character varying	<b>username</b> character varying
1	3	\$2a\$12\$RH.hzscSwfpWaUnnFYozXeKu9QQ7yNb7UBbtMi0soj9YQyKnrb...	navin