

MA4110/MA5020: Computational Methods for Fluid Flow

Lecture 7: Von Neumann Stability Analysis and Classical Schemes for Advection

Instructor: Biswarup Biswas

1 Introduction

In Lecture 6, we established the foundations of the Finite Difference Method (FDM) and proved that both the Forward-Time Central-Space (FTCS) and First-Order Upwind (FOU) schemes are formally consistent with the linear advection equation $u_t + au_x = 0$. However, we noted a critical caveat: when executed on a computer, the FTCS scheme rapidly explodes due to catastrophic growth of numerical round-off errors.

This brings us to the second pillar of the Lax Equivalence Theorem: **Numerical Stability**. In this lecture, we introduce the standard quantitative tool for analyzing the stability of linear finite difference schemes: **Von Neumann (Fourier) Stability Analysis**. We will:

1. Formulate the Fourier decomposition of discrete error modes.
2. Define the **amplification factor** $G(\xi)$ and the Von Neumann stability criterion $|G(\xi)| \leq 1$.
3. Prove why FTCS is unconditionally unstable for hyperbolic advection.
4. Derive the conditional stability of the First-Order Upwind (FOU) scheme.
5. Introduce and analyze the classical **Lax-Friedrichs** and **Lax-Wendroff** schemes.

2 The Concept of Numerical Stability

Let u_j^n be the exact algebraic solution to a finite difference equation, and let $\tilde{u}_j^n$ be the actual computed floating-point numerical solution. The **numerical error** at grid point (x_j, t^n) is:

$$\epsilon_j^n = \tilde{u}_j^n - u_j^n \quad (1)$$

Because the difference equations are linear, the error ϵ_j^n satisfies the exact same difference equation as the solution u_j^n .

Definition: Numerical Stability

A numerical scheme is said to be **stable** if small errors (such as machine round-off or initial perturbations) remain bounded as the calculation proceeds forward in time ($n \rightarrow \infty$ at fixed Δt). Conversely, if errors grow exponentially without bound as n increases, the scheme is **unstable**.

3 The Von Neumann Stability Analysis

Introduced by John von Neumann during the Manhattan Project, this method uses **discrete Fourier series** to track the growth or decay of individual spatial harmonic modes as time advances.

3.1 Fourier Representation of Grid Functions

Any spatial grid function ϵ_j^n on a domain with periodic boundary conditions can be represented as a sum of discrete Fourier modes:

$$\epsilon_j^n = \sum_k \hat{\epsilon}_k^n e^{ikx_j} = \sum_k \hat{\epsilon}_k^n e^{ik(j\Delta x)} \quad (2)$$

where k is the spatial wavenumber and $i = \sqrt{-1}$. Let us define the **dimensionless phase angle** ξ :

$$\xi = k \Delta x \in [-\pi, \pi] \quad (3)$$

- $\xi = 0$ ($k = 0$): Represents the infinitely long wave (constant mode).
- $\xi = \pm\pi$ ($k = \pm\pi/\Delta x$, wavelength $\lambda = 2\Delta x$): Represents the **highest frequency mode resolvable on the grid** (the high-frequency saw-tooth mode, alternating $\dots, +1, -1, +1, -1, \dots$).

3.2 The Amplification Factor $G(\xi)$

Because the difference equation is linear, the individual Fourier modes are decoupled. We can analyze a single representative harmonic mode:

$$\epsilon_j^n = \hat{\epsilon}^n e^{ij\xi} \quad (4)$$

At the next time level $t^{n+1} = (n+1)\Delta t$, this mode evolves to:

$$\epsilon_j^{n+1} = \hat{\epsilon}^{n+1} e^{ij\xi} = G(\xi) \hat{\epsilon}^n e^{ij\xi} \quad (5)$$

where $G(\xi)$ is the complex **amplification factor**:

$$G(\xi) = \frac{\hat{\epsilon}^{n+1}}{\hat{\epsilon}^n} \quad (6)$$

3.3 The Von Neumann Stability Criterion

Since $e^{ij\xi} \neq 0$, dividing equation (5) through by it strips out all spatial dependence and leaves a purely **scalar recursion** relating successive amplitudes:

$$\hat{\epsilon}^{n+1} = G(\xi) \hat{\epsilon}^n \quad (7)$$

This is nothing more than a one-term linear recursion of the form $x_{n+1} = Gx_n$ (compare compound interest), so by direct induction on (7), after n time steps the amplitude of a mode is given by:

$$\hat{\epsilon}^n = [G(\xi)]^n \hat{\epsilon}^0 \quad (8)$$

To ensure that errors do not grow exponentially as $n \rightarrow \infty$, the magnitude of the amplification factor must not exceed unity for all resolvable wave modes $\xi \in [-\pi, \pi]$:

$$|G(\xi)| \leq 1 \quad \forall \xi \in [-\pi, \pi] \quad (9)$$

Remark: From a Single Mode to the Full Error — Parseval's Identity

Equation (7) only tracks *one* Fourier mode, yet the full error ϵ_j^n is a *sum* over all modes (equation (2)). The bridge between the two is **Parseval's identity**: because the discrete Fourier transform is an isometry on a periodic grid,

$$\|\epsilon^n\|_2^2 = \sum_k |\hat{\epsilon}_k^n|^2 = \sum_k |G(\xi_k)|^{2n} |\hat{\epsilon}_k^0|^2.$$

Since the modes evolve independently (linearity again), the *total* error energy stays bounded for all n if and only if $|G(\xi_k)| \leq 1$ for **every** mode ξ_k present — which is exactly the criterion in the box above, now applied uniformly over $\xi \in [-\pi, \pi]$ to cover any possible initial error.

A sharper remark: the precise (Lax–Richtmyer) definition of stability only requires the error to stay bounded over any *fixed* final time $T = n\Delta t$ as $\Delta t \rightarrow 0$, which permits $|G(\xi)| \leq 1 + K\Delta t$ for some constant K independent of $\Delta t, \xi$ (since then $|G|^n \leq (1 + K\Delta t)^n \leq e^{KT}$, a controlled growth rather than none at all). The strict condition $|G(\xi)| \leq 1$ used here is the standard simplified version, valid whenever the scheme has no explicit lower-order source term — true for every scheme in this lecture, but worth knowing when you later encounter equations with reaction or source terms.

4 Stability Analysis of Classical Schemes for Advection

Remark: Why We Now Work with u Instead of ϵ

Section 2 defined stability in terms of the **error** $\epsilon_j^n = \tilde{u}_j^n - u_j^n$, since stability is, by definition, a statement about whether small perturbations grow or decay. Below, however, we substitute the Fourier mode directly into the **numerical solution** $u_j^n = \hat{u}^n e^{ij\xi}$ rather than into ϵ_j^n — this is standard practice, and is justified rather than merely convenient.

The justification is the linearity observation from Section 2: because every scheme below is a **linear** difference equation, ϵ_j^n satisfies *exactly the same* recurrence as u_j^n . Concretely, if $u_j^{n+1} = \mathcal{L}(u_{j-1}^n, u_j^n, u_{j+1}^n)$ for a linear operator $\mathcal{L}$, subtracting the identical equation written for $\tilde{u}_j^n$ gives $\epsilon_j^{n+1} = \mathcal{L}(\epsilon_{j-1}^n, \epsilon_j^n, \epsilon_{j+1}^n)$ — the same update formula. So substituting a Fourier mode into u_j^n or ϵ_j^n yields the **same** $G(\xi)$; we use u purely to avoid carrying the extra tilde/epsilon notation through every derivation.

Caution: this shortcut relies entirely on linearity. For a nonlinear scheme, u_j^n and ϵ_j^n obey *different* evolution equations, and Von Neumann analysis only applies after linearizing (e.g. freezing coefficients) about a background state.

We now apply Von Neumann analysis to the 1D linear advection equation:

$$\frac{\partial u}{\partial t} + a \frac{\partial u}{\partial x} = 0, \quad a > 0 \quad (10)$$

Recall the **CFL (Courant) number**:

$$\nu = \frac{a \Delta t}{\Delta x} \quad (11)$$

4.1 Forward Time, Central Space (FTCS)

The FTCS difference equation is:

$$\frac{u_j^{n+1} - u_j^n}{\Delta t} + a \frac{u_{j+1}^n - u_{j-1}^n}{2\Delta x} = 0 \implies u_j^{n+1} = u_j^n - \frac{\nu}{2} (u_{j+1}^n - u_{j-1}^n) \quad (12)$$

Substituting a Fourier mode $u_j^n = \hat{u}^n e^{ij\xi}$:

$$\begin{aligned} \hat{u}^{n+1} e^{ij\xi} &= \hat{u}^n e^{ij\xi} - \frac{\nu}{2} (\hat{u}^n e^{i(j+1)\xi} - \hat{u}^n e^{i(j-1)\xi}) \\ \hat{u}^{n+1} &= \hat{u}^n \left[1 - \frac{\nu}{2} (e^{i\xi} - e^{-i\xi}) \right] \end{aligned} \quad (13)$$

Using Euler's identity $\sin \xi = \frac{e^{i\xi} - e^{-i\xi}}{2i}$:

$$G_{\text{FTCS}}(\xi) = 1 - i\nu \sin \xi \quad (14)$$

Computing the squared magnitude of the amplification factor:

$$|G_{\text{FTCS}}(\xi)|^2 = 1^2 + (-\nu \sin \xi)^2 = 1 + \nu^2 \sin^2 \xi \quad (15)$$

Conclusion: FTCS is Unconditionally Unstable

For any non-zero time step ($\nu > 0$), we have:

$$|G_{\text{FTCS}}(\xi)| = \sqrt{1 + \nu^2 \sin^2 \xi} > 1 \quad \text{for all } \xi \neq 0, \pm\pi$$

Every interior Fourier mode is amplified at every time step ($|G| > 1$). The high frequencies blow up exponentially. Therefore, **FTCS is unconditionally unstable for hyperbolic advection**.

4.2 First-Order Upwind Scheme (FOU)

For $a > 0$, the backward-in-space upwind scheme is:

$$u_j^{n+1} = u_j^n - \nu(u_j^n - u_{j-1}^n) = (1 - \nu)u_j^n + \nu u_{j-1}^n \quad (16)$$

Substituting $u_j^n = \hat{u}^n e^{ij\xi}$:

$$\begin{aligned} \hat{u}^{n+1} &= \hat{u}^n \left[(1 - \nu) + \nu e^{-i\xi} \right] \\ G_{\text{FOU}}(\xi) &= (1 - \nu) + \nu(\cos \xi - i \sin \xi) = (1 - \nu + \nu \cos \xi) - i\nu \sin \xi \end{aligned} \quad (17)$$

Computing the squared magnitude $|G_{\text{FOU}}(\xi)|^2$:

$$\begin{aligned} |G_{\text{FOU}}(\xi)|^2 &= (1 - \nu + \nu \cos \xi)^2 + \nu^2 \sin^2 \xi \\ &= (1 - \nu)^2 + 2\nu(1 - \nu) \cos \xi + \nu^2 \cos^2 \xi + \nu^2 \sin^2 \xi \\ &= 1 - 2\nu + \nu^2 + 2\nu(1 - \nu) \cos \xi + \nu^2 \\ &= 1 - 2\nu(1 - \nu)(1 - \cos \xi) \end{aligned} \quad (18)$$

Using the trigonometric identity $1 - \cos \xi = 2 \sin^2(\xi/2)$:

$$\boxed{|G_{\text{FOU}}(\xi)|^2 = 1 - 4\nu(1 - \nu) \sin^2\left(\frac{\xi}{2}\right)} \quad (19)$$

For stability, we require $|G(\xi)|^2 \leq 1$, which implies:

$$4\nu(1 - \nu) \sin^2\left(\frac{\xi}{2}\right) \geq 0 \quad \text{and} \quad 4\nu(1 - \nu) \sin^2\left(\frac{\xi}{2}\right) \leq 1 \quad (20)$$

This holds for all ξ if and only if $\nu(1 - \nu) \geq 0$, which yields the celebrated **CFL stability condition**:

$$\boxed{0 \leq \nu = \frac{a \Delta t}{\Delta x} \leq 1} \quad (21)$$

4.3 The Lax-Friedrichs Scheme

In 1954, Peter Lax proposed a simple cure for the instability of FTCS: replace the central node value u_j^n in the time derivative by the spatial average of its neighbors, $\frac{u_{j+1}^n + u_{j-1}^n}{2}$:

$$\frac{u_j^{n+1} - \frac{1}{2}(u_{j+1}^n + u_{j-1}^n)}{\Delta t} + a \frac{u_{j+1}^n - u_{j-1}^n}{2\Delta x} = 0 \quad (22)$$

Solving for u_j^{n+1} :

$$\boxed{u_j^{n+1} = \frac{1}{2}(u_{j+1}^n + u_{j-1}^n) - \frac{\nu}{2}(u_{j+1}^n - u_{j-1}^n) = \frac{1 - \nu}{2}u_{j+1}^n + \frac{1 + \nu}{2}u_{j-1}^n} \quad (23)$$

4.3.1 Stability of Lax-Friedrichs

Substituting $u_j^n = \hat{u}^n e^{ij\xi}$ into equation (23):

$$G_{\text{LxF}}(\xi) = \frac{e^{i\xi} + e^{-i\xi}}{2} - \frac{\nu}{2}(e^{i\xi} - e^{-i\xi}) = \cos \xi - i\nu \sin \xi \quad (24)$$

Computing the magnitude squared:

$$|G_{\text{LxF}}(\xi)|^2 = \cos^2 \xi + \nu^2 \sin^2 \xi = 1 - \sin^2 \xi + \nu^2 \sin^2 \xi = 1 - (1 - \nu^2) \sin^2 \xi \quad (25)$$

For $|G_{\text{LxF}}(\xi)| \leq 1$ for all ξ , we require $1 - \nu^2 \geq 0 \implies \nu^2 \leq 1$. Thus, the Lax-Friedrichs scheme is **conditionally stable** under:

$$\boxed{|\nu| = \frac{|a| \Delta t}{\Delta x} \leq 1} \quad (26)$$

4.3.2 Modified Equation and Dissipation of Lax-Friedrichs

Notice that equation (22) can be rewritten as FTCS plus an artificial diffusion term:

$$\frac{u_j^{n+1} - u_j^n}{\Delta t} + a \frac{u_{j+1}^n - u_{j-1}^n}{2\Delta x} = \frac{\Delta x^2}{2\Delta t} \left(\frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2} \right) \quad (27)$$

The modified equation is:

$$\frac{\partial u}{\partial t} + a \frac{\partial u}{\partial x} = \underbrace{\left(\frac{\Delta x^2}{2\Delta t} - \frac{a^2 \Delta t}{2} \right)}_{\alpha_{\text{num}} = \frac{\Delta x^2}{2\Delta t} (1 - \nu^2)} \frac{\partial^2 u}{\partial x^2} \quad (28)$$

Lax-Friedrichs adds a large amount of artificial numerical dissipation $\mathcal{O}(\Delta x^2/\Delta t)$, which stabilizes the scheme but smears out sharp gradients.

4.4 The Lax-Wendroff Scheme (Second-Order)

The First-Order Upwind and Lax-Friedrichs schemes are only first-order accurate ($\mathcal{O}(\Delta t, \Delta x)$). In 1960, Peter Lax and Burton Wendroff developed a **second-order accurate in space and time** scheme ($\mathcal{O}(\Delta t^2, \Delta x^2)$) using the **Cauchy-Kovalevskaya procedure**.

4.4.1 Derivation

Expand $u(x_j, t^{n+1})$ in time via Taylor series up to second order:

$$u(x_j, t^{n+1}) = u(x_j, t^n) + \Delta t \frac{\partial u}{\partial t}(x_j, t^n) + \frac{\Delta t^2}{2} \frac{\partial^2 u}{\partial t^2}(x_j, t^n) + \mathcal{O}(\Delta t^3) \quad (29)$$

Using the advection PDE $u_t = -au_x$, we replace time derivatives with spatial derivatives:

$$\frac{\partial u}{\partial t} = -a \frac{\partial u}{\partial x} \quad (30)$$

$$\frac{\partial^2 u}{\partial t^2} = \frac{\partial}{\partial t} \left(-a \frac{\partial u}{\partial x} \right) = -a \frac{\partial}{\partial x} \left(\frac{\partial u}{\partial t} \right) = -a \frac{\partial}{\partial x} \left(-a \frac{\partial u}{\partial x} \right) = a^2 \frac{\partial^2 u}{\partial x^2} \quad (31)$$

Substituting these expressions into equation (29):

$$u(x_j, t^{n+1}) = u(x_j, t^n) - a\Delta t \frac{\partial u}{\partial x} + \frac{a^2 \Delta t^2}{2} \frac{\partial^2 u}{\partial x^2} + \mathcal{O}(\Delta t^3) \quad (32)$$

Now, replace spatial derivatives with standard second-order central difference formulas:

$$\boxed{u_j^{n+1} = u_j^n - \frac{\nu}{2}(u_{j+1}^n - u_{j-1}^n) + \frac{\nu^2}{2}(u_{j+1}^n - 2u_j^n + u_{j-1}^n)} \quad (33)$$

4.4.2 Stability Analysis of Lax-Wendroff

Substituting the Fourier mode $u_j^n = \hat{u}^n e^{ij\xi}$:

$$\begin{aligned} G_{\text{LW}}(\xi) &= 1 - \frac{\nu}{2}(e^{i\xi} - e^{-i\xi}) + \frac{\nu^2}{2}(e^{i\xi} - 2 + e^{-i\xi}) \\ &= 1 - i\nu \sin \xi + \nu^2(\cos \xi - 1) = (1 - 2\nu^2 \sin^2(\xi/2)) - i\nu \sin \xi \end{aligned} \quad (34)$$

Computing the squared magnitude:

$$\begin{aligned} |G_{\text{LW}}(\xi)|^2 &= (1 - 2\nu^2 \sin^2(\xi/2))^2 + \nu^2 \sin^2 \xi \\ &= 1 - 4\nu^2 \sin^2(\xi/2) + 4\nu^4 \sin^4(\xi/2) + 4\nu^2 \sin^2(\xi/2) \cos^2(\xi/2) \\ &= 1 - 4\nu^2 \sin^2(\xi/2) [1 - \cos^2(\xi/2) - \nu^2 \sin^2(\xi/2)] \\ &= 1 - 4\nu^2 \sin^2(\xi/2) [\sin^2(\xi/2)(1 - \nu^2)] \\ &= \boxed{1 - 4\nu^2(1 - \nu^2) \sin^4\left(\frac{\xi}{2}\right)} \end{aligned} \quad (35)$$

For $|G_{\text{LW}}(\xi)| \leq 1$ for all ξ , we require $4\nu^2(1 - \nu^2) \geq 0 \implies \nu^2 \leq 1$. Thus, Lax-Wendroff is **second-order accurate and stable** under:

$$|\nu| = \frac{|a|\Delta t}{\Delta x} \leq 1 \quad (36)$$

5 Summary of Classical Advection Schemes

Scheme	Order	Amplification Factor $G(\xi)$	Stability Condition
FTCS	$\mathcal{O}(\Delta t, \Delta x^2)$	$1 - i\nu \sin \xi$	Unconditionally Unstable
Upwind (FOU)	$\mathcal{O}(\Delta t, \Delta x)$	$(1 - \nu + \nu \cos \xi) - i\nu \sin \xi$	$0 \leq \nu \leq 1$ ($a > 0$)
Lax-Friedrichs	$\mathcal{O}(\Delta t, \Delta x^2/\Delta t)$	$\cos \xi - i\nu \sin \xi$	$ \nu \leq 1$
Lax-Wendroff	$\mathcal{O}(\Delta t^2, \Delta x^2)$	$1 - 2\nu^2 \sin^2(\xi/2) - i\nu \sin \xi$	$ \nu \leq 1$

6 Exercises

Exercises for Lecture 7

E1. Diffusion Equation Stability: Consider the 1D heat equation $u_t = \alpha u_{xx}$ with $\alpha > 0$, discretized using Forward-Time Central-Space (FTCS):

$$\frac{u_j^{n+1} - u_j^n}{\Delta t} = \alpha \frac{u_{j+1}^n - 2u_j^n + u_{j-1}^n}{\Delta x^2}$$

- Define the diffusion number $r = \frac{\alpha \Delta t}{\Delta x^2}$ and express the scheme in update form.
- Apply Von Neumann stability analysis to find the amplification factor $G(\xi)$ as a function of r and ξ .
- Prove that the scheme is stable if and only if $r \leq \frac{1}{2}$.

E2. Dissipation and Dispersion Errors: For the Lax-Wendroff scheme with $\nu = 0.5$, compute the magnitude $|G(\xi)|$ at the wave modes $\xi = \pi/4, \pi/2, \pi$. Which wave modes suffer the most numerical damping?

E3. Beam-Warming Scheme (Upwind Second-Order): By expanding $u(x_j, t^{n+1})$ in time and replacing spatial derivatives with second-order *backward* differences, derive the explicit update formula for the second-order upwind **Beam-Warming scheme**:

$$u_j^{n+1} = u_j^n - \frac{\nu}{2}(3u_j^n - 4u_{j-1}^n + u_{j-2}^n) + \frac{\nu^2}{2}(u_j^n - 2u_{j-1}^n + u_{j-2}^n)$$

Show that its CFL stability condition is $0 \leq \nu \leq 2$.

References

- [1] John D. Anderson. *Computational Fluid Dynamics: The Basics with Applications*. McGraw-Hill, New York, NY, 1995.
- [2] Randall J. LeVeque. *Finite Volume Methods for Hyperbolic Problems*. Cambridge University Press, Cambridge, UK, 2002.