

K1_DVP_BOARD

Revision History

Rev. Code	Date	By	Description
V1.0	2024-08-01	Bzliu	Initial version
V1.1	2025-01-01	Bzliu	1.Change resistor R2 to 0 ohms. 2.Change VCC1833_QSPI to VCC18_GPIO.



Bit-Brick Co.,Ltd		
K1_DVP_BOARD		
Size B	Document Number: REVISION HISTORY	Rev: V1.1
Date:	Thursday, February 06, 2025	Sheet 1 of 30

INDEX/NOTES

Page1	01 REVISION HISTORY
Page2	02 INDEX/NOTES
Page3	03 BLOCK DIAGRAM
Page4	04 POWER TREE
Page5	05 POWER SEQUENCE
Page6	06 CLOCK MAP/I2C MAP
Page7	07 UART MAP/OTHER MAP
Page8	08 GPIO ASSIGNMENT
Page9	09 SODIMM 260P MAIN
Page10	10 SODIMM 260P SUB1
Page11	11 SODIMM 260P SUB2
Page12	12 SODIMM 260P SUB3
Page13	13 POWER-EXT DCDC
Page14	14 5 Potr Controller
Page15	19 VO-HDMI
Page17	22 Ethernet-GMAC0
Page18	24 USB
Page19	25 PCIEB M.2 KEY M
Page20	30 Mechanical
Page22	
Page24	
Page25	
Page26	
Page27	
Page28	
Page29	
Page30	




Bit-Brick Co.,Ltd

K1_DVP_BOARD

Size A	Document Number: INDEX	Rev: V1.1
Date:	Thursday, February 06, 2025	Sheet 2 of 30


BLOCK



Bit-Brick Co., Ltd
K1_DVP_BOARD

Size B	Document Number: BLOCK	Rev: V1.1
Date:	Thursday, February 06, 2025	Sheet 3 of 30


POWER TREE



POWER SEQUENCE

Control by PMIC

冷起自动上电，后长按关机，短按开机



P1




Bit-Brick Co., Ltd


K1_DVP_BOARD

Size B	Document Number:	POWER SEQUENCE	Rev: V1.1
Date:	Thursday, February 06, 2025	Sheet 5 of 30	

CLOCK MAP




I2C MAP




Bit-Brick Co. Ltd
K1_DVP_BOARD


UART MAP



SW&RESET MAP



PCIE/USB MAP



Bit-Brick Co., Ltd.
K1_DVP_BOARD

GPIO ASSIGNMENT

PIN	Define	CFG	Function
GPIO0	GMAC0_RXDV	1	Ethernet -GMAC0
GPIO1	GMAC0_RXD0	1	
GPIO2	GMAC0_RXD1	1	
GPIO3	GMAC0_RXCLK	1	
GPIO4	GMAC0_RXD2	1	
GPIO5	GMAC0_RXD3	1	
GPIO6	GMAC0_TXD0	1	
GPIO7	GMAC0_TXD1	1	
GPIO8	GMAC0_TXCLK	1	
GPIO9	GMAC0_TXD2	1	
GPIO10	GMAC0_TXD3	1	
GPIO11	GMAC0_TXEN	1	
GPIO12	GMAC0_MDC	1	NA
GPIO13	GMAC0_MDIO	1	
GPIO14	GMAC0_INT_N	1	
GPIO15	MMC2_DATA3	1	
GPIO16	MMC2_DATA2	1	
GPIO17	MMC2_DATA1	1	
GPIO18	MMC2_DATA0	1	
GPIO19	MMC2_CMD	1	
GPIO20	MMC2_CLK	1	
GPIO21	UART2_TXD	1	
GPIO22	UART2_RXD	1	
GPIO23	UART2_CTS_N	1	40 pin
GPIO24	UART2_RTS_N	1	
GPIO25	I2S1_SCLK	1	
GPIO26	I2S1_LRCK	1	
GPIO27	I2S1_TXD	1	
GPIO28	I2S1_RXD	1	
GPIO29	GPIO29	0	
GPIO30	GPIO30	0	
GPIO31	GPIO31	0	
GPIO32	GPIO32	0	
GPIO33	GPIO33	0	
GPIO34	GPIO34	0	PCIEC
GPIO35	GPIO35	0	
GPIO36	PCIEC_WAKEN	4	40 pin
GPIO37	GPIO37	0	
GPIO38	AP_I2C3_SCL	2	LCD/CTP
GPIO39	AP_I2C3_SDA	2	
GPIO40	LCD_BL_EN_1V8	0	NA
GPIO41	LCD_RST_1V8	0	
GPIO42	CAMERA2_RST	0	LCD/CTP
GPIO43	CAMERA2_PDN	0	
GPIO44	LCD_BL_PWM_1V8	4	GMAC0
GPIO45	GMAC0_CLK_REF	1	40 pin
GPIO46	GPIO46	0	

PIN	Define	CFG	Function
GPIO110	GMAC0_RSTn_L	0	GMAC0
GPIO115	GPIO115	0	TP
GPIO116	WL_DIS_N	0	
GPIO117	PCIEC_CLKREQN	4	PCIEC
GPIO118	I2S0_SCLK	3	TP
GPIO119	I2S0_LRCK	3	
GPIO120	CAM_MCLK2	2	CAMERA2
GPIO121	CAMERA2_RST	0	
GPIO122	CAMERA2_PDN	0	USB2
GPIO123	USB2_PWREN	0	
GPIO124	TP_INT_1V8	0	LCD/CTP
GPIO125	AP_WAKE_BT	0	NA
GPIO126	CODEC_IRQ	0	
GPIO127	PA_SHUTDOWN	0	

PIN	Define	CFG	Function
GPIO53	CAM_MCLK0	1	CAMERA0
GPIO54	CAM_I2C0_SCL	1	
GPIO55	CAM_I2C0_SDA	1	CAMERA1
GPIO56	CAM_I2C1_SCL	1	
GPIO57	CAM_I2C1_SDA	1	LCD/CTP
GPIO58	CAM_MCLK1	1	CAMERA0
GPIO111	CAMERA0_RST	1	CAMERA1
GPIO112	CAMERA1_RST	1	CAMERA0
GPIO113	CAMERA0_PDN	1	CAMERA1
GPIO114	CAMERA1_PDN	1	NA
GPIO63	BT_RESEn	0	USB2
GPIO64	VBUS_ON0	1	NA
GPIO65	BT_WAKE_AP	0	
GPIO66	WL_WAKE_AP	0	
GPIO67	WL_REG_ON	0	X60 Debug
GPIO68	UART0_TXD	2	
GPIO69	UART0_RXD	2	

PIN	Define	CFG	Function
GPIO59	PCIEB_PERSTN	4	PCIEB
GPIO60	PCIEB_WAKEN	4	
GPIO61	PCIEB_CLKREQN	4	PCIEC
GPIO62	PCIEC_PERSTN	4	
GPIO70	GPIO70	1	40 pin
GPIO71	GPIO71	1	
GPIO72	GPIO72	1	
GPIO73	GPIO73	1	
GPIO74	GPIO74	0	

红色字体GPIO表示默认、持续上拉，等效上拉电阻约60K。需要软件修改才能解除默认上拉状态

PIN	Define	CFG	Function
GPIO93	PI2C_SCL	0	PMIC
GPIO94	PI2C_SDA	0	
GPIO95	SLEEP_OUT	0	LED
GPIO96	GPIO96	1	
GPIO97	TP_RST_1V8	0	LCD/CTP
GPIO81	AP_I2C5_SCL	5	
GPIO82	AP_I2C5_SDA	5	EEPROM Audio
GPIO83	LCD_PWR_EN_1V8	0	
GPIO84	AP_I2C2_SCL	4	HDMI_OUT
GPIO85	AP_I2C2_SDA	4	
GPIO86	HDMI_SCL	1	40 pin
GPIO87	HDMI_SDA	1	
GPIO88	HDMI_CEC	1	
GPIO89	HDMI_HPD	1	
GPIO90	GPIO90	0	
GPIO91	GPIO91	0	
GPIO92	GPIO92	0	

PIN	Define	CFG	Function
GPIO98	QSPI_DATA3	0	SPI FLASH
GPIO99	QSPI_DATA2	0	
GPIO100	QSPI_DATA1	0	
GPIO101	QSPI_DATA0	0	
GPIO102	QSPI_CLK	0	
GPIO103	QSPI_CS1	0	

PIN	Define	CFG	Function
GPIO104	MMC1_DATA3	0	TF CARD
GPIO105	MMC1_DATA2	0	
GPIO106	MMC1_DATA1	0	
GPIO107	MMC1_DATA0	0	
GPIO108	MMC1_CMD	0	
GPIO109	MMC1_CLK	0	

PIN	Define	CFG	Function
GPIO75	SPI3_SCLK_3V3	2	40 pin
GPIO76	SPI3_CS_3V3	2	
GPIO77	SPI3_MOSI_3V3	2	
GPIO78	SPI3_MISO_3V3	2	
GPIO79	USB3_PWREN	0	USB3
GPIO80	SD_CD_3V3	1	TF CARD

PIN	Define	CFG	Function
GPIO47	R_UART0_TXD_3V3	1	40 pin
GPIO48	R_UART0_RXD_3V3	1	
GPIO49	GPIO_49_3V3	0	
GPIO50	GPIO_50_3V3	0	
GPIO51	AP_I2C4_SCL_3V3	4	
GPIO52	AP_I2C4_SDA_3V3	4	


(14) P2_RJ45_AN << PHY1_MDIO*_SUB1
(14) P2_RJ45_AP << PHY1_MDIO*_SUB1
(14) P2_RJ45_BP << PHY1_MDIO*_SUB1
(14) P2_RJ45_CN << PHY1_MDIO*_SUB1
(14) P2_RJ45_CP << PHY1_MDIO*_SUB1
(14) P2_RJ45_DP << PHY1_MDIO*_SUB1

JTAG SEL


SEC JTAG SEL & Route

JTAG_SEL	Function	NMC1_CMD	JTAG Route
0	Other	0	X60
1	JTAG	1	N308


PowerON



LED




(14) PHY1_MDIO*_SUB1 << PHY1_MDIO*_SUB1
(14) PHY1_MDIO*_SUB1 << PHY1_MDIO*_SUB1
(14) PHY1_MDIO*_SUB1 << PHY1_MDIO*_SUB1
(14) PHY1_MDIO*_SUB1 << PHY1_MDIO*_SUB1
(14) PHY1_MDIO*_SUB1 << PHY1_MDIO*_SUB1
(14) PHY1_MDIO*_SUB1 << PHY1_MDIO*_SUB1
(14) PHY1_MDIO*_SUB1 << PHY1_MDIO*_SUB1
(14) PHY1_MDIO*_SUB1 << PHY1_MDIO*_SUB1
(14) PHY1_MDIO*_SUB1 << PHY1_MDIO*_SUB1
(14) PHY1_MDIO*_SUB1 << PHY1_MDIO*_SUB1



GPIO_90_SUB1 (10)

Flash Boot voltage sel



boot download sel


QSPI_DATA3	Function
0	启动
1	下载

download sel

QSPI_DATA2	Function
0	USB
1	UART

Boot SEL

QSPI_DATA1	QSPI_DATA0	Function
0	0	TF Card -> EMMC
0	1	TF Card -> SPI NOR
1	0	TF Card -> SPI NAND
1	1	TF Card -> SD



GPIO_96_SUB1 (10)

UART0_RXD_1 (24)

UART0_TXD_1 (24)

SW_PWRON_SUB1 (10)

SW_RST_SUB1 (9)

VCCSV0_SYS

VCC_BAT_SUB1

VCCSV0_SYS



Bilibili Co., Ltd.

K1_DVP_BOARD


(14) P3_RJ45_AN << PHY1_MDIO0_SUB2
(14) P3_RJ45_AP << PHY1_MDIO0_SUB2
(14) P3_RJ45_BN << PHY1_MDIO1_SUB2
(14) P3_RJ45_BP << PHY1_MDIO1_SUB2
(14) P3_RJ45_CN << PHY1_MDIO2_SUB2
(14) P3_RJ45_CP << PHY1_MDIO2_SUB2
(14) P3_RJ45_DN << PHY1_MDIO3_SUB2
(14) P3_RJ45_DP << PHY1_MDIO3_SUB2

JTAG SEL


SEC JTAG SEL & Route

JTAG_SEL	Function	MMC1_CMD	JTAG Route
0	Other	0	X60
1	JTAG	1	N308

PowerON



(14) PHY1_MDIO0_SUB2 << PHY1_MDIO0_SUB2
(14) PHY1_MDIO0_SUB2 << PHY1_MDIO0_SUB2
(14) PHY1_MDIO1_SUB2 << PHY1_MDIO1_SUB2
(14) PHY1_MDIO1_SUB2 << PHY1_MDIO1_SUB2
(14) PHY1_MDIO2_SUB2 << PHY1_MDIO2_SUB2
(14) PHY1_MDIO2_SUB2 << PHY1_MDIO2_SUB2
(14) PHY1_MDIO3_SUB2 << PHY1_MDIO3_SUB2
(14) PHY1_MDIO3_SUB2 << PHY1_MDIO3_SUB2



Flash Boot voltage sel

VCC18_GPIO

根据贴的SPI Flash
确认默认启动电压

(11) GPIO_90_SUB2 << GPIO_90_SUB2

GPIO 90	Function
0	1V8
1	3V3

boot download sel


QSPI_DATA3	Function
0	启动
1	下载

download sel


QSPI_DATA2	Function
0	USB
1	UART

Boot SEL



QSPI_DATA1	QSPI_DATA0	Function
0	0	TF Card -> EMMC
0	1	TF Card -> SPI NOR
1	0	TF Card -> SPI NAND
1	1	TF Card -> SD



LED



Bilibili Co., Ltd.
K1_DVP_BOARD



SEC JTAG SEL & Route

JTAG_SEL	Function	MMC1_CMD	JTAG Route
0	Other	0	X60
1	JTAG	1	N308

SW6

1 2 3 4


TS24ACA250P 013
SW4P_2R35X4R50

R32 1K
0.020µF


PDS30V01BL

0.020µF

SW_PWRON_SUB3 (12)



Flash Boot voltage sel VCC18 GPIO



GPIO 90	Function
0	1V8
1	3V3

```
boot download sel
```

QSPI_DATA3	Function
0	启动
1	下载


download sel

QSPI_DATA2	Function
0	USB
1	UART


Boot SEL

QSPI_DATA1	QSPI_DATA0	Function
0	0	TF Card -> EMMC
0	1	TF Card -> SPI NOR
1	0	TF Card -> SPI NAND
1	1	TF Card -> SD



PCIE_VCC3V3




8.3V<DCIN<15V




VCC5V0_SYS








RTL8367 VDDIO










HDMI

- HDMI_TX0P (9)
- HDMI_TX0N (9)
- HDMI_TX1P (9)
- HDMI_TX1N (9)
- HDMI_TX2P (9)
- HDMI_TX2N (9)
- HDMI_TXCP (9)
- HDMI_TXCN (9)
- HDMI_SCL (9)
- HDMI_SDA (9)
- HDMI_CEC (9)
- HDMI_HPD (9)



GMAC Ethernet0



Bit-Brick Co.,Ltd

K1_DVP_BOARD

Size A

Document Number: ETHERNET GMAC0




Rev: V1.1

Date:




Thursday, February 06, 2025

Sheet 22 of 30




USB3.0 TYPEA



USB2.0 TYPEA-HOST



USB2.0 TYPEC



CH9344L

PCIEB

