



R8 Tablet

Extreme Power, Ultra Compact.

- 8.0" LCD DynaVue® SR display with 800 nits
- 12th Generation Intel[®] Core[™] Processor
- Intel[®] Wi-Fi 6E AX211 & Bluetooth[®] V5.3
- Coolfinity[™] fanless thermal design

- Long-Life Battery up to 17 hours
- Optional barcode, RFID & smart card reader
- 10-point capacitive multi-touch panel with four touch modes

















R8 Specifications



DURABILITY	 MIL-STD 810H certified (Drop, Shock, Vibration, Rain, Dust, Altitude, Freeze/Thaw, High/Low Temperature, Temperature Shock, Humidity, Explosive Atmosphere, Salt Fog) MIL-STD 461G certified (Conduction, Radiation, Conducted Susceptibility, Radiated Susceptibility) Optional ANSI/UL 121201, Class I, Division 2 6' drop 26 faces 	SECURITY	 Intel[®] vPro[™] Technology (per CPU options) TPM 2.0 NIST BIOS compliant Stealth mode Night vision mode Optional smart card reader^{1,2} Optional LF/HF-RFID (NFC) reader^{1,2} Optional UHF-RFID (NFC) reader^{1,2}
	IP 66 certifiedAluminum-magnesium alloy chassisPort coversSunlight readable displayOptional swappable battery technology	I/O INTERFACES	 Thunderbolt 4 x 1 USB 3.2 Gen 2 (type C) x 1 (support DP) Audio in/out (combo jack) x 1 microSD card (microSDXC) x 1 Docking connector (20-pin Pogo) x 1
OPERATING SYSTEM	Windows [®] 11 Pro 64-bit		• Nano SIM card x 1
PROCESSORS	 Intel[®] Core[™] i7-1250U (12th Gen) Processor with vPro[™] (12MB Cache, up to 4.7 GHz, 2P+8E cores) Intel[®] Core[™] i5-1230U (12th Gen) Processor with vPro[™] (12MB Cache, up to 4.4 GHz, 2P+8E cores) Intel[®] Pentium[®] Gold Processor 8500 		 DC-In jack x 1 Optional USB 3.2 Gen1 (type A) x 1² Optional 10/100/1000 Ethernet (RJ45) x 1² Optional serial port (RS232) x 1² Optional 1D/2D barcode reader x 1² Optional RF antenna pass-through for GPS, WWAN and WLAN¹
	(8MB Cache, up to 4.4 GHz, 1P+4E cores)	EXPANSION SLOT	 Optional magnetic stripe reader^{1,2} Optional smart card reader with
GRAPHICS	Intel [®] Iris [®] Xe Graphics		LF/HF-RFID (NFC) or UHF-RFID (NFC) or RS232/RJ45/USB 3.2 Gen1 (type A) ^{1,2}
STORAGE DISPLAY	Onboard 8GB up to 16GB (LPDDR4x) 128GB NVMe PCIe SSD Optional 256GB/512GB/1TB PCIe SSD 8.0" LCD (1280 × 800)	POWER	AC adapter: 100-240V, 50Hz-60Hz, 65W Main battery Li-lon, 7.6V, 3600mAh, 8.5 hours ⁴ • Optional long life battery Li-lon 7.6V, 7200mAh, 17 hours ⁴ • Optional swappable battery: 5 minutes
	 800 nits DynaVue[®] sunlight readable display with capacitive multi-touch screen Optional with digitizer User selectable touch mode for Finger/Water, Glove or Stylus programmable function 	ENVIRONMENT	 swap time⁵ Temperature Operating: - 20°C ~ 60°C / - 4°F ~ 140°F Storage: - 46°C ~ 71°C / - 51°F ~ 160°F Humidity: 5% ~ 95%
AUDIO	 Integrated microphone Intel[®] High Definition Audio Compliant Integrated speaker × 1 	DIMENSION & WEIGHT	• 227 mm (L) x 150 mm (W) x 20.5 mm (H) • 0.86 kg
CAMERA	 Integrated 2.0 MP front-facing camera Optional 8.0 MP auto-focus rear camera with flash 	WARRANTY	3-year limited warranty standard
KEYBOARD & INPUT	4 buttons (1 user-definable key)	 Contact your sales representative for feature availability. Mutually exclusive options. GPS/WWAN and dedicated GPS are mutually exclusive. Tested using the MobileMark 2014 battery life benchmark. Results may vary under different situations including hardware configuration, software, operating conditions, power management settings and The system will stay operating (within 300 seconds in standby mode) when user swaps the battery. 	
COMMUNICATONS	 Intel[®] Wi-Fi 6E AX211 (802.11 ax) Bluetooth[®] V5.3 Optional dedicated GPS module³ Optional GPS and 4G LTE multi-carrier mobile broadband³ 		



WWAN and WLAN 1

• Optional RF antenna pass-through for GPS,



www.durabook.com Mar. 2024_V9