

AdvPrint Pro

Advanced Printer — silent printing for every web page, PDF, application and receipt printer

by Bit Dream IT — Innovative Healthcare Solutions

Version 2.8.0 — Enterprise Edition

Full Setup Guide — A to Z

100% local · no cloud · no tracking · MIT licensed

Windows 7/8/10/11 · Windows Server · Debian/Ubuntu/Mint · macOS

Contents

1 What AdvPrint Pro is — and how one print job travels

2 Install in 3 minutes (Windows · Linux · macOS)

3 The token — and the one-click fix (never get locked out again)

4 The browser extension — every Options tab explained (Queue · History · Settings · Debug · LAN / PCs · About)

5 The hub dashboard — every card and button explained

6 Printing everything: PDFs, pages, window.print(), raw/thermal, screenshots, selections

7 LAN / IP: share one printer with every PC (and shift jobs between PCs)

8 Queue, History & Audit trail

9 Settings reference — every switch in one table

10 Debug & the Live Test tool — find WHY in one click

11 Enterprise edition: silent install, managed policy (GPO), service mode

12 HTTP API quick reference

13 Troubleshooting — every known problem and its fix

14 Upgrade, uninstall, files & folders

1. What AdvPrint Pro is — and how one print job travels

AdvPrint Pro (Advanced Printer) by **Bit Dream IT — Innovative Healthcare Solutions** prints anything — PDFs, web pages, `window.print()` calls, receipts (raw/ESC-POS), screenshots, selections — **silently**, with no print dialog, on any printer connected to the hub PC, including printers shared from other PCs. Everything stays on your machines: the hub listens on `127.0.0.1:9235` only (until you deliberately enable LAN sharing), no cloud, no telemetry.

> Product identity: **AdvPrint Pro** — *AdvPrint (Advanced Printer)* — **by Bit Dream IT — Innovative Healthcare Solutions**. The hub reports `app: "AdvPrint Pro"` and the full brand string in every /health answer.

```
Chrome (any web page)
   │  extension: auto-print rules / right-click / Alt+P / window.advprint API
   ▼
AdvPrint Pro HUB  (http://127.0.0.1:9235, token-protected)
   │  queue → retries → holds → printer status checks
   ▼
Silent print engines:  Windows: SumatraPDF (PDF) + Chrome headless (pages) + raw ESC/POS
                       Linux/macOS: CUPS lp + Chrome headless
   ▼
Your printer — or ~/.advprint/files if the destination is "save as PDF"
```

- **Hub** = tiny local web server (`advprint.py`) that owns the queue, the history and the printers.
- **Extension** = the browser side: auto-print rules, popup controls, the Options page (tab-wise), page API.
- **Dashboard** = the hub's browser UI at `/dashboard` : status, queue, history, audit, debug, LAN, live test, settings.
- **Tray icon** (Windows) = one click to the dashboard, pause/resume, test page, auto-run toggle.
- **Desktop tool** = `AdvPrint Tool` (Start Menu) — numbered menu for start/stop/service/live test/updates plus **[13] Diagnose & fix** (repairs “hub offline” automatically).

2. Install in 3 minutes

2.1 Windows — the one-time installer (recommended)

1. Download `AdvPrint-Pro-v2.8.0-FULL.zip` and unzip it.
2. Run `AdvPrint-Pro-Setup-2.8.0.exe` . Windows asks for admin once (UAC — the exe requests it itself), no Python needed — the setup carries a **complete Python 3.11.9 runtime** (this is exactly what the broken 2.5.3 download missed: if an installer is smaller than ~9 MB it is incomplete — re-download).
3. Setup registers the **Startup app "AdvPrint Pro"** (Task Manager → Startup apps), creates Start Menu shortcuts, and starts the hub. A tray icon `A` appears next to the clock.
4. Optional ticks: **Run as Windows service** (headless, services.msc) and **Install browser extension files**.

> Windows says *"cannot access / Access is denied"* on a downloaded setup? That is Mark-of-the-Web on a damaged/incomplete download. The 2.6.x setup is complete (~9.6 MB) and the portable `install\install-windows.bat` unblocks every file automatically. If your AV quarantines the hub, whitelist the folder `%LOCALAPPDATA%\AdvPrintPro` — the hub is a plain stdlib Python script, signed-off and open source (MIT).

2.2 Windows — portable zip (no installer)

1. Unzip. Double-click `tool\windows\portable\install\install-windows.bat` . It unblocks files, frees port 9235, uses the bundled runtime, registers auto-run, health-checks the hub.
2. Undo any time: `UNINSTALL-WINDOWS.bat` .

2.3 Linux / Debian / Ubuntu / Mint — the .deb

```
sudo apt install ./advprint-pro_2.8.0_all.deb
advprint-start           # start now
advprint token           # show the current token
advprint livetest        # full A-to-Z self-test
```

Auto-run at login: run `/opt/advprint/install/install-unix.sh` (installs a **systemd --user** service — no root needed; falls back to XDG autostart). Headless server mode: `sudo /opt/advprint/install/install-unix.sh --service`.

2.4 macOS

Run the portable hub: `python3 tool/unix/hub/advprint.py serve`, then `install-unix.sh` (LaunchAgent auto-run). CUPS printers are used through `lp`; page printing uses Chrome/Edge if installed.

2.5 First print in 60 seconds

1. Hub running (tray icon green / `advprint status`).
2. Load the extension: `chrome://extensions` → Developer mode → **Load unpacked** → the `extension` folder (or the one installed to `%LOCALAPPDATA%\AdvPrintPro\extension`).
3. Open the extension Options → Settings → **Detect token** (one click) → **Connect** shows `CONNECTED`.
4. Click **Send test page**. Paper comes out. Done.

3. The token — and the one-click fix

Every request to the hub carries a token. Since v2.0 a **fresh install generates a private random token** and stores it in `%USERPROFILE%\.advprint\config.json` (Linux/macOS `~/.advprint/config.json`). Upgrades of pre-2.0 installs keep working with the old default `PrintHub-2024` until you rotate it — the hub warns you in the dashboard until then. Pre-2.6 installs with a `~/.printhub` folder are **migrated automatically** to `~/.advprint` on first start (old folder kept as backup).

3.1 The one-click fix (v2.6)

Open a stale bookmark like `/dashboard?token=PrintHub-2024` and you get the friendly error page — with a green **“Fix it now — open the dashboard with the current token”** button. One click and you are in. It works because the hub hands the current token only to programs **on the hub PC itself** (loopback-only `GET /token/current`); other PCs on the LAN still see the manual steps only. The same button exists in the extension Options → Settings → **Detect token**.

3.2 Every way to get the current token

Way	How
Tray icon (easiest)	Right-click the **AdvPrint Pro** tray icon → **Open dashboard** — always opens with the right token.
Dashboard error page	Green **Fix it now** button (hub PC only) — or **Copy current token**.
Extension Options	Settings → **Detect token** button fills and saves it automatically.
Command line	`python advprint.py token` (portable) / `advprint token` (deb).
Config file	`"token"` value in `~/.advprint/config.json`.

3.3 Rotating the token

```
python advprint.py token-rotate        # CLI
POST /token/rotate (header auth)       # API
Dashboard → “Rotate token” button
```

After rotating: press **Detect token** in the extension (or paste the new token), and update old dashboard bookmarks. Rotating **invalidates the old token immediately** — including `PrintHub-2024` on upgraded installs.

4. The browser extension — every Options tab explained

Open the extension icon → ⚙ (or right-click the toolbar icon → Options). The Options page is **tab-wise**: `Queue` `History` `Settings` `Debug` `LAN / PCs` `About`. The extension opens on Queue when something is waiting, otherwise on Settings. Every tab auto-refreshes live.

4.1 Queue tab — live FIFO

- Hub state dot: running / PAUSED / offline, pending count, jobs today, hub version.

- Every waiting job row: id, title, printer, kind, status chip + buttons: **Cancel**, **Shift to PC** (print this job on another PC's hub over the LAN), **Print now** (bypasses pause and printer-status hold — the remedy when jobs sit "stuck").
- **Pause / Resume** queue, **Clear** queue, **Refresh**. Auto-refresh every 3 s.

4.2 History tab — last 100 jobs

- Every job with time, title, printer, kind and a colored status chip — **queued** gray, **printed** green, **failed/dead/canceled** red, **held** orange (with the exact held reason, e.g. "printer offline").
- Row actions: **Retry** (failed jobs — optionally on another printer), **Reprint** (printed jobs — reason goes to the audit log), **Cancel/Print now** (waiting jobs).
- History auto-refreshes every 8 s — a stuck "queued" row turns "printed" in front of you.
- “Clear” wipes only the browser-side copy; the hub history stays.

4.3 Settings tab — all switches

- **Power switches**: master **AdvPrint enabled** (OFF = nothing prints, gray OFF badge), **Queue mode** (ON = FIFO order + pause; OFF = instant print with auto-queue fallback), **Debug mode**, **Retry when the hub comes back**, UI language (English / বাংলা / auto).
- **Connection**: Hub URL (`http://127.0.0.1:9235`), Token + **Connect** + **Detect token**; buttons to open the dashboard and the audit log.
- **Printing**: default printer (or "File (save as PDF)"), plus **default print options** sent with every job: copies, pages (odd/even/custom), quality (draft…1200 dpi), per-sheet n-up, duplex, layout, scale, margins, paper size — with live capability hints from the selected printer.
- **Auto-print & routing rules**: URL pattern (glob or regex), page-title filter, per-rule printer, action (auto/PDF/page), per-site ON/OFF, auto-print-on-open, delete. First match wins.
- **Behavior**: print every PDF opened in the browser (simple mode), intercept `window.print()` (also Ctrl+P), close tab after auto-print, failure fallback (new tab vs silent), right-click menu, toolbar badge.
- **Hub settings (advanced)** — v2.6: the hub's own switches, editable live (see §9 for the full list): queue & retries, security/lockout, reprint watermark & reason, audit, thermal text engine + ESC/POS codepage, save-as-PDF folder, keep-files, SumatraPDF path.

4.4 Debug tab — WHEN / WHY / WHERE

- One card: hub version, debug mode on/off, worker alive, queue paused, printers ready, instant auto-queue state.
- **Problems found by the hub** table with the exact fix for each finding.
- **Browser error reports**: everything this browser hit (network, token, page JS) while Debug mode was on.
- Buttons: Refresh · Send test report · Copy report (everything for a bug report) · Open /debug JSON · **Run full self-test (A-to-Z)** — runs the hub's live test right here and prints OK/!! lines (v2.6).

4.5 LAN / PCs tab — share & shift

- Shows this PC's LAN URL (`http://192.168.x.x:9235`) when sharing is ON, with copy button.
- **Enable/Disable LAN sharing** (writes `share_lan` ; restart the hub to rebind + open TCP 9235 in the firewall).
- **Other PCs (peers)**: online/offline + version of each configured peer hub, one-click **Shift all waiting jobs**. Or type a LAN URL and shift everything ad hoc.

4.6 About tab

Version + full brand line, update check against GitHub releases, links to the user guide served by the hub (`/docs`), the developer API (`window.advprint`) and the test tools.

4.7 The popup (toolbar icon)

Master switch, queue mode switch, live queue state, pause/resume, last jobs, test page, screenshot-to-printer, save-page-as-PDF, offline banner with retry counter, token warnings with the exact remedy. Hotkey `Alt+P` prints the current tab. Right-click menu prints page / selection / linked PDF / screenshot.

> **v2.7.0 — popup LAN sharing switches:** the toolbar popup now has a **LAN sharing** section with **Share Receive Mode** (this PC accepts jobs from other PCs = hub `share_lan` , saved straight into the hub config) and **Share Send Mode** (this browser may shift jobs to peer PCs — OFF locks every send-to-PC button here). Both turn gray while the hub is offline and exist in English + Bangla. Nothing was removed anywhere.

5. The hub dashboard — every card and button

Open `http://127.0.0.1:9235/dashboard?token=…` (the tray icon does this with one click). All cards refresh live (5–15 s).

Area	What it shows / does
Status cards	Success rate (7 days) · queue size · jobs today · printers ready · hub version.
Action bar	Pause/Clear queue · Docs (user guide) · History CSV · Audit CSV · Diagnostics JSON · Debug · Health JSON · **Rotate token**.
Token warning	Appears while the old default `PrintHub-2024` is active, with a one-click **Rotate now**.
LAN sharing & other PCs	Enable/disable + this PC's LAN URL + printer-status-hold switch + peer PCs with “Shift all waiting jobs”.
Debug card	Debug mode toggle, worker/queue state, problems with fixes, client error reports, copy report.
Printers	Every printer + live status (ready / offline / paper-out / error).
Queue (waiting + printing)	Cancel · Print now · Shift per job.
Job history (v2.7.0)	Full manager: **filter** by status (incl. one-click “Not printed”), **search** title/printer/#id, load 50/100/300/1000, paging, **tick rows** (check / uncheck all) with a live “N selected” counter, **Reprint selected**, **Reprint all non-printed**, **Clear ALL history** (finished jobs only — waiting jobs are never touched), per-row Retry / Reprint.
Audit trail	Latest events: who printed what from where, reprint reasons, token errors.
DropZone (v2.8.0)	Print WITHOUT the extension: pick a folder; in Word / Excel / ANY app print to “Microsoft Print to PDF” and save the PDF into it — AdvPrint prints it seconds later and moves it to `done\\`. Live on/off (no restart), delete-after-print option, **Open folder** button. Phones/tablets print through the **Send portal** button (`/send`) — token-protected, 100% local.
Restart hub (v2.8.0)	One button in the toolbar: the hub relaunches ITSELF as a new process (queued jobs, settings and history kept) and this page reloads automatically when `/health` answers again. Same restart lives in the tray menu (Restart hub), AdvPrint Tool [14] and `POST /restart`.
Live debug & test tool + Hub settings	**Send test print & watch live** (job → printer verdict), **Release ALL held jobs**, **Full self-test (A-to-Z)**, SumatraPDF path setting. **v2.7.0:** both panels now sit properly INSIDE the page (they used to hang below it, unstyled and full-width).

6. Printing everything

6.1 PDFs (the lab-report flow)

- **Simple mode** (default ON): any PDF opened in the browser prints silently and the tab closes.
- **Rules**: URL pattern + optional title filter + optional printer → auto-prints the moment the URL opens (glob or regex).
- **From your app's code**: `printPdfLink(url, 'Lab report', {fallback:false})` — the page API prints via the hub and never opens a dialog. Full API: extension `content/api.js`, docs at `/docs`.

6.2 Web pages

Right-click → AdvPrint Pro → Print page · `Alt+P` · popup button · `window.advprint.printPage()`. Rendered with headless Chrome/Edge at print quality. `window.print()` and Ctrl+P are intercepted (toggle in Settings) and routed silently.

6.3 Receipts / raw text (ESC/POS)

Send `kind:"raw"` or `|center|…|` markup to `/print`. Codepage selectable (cp437/cp850/cp866/cp1251/cp1252). Bangla and other complex scripts are automatically rendered through headless Chrome so they shape correctly on thermal rolls (`thermal_text_engine`).

6.4 Selections & screenshots

Right-click a selection to print exactly it; the popup can print the visible page as an image — useful for POS systems and stubborn apps.

6.5 Save as PDF instead of paper

Choose printer `File (save as PDF)` or send `"printer":"__file__"`. Files land in `~/Downloads/AdvPrint` or the folder set in Hub settings (`file_dir`).

7. LAN / IP — share one printer with every PC

v2.8.0 — TWO HUB PROFILES (Self PC + LAN PC). The extension now keeps two complete hub profiles. **Connection 1 - Self PC** = this computer's hub URL + token (used when Share Send is OFF — the default). **Connection 2 - LAN PC** = the OTHER PC's hub URL + its token. The popup **Share Send Mode** toggle is the routing switch: **ON → every print job prints on the LAN PC**; OFF → prints on this PC. Recent jobs and Pause/Resume in the popup follow the active target, and Options has four buttons — Open dashboard / audit log — Self PC and — LAN PC. Receiving (Share Receive Mode, hub `share_lan`) is configured on the PC that OWNS the printer; a sender only needs that PC's URL + token. The setup adds the TCP 9235 firewall rule automatically, so "restart the hub and allow the port" is usually the only manual step.

1. On the **printer PC**: extension Options → LAN / PCs → **Enable LAN sharing** (or dashboard → LAN card). Restart the hub.
2. Firewall: allow inbound TCP 9235 (Windows: `netsh advfirewall firewall add rule name="AdvPrint Pro" dir=in action=allow protocol=TCP localport=9235` — run once as admin).
3. On each **client PC**: install the extension, set **Hub URL** to `http://<printer-PC-ip>:9235`, press **Detect token** on the printer PC (or paste the token) → Connect.
4. Every PC now prints to the shared printers; jobs can be **shifted** between PCs (single job or the whole waiting queue) when a PC goes down.

The token is required from every LAN PC — no token, no printing (the hub rate-limits and locks out foreign IPs after too many bad tokens, while your own PC (127.0.0.1) is **never** locked out by default).

8. Queue, History & Audit trail

- **Queue mode ON**: jobs wait in FIFO order, Pause/Resume works, one job prints at a time.
- **Queue mode OFF (instant)**: each job prints immediately; if the printer is not active the job is **auto-queued** (`instant_auto_queue`) and prints when the printer is back.
- **Printer-status hold** (`hold_offline`): jobs whose printer reports offline/paper-out are held with a reason and auto-print on recovery — or hit **Release ALL held jobs** / per-job **Print now** to force.
- **Retries**: failed jobs retry with exponential backoff (`max_retries` × `retry_base_seconds`).
- **Duplicates**: identical jobs inside `dedupe_minutes` are blocked (double-click protection).
- **History — v2.7.0 manager**: last 50/100/300/1000 jobs in the hub DB (SQLite), per-job file for reprints (`keep_files`); in the dashboard AND in Options → History: **filter** by status, **search**, **tick** rows, **Reprint selected**, **Reprint all non-printed**, **Clear ALL history** (finished jobs only — queued/held jobs survive). Export CSV from the dashboard. API: `POST /jobs/bulk-reprint` (`{"ids":[…]}` or `{"scope":"not_printed"}`), `POST /history/clear`.
- **Audit trail**: who printed what, from which site/IP, reprint reasons, auth failures — CSV export too; disable with `audit_enabled:false`.

9. Settings reference — every switch in one table

Change from: extension Options → Hub settings (live) · dashboard · `~/.advprint/config.json` · environment variables (`ADVPRINT_*`; legacy `PRINTHUB_*` still honored).

Key	Default	Meaning
`token`	random per install	API token — rotate via /token/rotate. Old default PrintHub-2024 kept on legacy upgrades.
`token_header_only`	false (true on fresh installs)	Strict mode: POST calls must send the X-AdvPrint-Token header.
`allowed_origins`	[] (all)	Restrict which websites may print, e.g. ["https://www.htncr.org"].
`max_auth_failures / lockout_minutes / lockout_exempt_loopback`	10 / 5 / true	Lockout policy for wrong tokens; loopback exempt by default (owner can never lock himself out).
`printer`	"	Force a printer; empty = OS default; "__file__" = save as PDF.
`printer_groups`	{}	{"Front Desk": ["A","B"]} — fallback printers in order.
`profiles`	{}	{"Invoice": {"paper":"a4","duplex":true}} — named option sets; send "profile":"Invoice".
`queue_mode (extension)`	true	FIFO queue vs instant print.
`max_retries / retry_base_seconds`	2 / 30	Exponential retry of failed jobs.
`dedupe_minutes`	5	Duplicate block window.
`hold_offline`	true	Hold jobs while the printer reports offline/out of paper.
`instant_auto_queue`	true	Instant mode falls back to queue when no printer is active.
`share_lan`	false	Listen on 0.0.0.0 so other PCs can print (token always required).
`peer_hubs / peer_forwarding`	[] / false	Other PCs' hubs for queue shifting / auto-forwarding.
`thermal_text_engine / escpos_codepage`	auto / cp437	Raw text rendering (Bangla → browser engine) and ESC/POS codepage.
`audit_enabled / reprint_watermark / reprint_reason_required`	true / false / false	Audit trail + compliance switches for reprints.
`file_dir / keep_files`	~/Downloads/AdvPrint / true	Save-as-PDF destination; keep files for reprint.
`drop_enabled / drop_dir / drop_delete`	true / "" / false	**v2.8.0 DropZone**: watch a folder and print every PDF that lands in it (default folder `data\DropZone`; drop_delete=true deletes instead of moving to `done\`).
`sumatra_path`	"	Manual SumatraPDF.exe path (empty = auto-find).
`debug`	false	Verbose [DEBUG] logs + client error reports in /debug.
`log_max_mb / log_backups`	5 / 3	hub.log rotation.

10. Debug & the Live Test tool

Four layers, from one-click to full control:

1. **Full self-test (A-to-Z)** — v2.6: extension Debug tab button · dashboard “Full self-test” · `AdvPrint Tool` menu [11] · CLI `python advprint.py livetest` (add `print` to also queue a real test page). Checks: Python, data folder writable, token, SumatraPDF/lp, browser, port, queue DB mechanics, printers, default printer — each line `[OK]` or `[!!]` with the fix. Exit code 0 = production-ready.
2. **Test print & watch live** — dashboard button queues a real page and follows the job to the printer with a verdict (REAL PRINTER HIT / SAVED / FAILED + reason). Tray icon → Print test page. CLI `testprint`.
3. **Debug mode** — verbose logs + browser error reports; the Debug tab and `/debug` answer "WHY is nothing printing?" with concrete problems + fixes.
4. **Bundles for support** — `/diagnostics`, `/health`, `/debug` JSON, audit CSV, history CSV, "Copy report" buttons. Token is redacted in diagnostics.

```
$ python advprint.py livetest
  [OK] Python >= 3.8                       3.11.9
  [OK] Data folder + history.db writable   /home/you/.advprint
  [OK] API token configured                private random token
  [OK] CUPS lp command                     /usr/bin/lp
  [OK] Chrome/Edge (page printing)         /usr/bin/chromium
  [OK] Port 9235 available                 OK
  [OK] Queue DB enqueue/read/update        job #42
  [OK] Printers detected                   HP_LaserJet, XP-80C
  [OK] Default printer                     HP_LaserJet

  ALL CHECKS PASSED - AdvPrint Pro is ready for production.
```

11. Enterprise edition — silent install, policy, service

11.1 Silent / scripted Windows install

```
AdvPrint-Pro-Setup-2.8.0.exe /S          # silent (UAC once), hub auto-starts
# enterprise rollout via Intune/GPO/SCCM: run per user, no elevation needed
```

11.2 Managed policy (force settings on all PCs)

Deploy `extension/managed.json` content as Chrome policy `HKLM\SOFTWARE\Policies\Google\Chrome\ExtensionInstallForcelist` + managed storage, or simply push the keys. Forceable settings: `hubUrl`, `token`, `defaultPrinter`, `enabled`, `queueMode`, `retryOfflin e`, `lang`, `hookPrint`, `autoPrintAllPdfs`, `failFallback`, `closeAfterPrint`, `rules` (rules fully override local ones — central lockdown). Managed values win over user settings.

11.3 Windows service mode (headless)

```
python advprint.py service-install     # UAC → registers services.msc: "AdvPrint Pro Service"
python advprint.py service-status / service-remove
```

Service mode = no tray, runs before logon, perfect for a print-server PC. The normal Startup app stays the default on desktops; if both run, the second exits gracefully (port guard).

11.4 Lockdown checklist

- `allowed_origins` → only your web app may print.
- `token_header_only:true` + rotated token on every PC.
- `share_lan:false` everywhere except the print-server PC; that one keeps `lockout_exempt_loopback` and strict lockouts for foreign IPs.
- `audit_enabled:true` + `reprint_reason_required:true` for compliance; audit CSV ships out nightly.
- LAN firewall rule only where needed (§7).

12. HTTP API quick reference

Auth: header `X-AdvPrint-Token` (legacy `X-PrintHub-Token` accepted), or `?token=` on GET navigation. Full docs: `docs/API.md` and the hub's own `/docs` page.

```
# v2.8.0 - DropZone / send portal / restart (no extension needed)
curl -H "X-AdvPrint-Token: $TOKEN" http://127.0.0.1:9235/dropzone
curl -X POST -H "X-AdvPrint-Token: $TOKEN" -F "file=@report.pdf" \
     "http://127.0.0.1:9235/send?title=Report"   # upload + print
curl -X POST -H "X-AdvPrint-Token: $TOKEN" http://127.0.0.1:9235/restart

# status
curl http://127.0.0.1:9235/health
curl -H "X-AdvPrint-Token: $TOKEN" http://127.0.0.1:9235/printers
# print a PDF from bytes (silent)
curl -X POST -H "X-AdvPrint-Token: $TOKEN" -H "Content-Type: application/pdf" \
     --data-binary @report.pdf "http://127.0.0.1:9235/print?title=Report"
# print a page with options
curl -X POST -H "X-AdvPrint-Token: $TOKEN" -H "Content-Type: application/json" \
  -d '{"url":"https://intranet/roster","paper":"a4","duplex":"duplex","copies":2}' \
  http://127.0.0.1:9235/print
# queue control / tokens / settings
curl -X POST -H "X-AdvPrint-Token: $TOKEN" http://127.0.0.1:9235/queue/pause
curl -X POST -H "X-AdvPrint-Token: $TOKEN" http://127.0.0.1:9235/token/rotate
curl -H "X-AdvPrint-Token: $TOKEN" http://127.0.0.1:9235/config
# live test over HTTP (same check as the CLI)
curl -X POST -H "X-AdvPrint-Token: $TOKEN" http://127.0.0.1:9235/livetest
```

Page-side API (in any web page once the extension is installed): `printPdfLink(url, title, opts)` · `window.advprint.printPdf/printPage/printers/status/history`.

13. Troubleshooting — every known problem and its fix

Symptom	Cause → Fix
Setup says *cannot access / Access is denied*	Incomplete/damaged download (pre-2.6 bug) or Mark-of-the-Web → re-download the 2.8.0 zip (setup ≈ 9.7 MB), right-click zip → Properties → Unblock, or run `install-windows.bat` which unblocks automatically.
Dashboard shows “needs the current token”	Stale bookmark → press the green **Fix it now** button on that very page (hub PC), or tray → Open dashboard, or extension → Detect token.
Extension shows 401 / token rejected	Options → Settings → **Detect token** (or paste the token from `advprint token`). After a rotation always re-detect.
Nothing prints, no error	Debug tab → Run full self-test → fix the [!!] line (usually SumatraPDF missing or no default printer). Then send a test print & watch live.
Jobs stuck “queued”	Queue paused → Resume; printer held → **Print now** or Release ALL held jobs; check printer status in the dashboard Printers card.
Jobs stuck “held”	That is the printer-status hold doing its job — fix the printer or **Print now**; disable hold in Hub settings (`hold_offline`).
Bangla/receipt text is garbage	Hub settings → thermal engine `auto` (browser render) + correct codepage; browser printing needs Chrome/Edge installed.
LAN PC cannot connect	`share_lan` ON + hub restarted + firewall TCP 9235 + correct Hub URL + token; check the LAN/PCs tab shows the PC's URL.
“python” in Task Manager	You started with system python — the installer's `AdvPrintPro.exe` (renamed pythonw) shows “AdvPrintPro”; re-run setup or the Startup shortcut.
Auto-run missing	Task Manager → Startup apps → “AdvPrint Pro” enable; or tray menu → Start at Windows logon.
Old PrintHub Pro traces after upgrade	Setup 2.6 removes the old Startup app/task/service/registry keys automatically; leftovers: uninstall the old version once, or delete `%LOCALAPPDATA%\PrintHubPro`.
Hub shows OFFLINE / start “did not answer”	Open the desktop tool → **[13] Diagnose & fix**: it unblocks the folder (Mark-of-the-Web), frees port 9235 from zombies, then starts the hub in plain view so the real error shows as text. Ends with the hub.log tail + a copy/paste start command with the full path.
Tool prints the diagnosis but hub.log is empty	The hub died before logging (AV quarantined the fresh exe) → add the AdvPrint folder to the antivirus exclusions, run [13] again (it unblocks), then [1] Start.
“python advprint.py serve” says *can't open file*	You are in the wrong folder — that command needs the file's real location. Use the tool's copy/paste command (menu [13], step [5/5]) or just menu [1].
Dashboard tables show “-” and buttons do nothing	Old-build JS bug (one broken quote killed the whole dashboard script) — **fixed in 2.6.4**; update, hard-refresh the dashboard (Ctrl+F5).
Tray icon missing	Fixed in 2.6.4 (embedded-runtime isolated mode). Update + start the hub; the icon sits next to the clock — may hide under the `^` arrow. If the hub is not running there is no tray — start with [1] first.
Hub will not start (port busy)	Another instance runs — check the tray icon; the hub exits gracefully with a clear message instead of crashing; [13] can free the port for you.
Screen “glitch” / black console flashes every few seconds	Old build (pre-2.6.6): the hub polled the service state with `sc query` without the windowless flag — Windows flashed a console each time. **Fixed in 2.6.6** — every background child now runs windowless; update.
`save-as-PDF failed: [Errno 13] Permission denied`	A real-time antivirus / indexer briefly locked the fresh PDF. **Fixed in 2.6.7** — the hub now writes atomically and retry-reads ~4 s. If it still repeats: add `C:\Users\<you>\.advprint` to your AV exclusions, then **Retry** the job from History.
`print backend exit 1:` with no message (File (PDF))	**Fixed in 2.6.7** — “File (PDF)” is now a virtual printer: the PDF is **saved** to `Downloads\AdvPrint` with status “saved” (also with Queue Mode OFF). The backend's stdout is captured too, so real printer errors now show a readable reason.
Windows service “AdvPrint” stuck in *start pending*	A stale state left by an older service process — the hub actually runs from the Startup app / tray. Fix: `services.msc` → AdvPrint → Restart (or reboot), or run `service-remove` — keep only ONE of service / Startup app active. The Debug tab lists this automatically.

`printer 'X...X not found'` — the name shows TWICE in a row (e.g. `CanonCanon`)	A stored printer name was typed/pasted twice. **Self-healed in 2.6.8** — the hub collapses the doubled name to the real printer, prints, and corrects the history (audit: `printer.corrected`). Old dead jobs: just press **Retry**. Still check Settings → Printer for the stale entry.
Every page prints TWICE — two sheets, and the log shows two `[OK] job #N` lines	Queue Mode OFF race in v2.6.8 and earlier: the FIFO worker and the direct thread both grabbed the same job. **Fixed in 2.6.9** — the job row is created in its final state, one job = one sheet. Not a printer or driver problem (the printer was innocent). Upgrade the hub to 2.6.9+; nothing to change on the printer.
Right-click "Print this page" fails with *Cannot access contents of url chrome-extension://…*	The menu was used on a browser-internal page (chrome://, settings, extension page). **Fixed in 2.6.8** — the menu now only appears on printable pages (http/https/file) and shows a friendly notice otherwise.
HP Laser 103/107/108 shows *offline*	That is the printer device itself (USB/network/sleep), not a hub error — check cable/power, set it online in Windows, then **Retry** the held jobs.

14. Upgrade, uninstall, files & folders

v2.8.0 — BULLET-PROOF UPGRADE & UNINSTALL. Setup runs `hub-stop.ps1` BEFORE touching files: it stops the optional *AdvPrint* service (wait + PID kill when stuck), **deletes the service registration** (it is reinstalled fresh automatically on upgrade), kills every process under the install folder and frees TCP 9235. Old program folders are wiped first, so no stale file can abort the new install any more. The uninstaller uses the same stop, removes the firewall rule and retries the folder sweep 3×. Silent install: `AdvPrint-Pro-Setup-2.8.0.exe /S` (UAC once — the exe requests admin itself; the hub auto-starts afterwards).

14.1 Upgrade

Run the new setup over the old one (same per-user location, settings/history kept) — or replace the portable folder. The extension updates by Remove + Load unpacked (or GitHub update check → new zip). Data folders migrate: `~/.printhub` → `~/.advprint` automatically.

14.2 Uninstall

Windows: Start Menu → Uninstall AdvPrint Pro (or Apps & features). Service: removed automatically. History/settings in `~/.advprint` are kept (delete manually if unwanted). Linux: `sudo apt remove advprint-pro` + `uninstall-unix.sh`.

14.3 Where everything lives

What	Path
Program (Windows)	`%LOCALAPPDATA%\AdvPrintPro` (hub, runtime, install scripts, extension, docs)
Data (config, history.db, hub.log, files)	`%USERPROFILE%\.advprint` (migrated from `.printhub`)
Auto-run	Startup app “AdvPrint Pro” (Task Manager) · optional service “AdvPrint” (services.msc)
Program (Linux deb)	`/opt/advprint` + `/usr/bin/advprint*` · data `~/.advprint`
Logs	`~/.advprint/hub.log` (rotating)

You are never locked out: the hub never locks out your own PC (127.0.0.1) by default, the tray always opens the dashboard with the right token, and the error page itself offers the one-click fix. That is the v2.6 promise: **auto security, zero manual Security-tab surgery**.

AdvPrint Pro (Advanced Printer) v2.8.0 — by Bit Dream IT — Innovative Healthcare Solutions — MIT license — 100% local, no cloud, no tracking. Repository: github.com/bitdreamit/AdvPrint-Pro