

Ecamm Live Remote API v4.4

Locating the Service

`searchForServicesOfType:@"_ecammliveremote._tcp." inDomain:@"local."`

If your client is only intended to be run on the same Mac as Ecamm Live, once discovered, check to ensure that it has discovered the local host, as it could potentially discover Ecamm Live running on other Macs.

Additional HTTP Headers

Send the following HTTP headers along with your requests:

User-Agent: [app name]/[app version]

EcammLive-UUID: A GUID string, should persist between sessions.

EcammLive-ClientName: Your app name for presenting to users.

EcammLive-DeviceName: If this is an app on a different device, the device's name, from `UIDevice.current.name` (e.g. Gary's iPhone) [optional]

EcammLive-ClientIcon: URL of your square-aspect app icon [optional]

Commands

All requests are HTTP **GET** requests.

Requests with *get* prefix retrieve information from Ecamm Live and return JSON. Sometimes with parameters sent URL-encoded in the query string.

Requests with *set* prefix make changes to Ecamm Live, usually with parameters sent URL-encoded in the query string. They do not return anything but "Done".

Display Info

`getInfo`

Note: Although this is a fairly lightweight operation, avoid calling it more frequently than every 2 seconds.

Returns: Dictionary containing strings for `ButtonLabel`, `PauseButtonLabel`, `CurrentScene`, `Viewers`, `LiveDemo`, `PreviewMode`, `HidingUI`, mute settings, volume levels and Zoom/Interview guest names.

If a Zoom meeting is in progress, it will also contains yes/no values for `ZoomInMeeting`, `ZoomMuted`, `ZoomHandRaised`, `ZoomCamOn`, `ZoomCloudRecording`, `ZoomLocalRecording`, `ZoomRecordingPaused`, and `ZoomHosting`.

`getButtonLabel`

Returns: Label for Start button. *string*

`getPauseButtonLabel`

Returns: Label for Pause button. *string*

`setClickButton`

Clicks the start or record button.

Parameters: *channel* - A destination UUID from `getChannels` or leave out to use currently scheduled live event.

title - Title for new live broadcast.

desc - Description for new live broadcast.

`setClickPauseButton`

Clicks the pause recording button.

Parameters: None

Scenes

`getSceneList`

Returns: An array of Scene info dictionaries.

`getSceneDict`

Returns: A dictionary of Scene info dictionaries.

`getSceneImage`

Parameters: *id* - The scene's UUID.

Returns: *icon*: The Scene's last thumbnail image, as a Base 64 encoded JPG.

`getCurrentScene`

Returns: UUID of the current Scene.

`setScene`

Switch to a Scene.

Parameters: *id* - The scene's UUID.

`setNext`

Go to next Scene.

`setPrev`

Go to previous Scene.

Mute

`getMute`

Returns: Mute status (*yes / no*) *string*

`setMute`

Toggles mute status.

Volume

`getVolume`

Returns: Volume level *string*

Parameters: *bus* - Audio bus (*mic* | *mic2* | *skype* | *system audio* | *interview* | *zoom* | *soundeffects* | *movie* | *guest_1* | *guest_2* | *guest_3* | *guest_4*)

setVolume

Parameters: *volume* - new volume level *string*

bus - Audio bus (*mic* | *mic2* | *skype* | *system audio* | *interview* | *zoom* | *soundeffects* | *movie* | *guest_1* | *guest_2* | *guest_3* | *guest_4*)

Concurrent Viewers

getViewers

Returns: Number of concurrent viewers. *string*

Cameras

getInputs

Returns: An array of camera inputs.

getDefaultCamera

Returns: UUID of the default camera *string*

setInput

Pick a camera.

Parameters: *id* - UUID of a camera to use.

Source Mode

getCurrentMode

Returns: Current source mode (*cam* | *screen* | *video*) *string*

setMode

Parameters: *mode* - Mode to use. (*cam* | *screen* | *video*) *string*

PIP

setPIP

Toggle PIP visibility.

Video Playback Mode

getVideoList

Returns: An array of recently used video files.

getVideoDict

Returns: A dictionary of recently used video files.

setVideo

Parameters: *id* - File path of video to play. *string*

getVideoImage

Parameters: *id* - A file path to a video.

Returns: *icon*: The videos' thumbnail image, as a Base 64 encoded JPG.

Overlays

getOverlayList

Returns: An array of Overlay info dictionaries.

getOverlayDict

Returns: A dictionary of Overlay info dictionaries.

getOverlayImage

Parameters: *id* - The Overlay's UUID.

Returns: *icon*: The Overlay's thumbnail image, as a Base 64 encoded JPG.

setOverlay

Toggle an overlay's visibility.

Parameters: *id* - UUID of the Overlay. *string*

setHideComment

Hide the most recent comment Overlay.

setShowComment

Show the most recent comment and as Overlay.

Sound Effects

getSoundList

Returns: An array of Sound Effect info dictionaries.

getSoundDict

Returns: A dictionary of Sound Effect info dictionaries.

setSound

Play a sound.

Parameters: *id* - a UUID **OR** file path to a sound effect. *string*

volume - Volume level 0 to 100. *string*

action - Playback behavior. (*stop* / *loop* / *restart*) *string*

setSoundVolume

Set the volume level of the currently playing sound.

Parameters: *volume* - Volume level 0 to 100. *string*

setSoundStop

Stop the currently playing sound.

setSoundPause

Pause the currently playing sound.

Audio Filters

`getAudioFilterList`

Returns: An array of Audio Filter info dictionaries.

`getAudioFilterDict`

Returns: A dictionary of Sound Audio Filter info dictionaries.

`setAudioFilter`

Toggle an audio filter.

Parameters: *id* - a UUID of an audio filter. *string*

Preview Mode

`setPreviewMode`

Toggle Preview Mode.

`setPublish`

Publish Preview Mode.

Profiles

`getProfileList`

Returns: An array of Profiles dictionaries.

`setProfile`

Switches to a new Profile.

Parameters: *id* - UUID of the new Profile. *string*

Ecam for Zoom

`setZoomNew`

Starts a new Zoom meeting.

Parameters: *pmi* - [optional] Use Personal Meeting ID *true* / *false* (defaults to *true*)

`setZoomLeave`

Leave the current Zoom meeting.

Parameters: *end* - [optional] End meeting for all *true* / *false* (defaults to *true*)
(Host only)

`setZoomPanel`

Show/hide a Zoom meeting panel.

Parameters: *panel* - *meeting* / *chat* / *participants* / *share*

`setZoomVideo`

Start/stop Zoom video.

`setZoomAudio`

Mute/unmute Zoom mic audio.

`setZoomMuteAll`

Mute all participants except host. (Host and co-host only)

`setZoomRaiseHand`

Raise/lower hand.

`setZoomFullScreen`

Toggle full screen meeting.

`setZoomCloudRecord`

Start/stop Zoom cloud recording.

`setZoomLocalRecord`

Start/stop Zoom local recording.

`setZoomPauseRecord`

Pause/resume Zoom local or cloud recording.

`setZoomPrevGallery`

Go to previous Zoom gallery page.

`setZoomNextGallery`

Go to next Zoom gallery page.

`setZoomGallerySpeaker`

Switch between Zoom gallery view and speaker view.

`setSpotlightSelf`

Toggles Zoom spotlighting.

Other

`getChannels`

Returns: A dictionary of streaming destinations, used for `setClickButton`

`setComment`

Parameters: *text* - comment to post to Twitch, YouTube or Facebook Pages

`setMarker`

Parameters: *text* - [optional] marker text *url-escaped string*
dialogbox - show marker dialog box *true / false*

`getLiveDemo`

Returns: Status of Live Demo Mode. *(yes / no) string*

`setLiveDemo`

Toggles Live Demo Mode.

`getHideShowUI`

Returns: Status of on-screen button visibility. *(yes / no) string*

setHideShowUI

Toggles Hide Main Window Controls feature.

getConnectionStatus

Returns: The client's permissions in the receiver's Remote Control permission screen. *Allowed* | *Denied* | *Pending* | *Not Found*

setStartNewRecording

Start a new recording when streaming or recording.