

Element G

Addressing non-Testable Attribute

Span of 45 minutes

The students did not proceed further with a design idea and a completed procedure. But will continue to research and decide which materials are best to test using humidity sensors.

The outside sensor indicates the humidity level when there were no materials present to shield the sensor.

Materials	Outside sensor	Inside sensor %	Temperature
Bottle	70%	66%	71.7 degrees F
Clgar Box	70%	57%	71.6 degrees F
Zip lock	70%	62%	71.7 degrees F
Tupperware (clear)	70%	64%	72.5 degrees F
Bubble wrap foil	70%	61%	N/A
Lunchbag	70%	61%	71.7 degrees F

Meeting Requirements and Testing Viability

Currently, the student engineers have not tested any of the designs, but rather, they have talked to experts on the matter in order to reiterate our design. The students asked them for feedback and are currently working on adding it into the new design. The students have figured out what type of material to use through testing the humidity in different containers. Nothing has been tested and won't be tested until the final CAD design is finished.

Expert Review to Justify the Decisions of the Student Engineers

Two of the students in the engineering team presented a design concept to an engineering professor/expert at the University of Maryland. After discussing the design with them, the whole engineering team have come together to reiterate the design to better fit the criteria and requirements given. Still, no final design has been established and they are planning on making it official soon.