The Sen API

Interface Control Document

An example, generated from the data model by Sen. The reference that follows — every package, every type, every table — is written by the tool and is rewritten whenever the model changes.

This page is not. It is an ordinary Typst file included at a point the generated document leaves open, which is how a project puts its own cover, approvals and appendices around a reference it never has to edit.

Placeholder for your own project or product assets

Contents

About this document . . . 3
Model overview . . . 4
Reading the tables . . . 5
components . . . 6
  ether . . . 7
  explorer . . . 13
  influx . . . 14
  jsonrpc . . . 15
  logmaster . . . 26
  py . . . 27
  recorder . . . 28
  replayer . . . 30
  rest . . . 32
  shell . . . 38
  term . . . 43
db . . . 45
kernel . . . 46
  log . . . 77
Built-in types . . . 80
Index . . . 81

About this document

This is an example published with Sen's documentation. It was produced by running the model through `sen generate typst` and compiling the result, with no editing in between.

Everything from *Model overview* onwards is generated. It follows the model and only the model: if a type is added, renamed or given a new description, the next build says so, and nothing anyone wrote by hand is lost in the process.

This page, and the cover before it, are not generated. They are Typst files of your own that the document includes at points it leaves open for you:

`--front-matter`	A cover, before the contents.
`--before-reference`	Anything between the contents and the model — a scope, a set of conventions, an approvals table. This page.
`--after-reference`	Appendices, after the model.
`--style`	Every decision about how the document looks.

The generator does not read any of those files. It writes an `#raw("#include")` and Typst resolves it when the document is compiled, so a cover page can be anything Typst can set — and changing it never means regenerating the model.

Model overview

343 types in 14 packages. 14 classes in 12 independent hierarchies.

Packages

Package	Types	Object classes	Fixed records	Enumerations	Variant records	Arrays	Optionals
components	—	—	—	—	—	—	—
ether	31	—	20	1	3	4	3
explorer	1	—	1	—	—	—	—
influx	3	—	1	1	—	1	—
jsonrpc	41	2	17	—	1	8	13
logmaster	3	2	1	—	—	—	—
py	3	1	1	—	—	1	—
recorder	6	1	2	1	—	2	—
replayer	4	2	1	1	—	—	—
rest	37	—	20	5	—	9	3
shell	27	1	20	3	1	2	—
term	8	1	2	2	—	3	—
db	3	—	3	—	—	—	—
kernel	160	4	80	23	8	37	8
log	16	—	11	1	1	3	—

Class hierarchy across all packages

components.jsonrpc.JsonRpcServer 15
components.jsonrpc.StaticFileServer 18
components.logmaster.LogMaster 26
components.logmaster.Logger 26
components.py.PythonInterpreter 27
components.recorder.Recorder 28
components.replayer.Replay 30
components.replayer.Replayer 30
components.shell.Shell 38
components.term.Term 43
kernel.KernelApi 46
kernel.VirtualClock 46
├── kernel.VirtualKernelClock 46
└── kernel.VirtualMasterClock 46

Reading the tables

Every property carries three flags, in this order.

Flag	Meaning
`RO`	Read-only: the value is published by whoever owns it and cannot be set from outside.
`RW`	Read-write: the value can be set as well as read.
`D`	Dynamic: the value changes over the life of an instance.
`S`	Static: the value is fixed once an instance exists.
`C`	Confirmed: delivery is acknowledged, and the update is retried until it arrives.
`BE`	Best effort: the update is sent once and may be lost.

components

ether

31 types.

Fixed records

BusConfig	Remember to set these to the same value in all related Sen instances	7
BusJoined		7
BusLeft		7
ByteRange	Range of values of a u8	8
Configuration	Overall component configuration	8
DiscoveryHubAddress	TCP-based discovery hub parameters	8
Endpoint		8
Ephemeral	Let the operating system select an ephemeral port	8
Hello		8
MulticastAddressRange	Inclusive IPv4 multicast address range	9
MulticastDiscovery	Multicast-based discovery parameters	9
PinnedPort	Bind exactly this port, fail closed if taken	9
PortConfig	This configuration is per process and does not need to match across Sen instances. Exclusions apply to a pinned port, not to an ephemeral one: an ephemeral bind asks the OS for any free port and does not learn which it was given. udpUnicast cannot be pinned. Its socket is per peer and UDP has no four-tuple to demultiplex on, so a second peer either fails to bind or silently takes the first peer's traffic.	9
PortRange	Inclusive port range	9
ProbePortRange	Bind within [min,max], random start, walk forward	10
ProtocolVersion		10
QueueConfig		10
Ready		10
SessionPresenceBeam		10
TcpDiscovery	TCP-based discovery parameters	10

BusConfig STRUCTURE

Remember to set these to the same value in all related Sen instances

Name	Type	Description
`multicastRange`	MulticastRange	Defaults to the Organization Local scope (RFC 2365): [239], [192-195], [0-255], [0-255] Remember to keep a range wide enough for avoiding collisions if you have many buses.
`multicastExclusions`	MulticastAddress Exclusions	Address ranges that must not be allocated
`multicastPort`	u16	Defaults to 50985 Change this in case you have limited control over the infrastructure.
`multicastDisabled`	bool	If true, no multicast traffic is performed and all the bus settings above become meaningless. Defaults to false.

Named by Configuration.

BusJoined STRUCTURE

Name	Type	Description
`participantId`	u32	
`busId`	u32	
`busName`	string	

Named by ControlMessage.

BusLeft STRUCTURE

Name	Type	Description
`participantId`	u32	
`busId`	u32	

Name	Type	Description
busName	string	

Named by ControlMessage.

ByteRange STRUCTURE

Range of values of a u8

Name	Type	Description
min	u8	minimum range
max	u8	needs to be >= min

Named by MulticastRange.

Configuration STRUCTURE

Overall component configuration

Name	Type	Description
discovery	DiscoveryConfig	Discovery-related parameters
busOutQueue	QueueConfig	Queue for broadcasting to buses
processUdpOutQueue	QueueConfig	Queue for communicating with processes over UDP
processTcpOutQueue	QueueConfig	Queue for communicating with processes over TCP
busConfig	BusConfig	Bus transport configuration
portExclusions	PortExclusions	Port ranges that this process must not use
portConfig	PortConfig	If not present, all port bindings are Ephemeral
runDiscoveryHub	u16	If present, run the TCP discovery hub on this port
networkDevice	string	If present, the network device to use

DiscoveryHubAddress STRUCTURE

TCP-based discovery hub parameters

Name	Type	Description
port	u16	Port where the discovery hub is running
host	string	name or IP of the host where the discovery hub is running

Named by TcpDiscovery.

Endpoint STRUCTURE

Name	Type	Description
ip	u32	
port	u16	

Named by EnpointList.

Ephemeral STRUCTURE

Let the operating system select an ephemeral port

Named by PortBinding.

Hello STRUCTURE

Name	Type	Description
info	sen.kernel.ProcessInfo	

Name	Type	Description
udpPort	u16	
version	ProtocolVersion	

Named by ControlMessage.

MulticastAddressRange STRUCTURE

Inclusive IPv4 multicast address range

Name	Type	Description
min	string	
max	string	

Named by MulticastAddressExclusions.

MulticastDiscovery STRUCTURE

Multicast-based discovery parameters

Name	Type	Description
beamPeriod	sen.Duration	How often are we beaming our presence
beamExpirationTime	sen.Duration	Expiry time used by the beam tracker
mcastGroup	string	Defaults to '239.255.0.44'
port	u16	Defaults to 60543
device	string	Device to use for the network communication
allowVirtual Interfaces	bool	If true, virtual (NO_CARRIER) interfaces are also considered

Named by DiscoveryConfig.

PinnedPort STRUCTURE

Bind exactly this port, fail closed if taken

Name	Type	Description
port	u16	

Named by PortBinding.

PortConfig STRUCTURE

This configuration is per process and does not need to match across Sen instances. Exclusions apply to a pinned port, not to an ephemeral one: an ephemeral bind asks the OS for any free port and does not learn which it was given. udpUnicast cannot be pinned. Its socket is per peer and UDP has no four-tuple to demultiplex on, so a second peer either fails to bind or silently takes the first peer's traffic.

Name	Type	Description
tcpAcceptor	PortBinding	inbound TCP listener
udpUnicast	PortBinding	per-peer UDP unicast; must be Ephemeral
tcpSource	PortBinding	outbound TCP source port

Named by Configuration.

PortRange STRUCTURE

Inclusive port range

Name	Type	Description
min	u16	

Name	Type	Description
max	u16	

Named by PortExclusions.

ProbePortRange STRUCTURE

Bind within [min,max], random start, walk forward

Name	Type	Description
min	u16	
max	u16	

Named by PortBinding.

ProtocolVersion STRUCTURE

Name	Type	Description
kernel	u32	
ether	u32	

Named by Hello.

QueueConfig STRUCTURE

Name	Type	Description
evictionPolicy	QueueEvictionPolicy	What to do when a queue is full
maxSize	u64	Maximum element count, 0 means unbounded
warningLevel	u64	Element count where warning will be issued, 0 means none

Named by Configuration.

Ready STRUCTURE

Named by ControlMessage.

SessionPresenceBeam STRUCTURE

Name	Type	Description
protocolVersion	u16	
info	sen.kernel.ProcessInfo	
beamPeriod	sen.Duration	
endpoints	EnpointList	

TcpDiscovery STRUCTURE

TCP-based discovery parameters

Name	Type	Description
beamPeriod	sen.Duration	How often are we beaming our presence
beamExpirationTime	sen.Duration	Expiry time used by the beam tracker
hubAddress	DiscoveryHubAddress	Where to find the discovery hub
allowVirtual Interfaces	bool	If true, virtual (NO_CARRIER) interfaces are also considered

Named by DiscoveryConfig.

Enumerations

QueueEvictionPolicy	What to do when a queue is full	11

QueueEvictionPolicy ENUMERATION

What to do when a queue is full

Held as u32.

dropOldest	0
dropNewest	1

Named by QueueConfig.

Variant records

ControlMessage		11
DiscoveryConfig	Configuration parameters related to the discovery protocol	11
PortBinding		11

ControlMessage VARIANT

Type	Description
Hello	
Ready	
BusJoined	
BusLeft	

DiscoveryConfig VARIANT

Configuration parameters related to the discovery protocol

Type	Description
MulticastDiscovery	
TcpDiscovery	

Named by Configuration.

PortBinding VARIANT

Type	Description
Ephemeral	
PinnedPort	
ProbePortRange	

Named by PortConfig.

Arrays

EnpointList		11
MulticastAddressExclusions		12
MulticastRange	Range of values of a IPv4 multicast address	12
PortExclusions		12

EnpointList SEQUENCE

```
sequence<Endpoint, 27> EnpointList;
```

Named by SessionPresenceBeam.

MulticastAddressExclusions SEQUENCE

```
sequence<MulticastAddressRange> MulticastAddressExclusions;
```

Named by BusConfig.

MulticastRange SEQUENCE

Range of values of a IPv4 multicast address

```
array<ByteRange, 4> MulticastRange;
```

Named by BusConfig.

PortExclusions SEQUENCE

```
sequence<PortRange> PortExclusions;
```

Named by Configuration.

Optionals

MaybeDeviceName 12
MaybeDiscoveryHubPort 12
MaybePortConfig 12

MaybeDeviceName OPTIONAL

```
optional<string> MaybeDeviceName;
```

MaybeDiscoveryHubPort OPTIONAL

```
optional<u16> MaybeDiscoveryHubPort;
```

MaybePortConfig OPTIONAL

```
optional<PortConfig> MaybePortConfig;
```

explorer

1 types.

Fixed records

Configuration Overall component configuration 13

Configuration STRUCTURE

Overall component configuration

Name	Type	Description
`layoutFile`	string	the imgui layout file. Defaults to ""

influx

3 types.

Fixed records

Configuration Overall component configuration 14

Configuration STRUCTURE

Overall component configuration

Name	Type	Description
`samplingPeriod`	sen.Duration	sampling period for the recordings
`selections`	SelectionList	objects to be monitored (using sql)
`telegrafAddress`	string	ip or name of the Telegraf server
`telegrafPort`	u16	port used by the Telegraf server
`protocol`	Protocol	protocol used
`batchSize`	u32	points to batch before emission (0 means no batching)

Enumerations

Protocol 14

Protocol ENUMERATION

Held as u8.

udp	0
tcp	1

Named by Configuration.

Arrays

SelectionList 14

SelectionList SEQUENCE

```
sequence<string> SelectionList;
```

Named by Configuration.

jsonrpc

41 types.

Object classes

JsonRpcServer	JsonRpcServer -- the JSON-RPC over WebSocket external API, expressed as a Sen class. One instance per connected client lives on `local.jsonrpc`. Methods are the RPC surface; events are the server-pushed notifications. Wire framing (envelope, id, error mapping) is the dispatcher's job, not this class's. Wire-shape convention: JSON-RPC named params (`"params": { ... }`) use the same field names as the STL method's argument list. The dispatcher treats every method's params object as `{ <argName>: <value>, ... }` and walks `method->getArgs()` to build the VarList in declaration order. That lets the inbound dispatch path go through Sen's meta machinery with no per-method translation.	15
StaticFileServer	Server-wide registry of in-memory static-file bundles, served alongside the WebSocket+JSON-RPC surface by the same uWS app. Internal-only: lives on the configurable control bus (defaults to `local.jsonrpc_control`), not on the data-plane bus that hosts authenticated per-connection JsonRpcServer instances. The component publishes exactly one instance.	18

JsonRpcServer CLASS

JsonRpcServer -- the JSON-RPC over WebSocket external API, expressed as a Sen class. One instance per connected client lives on `local.jsonrpc`. Methods are the RPC surface; events are the server-pushed notifications. Wire framing (envelope, id, error mapping) is the dispatcher's job, not this class's. Wire-shape convention: JSON-RPC named params (`"params": { ... }`) use the same field names as the STL method's argument list. The dispatcher treats every method's params object as `{ <argName>: <value>, ... }` and walks `method->getArgs()` to build the VarList in declaration order. That lets the inbound dispatch path go through Sen's meta machinery with no per-method translation.

Name	Type	Flags	Description
`identity`	Identity	RO S BE	Identity of the connected client.

Method	Signature	Description
`ping`	`() → string`	Liveness probe.
`listTopology`	`() → SessionInfoList`	Snapshot of the currently-detected sessions, each with the buses currently detected inside it. The kernel's discovery surface is asynchronous; this returns whatever was visible at the moment of the call. Use `subscribeTopology` for live updates.
`subscribeTopology`	`()`	Sticky subscription to topology changes. Idempotent per connection. Wires a `topologyChanged` push immediately with the current full snapshot, then again on every session or bus add/remove. Cancel with `unsubscribeTopology`; the subscription is also torn down automatically when the connection closes.
`unsubscribeTopology`	`()`	Cancel the topology subscription created by `subscribeTopology`. Idempotent.
`getTypes`	`() → sen.kernel.StringList`	Returns the qualified names of every custom type registered with the kernel. Catalog only -- pair with `getType` to fetch a chosen spec. The bundled-with-objects path on `interestUpdate.types` remains the primary way clients learn about types they observe.

Method	Signature	Description
getType	(qualifiedName: string, withSchema: bool) → TypeLookupResult	Look up one type by qualified name. Returns the CustomTypeSpec; when `withSchema` is true, also returns the JSON-Schema fragment for the type (empty string otherwise). Dependency chasing is the client's job: each schema fragment carries `$ref` strings keyed by qualified name, resolved against whatever schema cache the client maintains.
createInterest	(interestName: string, query: string, subscribe: SubscribeBlock, withSchemas: bool)	Register a sticky interest defined by an STL query. Optional `subscribe` block pre-subscribes to properties/events on every matched object, including ones that arrive later. When `withSchemas` is true, every subsequent `interestUpdate` for this interest carries the JSON-Schema fragment for each previously-unseen type alongside the existing `CustomTypeSpec`. Re-registering the same name = invalidParams. Wire-ordering contract: the initial `interestUpdate.added` for the current match set is emitted *before* this RPC's response lands on the wire. Clients must accept pushes for an interest whose response has not yet been observed.
releaseInterest	(interestName: string)	Drop an interest and every subscription living under it.
listObjects	(interestName: string) → ObjectInfos	List the names and classes of objects currently in an interest's match set.
getProperty	(interestName: string, objectName: string, propertyName: string) → string	Read a property's current value, synchronously.
getObjectsBatchState	(interestName: string, objectNames: sen.kernel.StringList, propertyNames: sen.kernel.StringList) → ObjectStateList	Batched per-object snapshot. Walks the interest's match set in one pass instead of forcing the caller to issue N*M `getProperty` round-trips. Omitting `objectNames` reads every object currently matched; omitting `propertyNames` reads every property of each object (the class hierarchy is walked, so inherited members are included). Names from `objectNames` that aren't currently in the match set are silently skipped -- the caller compares its requested list against the returned `objectName`s to detect omissions. Names from `propertyNames` that don't exist on a given object's class are recorded per-object under `errors`, so a heterogeneous batch still returns useful partial results. Bounded: the call rejects with `invalidParams` when the resolved object set exceeds 512 entries (either via an explicit

Method	Signature	Description
		`objectNames` list of that length, or via an implicit walk over a match set that has grown that large). Page the request by passing `objectNames`.
setProperty	(interestName: string, objectName: string, propertyName: string, value: string)	Write a property's value (sugar over invoking the generated setter). Hand-routed in `Dispatcher::handleSetProperty`: the dispatcher issues `invokeUntyped` against the property's setter and wires the response through the kernel callback in a single tick. The typed `setPropertyImpl` override in the C++ `Server` exists only to satisfy the codegen-generated abstract base and is unreachable at runtime. See `architecture.md` "Method dispatch" for why this method (and `invoke`) bypass the generic meta path.
subscribeProperty	(interestName: string, objectName: string, propertyName: string, maxRate Hz: f64)	Subscribe to propertyChanged notifications for one (interest, object, property). Sticky: persists across object churn; auto-rewires when the named object (re)enters the match set. Snapshot of the current value is delivered immediately after wiring. The throttle is per-object, shared across every property/event subscribed for the same object. An explicit `maxRateHz` overrides the current rate for the object; omitting it preserves whatever rate is already in effect (so adding a per-property sub doesn't accidentally retune existing subs back to unlimited).
unsubscribeProperty	(interestName: string, objectName: string, propertyName: string)	Cancel a property subscription previously created with subscribeProperty.
subscribeEvent	(interestName: string, objectName: string, eventName: string)	Subscribe to eventTriggered notifications for one (interest, object, event).
unsubscribeEvent	(interestName: string, objectName: string, eventName: string)	Cancel an event subscription previously created with subscribeEvent.
subscribeAll	(interestName: string, objectName: string, maxRateHz: f64)	Subscribe to every property and every event of one named object. Wildcard expansion against the object's actual class (including parent classes). Object must currently be in the match set; absent objects are invalidParams.
unsubscribeAll	(interestName: string, objectName: string)	Cancel an all-members subscription previously created with subscribeAll.
invoke	(interestName: string, objectName: string, methodName: string, argsJson: string) → string	Call a method on a kernel object and await its return value. Hand-routed in `Dispatcher::handleInvoke`: validates the args, issues `invokeUntyped`, and wires the response through the kernel callback in a single tick. The typed

Method	Signature	Description
		`invokeImpl` override in the C++ `Server` exists only to satisfy the codegen-generated abstract base and is unreachable at runtime. See `architecture.md` "Method dispatch".

Event	Payload	Description
`propertyChanged`	`(interestName: string, objectName: string, values: PropertyValueList, timestamp: sen.TimeStamp)`	Bundled per-object snapshot of changed properties. Per-object bundling, not per-property: any property change on one object lands in a single envelope.
`eventTriggered`	`(interestName: string, objectName: string, eventName: string, args: string, timestamp: sen.TimeStamp)`	An event fired on one object in one interest. The event signature is decided by the source object's class, not by JSON-RPC.
`interestUpdate`	`(interestName: string, added: AddedObjectList, removed: sen.kernel.StringList, types: sen.kernel.CustomTypeSpecList, typeSchemas: string)`	Match-set delta for one interest. The dispatcher tracks knownTypes / knownSchemas per connection and only re-sends specs / schemas new to the client.
`topologyChanged`	`(sessions: SessionInfoList)`	Full snapshot of the topology after a session or bus add/remove. Pushed once on `subscribeTopology` (with the current state) and again on every change. Snapshot form rather than deltas: topology changes are rare, and the snapshot keeps client logic trivial and idempotent.
`notificationsDropped`	`(count: u64)`	Sent once when outbound backpressure clears on this connection, reporting how many unreliable notifications were dropped while the buffer was above the high watermark. Emitted reliably on purpose: the notice about dropped messages must not be droppable. A client that receives this has an incomplete picture and cannot tell which updates it missed -- only that it missed some. The correct response is to re-read what it displays (getObjectsBatchState over the affected interests) rather than to wait for the next change, which may never come for a property that has stopped moving.

StaticFileServer CLASS

Server-wide registry of in-memory static-file bundles, served alongside the WebSocket+JSON-RPC surface by the same uWS app. Internal-only: lives on the configurable control bus (defaults to `local.jsonrpc_control`), not on the data-plane bus that hosts authenticated per-connection JsonRpcServer instances. The component publishes exactly one instance.

Name	Type	Flags	Description
`registeredBundles`	RegisteredBundleInfoList	RO D C	Currently-registered bundles. Externally read-only; the component mutates this whenever a bundle is registered or unregistered. Subscribe to receive notifications on every change.

Method	Signature	Description
`registerStaticBundle`	`(bundle: StaticBundle) → u64`	Register a bundle. The bundle is copied into the registry; the caller may release the argument

Method	Signature	Description
		afterwards. Routes are wired up asynchronously on the uWS thread; the returned bundleId is stable and may be used immediately with `unregisterStaticBundle`.
`unregisterStaticBundle`	`(bundleId: u64)`	Stop serving the bundle. The slot in the registry is nulled; the underlying uWS route remains registered (uWS does not expose a clean route-removal API) but becomes inert and returns 404. No-op if `bundleId` is unknown.

Fixed records

AddedObjectEntry	One object newly entering an interest's match set.	19
Configuration	JSON-RPC over WebSocket component configuration. Only `address` and `port` are required; every other field falls back to a documented default.	20
ConnectionLimits	Per-connection buffer / timeout knobs consulted on the uWS thread for the lifetime of the server. Every field is optional; unset fields fall back to the defaults resolved inside ws_server.cpp at the use site.	20
Identity	Identity of the connected client. Set once on connect by the dispatcher from the WebSocket upgrade authenticator. Read-only externally. Other components / admin tools can SELECT * FROM local.jsonrpc to enumerate currently-connected clients.	20
NamedSelection	Named arm of MemberSelector: matches only the listed members. Wire shape: `{type: "NamedSelection", value: {memberNames: [...]}}`.	20
ObjectInfo	One entry of listObjects' result.	20
ObjectState	Per-object snapshot returned by `getObjectsBatchState`. `properties` carries successful reads (one entry per property name resolved against the object's class hierarchy); `errors` is empty when nothing failed for this object.	21
PropertyError	Per-property read error. Used when the caller-supplied `propertyNames` includes a name that doesn't exist on a given object's class, or when the accessor itself throws. Carried in a separate list from successful reads so a property literally named `error` can never collide with the failure envelope.	21
PropertyValuePair	Per-property changed value. The value type is decided by the addressed kernel object, not by JSON-RPC, so STL can't statically describe it.	21
RegisteredBundleInfo	Summary record returned by `listRegisteredBundles`. Excludes the file bytes; just enough to answer "what is currently being served, and where".	21
SessionInfo	One discovered session and the buses currently detected inside it. Names are opaque strings from the kernel's session-discovery surface.	21
StaticBundle	One bundle of in-memory files served on a configurable URL prefix. The same bundle's files are served at `<urlPrefix>/<file.path>`. `indexFileName` is the SPA fallback served whenever a request under `urlPrefix` does not match any file (lets the client-side router handle paths the server does not know about).	22
StaticFile	One file inside a StaticBundle. Bytes are owned by the bundle; `path` is relative to the bundle's `urlPrefix` and uses forward slashes regardless of the producer's OS. `contentType` is the MIME type the server will return verbatim; the bundle producer decides it (no extension-based inference happens server-side).	22
SubscribeBlock	Pre-subscription block bundled into createInterest. Wires the listed property / event subscriptions on every matched object -- including ones that arrive later. Wire shape mirrors the typed STL representation exactly: each `MaybeMemberSelector` is either omitted (no auto-subscribe), `null`, or one of the typed variant arms (`{type: "WildcardSelection", value: {}}` or `{type: "NamedSelection", value: {memberNames: [...]}}`); `maxRateHz` is an optional positive number. Strict alignment with the typed surface lets the dispatcher's uniform meta-dispatch path consume the wire directly via `fromJson`, without a per-method translation step.	22
TlsConfig	TLS materials. The schema is reserved so configs stay forward-compatible, but the component fails to start if `tls` is set; full TLS support is not yet wired through the uWebSockets SSL backend.	22
TypeLookupResult	Bundled return of getType: always the CustomTypeSpec, plus the JSON-Schema fragment when the caller opted in. `schema` is empty when not requested.	22
WildcardSelection	Wildcard arm of MemberSelector: matches every member of the relevant kind. Wire shape: `{type: "WildcardSelection", value: {}}`.	23

`AddedObjectEntry` STRUCTURE

One object newly entering an interest's match set.

Name	Type	Description
`objectName`	string	name of the newly-matched object
`qualifiedClassName`	string	package-qualified class name of the object
`currentValues`	PropertyValueList	initial values of pre-subscribed properties (empty if none wired)

Named by AddedObjectList.

Configuration STRUCTURE

JSON-RPC over WebSocket component configuration. Only `address` and `port` are required; every other field falls back to a documented default.

Name	Type	Description
address	string	The IP address or hostname the server will bind to
port	u16	The port number the server will listen on
updateFreqHz	f64	Run-loop frequency in Hz; defaults to 60
connectionLimits	ConnectionLimits	Per-connection uWS buffer / timeout knobs
tls	TlsConfig	schema placeholder; setting this fails component start
controlBusName	string	Control-plane bus on `local`; defaults to "jsonrpc_control"

ConnectionLimits STRUCTURE

Per-connection buffer / timeout knobs consulted on the uWS thread for the lifetime of the server. Every field is optional; unset fields fall back to the defaults resolved inside ws_server.cpp at the use site.

Name	Type	Description
idleTimeoutSeconds	u16	uWS idle close timeout; defaults to 120
maxPayloadBytes	u32	Max inbound frame size; defaults to 16 KiB
maxBackpressureBytes	u32	uWS hard outbound buffer ceiling; defaults to 64 KiB
highBackpressureBytes	u32	Soft trigger for the BackpressureUpdate signal; defaults to 32 KiB

Named by Configuration.

Identity STRUCTURE

Identity of the connected client. Set once on connect by the dispatcher from the WebSocket upgrade authenticator. Read-only externally. Other components / admin tools can SELECT * FROM local.jsonrpc to enumerate currently-connected clients.

Name	Type	Description
subject	string	authenticated subject identifier (e.g. user / service principal)

Named by JsonRpcServer.

NamedSelection STRUCTURE

Named arm of MemberSelector: matches only the listed members. Wire shape: `{type: "NamedSelection", value: {memberNames: [...]}}`.

Name	Type	Description
memberNames	sen.kernel.StringList	member names to match

Named by MemberSelector.

ObjectInfo STRUCTURE

One entry of listObjects' result.

Name	Type	Description
objectName	string	object name within the interest's match set
qualifiedClassName	string	package-qualified class name of the object

Named by ObjectInfos.

ObjectState STRUCTURE

Per-object snapshot returned by `getObjectsBatchState`. `properties` carries successful reads (one entry per property name resolved against the object's class hierarchy); `errors` is empty when nothing failed for this object.

Name	Type	Description
`objectName`	string	object name within the interest's match set
`qualifiedClassName`	string	package-qualified class name at read time
`properties`	PropertyValueList	resolved property values; empty when caller's filter matched nothing
`errors`	PropertyErrorList	per-property failures; empty when none occurred

Named by ObjectStateList.

PropertyError STRUCTURE

Per-property read error. Used when the caller-supplied `propertyNames` includes a name that doesn't exist on a given object's class, or when the accessor itself throws. Carried in a separate list from successful reads so a property literally named `error` can never collide with the failure envelope.

Name	Type	Description
`propertyName`	string	name from the caller's `propertyNames` list that could not be read
`error`	string	human-readable reason (e.g. "unknown property")

Named by PropertyErrorList.

PropertyValuePair STRUCTURE

Per-property changed value. The value type is decided by the addressed kernel object, not by JSON-RPC, so STL can't statically describe it.

Name	Type	Description
`propertyName`	string	property member name
`value`	string	JSON-encoded SenValue

Named by PropertyValueList.

RegisteredBundleInfo STRUCTURE

Summary record returned by `listRegisteredBundles`. Excludes the file bytes; just enough to answer "what is currently being served, and where".

Name	Type	Description
`bundleId`	u64	opaque id assigned by the server, stable for the bundle's lifetime
`urlPrefix`	string	bundle's URL prefix
`fileCount`	u64	number of files in the bundle

Named by RegisteredBundleInfoList.

SessionInfo STRUCTURE

One discovered session and the buses currently detected inside it. Names are opaque strings from the kernel's session-discovery surface.

Name	Type	Description
`name`	string	session name
`buses`	sen.kernel.StringList	bus names currently detected in this session

Named by SessionInfoList.

StaticBundle STRUCTURE

One bundle of in-memory files served on a configurable URL prefix. The same bundle's files are served at `<urlPrefix>/<file.path>`. `indexFileName` is the SPA fallback served whenever a request under `urlPrefix` does not match any file (lets the client-side router handle paths the server does not know about).

Name	Type	Description
`urlPrefix`	string	URL prefix, e.g. "/explorer"; must start with "/"
`indexFileName`	string	SPA fallback, e.g. "index.html"; must match a `path` in `files`
`files`	StaticFileList	file set

Named by StaticFileServer.

StaticFile STRUCTURE

One file inside a StaticBundle. Bytes are owned by the bundle; `path` is relative to the bundle's `urlPrefix` and uses forward slashes regardless of the producer's OS. `contentType` is the MIME type the server will return verbatim; the bundle producer decides it (no extension-based inference happens server-side).

Name	Type	Description
`path`	string	path within the bundle, e.g. "assets/main.js"
`contentType`	string	MIME type, e.g. "text/html"
`contents`	sen.kernel.Buffer	raw file bytes

Named by StaticFileList.

SubscribeBlock STRUCTURE

Pre-subscription block bundled into createInterest. Wires the listed property / event subscriptions on every matched object -- including ones that arrive later. Wire shape mirrors the typed STL representation exactly: each `MaybeMemberSelector` is either omitted (no auto-subscribe), `null`, or one of the typed variant arms (`{type: "WildcardSelection", value: {}}` or `{type: "NamedSelection", value: {memberNames: [...]}}`); `maxRateHz` is an optional positive number. Strict alignment with the typed surface lets the dispatcher's uniform meta-dispatch path consume the wire directly via `fromJson`, without a per-method translation step.

Name	Type	Description
`properties`	MemberSelector	which properties to auto-subscribe to (or none)
`events`	MemberSelector	which events to auto-subscribe to (or none)
`maxRateHz`	f64	optional throttle cap shared across the wired subscriptions

Named by JsonRpcServer.

TlsConfig STRUCTURE

TLS materials. The schema is reserved so configs stay forward-compatible, but the component fails to start if `tls` is set; full TLS support is not yet wired through the uWebSockets SSL backend.

Name	Type	Description
`certPath`	string	PEM-encoded server certificate
`keyPath`	string	PEM-encoded server private key

Named by Configuration.

TypeLookupResult STRUCTURE

Bundled return of getType: always the CustomTypeSpec, plus the JSON-Schema fragment when the caller opted in. `schema` is empty when not requested.

Name	Type	Description
`spec`	sen.kernel.CustomTypeSpec	

Name	Type	Description
schema	string	JSON-encoded schema fragment; "" when withSchema=false

Named by JsonRpcServer.

WildcardSelection STRUCTURE

Wildcard arm of MemberSelector: matches every member of the relevant kind. Wire shape: `{type: "WildcardSelection", value: {}}`.

Named by MemberSelector.

Variant records

MemberSelector	Selector for properties or events in a SubscribeBlock. Absent = no auto-subscribe; WildcardSelection = "*"; NamedSelection = explicit list.	23

MemberSelector VARIANT

Selector for properties or events in a SubscribeBlock. Absent = no auto-subscribe; WildcardSelection = "*"; NamedSelection = explicit list.

Type	Description
WildcardSelection	
NamedSelection	

Named by SubscribeBlock.

Arrays

AddedObjectList	23
ObjectInfos	23
ObjectStateList	23
PropertyErrorList	23
PropertyValueList	24
RegisteredBundleInfoList	24
SessionInfoList	24
StaticFileList	24

AddedObjectList SEQUENCE

```
sequence<AddedObjectEntry> AddedObjectList;
```

Named by JsonRpcServer.

ObjectInfos SEQUENCE

```
sequence<ObjectInfo> ObjectInfos;
```

Named by JsonRpcServer.

ObjectStateList SEQUENCE

```
sequence<ObjectState> ObjectStateList;
```

Named by JsonRpcServer.

PropertyErrorList SEQUENCE

```
sequence<PropertyError> PropertyErrorList;
```

Named by ObjectState.

PropertyValueList SEQUENCE

```
sequence<PropertyValuePair> PropertyValueList;
```

Named by AddedObjectEntry, JsonRpcServer, ObjectState.

RegisteredBundleInfoList SEQUENCE

```
sequence<RegisteredBundleInfo> RegisteredBundleInfoList;
```

Named by StaticFileServer.

SessionInfoList SEQUENCE

```
sequence<SessionInfo> SessionInfoList;
```

Named by JsonRpcServer.

StaticFileList SEQUENCE

```
sequence<StaticFile> StaticFileList;
```

Named by StaticBundle.

Optionals

MaybeConnectionLimits		24
MaybeControlBusName		24
MaybeFlag		24
MaybeHighBackpressureBytes		24
MaybeIdleTimeoutSeconds		25
MaybeMaxBackpressureBytes		25
MaybeMaxPayloadBytes		25
MaybeMemberSelector		25
MaybeRateHz		25
MaybeStringList	Optional list of object names. Absent on the wire (or `null`) selects every object currently in the addressed interest's match set; present limits the read to the listed names.	25
MaybeSubscribeBlock		25
MaybeTlsConfig		25
MaybeUpdateFreqHz		25

MaybeConnectionLimits OPTIONAL

```
optional<ConnectionLimits> MaybeConnectionLimits;
```

MaybeControlBusName OPTIONAL

```
optional<string> MaybeControlBusName;
```

MaybeFlag OPTIONAL

```
optional<bool> MaybeFlag;
```

MaybeHighBackpressureBytes OPTIONAL

```
optional<u32> MaybeHighBackpressureBytes;
```

MaybeIdleTimeoutSeconds OPTIONAL

```
optional<u16> MaybeIdleTimeoutSeconds;
```

MaybeMaxBackpressureBytes OPTIONAL

```
optional<u32> MaybeMaxBackpressureBytes;
```

MaybeMaxPayloadBytes OPTIONAL

```
optional<u32> MaybeMaxPayloadBytes;
```

MaybeMemberSelector OPTIONAL

```
optional<MemberSelector> MaybeMemberSelector;
```

MaybeRateHz OPTIONAL

```
optional<f64> MaybeRateHz;
```

MaybeStringList OPTIONAL

Optional list of object names. Absent on the wire (or `null`) selects every object currently in the addressed interest's match set; present limits the read to the listed names.

```
optional<sen.kernel.StringList> MaybeStringList;
```

MaybeSubscribeBlock OPTIONAL

```
optional<SubscribeBlock> MaybeSubscribeBlock;
```

MaybeTlsConfig OPTIONAL

```
optional<TlsConfig> MaybeTlsConfig;
```

MaybeUpdateFreqHz OPTIONAL

```
optional<f64> MaybeUpdateFreqHz;
```

logmaster

3 types.

Object classes

LogMaster	allows controlling the loggers	26
Logger	represents a logger	26

LogMaster CLASS

allows controlling the loggers

Name	Type	Flags	Description
targetBus	string	RO S BE	

Method	Signature	Description
muteAll	()	mute all the loggers
unmuteAll	()	un-mutes all the muted loggers
toggleMuteAll	()	toggles the muting of all loggers
setLevel	(level: sen.kernel.log.LogLevel)	sets all the loggers to a given level

Logger CLASS

represents a logger

Name	Type	Flags	Description
level	sen.kernel.log.LogLevel	RO D BE	the current log level of this logger
pattern	string	RO D C	the pattern used by this logger
muted	bool	RO D BE	true if muted

Method	Signature	Description
mute	()	mute this logger
unmute	()	unmute this logger
setLevel	(level: sen.kernel.log.LogLevel)	unmute this logger
setPattern	(pattern: string)	sets the pattern for this logger

Fixed records

Config	component configuration	26

Config STRUCTURE

component configuration

Name	Type	Description
targetBus	string	defaults to "local.log"
period	sen.Duration	defaults to 500 milliseconds

py

3 types.

Object classes

PythonInterpreter represents the embedded Python interpreter 27

PythonInterpreter CLASS

represents the embedded Python interpreter

Method	Signature	Description
eval	(expr: string) → string	evaluates a Python expression
exec	(code: string)	executes a Python code block
execFile	(file: string)	executes a Python file

Fixed records

Configuration Overall component configuration 27

Configuration STRUCTURE

Overall component configuration

Name	Type	Description
freqHz	f32	update frequency in Hertz
module	string	python module to use (name of a python script, without the .py)
imports	StringList	sen packages to import
bus	string	bus where to publish the interpreter object (none by default)

Arrays

StringList 27

StringList SEQUENCE

```
sequence<string> StringList;
```

Named by Configuration.

recorder

6 types.

Object classes

Recorder represents an recording session 28

Recorder CLASS

represents an recording session

Name	Type	Flags	Description
settings	RecordingSettings	RO S BE	
state	RecorderState	RO D C	

Method	Signature	Description
start	()	starts (or resumes) recording
stop	()	stops recording
fetchStats	() → sen.db.OutStats	sample the output statistics

Fixed records

Configuration Overall component configuration 28
RecordingSettings Configuration of a predefined recording 28

Configuration STRUCTURE

Overall component configuration

Name	Type	Description
samplingPeriod	sen.Duration	sampling period for the recordings
recordings	RecordingSettingsList	predefined recordings
bus	string	bus to publish the object (local.rec by default)

RecordingSettings STRUCTURE

Configuration of a predefined recording

Name	Type	Description
name	string	name of the recording (cannot be empty)
folder	string	storage folder
selections	SelectionList	which objects shall be recorded
keyframePeriod	sen.Duration	period between keyframes (0 means no keyframes)
indexKeyframes	bool	should we create indexes for keyframes
indexObjects	bool	should we create indexes for objects
autoStart	bool	should we start recording automatically

Named by Recorder, RecordingSettingsList.

Enumerations

RecorderState the state of a recording session 28

RecorderState ENUMERATION

the state of a recording session

Held as u8.

stopped	0	error	2
recording	1		

Named by Recorder.

Arrays

RecordingSettingsList	List of predefined recordings	29
SelectionList	List of selection queries	29

RecordingSettingsList SEQUENCE

List of predefined recordings

```
sequence<RecordingSettings> RecordingSettingsList;
```

Named by Configuration.

SelectionList SEQUENCE

List of selection queries

```
sequence<string> SelectionList;
```

Named by RecordingSettings.

replayer

4 types.

Object classes

Replay	controls the replay of a given archive	30
Replayer	represents the replayer component and manages Replay objects.	30

Replay CLASS

controls the replay of a given archive

Name	Type	Flags	Description
archiveInfo	sen.db.Summary	RO S BE	information about the archive being replayed
archivePath	string	RO S BE	file path to the archive
status	ReplayStatus	RO D C	playback status
playbackTime	sen.TimeStamp	RO D BE	playback time

Method	Signature	Description
play	()	starts the playback from the current position
pause	()	hold the playback position, if playing
stop	()	goes to the start of the playback, erasing all objects
seek	(time: sen.TimeStamp)	restores the playback to the keyframe that's closest to a given time
advance	(time: sen.Duration)	if paused or stopped, advances the playback a given time delta

Replayer CLASS

represents the replayer component and manages Replay objects.

Name	Type	Flags	Description
autoPlay	bool	RO S BE	if true, automatically calls play when opening a replay

Method	Signature	Description
open	(name: string, path: string)	opens an archive in a given path, and creates a named Replay object.
close	(name: string)	closes the named Replay object, if any.
closeAll	()	closes all previously opened replays

Fixed records

Configuration	Overall component configuration	30

Configuration STRUCTURE

Overall component configuration

Name	Type	Description
bus	string	bus to publish the object (local.replay by default)
samplingPeriod	sen.Duration	max sampling period for flushing the replayed data
autoOpen	string	optional archive path to auto open on start-up (empty by default)
autoPlay	bool	if autoOpen is not empty, try to play it on start-up (false by default)

Enumerations

ReplayStatus the state in which a Replay can be 31

ReplayStatus ENUMERATION

the state in which a Replay can be

Held as u8.

stopped	0
paused	1
playing	2

Named by Replay.

rest

37 types.

Fixed records

Argument 32
Bus 32
BusSummary 32
ClientAuth 32
Configuration 33
Error 33
Interest 33
InterestSummary 33
Link 33
Notification 33
Object 33
ObjectEvent 34
ObjectMethod 34
ObjectSummary 34
Session 34
SessionSummary 34
SubscriptionOptions 34
Subscriptions 34
Success 35
Version 35

Argument STRUCTURE

Name	Type	Description
name	string	
description	string	
type	string	

Named by Arguments.

Bus STRUCTURE

Name	Type	Description
id	string	
status	Status	
objects	ObjectsSummary	

BusSummary STRUCTURE

Name	Type	Description
id	string	
status	Status	

Named by Buses.

ClientAuth STRUCTURE

Name	Type	Description
id	string	

Configuration STRUCTURE

Name	Type	Description
address	string	The IP address or hostname the server will bind to
port	u16	The port number the server will listen on
freqHz	f32	Update frequency in Hertz

Error STRUCTURE

Name	Type	Description
error	string	

Interest STRUCTURE

Name	Type	Description
query	string	
name	string	

InterestSummary STRUCTURE

Name	Type	Description
name	string	
session	string	
bus	string	

Named by InterestsSummary.

Link STRUCTURE

Name	Type	Description
rel	RelType	
href	string	
method	HttpMethod	

Named by Links, ObjectSummary.

Notification STRUCTURE

Name	Type	Description
type	NotificationType	
interest	string	
time	sen.TimeStamp	
data	string	

Object STRUCTURE

Name	Type	Description
objectId	u32	
name	string	
className	string	
localName	string	

Name	Type	Description
description	string	
links	Links	

ObjectEvent STRUCTURE

Name	Type	Description
name	string	
description	string	

ObjectMethod STRUCTURE

Name	Type	Description
name	string	
description	string	
retType	string	
args	Arguments	

ObjectSummary STRUCTURE

Name	Type	Description
objectId	u32	
name	string	
className	string	
localName	string	
link	Link	

Named by ObjectsSummary.

Session STRUCTURE

Name	Type	Description
name	string	

SessionSummary STRUCTURE

Name	Type	Description
name	string	
buses	BusNames	

SubscriptionOptions STRUCTURE

Name	Type	Description
maxUpdateTime	sen.Duration	Max. update time

Subscriptions STRUCTURE

Name	Type	Description
properties	Properties	
events	Events	

Success STRUCTURE

Name	Type	Description
msg	string	

Version STRUCTURE

Name	Type	Description
version	string	

Enumerations

HttpMethod 35
InvokeStatus 35
NotificationType 35
RelType 35
Status 36

HttpMethod ENUMERATION

Held as u8.

httpGet	0
httpPost	1
httpPut	2
httpDelete	3
httpOption	4

Named by Link.

InvokeStatus ENUMERATION

Held as u8.

pending	0
finished	1
failed	2

NotificationType ENUMERATION

Held as u8.

evt	0
invoke	1
property	2
objectAdded	3
objectRemoved	4
count	5

Named by Notification.

RelType ENUMERATION

Held as u8.

method	0
setter	1
getter	2
evt	3
property	4
propertySubscribe	5
propertyUnsubscribe	6
def	7

Named by Link.

Status ENUMERATION

Held as u8.

open	0
close	1

Named by Bus, BusSummary.

Arrays

Arguments 36
BusNames 36
Buses 36
Events 36
InterestsSummary 36
Links 36
ObjectsSummary 36
Properties 37
Sessions 37

Arguments SEQUENCE

```
sequence<Argument> Arguments;
```

Named by ObjectMethod.

BusNames SEQUENCE

```
sequence<string> BusNames;
```

Named by SessionSummary.

Buses SEQUENCE

```
sequence<BusSummary> Buses;
```

Events SEQUENCE

```
sequence<string> Events;
```

Named by Subscriptions.

InterestsSummary SEQUENCE

```
sequence<InterestSummary> InterestsSummary;
```

Links SEQUENCE

```
sequence<Link> Links;
```

Named by Object.

ObjectsSummary SEQUENCE

```
sequence<ObjectSummary> ObjectsSummary;
```

Named by Bus.

Properties SEQUENCE

```
sequence<string> Properties;
```

Named by Subscriptions.

Sessions SEQUENCE

```
sequence<string> Sessions;
```

Optionals

ThreadPoolSize 37
UpdateFrequency 37
UpdateTime 37

ThreadPoolSize OPTIONAL

```
optional<u16> ThreadPoolSize;
```

UpdateFrequency OPTIONAL

```
optional<f32> UpdateFrequency;
```

UpdateTime OPTIONAL

```
optional<sen.Duration> UpdateTime;
```

shell

27 types.

Object classes

Shell Provides a text-based interface to interact with the a sen kernel 38

Shell CLASS

Provides a text-based interface to interact with the a sen kernel

Name	Type	Flags	Description
config	Configuration	RO S BE	service configuration

Method	Signature	Description
clear	()	clears the screen
help	()	basic usage help
history	()	lists previous commands
ls	()	lists all the existing objects and sources.
open	(source: string)	opens a source (bus or session) without any condition
query	(name: string, condition: string)	opens a named source using a condition expression
close	(source: string)	closes a previously-opened source (session, bus or query)
info	(term: string)	prints information about a type or instance
shutdown	()	requests the kernel to be shut-down
src	()	lists the current sources

Fixed records

CPrint 38
ClearCurrentLine 39
ClearRemainingCurrentLine 39
ClearScreen 39
Configuration Configuration params for the shell 39
HideCursor 39
MoveCursorAllLeft 39
MoveCursorDown 39
MoveCursorLeft 39
MoveCursorRight 39
MoveCursorUp 40
NewLine 40
Print 40
Query Holds information about a named query 40
RestoreCursorPosition 40
SaveCursorPosition 40
SetBgColor 40
SetFgColor 40
SetWindowTitle 40
ShowCursor 41

CPrint STRUCTURE

Name	Type	Description
flags	u32	
color	u32	
text	string	

Named by TerminalCmd.

ClearCurrentLine STRUCTURE

Named by TerminalCmd.

ClearRemainingCurrentLine STRUCTURE

Named by TerminalCmd.

ClearScreen STRUCTURE

Named by TerminalCmd.

Configuration STRUCTURE

Configuration params for the shell

Name	Type	Description
prompt	string	defaults to 'sen> '
timeStyle	TimeStyle	how to display time
bufferStyle	BufferStyle	how to display buffers
serverEnabled	bool	enables remote shell access (false by default)
serverPort	u16	0 means default
noLogo	bool	true if you don't want a welcoming logo
open	SourcesList	list of sources to open automatically
query	QueryList	list of queries to create automatically
logBus	string	where to find the logmaster, if any (default: local.log)

Named by Shell.

HideCursor STRUCTURE

Named by TerminalCmd.

MoveCursorAllLeft STRUCTURE

Named by TerminalCmd.

MoveCursorDown STRUCTURE

Name	Type	Description
cells	u32	

Named by TerminalCmd.

MoveCursorLeft STRUCTURE

Name	Type	Description
cells	u32	

Named by TerminalCmd.

MoveCursorRight STRUCTURE

Name	Type	Description
cells	u32	

Named by TerminalCmd.

MoveCursorUp STRUCTURE

Name	Type	Description
cells	u32	

Named by TerminalCmd.

NewLine STRUCTURE

Named by TerminalCmd.

Print STRUCTURE

Name	Type	Description
text	string	

Named by TerminalCmd.

Query STRUCTURE

Holds information about a named query

Name	Type	Description
name	string	the name of the query (cannot contain spaces or dots)
selection	string	the query expression

Named by QueryList.

RestoreCursorPosition STRUCTURE

Named by TerminalCmd.

SaveCursorPosition STRUCTURE

Named by TerminalCmd.

SetBgColor STRUCTURE

Name	Type	Description
color	u32	

Named by TerminalCmd.

SetFgColor STRUCTURE

Name	Type	Description
color	u32	

Named by TerminalCmd.

SetWindowTitle STRUCTURE

Name	Type	Description
text	string	

Named by TerminalCmd.

ShowCursor STRUCTURE

Named by TerminalCmd.

Enumerations

BufferStyle	How buffers should be printed	41
ListStyle	How lists should be printed	41
TimeStyle	How timestamps should be printed	41

BufferStyle ENUMERATION

How buffers should be printed

Held as u8.

size	0
hexdump	1

Named by Configuration.

ListStyle ENUMERATION

How lists should be printed

Held as u8.

treeStyle	0
plainStyle	1

TimeStyle ENUMERATION

How timestamps should be printed

Held as u8.

timestampUTC	0
timestampLocal	1

Named by Configuration.

Variant records

TerminalCmd	41

TerminalCmd VARIANT

Type	Description
Print	
CPrint	
NewLine	
MoveCursorLeft	
MoveCursorRight	
MoveCursorUp	
MoveCursorDown	
MoveCursorAllLeft	
SetFgColor	
SetBgColor	
ClearCurrentLine	
ClearRemainingCurrentLine	
HideCursor	
ShowCursor	
SaveCursorPosition	

Type	Description
RestoreCursorPosition	
ClearScreen	
SetWindowTitle	

Arrays

QueryList 42
SourcesList 42

QueryList SEQUENCE

```
sequence<Query> QueryList;
```

Named by Configuration.

SourcesList SEQUENCE

```
sequence<string> SourcesList;
```

Named by Configuration.

term

8 types.

Object classes

Term Modern TUI-based interactive terminal for the sen kernel 43

Term CLASS

Modern TUI-based interactive terminal for the sen kernel

Name	Type	Flags	Description
config	Configuration	RO S BE	service configuration

Fixed records

Configuration Configuration params for the term component 43
QueryDef Holds information about a named query 43

Configuration STRUCTURE

Configuration params for the term component

Name	Type	Description
initialScope	string	initial scope, e.g. "local.demo"; its bus must be in open too. Empty means root.
timeStyle	TimeStyle	how to display time (default: utc)
theme	ThemeStyle	color theme (default: catppuccinMocha)
noLogo	bool	true to suppress the welcome banner
open	SourcesList	sources to open automatically at startup
query	QueryList	named queries to create automatically at startup
listen	NameList	event listeners to register at startup (object or object.event)
callTimeout	sen.Duration	async call timeout (default: 30s)

Named by Term.

QueryDef STRUCTURE

Holds information about a named query

Name	Type	Description
name	string	the name of the query (cannot contain spaces or dots)
selection	string	the query expression

Named by QueryList.

Enumerations

ThemeStyle Color theme for the terminal UI 43
TimeStyle How timestamps should be displayed 44

ThemeStyle ENUMERATION

Color theme for the terminal UI

Held as u8.

oneDark	0	gruvboxDark	6
oneLight	1	gruvboxLight	7
catppuccinMocha	2	tokyoNight	8
catppuccinLatte	3	solarizedLight	9
dracula	4		
nord	5		

Named by Configuration.

TimeStyle ENUMERATION

How timestamps should be displayed

Held as u8.

utc	0
local	1

Named by Configuration.

Arrays

NameList 44
QueryList 44
SourcesList 44

NameList SEQUENCE

```
sequence<string> NameList;
```

Named by Configuration.

QueryList SEQUENCE

```
sequence<QueryDef> QueryList;
```

Named by Configuration.

SourcesList SEQUENCE

```
sequence<string> SourcesList;
```

Named by Configuration.

db

3 types.

Fixed records

OutSettings	Settings for outputs	45
OutStats	Statistics of writing	45
Summary	Summary of an archive	45

OutSettings STRUCTURE

Settings for outputs

Name	Type	Description
name	string	name of the archive (cannot be empty)
folder	string	storage folder
indexKeyframes	bool	should we create indexes for keyframes

OutStats STRUCTURE

Statistics of writing

Name	Type	Description
maxQueueSize	u64	in bytes

Named by sen.components.recorder.Recorder.

Summary STRUCTURE

Summary of an archive

Name	Type	Description
firstTime	sen.TimeStamp	the time of the first event
lastTime	sen.TimeStamp	the time of the last event
keyframeCount	u32	number of written keyframes
objectCount	u32	number of recorded objects
typeCount	u32	number of types written
annotationCount	u32	number of annotations
indexedObjectCount	u32	number of indexed objects

Named by sen.components.replayer.Replay.

kernel

160 types.

Object classes

KernelApi	Represents the kernel	46
VirtualClock	Allows inspecting and controlling the advance of virtual time and associated component iteration	46
VirtualKernelClock	A clock for all the components loaded by the kernel	46
VirtualMasterClock	Controls all the VirtualKernelClock that it discovers in the bus where it's published. One step reaches the next component due to run: each clock reports how long until its own next one, and the soonest wins	46

KernelApi CLASS

Represents the kernel

Name	Type	Flags	Description
buildInfo	BuildInfo	RO S BE	kernel build information

Method	Signature	Description
shutdown	()	requests the kernel to shut down
getUnits	() → UnitList	registered units
getTypes	() → StringList	registered types, by name
getConfig	() → KernelParams	configuration of the kernel execution
getRuntimeNetworkFootprint	() → NetworkFootprint	actual network addresses and ports currently used by this process

VirtualClock CLASS

Allows inspecting and controlling the advance of virtual time and associated component iteration

Name	Type	Flags	Description
time	sen.TimeStamp	RO D BE	the current virtual time

VirtualKernelClock CLASS

A clock for all the components loaded by the kernel

Method	Signature	Description
processNoFlush	(delta: sen.Duration) → sen.Duration	updates the time, drains the inputs, and cycles components - doesn't flush outputs
flushOutputs	() → sen.Duration	makes component outputs visible to other components and returns the next step duration

VirtualMasterClock CLASS

Controls all the VirtualKernelClock that it discovers in the bus where it's published. One step reaches the next component due to run: each clock reports how long until its own next one, and the soonest wins

Method	Signature	Description
advanceTime	(duration: sen.Duration) → sen.Duration	steps until the virtual time advanced reaches duration, rounding up to a whole step. Returns the wall time the call took
step	() → sen.Duration	single step forward
steps	(count: u64) → sen.Duration	perform 'count' steps forward

Fixed records

AliasTypeSpec	data of an aliased type	48

AliasTypeSpecV4		48
AliasTypeSpecV5		48
ArgSpec	an argument of a callable (methods and events)	48
ArgSpecV4		48
ArgSpecV5		49
BuildInfo	Build-related information	49
BuiltComponentParams	Parameters related to components build by the kernel	49
BusAddress	Address to connect to a bus	49
ClassTypeSpec	spec of a class	49
ClassTypeSpecV4		50
ClassTypeSpecV5		50
ComponentConfig	Basic runtime configuration for a component	50
ComponentInfo	Basic information of a kernel component	50
CustomTypeSpec	spec of a custom type	51
CustomTypeSpecV4		51
CustomTypeSpecV5		51
EnumTypeSpec	spec of an enum type	51
EnumTypeSpecV4		51
EnumTypeSpecV5		52
EnumeratorSpec	an enumerator	52
EnumeratorSpecV4		52
EnumeratorSpecV5		52
EnvVar	Information about an environment variable	52
ErrorData	Information related to the error	52
ErrorReport	Information about a detected error	53
EventSpec	spec for an event	53
EventSpecV4		53
EventSpecV5		53
ExecError	Holds details of an execution error	53
KernelParams	This struct is reachable over the wire through Kernel.getConfig() and is embedded in SenData, and the encoding is positional, so adding a field here shifts what follows it either way.	53
LoadedComponentParams	Parameters related to a component that will be loaded by the kernel	54
MethodSpec	spec for methods	54
MethodSpecV4		54
MethodSpecV5		55
NetworkFootprint	Network endpoints predicted offline or observed at runtime for one process	55
NetworkFootprintAddressRange	Inclusive IPv4 address range excluded from multicast allocation	55
NetworkFootprintBus	Multicast endpoint allocated to a bus	55
NetworkFootprintBusIdentity	Names and IDs that identify a bus	56
NetworkFootprintCollision	Multicast allocation capacity and collision information	56
NetworkFootprintMulticast	Multicast information in the network footprint	56
NetworkFootprintPort	Socket type, port selection mode and port value	56
NetworkFootprintPortExclusions	Port ranges that cannot be used	57
NetworkFootprintPortRange	Inclusive range from which a port may be selected	57
NetworkFootprintSelfCollision	Two buses allocated to the same multicast group	57
OpFinished	An operation is complete	57
OpNotFinished	An operation is not complete	57
OptionalTypeSpec	data of an optional type	57
OptionalTypeSpecV4		58
OptionalTypeSpecV5		58
PrecisionSleep	Be more precise at the expense of some CPU cycles.	58
ProcessData	Information about the process	58
ProcessInfo	Basic information about a process	58
PropertySpec	spec of a property	58
PropertySpecV4		59
PropertySpecV5		59
QuantityTypeSpec	spec of a quantity type	59
QuantityTypeSpecV4		59
QuantityTypeSpecV5		60
QueueConfig		60
SenData	Information about Sen	60
SequenceTypeSpec	spec of a sequence type	60
SequenceTypeSpecV4		61
SequenceTypeSpecV5		61
SignalData	Information about an unhandled signal	61
StructTypeFieldSpec	a field of a struct	61
StructTypeFieldSpecV4		61

StructTypeFieldSpecV5		61
StructTypeSpec	spec of an struct type	62
StructTypeSpecV4		62
StructTypeSpecV5		62
SystemSleep	Use the native system sleep	62
UncaughtException	Information about an unhandled exception	62
UnitInfo	Describes a unit	62
VariantTypeFieldSpec	a field of a variant	63
VariantTypeFieldSpecV4		63
VariantTypeFieldSpecV5		63
VariantTypeSpec	spec of an struct type	63
VariantTypeSpecV4		63
VariantTypeSpecV5		63

AliasTypeSpec STRUCTURE

data of an aliased type

Name	Type	Description
aliasedType	string	qualified type name being aliased

Named by CustomTypeData.

AliasTypeSpecV4 STRUCTURE

Name	Type	Description
aliasedType	string	qualified type name being aliased

Named by CustomTypeDataV4.

AliasTypeSpecV5 STRUCTURE

Name	Type	Description
aliasedType	string	qualified type name being aliased
hash	u32	unique hash

Named by CustomTypeDataV5.

ArgSpec STRUCTURE

an argument of a callable (methods and events)

Name	Type	Description
name	string	argument name
description	string	documentation
type	string	qualified type name of the argument

Named by ArgSpecList.

ArgSpecV4 STRUCTURE

Name	Type	Description
name	string	argument name
description	string	documentation
type	string	qualified type name of the argument

Named by ArgSpecListV4.

ArgSpecV5 STRUCTURE

Name	Type	Description
name	string	argument name
nameHash	u32	hash computed with the argument name
description	string	documentation
type	string	qualified type name of the argument
hash	u32	unique hash

Named by ArgSpecListV5.

BuildInfo STRUCTURE

Build-related information

Name	Type	Description
maintainer	string	principal maintainer of the software
version	string	version string (format-agnostic)
compiler	string	vendor-specific compiler string
debugMode	bool	compiled in debug mode or not
buildTime	string	the commit's timestamp, ISO-8601; not the compiler's clock
wordSize	WordSize	architecture
gitRef	string	git ref spec
gitHash	string	git hash
gitStatus	GitStatus	git status

Named by ComponentInfo, KernelApi.

BuiltComponentParams STRUCTURE

Parameters related to components build by the kernel

Name	Type	Description
name	string	the name of the component
period	sen.Duration	the execution period
config	ComponentConfig	the configuration of the component
imports	StringList	the imported packages

Named by BuiltComponentList.

BusAddress STRUCTURE

Address to connect to a bus

Name	Type	Description
sessionName	string	
busName	string	

ClassTypeSpec STRUCTURE

spec of a class

Name	Type	Description
properties	PropertySpecList	
methods	MethodSpecList	
events	EventSpecList	
constructor	MethodSpec	

Name	Type	Description
parents	StringList	
isInterface	bool	

Named by CustomTypeData.

ClassTypeSpecV4 STRUCTURE

Name	Type	Description
properties	PropertySpecListV4	
methods	MethodSpecListV4	
events	EventSpecListV4	
isInterface	bool	
id	u32	
constructor	MethodSpecV4	
parents	StringList	

Named by CustomTypeDataV4.

ClassTypeSpecV5 STRUCTURE

Name	Type	Description
properties	PropertySpecListV5	
methods	MethodSpecListV5	
events	EventSpecListV5	
isInterface	bool	
id	u32	
constructor	MethodSpecV5	
parents	StringList	
hash	u32	

Named by CustomTypeDataV5.

ComponentConfig STRUCTURE

Basic runtime configuration for a component

Name	Type	Description
priority	Priority	thread priority
stackSize	u32	thread stack size in bytes, 0 means default
group	u32	the group where to run the component
cpuAffinity	u64	CPU affinity mask
inQueue	QueueConfig	queuing of inbound information
outQueue	QueueConfig	queuing of outbound information
sleepPolicy	SleepPolicy	configurable component sleep policy

Named by BuiltComponentParams, LoadedComponentParams.

ComponentInfo STRUCTURE

Basic information of a kernel component

Name	Type	Description
name	string	
description	string	

Name	Type	Description
buildInfo	BuildInfo	

CustomTypeSpec STRUCTURE

spec of a custom type

Name	Type	Description
name	string	name of the type
qualifiedName	string	package-qualified name
description	string	documentation
data	CustomTypeData	spec data

Named by sen.components.jsonrpc.TypeLookupResult, CustomTypeSpecList.

CustomTypeSpecV4 STRUCTURE

Name	Type	Description
name	string	name of the type
qualifiedName	string	package-qualified name
description	string	documentation
data	CustomTypeDataV4	spec data

Named by CustomTypeSpecListV4.

CustomTypeSpecV5 STRUCTURE

Name	Type	Description
name	string	name of the type
qualifiedName	string	package-qualified name
description	string	documentation
data	CustomTypeDataV5	spec data

Named by CustomTypeSpecListV5.

EnumTypeSpec STRUCTURE

spec of an enum type

Name	Type	Description
enums	EnumeratorSpecList	enumerators
storageType	IntegralType	type used to store the value

Named by CustomTypeData.

EnumTypeSpecV4 STRUCTURE

Name	Type	Description
enums	EnumeratorSpecListV4	enumerators
storageType	IntegralType	type used to store the value

Named by CustomTypeDataV4.

EnumTypeSpecV5 STRUCTURE

Name	Type	Description
enums	EnumeratorSpecListV5	enumerators
storageType	IntegralType	type used to store the value
hash	u32	unique hash

Named by CustomTypeDataV5.

EnumeratorSpec STRUCTURE

an enumerator

Name	Type	Description
name	string	enumerator name
key	u32	enumerator value
description	string	enumerator description

Named by EnumeratorSpecList.

EnumeratorSpecV4 STRUCTURE

Name	Type	Description
name	string	enumerator name
key	u64	enumerator value

Named by EnumeratorSpecListV4.

EnumeratorSpecV5 STRUCTURE

Name	Type	Description
name	string	enumerator name
key	u64	enumerator value
hash	u32	unique hash

Named by EnumeratorSpecListV5.

EnvVar STRUCTURE

Information about an environment variable

Name	Type	Description
name	string	name of the variable
value	string	value of the variable

Named by EnvironmentVarList.

ErrorData STRUCTURE

Information related to the error

Name	Type	Description
time	sen.TimeStamp	time of the error
errorMessage	StringList	message presented to the user
exceptionData	UncaughtException	information about the unhandled exception (if any)
signalData	SignalData	information about the received signal (if any)

Named by ErrorReport.

ErrorReport STRUCTURE

Information about a detected error

Name	Type	Description
senData	SenData	information related to Sen
processData	ProcessData	information related to the process
errorData	ErrorData	information related to the error

EventSpec STRUCTURE

spec for an event

Name	Type	Description
name	string	name of the type
description	string	documentation
args	ArgSpecList	arguments
transportMode	TransportModeSpec	transport mode

Named by EventSpecList.

EventSpecV4 STRUCTURE

Name	Type	Description
memberHash	u32	hash of the class member
name	string	name of the type
description	string	documentation
args	ArgSpecListV4	arguments
transportMode	TransportModeSpec	transport mode

Named by EventSpecListV4.

EventSpecV5 STRUCTURE

Name	Type	Description
memberHash	u32	hash of the class member
name	string	name of the type
description	string	documentation
args	ArgSpecListV5	arguments
transportMode	TransportModeSpec	transport mode
hash	u32	unique hash

Named by EventSpecListV5.

ExecError STRUCTURE

Holds details of an execution error

Name	Type	Description
category	ErrorCategory	general problem
explanation	string	human-readable explanation

KernelParams STRUCTURE

This struct is reachable over the wire through Kernel.getConfig() and is embedded in SenData, and the encoding is positional, so adding a field here shifts what follows it either way.

Name	Type	Description
runMode	RunMode	how to run the kernel
appName	string	optional name of the application
bus	string	where to publish the kernel objects (defaults to local.kernel)
clockBus	string	where to publish the virtual clock (if any), defaults to bus
clockName	string	the name of the virtual clock (if any), defaults to 'clock'
clockMaster	bool	if time is virtualized, publish a master clock to clockBus
logConfig	log.Config	logging configuration
crashReportDir	string	where to store crash reports (defaults to the temp dir)
crashReportDisabled	bool	if true, no reports are generated
lockMemoryPages	bool	keep process pages memory-resident
sleepPolicy	SleepPolicy	configurable sleep policy of the kernel component
compatibilityMode	CompatibilityMode	what to do with a remote type that does not match
limitCpuIdleLatency	bool	keep the CPUs out of the deep idle states they are slow to leave

Named by KernelApi, SenData.

LoadedComponentParams STRUCTURE

Parameters related to a component that will be loaded by the kernel

Name	Type	Description
name	string	the name of the component
config	ComponentConfig	the configuration of the component

Named by LoadedComponentList.

MethodSpec STRUCTURE

spec for methods

Name	Type	Description
name	string	name of the type
description	string	documentation
args	ArgSpecList	arguments
transportMode	TransportModeSpec	transport mode
constness	MethodConstness Spec	if it changes the state of the object
deferred	bool	if the execution of the method is deferred
returnType	string	qualified return type name
propertyRelation	PropertyRelationSpec	property relation of the method
localOnly	bool	true if the method can only be called locally

Named by ClassTypeSpec, MethodSpecList.

MethodSpecV4 STRUCTURE

Name	Type	Description
memberHash	u32	hash of the class member
name	string	name of the type
description	string	documentation
args	ArgSpecListV4	arguments
transportMode	TransportModeSpec	transport mode

Name	Type	Description
`constness`	MethodConstness Spec	if it changes the state of the object
`deferred`	bool	true if the method is marked as deferred
`returnTypeId`	string	qualified return type name (empty for none)

Named by ClassTypeSpecV4, MethodSpecListV4.

MethodSpecV5 STRUCTURE

Name	Type	Description
`memberHash`	u32	hash of the class member
`name`	string	name of the type
`description`	string	documentation
`args`	ArgSpecListV5	arguments
`transportMode`	TransportModeSpec	transport mode
`constness`	MethodConstness Spec	if it changes the state of the object
`localOnly`	bool	true if the method can only be called locally
`returnTypeId`	string	qualified return type name (empty for none)
`hash`	u32	unique hash

Named by ClassTypeSpecV5, MethodSpecListV5.

NetworkFootprint STRUCTURE

Network endpoints predicted offline or observed at runtime for one process

Name	Type	Description
`discoveryPort`	u16	Discovery port used to calculate multicast addresses
`multicast`	NetworkFootprint Multicast	Multicast allocation details
`ports`	NetworkFootprintPort List	Port settings
`portExclusions`	NetworkFootprintPort Exclusions	Port ranges that cannot be used

Named by KernelApi.

NetworkFootprintAddressRange STRUCTURE

Inclusive IPv4 address range excluded from multicast allocation

Name	Type	Description
`min`	string	
`max`	string	

Named by NetworkFootprintAddressRangeList.

NetworkFootprintBus STRUCTURE

Multicast endpoint allocated to a bus

Name	Type	Description
`sessionName`	string	
`busName`	string	
`sessionId`	u32	

Name	Type	Description
busId	u32	
groupAddress	string	
source	NetworkFootprintBusSource	

Named by NetworkFootprintBusList.

NetworkFootprintBusIdentity STRUCTURE

Names and IDs that identify a bus

Name	Type	Description
sessionName	string	
busName	string	
sessionId	u32	
busId	u32	

Named by NetworkFootprintSelfCollision.

NetworkFootprintCollision STRUCTURE

Multicast allocation capacity and collision information

Name	Type	Description
usableSpaceSize	u64	Number of addresses available
busCount	u64	Number of reported buses
probability	f64	Estimated conflict from 0 to 1
selfCollisions	NetworkFootprintSelfCollisionList	Collisions in the reported buses

Named by NetworkFootprintMulticast.

NetworkFootprintMulticast STRUCTURE

Multicast information in the network footprint

Name	Type	Description
port	u16	Shared multicast port used by every bus
buses	NetworkFootprintBusList	Multicast address used by each bus
exclusions	NetworkFootprintAddressRangeList	Addresses that cannot be used
collision	NetworkFootprintCollision	Available addresses and conflict information

Named by NetworkFootprint.

NetworkFootprintPort STRUCTURE

Socket type, port selection mode and port value

Name	Type	Description
kind	NetworkFootprintPortKind	
mode	NetworkFootprintPortMode	
value	NetworkFootprintPortValue	

Named by NetworkFootprintPortList.

NetworkFootprintPortExclusions STRUCTURE

Port ranges that cannot be used

Name	Type	Description
builtIn	NetworkFootprintPortRangeList	
configured	NetworkFootprintPortRangeList	
operatingSystem	NetworkFootprintPortRangeList	

Named by NetworkFootprint.

NetworkFootprintPortRange STRUCTURE

Inclusive range from which a port may be selected

Name	Type	Description
min	u16	
max	u16	

Named by NetworkFootprintPortRangeList, NetworkFootprintPortValue.

NetworkFootprintSelfCollision STRUCTURE

Two buses allocated to the same multicast group

Name	Type	Description
firstBus	NetworkFootprintBusIdentity	
secondBus	NetworkFootprintBusIdentity	
groupAddress	string	

Named by NetworkFootprintSelfCollisionList.

OpFinished STRUCTURE

An operation is complete

Named by OpState.

OpNotFinished STRUCTURE

An operation is not complete

Name	Type	Description
waitHint	sen.Duration	How long to wait until the next try

Named by OpState.

OptionalTypeSpec STRUCTURE

data of an optional type

Name	Type	Description
type	string	qualified type name

Named by CustomTypeData.

OptionalTypeSpecV4 STRUCTURE

Name	Type	Description
type	string	qualified type name

Named by CustomTypeDataV4.

OptionalTypeSpecV5 STRUCTURE

Name	Type	Description
type	string	qualified type name
hash	u32	unique hash

Named by CustomTypeDataV5.

PrecisionSleep STRUCTURE

Be more precise at the expense of some CPU cycles.

Name	Type	Description
veryCoarseGrainSleepTime	sen.Duration	First set of sleeps. If 0 defaults to 7ms
coarseGrainSleepTime	sen.Duration	Second set of sleeps. If 0 defaults to 1ms

Named by SleepPolicy.

ProcessData STRUCTURE

Information about the process

Name	Type	Description
processInfo	ProcessInfo	general process information
environment	EnvironmentVarList	list of environment variables
stacktrace	StringList	the stack trace (if any)
recentLogs	StringList	the last logs emitted by the process

Named by ErrorReport.

ProcessInfo STRUCTURE

Basic information about a process

Name	Type	Description
hostId	u32	
processId	u32	
sessionId	u32	
sessionName	string	
appName	string	
hostName	string	
osKind	OsKind	
osName	string	
cpuArch	CpuArch	

Named by sen.components.ether.Hello, sen.components.ether.SessionPresenceBeam, ProcessData, Processes.

PropertySpec STRUCTURE

spec of a property

Name	Type	Description
name	string	name of the type
description	string	documentation
category	PropertyCategorySpec	category
type	string	qualified type name of the property
transportMode	TransportModeSpec	how to transport the data
tags	StringList	user-defined tags
checkedSet	bool	if setting the property is checked

Named by PropertySpecList.

PropertySpecV4 STRUCTURE

Name	Type	Description
memberHash	u32	hash of the class member
name	string	name of the type
description	string	documentation
category	PropertyCategorySpec	category
type	string	qualified type name of the property
transportMode	TransportModeSpec	how to transport the data
tags	StringList	user-defined tags

Named by PropertySpecListV4.

PropertySpecV5 STRUCTURE

Name	Type	Description
memberHash	u32	hash of the class member
name	string	name of the type
description	string	documentation
category	PropertyCategorySpec	category
type	string	qualified type name of the property
transportMode	TransportModeSpec	how to transport the data
tags	StringList	user-defined tags
hash	u32	unique hash

Named by PropertySpecListV5.

QuantityTypeSpec STRUCTURE

spec of a quantity type

Name	Type	Description
elementType	NumericType	type used to store the value
unit	UnitInfo	used unit
minValue	f64	discarded if >= maxValue
maxValue	f64	discarded if <= minValue

Named by CustomTypeData.

QuantityTypeSpecV4 STRUCTURE

Name	Type	Description
numericType	NumericType	type used to store the value

Name	Type	Description
`unit`	UnitInfo	used unit
`minValue`	f64	discarded if >= maxValue
`maxValue`	f64	discarded if <= minValue

Named by CustomTypeDataV4.

`QuantityTypeSpecV5` STRUCTURE

Name	Type	Description
`numericType`	NumericType	type used to store the value
`unit`	UnitInfo	used unit
`minValue`	f64	discarded if >= maxValue
`maxValue`	f64	discarded if <= minValue
`hash`	u32	unique hash

Named by CustomTypeDataV5.

`QueueConfig` STRUCTURE

Name	Type	Description
`evictionPolicy`	QueueEvictionPolicy	what to do when the queue is full
`maxSize`	u64	0 means unbounded

Named by ComponentConfig.

`SenData` STRUCTURE

Information about Sen

Name	Type	Description
`version`	string	the Sen version
`compiler`	string	the compiler used to build Sen
`debugMode`	bool	true if it was build in debug mode
`buildTime`	string	the commit's timestamp, not the compiler's clock
`wordSize`	WordSize	architecture
`gitRef`	string	git ref
`gitHash`	string	git hash
`gitStatus`	GitStatus	status of the branch when build
`kernelParams`	KernelParams	Sen kernel parameters
`kernelProtocol`	u32	version of the kernel protocol
`transportProtocol`	u32	version of the transport protocol (if present)
`loadedComponents`	LoadedComponentList	components to load
`builtComponents`	BuiltComponentList	components to build

Named by ErrorReport.

`SequenceTypeSpec` STRUCTURE

spec of a sequence type

Name	Type	Description
`elementType`	string	qualified type name for stored values
`maxSize`	u64	discarded when 0
`fixedSize`	bool	

Named by CustomTypeData.

SequenceTypeSpecV4 STRUCTURE

Name	Type	Description
elementType	string	qualified type name for stored values
maxSize	u64	discarded when 0

Named by CustomTypeDataV4.

SequenceTypeSpecV5 STRUCTURE

Name	Type	Description
elementType	string	qualified type name for stored values
maxSize	u64	discarded when 0
fixedSize	bool	
hash	u32	unique hash

Named by CustomTypeDataV5.

SignalData STRUCTURE

Information about an unhandled signal

Name	Type	Description
signalNumber	i32	signal number
signalName	string	human-readable name

Named by ErrorData.

StructTypeFieldSpec STRUCTURE

a field of a struct

Name	Type	Description
name	string	field name
description	string	documentation
type	string	qualified type name held by this field

Named by StructTypeFieldSpecList.

StructTypeFieldSpecV4 STRUCTURE

Name	Type	Description
name	string	field name
description	string	documentation
type	string	qualified type name held by this field

Named by StructTypeFieldSpecListV4.

StructTypeFieldSpecV5 STRUCTURE

Name	Type	Description
name	string	field name
description	string	documentation
type	string	qualified type name held by this field

Name	Type	Description
hash	u32	unique hash

Named by StructTypeFieldSpecListV5.

StructTypeSpec STRUCTURE

spec of an struct type

Name	Type	Description
fields	StructTypeFieldSpecList	fields
parent	string	qualified type name the parent struct, empty means none

Named by CustomTypeData.

StructTypeSpecV4 STRUCTURE

Name	Type	Description
fields	StructTypeFieldSpecListV4	fields
parent	string	qualified type name the parent struct, empty means none

Named by CustomTypeDataV4.

StructTypeSpecV5 STRUCTURE

Name	Type	Description
fields	StructTypeFieldSpecListV5	fields
parent	string	qualified type name the parent struct, empty means none
hash	u32	unique hash

Named by CustomTypeDataV5.

SystemSleep STRUCTURE

Use the native system sleep

Named by SleepPolicy.

UncaughtException STRUCTURE

Information about an unhandled exception

Name	Type	Description
exceptionKind	ExceptionKind	kind of exception
message	string	message it provides (if any)

Named by ErrorData.

UnitInfo STRUCTURE

Describes a unit

Name	Type	Description
name	string	
abbreviation	string	
category	UnitCat	

Named by QuantityTypeSpec, QuantityTypeSpecV4, QuantityTypeSpecV5, UnitList.

VariantTypeFieldSpec STRUCTURE

a field of a variant

Name	Type	Description
key	u32	key/index of this type within the variant
description	string	documentation
type	string	qualified type name held by this field

Named by VariantTypeFieldSpecList.

VariantTypeFieldSpecV4 STRUCTURE

Name	Type	Description
key	u32	key/index of this type within the variant
description	string	documentation
type	string	qualified type name held by this field

Named by VariantTypeFieldSpecListV4.

VariantTypeFieldSpecV5 STRUCTURE

Name	Type	Description
key	u32	key/index of this type within the variant
description	string	documentation
type	string	qualified type name held by this field
hash	u32	unique hash

Named by VariantTypeFieldSpecListV5.

VariantTypeSpec STRUCTURE

spec of an struct type

Name	Type	Description
fields	VariantTypeFieldSpecList	

Named by CustomTypeData.

VariantTypeSpecV4 STRUCTURE

Name	Type	Description
fields	VariantTypeFieldSpecListV4	

Named by CustomTypeDataV4.

VariantTypeSpecV5 STRUCTURE

Name	Type	Description
fields	VariantTypeFieldSpecListV5	
hash	u32	

Named by CustomTypeDataV5.

Enumerations

BasicType	built-in others	64
CompatibilityMode	What to do when a type published by another kernel does not match the local one	64
ComponentState	State of a kernel component	64
CpuArch	Type of CPU	65
ErrorCategory	Category of a problem during component execution	65
ExceptionKind	Types of exceptions that can occur.	65
GitStatus	Status of git	65
IntegralType	built-in integrals	65
MethodConstnessSpec	method constness	66
NetworkFootprintBusSource	Bus source	66
NetworkFootprintPortKind	Type of socket opened by the process	66
NetworkFootprintPortMode	Port allocation policy	66
OsKind	Type of operating system	66
Priority	Thread execution priorities	67
PropertyCategorySpec	how a property is seen by others	67
PropertyRelationSpec	method property relation	67
QueueEvictionPolicy	Component queue eviction policy	67
RealType	built-in reals	67
RunMode	Run modes for the kernel	67
ThreadCreateErr	What can go wrong when creating a thread	68
TransportModeSpec	how to transport information	68
UnitCat	Type of measurement	68
WordSize	Native processor word size	68

BasicType ENUMERATION

built-in others

Held as u8.

booleanType	0
stringType	1
durationType	2
timestampType	3

Named by BuiltInType.

CompatibilityMode ENUMERATION

What to do when a type published by another kernel does not match the local one

Held as u8.

relaxed	0
strict	1
disabled	2

Named by KernelParams.

ComponentState ENUMERATION

State of a kernel component

Held as u8.

unloaded	0
preloaded	1
loading	2
loaded	3
initializing	4
initialized	5
running	6
stopping	7
stopped	8
unloading	9
error	10

CpuArch ENUMERATION

Type of CPU

Held as u8.

x86	0
x64	1
arm2	2
arm3	3
arm4T	4
arm5	5
arm6T2	6
arm6	7
arm7	8
arm7a	9
arm7r	10
arm7s	11
arm64	12
mips	13
superH	14
ppc	15
ppc64	16
sparc	17
m68k	18
otherArch	19

Named by ProcessInfo.

ErrorCategory ENUMERATION

Category of a problem during component execution

Held as u8.

runtimeError	0
logicError	1
expectationsNotMet	2
ioError	3
other	4

Named by ExecError.

ExceptionKind ENUMERATION

Types of exceptions that can occur.

Held as u8.

runtime	0
logic	1
standard	2
unknown	3

Named by UncaughtException.

GitStatus ENUMERATION

Status of git

Held as u8.

clean	0
modified	1
unknown	2

Named by BuildInfo, SenData.

IntegralType ENUMERATION

built-in integrals

Held as u8.

uint8Type	0
int16Type	1
uint16Type	2
int32Type	3
uint32Type	4
int64Type	5
uint64Type	6

Named by EnumTypeSpec, EnumTypeSpecV4, EnumTypeSpecV5, NumericType.

MethodConstnessSpec ENUMERATION

method constness

Held as u8.

constant	0
nonConstant	1

Named by MethodSpec, MethodSpecV4, MethodSpecV5.

NetworkFootprintBusSource ENUMERATION

Bus source

Held as u8.

configured	0
supplied	1
runtime	2

Named by NetworkFootprintBus.

NetworkFootprintPortKind ENUMERATION

Type of socket opened by the process

Held as u8.

tcpAcceptor	0
udpUnicast	1
tcpSource	2

Named by NetworkFootprintPort.

NetworkFootprintPortMode ENUMERATION

Port allocation policy

Held as u8.

ephemeral	0
probe	1
pinned	2

Named by NetworkFootprintPort.

OsKind ENUMERATION

Type of operating system

Held as u8.

windowsOs	0
linuxOs	1
androidOs	2
appleOs	3
unixOs	4
posixOs	5
otherOs	6

Named by ProcessInfo.

Priority ENUMERATION

Thread execution priorities

Held as u32.

lowest	0
nominalMin	1
nominalMax	2
highest	3

Named by ComponentConfig.

PropertyCategorySpec ENUMERATION

how a property is seen by others

Held as u8.

staticRW	0
staticRO	1
dynamicRW	2
dynamicRO	3

Named by PropertySpec, PropertySpecV4, PropertySpecV5.

PropertyRelationSpec ENUMERATION

method property relation

Held as u8.

nonPropertyRelated	0
propertyGetter	1
propertySetter	2

Named by MethodSpec.

QueueEvictionPolicy ENUMERATION

Component queue eviction policy

Held as u32.

dropOldest	0
dropNewest	1

Named by QueueConfig.

RealType ENUMERATION

built-in reals

Held as u8.

float32Type	0
float64Type	1

Named by NumericType.

RunMode ENUMERATION

Run modes for the kernel

Held as u8.

realTime	0
virtualTime	1
virtualTimeRunning	2
startAndStop	3

Named by KernelParams.

ThreadCreateErr ENUMERATION

What can go wrong when creating a thread

Held as u32.

schedulerAlreadyStarted	0
invalidStackSize	1
invalidThreadFunction	2
invalidThreadFunctionArgument	3
invalidAffinity	4
tooManyThreads	5
internalOsError	6

TransportModeSpec ENUMERATION

how to transport information

Held as u8.

unicast	0
multicast	1
confirmed	2

Named by EventSpec, EventSpecV4, EventSpecV5, MethodSpec, MethodSpecV4, MethodSpecV5, PropertySpec, PropertySpecV4, PropertySpecV5.

UnitCat ENUMERATION

Type of measurement

Held as u8.

length	0
mass	1
time	2
angle	3
temperature	4
frequency	5
velocity	6
angularVelocity	7
acceleration	8
angularAcceleration	9
density	10
pressure	11
area	12
force	13
torque	14

Named by UnitInfo.

WordSize ENUMERATION

Native processor word size

Held as u32.

bits32	0
bits64	1

Named by BuildInfo, SenData.

Variant records

BuiltInType	all built-in types	69
CustomTypeData	all custom types	69
CustomTypeDataV4		69
CustomTypeDataV5		69
NetworkFootprintPortValue	Known port number or range	69
NumericType	all built-in numeric types	70
OpState	The status of an operation	70
SleepPolicy	Component sleep policy	70

BuiltInType VARIANT

all built-in types

Type	Description
NumericType	
BasicType	

CustomTypeData VARIANT

all custom types

Type	Description
EnumTypeSpec	
QuantityTypeSpec	
SequenceTypeSpec	
StructTypeSpec	
VariantTypeSpec	
AliasTypeSpec	
OptionalTypeSpec	
ClassTypeSpec	

Named by CustomTypeSpec.

CustomTypeDataV4 VARIANT

Type	Description
EnumTypeSpecV4	
QuantityTypeSpecV4	
SequenceTypeSpecV4	
StructTypeSpecV4	
VariantTypeSpecV4	
AliasTypeSpecV4	
OptionalTypeSpecV4	
ClassTypeSpecV4	

Named by CustomTypeSpecV4.

CustomTypeDataV5 VARIANT

Type	Description
EnumTypeSpecV5	
QuantityTypeSpecV5	
SequenceTypeSpecV5	
StructTypeSpecV5	
VariantTypeSpecV5	
AliasTypeSpecV5	
OptionalTypeSpecV5	
ClassTypeSpecV5	

Named by CustomTypeSpecV5.

NetworkFootprintPortValue VARIANT

Known port number or range

Type	Description
u16	
NetworkFootprintPort	
Range	

Named by NetworkFootprintPort.

NumericType VARIANT

all built-in numeric types

Type	Description
IntegralType	
RealType	

Named by BuiltInType, QuantityTypeSpec, QuantityTypeSpecV4, QuantityTypeSpecV5.

OpState VARIANT

The status of an operation

Type	Description
OpFinished	done
OpNotFinished	not done

SleepPolicy VARIANT

Component sleep policy

Type	Description
PrecisionSleep	
SystemSleep	

Named by ComponentConfig, KernelParams.

Arrays

ArgSpecList	list of argument specs	71
ArgSpecListV4		71
ArgSpecListV5		71
Buffer	A general-purpose unbounded buffer	71
BuiltComponentList		71
CustomTypeSpecList	list of custom types	71
CustomTypeSpecListV4		71
CustomTypeSpecListV5		71
EnumeratorSpecList	list of enumerators	72
EnumeratorSpecListV4		72
EnumeratorSpecListV5		72
EnvironmentVarList		72
EventSpecList	list of event specs	72
EventSpecListV4		72
EventSpecListV5		72
LoadedComponentList		72
MethodSpecList	list of method specs	72
MethodSpecListV4		73
MethodSpecListV5		73
NetworkFootprintAddressRangeList		73
NetworkFootprintBusList	Buses included in a network footprint	73
NetworkFootprintPortList	Ports used by the process	73
NetworkFootprintPortRangeList		73
NetworkFootprintSelfCollisionList	Multicast address conflicts found in the reported buses	73
Processes	Unbounded sequence of ProcessInfo	73
PropertySpecList	list of property specs	73
PropertySpecListV4		74

PropertySpecListV5		74
StringList	Unbounded sequence of strings for general purpose	74
StructTypeFieldSpecList	list of struct fields	74
StructTypeFieldSpecListV4		74
StructTypeFieldSpecListV5		74
U32List		74
UnitList	Unbounded sequence of unit information structs	74
VariantTypeFieldSpecList	list of variant fields	74
VariantTypeFieldSpecListV4		75
VariantTypeFieldSpecListV5		75

ArgSpecList SEQUENCE

list of argument specs

```
sequence<ArgSpec> ArgSpecList;
```

Named by EventSpec, MethodSpec.

ArgSpecListV4 SEQUENCE

```
sequence<ArgSpecV4> ArgSpecListV4;
```

Named by EventSpecV4, MethodSpecV4.

ArgSpecListV5 SEQUENCE

```
sequence<ArgSpecV5> ArgSpecListV5;
```

Named by EventSpecV5, MethodSpecV5.

Buffer SEQUENCE

A general-purpose unbounded buffer

```
sequence<u8> Buffer;
```

Named by sen.components.jsonrpc.StaticFile.

BuiltComponentList SEQUENCE

```
sequence<BuiltComponentParams> BuiltComponentList;
```

Named by SenData.

CustomTypeSpecList SEQUENCE

list of custom types

```
sequence<CustomTypeSpec> CustomTypeSpecList;
```

Named by sen.components.jsonrpc.JsonRpcServer.

CustomTypeSpecListV4 SEQUENCE

```
sequence<CustomTypeSpecV4> CustomTypeSpecListV4;
```

CustomTypeSpecListV5 SEQUENCE

```
sequence<CustomTypeSpecV5> CustomTypeSpecListV5;
```

EnumeratorSpecList SEQUENCE

list of enumerators

```
sequence<EnumeratorSpec> EnumeratorSpecList;
```

Named by EnumTypeSpec.

EnumeratorSpecListV4 SEQUENCE

```
sequence<EnumeratorSpecV4> EnumeratorSpecListV4;
```

Named by EnumTypeSpecV4.

EnumeratorSpecListV5 SEQUENCE

```
sequence<EnumeratorSpecV5> EnumeratorSpecListV5;
```

Named by EnumTypeSpecV5.

EnvironmentVarList SEQUENCE

```
sequence<EnvVar> EnvironmentVarList;
```

Named by ProcessData.

EventSpecList SEQUENCE

list of event specs

```
sequence<EventSpec> EventSpecList;
```

Named by ClassTypeSpec.

EventSpecListV4 SEQUENCE

```
sequence<EventSpecV4> EventSpecListV4;
```

Named by ClassTypeSpecV4.

EventSpecListV5 SEQUENCE

```
sequence<EventSpecV5> EventSpecListV5;
```

Named by ClassTypeSpecV5.

LoadedComponentList SEQUENCE

```
sequence<LoadedComponentParams> LoadedComponentList;
```

Named by SenData.

MethodSpecList SEQUENCE

list of method specs

```
sequence<MethodSpec> MethodSpecList;
```

Named by ClassTypeSpec.

MethodSpecListV4 SEQUENCE

```
sequence<MethodSpecV4> MethodSpecListV4;
```

Named by ClassTypeSpecV4.

MethodSpecListV5 SEQUENCE

```
sequence<MethodSpecV5> MethodSpecListV5;
```

Named by ClassTypeSpecV5.

NetworkFootprintAddressRangeList SEQUENCE

```
sequence<NetworkFootprintAddressRange> NetworkFootprintAddressRangeList;
```

Named by NetworkFootprintMulticast.

NetworkFootprintBusList SEQUENCE

Buses included in a network footprint

```
sequence<NetworkFootprintBus> NetworkFootprintBusList;
```

Named by NetworkFootprintMulticast.

NetworkFootprintPortList SEQUENCE

Ports used by the process

```
sequence<NetworkFootprintPort> NetworkFootprintPortList;
```

Named by NetworkFootprint.

NetworkFootprintPortRangeList SEQUENCE

```
sequence<NetworkFootprintPortRange> NetworkFootprintPortRangeList;
```

Named by NetworkFootprintPortExclusions.

NetworkFootprintSelfCollisionList SEQUENCE

Multicast address conflicts found in the reported buses

```
sequence<NetworkFootprintSelfCollision> NetworkFootprintSelfCollisionList;
```

Named by NetworkFootprintCollision.

Processes SEQUENCE

Unbounded sequence of ProcessInfo

```
sequence<ProcessInfo> Processes;
```

PropertySpecList SEQUENCE

list of property specs

```
sequence<PropertySpec> PropertySpecList;
```

Named by ClassTypeSpec.

PropertySpecListV4 SEQUENCE

```
sequence<PropertySpecV4> PropertySpecListV4;
```

Named by ClassTypeSpecV4.

PropertySpecListV5 SEQUENCE

```
sequence<PropertySpecV5> PropertySpecListV5;
```

Named by ClassTypeSpecV5.

StringList SEQUENCE

Unbounded sequence of strings for general purpose

```
sequence<string> StringList;
```

Named by sen.components.jsonrpc.JsonRpcServer, sen.components.jsonrpc.NamedSelection, sen.components.jsonrpc.SessionInfo, BuiltComponentParams, ClassTypeSpec, ClassTypeSpecV4, ClassTypeSpecV5, ErrorData, KernelApi, ProcessData, PropertySpec, PropertySpecV4, PropertySpecV5.

StructTypeFieldSpecList SEQUENCE

list of struct fields

```
sequence<StructTypeFieldSpec> StructTypeFieldSpecList;
```

Named by StructTypeSpec.

StructTypeFieldSpecListV4 SEQUENCE

```
sequence<StructTypeFieldSpecV4> StructTypeFieldSpecListV4;
```

Named by StructTypeSpecV4.

StructTypeFieldSpecListV5 SEQUENCE

```
sequence<StructTypeFieldSpecV5> StructTypeFieldSpecListV5;
```

Named by StructTypeSpecV5.

U32List SEQUENCE

```
sequence<u32> U32List;
```

UnitList SEQUENCE

Unbounded sequence of unit information structs

```
sequence<UnitInfo> UnitList;
```

Named by KernelApi.

VariantTypeFieldSpecList SEQUENCE

list of variant fields

```
sequence<VariantTypeFieldSpec> VariantTypeFieldSpecList;
```

Named by VariantTypeSpec.

VariantTypeFieldSpecListV4 SEQUENCE

```
sequence<VariantTypeFieldSpecV4> VariantTypeFieldSpecListV4;
```

Named by VariantTypeSpecV4.

VariantTypeFieldSpecListV5 SEQUENCE

```
sequence<VariantTypeFieldSpecV5> VariantTypeFieldSpecListV5;
```

Named by VariantTypeSpecV5.

Optionals

MaybeException		75
MaybeF64	optional value for a f64	75
MaybeNetworkFootprintMulticast		75
MaybeNetworkFootprintPortValue	The value is not present when the port number is not known	75
MaybeSignal		75
MaybeStacktrace		75
MaybeTransportProtocol		75
MaybeU64	optional value for a u64	76

MaybeException OPTIONAL

```
optional<UncaughtException> MaybeException;
```

MaybeF64 OPTIONAL

optional value for a f64

```
optional<f64> MaybeF64;
```

MaybeNetworkFootprintMulticast OPTIONAL

```
optional<NetworkFootprintMulticast> MaybeNetworkFootprintMulticast;
```

MaybeNetworkFootprintPortValue OPTIONAL

The value is not present when the port number is not known

```
optional<NetworkFootprintPortValue> MaybeNetworkFootprintPortValue;
```

MaybeSignal OPTIONAL

```
optional<SignalData> MaybeSignal;
```

MaybeStacktrace OPTIONAL

```
optional<StringList> MaybeStacktrace;
```

MaybeTransportProtocol OPTIONAL

```
optional<u32> MaybeTransportProtocol;
```

MaybeU64 OPTIONAL

optional value for a u64

```
optional<u64> MaybeU64;
```

log

16 types.

Fixed records

BasicFile	Basic file sink	77
ColorStderr	Colored stderr sink	77
ColorStdout	Colored stdout sink	77
Config	Overall component configuration	77
LoggerConfig	Configuration used for a given spdlog logger.	77
Null	Single-threaded null sink	78
RotatingFile	Rotating file sink	78
SinkConfig	Configuration used for a given spdlog Sink.	78
Stderr	stderr sink	78
Stdout	stdout sink	78
Syslog	Syslog sink (only in linux)	78

BasicFile STRUCTURE

Basic file sink

Name	Type	Description
`fileName`	string	file to log to
`truncate`	bool	defaults to false
`createParentDir`	bool	true if we should create the parent dir first

Named by SinkType.

ColorStderr STRUCTURE

Colored stderr sink

Named by SinkType.

ColorStdout STRUCTURE

Colored stdout sink

Named by SinkType.

Config STRUCTURE

Overall component configuration

Name	Type	Description
`pattern`	string	default format (empty means default)
`level`	LogLevel	default global level for all
`sinks`	SinkConfigList	sinks to configure
`loggers`	LoggerConfigList	loggers to configure
`backtrace`	bool	log backtrace is printed on failure

Named by sen.kernel.KernelParams.

LoggerConfig STRUCTURE

Configuration used for a given spdlog logger.

Name	Type	Description
`name`	string	name of the logger
`sinks`	SinkNameList	name of the sinks to connect the logger to
`level`	LogLevel	default log level for this logger

Name	Type	Description
`pattern`	string	Formatting for the sinks in this logger. Does nothing if empty. Note that this replaces the format of the associated sinks, and this could affect other loggers using those sinks. The config is applied following the order of the Config.loggers field.

Named by LoggerConfigList.

`Null` STRUCTURE

Single-threaded null sink

Named by SinkType.

`RotatingFile` STRUCTURE

Rotating file sink

Name	Type	Description
`baseFileName`	string	
`maxSize`	u32	0 means use defaults
`maxFiles`	u32	0 means use defaults

Named by SinkType.

`SinkConfig` STRUCTURE

Configuration used for a given spdlog Sink.

Name	Type	Description
`name`	string	name of the sink
`singleThreaded`	bool	if true, single-threaded (defaults to false)
`pattern`	string	the pattern used for the formatting (empty means default).
`level`	LogLevel	default log level for this sink
`config`	SinkType	the type-specific configuration parameters

Named by SinkConfigList.

`Stderr` STRUCTURE

stderr sink

Named by SinkType.

`Stdout` STRUCTURE

stdout sink

Named by SinkType.

`Syslog` STRUCTURE

Syslog sink (only in linux)

Name	Type	Description
`identity`	string	
`option`	u32	
`enableFormatting`	bool	

Named by SinkType.

Enumerations

LogLevel Severity/importance of a log message. 79

LogLevel ENUMERATION

Severity/importance of a log message.

Held as u8.

warn	0
err	1
critical	2
trace	3
debug	4
info	5
off	6

Named by sen.components.logmaster.LogMaster, sen.components.logmaster.Logger, Config, LoggerConfig, SinkConfig.

Variant records

SinkType The type-specific configuration of the used spdlog Sink. 79

SinkType VARIANT

The type-specific configuration of the used spdlog Sink.

Type	Description
ColorStdout	
ColorStderr	
Stdout	
Stderr	
BasicFile	
RotatingFile	
Null	
Syslog	

Named by SinkConfig.

Arrays

LoggerConfigList 79
SinkConfigList 79
SinkNameList 79

LoggerConfigList SEQUENCE

```
sequence<LoggerConfig> LoggerConfigList;
```

Named by Config.

SinkConfigList SEQUENCE

```
sequence<SinkConfig> SinkConfigList;
```

Named by Config.

SinkNameList SEQUENCE

```
sequence<string> SinkNameList;
```

Named by LoggerConfig.

Built-in types

The types the language provides. Every one is written the same way on the wire wherever it appears.

Type	Meaning
`bool`	classic boolean
`f32`	32 bit floating point number
`f64`	64 bit floating point number
`i32`	32 bit signed integer
`sen.Duration`	a time duration
`sen.TimeStamp`	a point in time
`string`	unbounded string
`u16`	16 bit unsigned integer
`u32`	32 bit unsigned integer
`u64`	64 bit unsigned integer
`u8`	8 bit unsigned integer

Index

components.ether.BusConfig 7
components.ether.BusJoined 7
components.ether.BusLeft 7
components.ether.ByteRange 8
components.ether.Configuration 8
components.ether.ControlMessage 11
components.ether.DiscoveryConfig 11
components.ether.DiscoveryHubAddress 8
components.ether.Endpoint 8
components.ether.EnpointList 11
components.ether.Ephemeral 8
components.ether.Hello 8
components.ether.MaybeDeviceName 12
components.ether.MaybeDiscoveryHub Port 12
components.ether.MaybePortConfig 12
components.ether.MulticastAddress Exclusions 12
components.ether.MulticastAddress Range 9
components.ether.MulticastDiscovery 9
components.ether.MulticastRange 12
components.ether.PinnedPort 9
components.ether.PortBinding 11
components.ether.PortConfig 9
components.ether.PortExclusions 12
components.ether.PortRange 9
components.ether.ProbePortRange 10
components.ether.ProtocolVersion 10
components.ether.QueueConfig 10
components.ether.QueueEvictionPolicy 11
components.ether.Ready 10
components.ether.SessionPresenceBeam 10
components.ether.TcpDiscovery 10
components.explorer.Configuration 13
components.influx.Configuration 14
components.influx.Protocol 14
components.influx.SelectionList 14
components.jsonrpc.AddedObjectEntry 19
components.jsonrpc.AddedObjectList 23
components.jsonrpc.Configuration 20
components.jsonrpc.ConnectionLimits 20
components.jsonrpc.Identity 20
components.jsonrpc.JsonRpcServer 15
components.jsonrpc.MaybeConnection Limits 24
components.jsonrpc.MaybeControlBus Name 24
components.jsonrpc.MaybeFlag 24
components.jsonrpc.MaybeHigh BackpressureBytes 24
components.jsonrpc.MaybeIdleTimeout Seconds 25
components.jsonrpc.MaybeMax BackpressureBytes 25
components.jsonrpc.MaybeMaxPayload Bytes 25
components.jsonrpc.MaybeMember Selector 25
components.jsonrpc.MaybeRateHz 25
components.jsonrpc.MaybeStringList 25
components.jsonrpc.MaybeSubscribe Block 25
components.jsonrpc.MaybeTlsConfig 25
components.jsonrpc.MaybeUpdateFreqHz 25
components.jsonrpc.MemberSelector 23
components.jsonrpc.NamedSelection 20
components.jsonrpc.ObjectInfo 20
components.jsonrpc.ObjectInfos 23
components.jsonrpc.ObjectState 21
components.jsonrpc.ObjectStateList 23
components.jsonrpc.PropertyError 21
components.jsonrpc.PropertyErrorList 23
components.jsonrpc.PropertyValueList 24
components.jsonrpc.PropertyValuePair 21
components.jsonrpc.RegisteredBundle Info 21
components.jsonrpc.RegisteredBundle InfoList 24
components.jsonrpc.SessionInfo 21
components.jsonrpc.SessionInfoList 24
components.jsonrpc.StaticBundle 22
components.jsonrpc.StaticFile 22
components.jsonrpc.StaticFileList 24
components.jsonrpc.StaticFileServer 18
components.jsonrpc.SubscribeBlock 22
components.jsonrpc.TlsConfig 22
components.jsonrpc.TypeLookupResult 22
components.jsonrpc.WildcardSelection 23
components.logmaster.Config 26
components.logmaster.LogMaster 26
components.logmaster.Logger 26
components.py.Configuration 27
components.py.PythonInterpreter 27
components.py.StringList 27
components.recorder.Configuration 28
components.recorder.Recorder 28
components.recorder.RecorderState 28
components.recorder.RecordingSettings 28
components.recorder.RecordingSettings List 29
components.recorder.SelectionList 29
components.replayer.Configuration 30
components.replayer.Replay 30
components.replayer.ReplayStatus 31
components.replayer.Replayer 30
components.rest.Argument 32
components.rest.Arguments 36
components.rest.Bus 32
components.rest.BusNames 36
components.rest.BusSummary 32
components.rest.Buses 36
components.rest.ClientAuth 32
components.rest.Configuration 33
components.rest.Error 33
components.rest.Events 36
components.rest.HttpMethod 35
components.rest.Interest 33
components.rest.InterestSummary 33
components.rest.InterestsSummary 36
components.rest.InvokeStatus 35
components.rest.Link 33
components.rest.Links 36
components.rest.Notification 33
components.rest.NotificationType 35
components.rest.Object 33
components.rest.ObjectEvent 34
components.rest.ObjectMethod 34
components.rest.ObjectSummary 34
components.rest.ObjectsSummary 36
components.rest.Properties 37
components.rest.RelType 35
components.rest.Session 34
components.rest.SessionSummary 34
components.rest.Sessions 37
components.rest.Status 36
components.rest.SubscriptionOptions 34
components.rest.Subscriptions 34
components.rest.Success 35
components.rest.ThreadPoolSize 37
components.rest.UpdateFrequency 37
components.rest.UpdateTime 37
components.rest.Version 35
components.shell.BufferStyle 41
components.shell.CPrint 38
components.shell.ClearCurrentLine 39
components.shell.ClearRemainingCurrent Line 39
components.shell.ClearScreen 39
components.shell.Configuration 39
components.shell.HideCursor 39
components.shell.ListStyle 41
components.shell.MoveCursorAllLeft 39
components.shell.MoveCursorDown 39
components.shell.MoveCursorLeft 39
components.shell.MoveCursorRight 39
components.shell.MoveCursorUp 40
components.shell.NewLine 40
components.shell.Print 40
components.shell.Query 40
components.shell.QueryList 42
components.shell.RestoreCursorPosition 40
components.shell.SaveCursorPosition 40
components.shell.SetBgColor 40
components.shell.SetFgColor 40
components.shell.SetWindowTitle 40
components.shell.Shell 38
components.shell.ShowCursor 41
components.shell.SourcesList 42
components.shell.TerminalCmd 41
components.shell.TimeStyle 41
components.term.Configuration 43
components.term.NameList 44
components.term.QueryDef 43
components.term.QueryList 44
components.term.SourcesList 44
components.term.Term 43
components.term.ThemeStyle 43
components.term.TimeStyle 44
db.OutSettings 45
db.OutStats 45
db.Summary 45
kernel.AliasTypeSpec 48
kernel.AliasTypeSpecV4 48
kernel.AliasTypeSpecV5 48
kernel.ArgSpec 48
kernel.ArgSpecList 71
kernel.ArgSpecListV4 71
kernel.ArgSpecListV5 71
kernel.ArgSpecV4 48
kernel.ArgSpecV5 49
kernel.BasicType 64
kernel.Buffer 71
kernel.BuildInfo 49
kernel.BuiltComponentList 71
kernel.BuiltComponentParams 49
kernel.BuiltInType 69
kernel.BusAddress 49
kernel.ClassTypeSpec 49
kernel.ClassTypeSpecV4 50
kernel.ClassTypeSpecV5 50
kernel.CompatibilityMode 64
kernel.ComponentConfig 50
kernel.ComponentInfo 50
kernel.ComponentState 64
kernel.CpuArch 65
kernel.CustomTypeData 69
kernel.CustomTypeDataV4 69
kernel.CustomTypeDataV5 69
kernel.CustomTypeSpec 51
kernel.CustomTypeSpecList 71
kernel.CustomTypeSpecListV4 71
kernel.CustomTypeSpecListV5 71
kernel.CustomTypeSpecV4 51
kernel.CustomTypeSpecV5 51
kernel.EnumTypeSpec 51
kernel.EnumTypeSpecV4 51
kernel.EnumTypeSpecV5 52
kernel.EnumeratorSpec 52
kernel.EnumeratorSpecList 72
kernel.EnumeratorSpecListV4 72
kernel.EnumeratorSpecListV5 72
kernel.EnumeratorSpecV4 52
kernel.EnumeratorSpecV5 52
kernel.EnvVar 52
kernel.EnvironmentVarList 72
kernel.ErrorCategory 65
kernel.ErrorData 52
kernel.ErrorReport 53
kernel.EventSpec 53
kernel.EventSpecList 72
kernel.EventSpecListV4 72
kernel.EventSpecListV5 72
kernel.EventSpecV4 53
kernel.EventSpecV5 53
kernel.ExceptionKind 65
kernel.ExecError 53
kernel.GitStatus 65
kernel.IntegralType 65
kernel.KernelApi 46
kernel.KernelParams 53
kernel.LoadedComponentList 72
kernel.LoadedComponentParams 54
kernel.MaybeException 75
kernel.MaybeF64 75
kernel.MaybeNetworkFootprintMulticast 75
kernel.MaybeNetworkFootprintPortValue 75
kernel.MaybeSignal 75
kernel.MaybeStacktrace 75
kernel.MaybeTransportProtocol 75
kernel.MaybeU64 76
kernel.MethodConstnessSpec 66
kernel.MethodSpec 54
kernel.MethodSpecList 72
kernel.MethodSpecListV4 73
kernel.MethodSpecListV5 73
kernel.MethodSpecV4 54
kernel.MethodSpecV5 55
kernel.NetworkFootprint 55
kernel.NetworkFootprintAddressRange 55
kernel.NetworkFootprintAddressRange List 73
kernel.NetworkFootprintBus 55
kernel.NetworkFootprintBusIdentity 56
kernel.NetworkFootprintBusList 73
kernel.NetworkFootprintBusSource 66
kernel.NetworkFootprintCollision 56
kernel.NetworkFootprintMulticast 56
kernel.NetworkFootprintPort 56
kernel.NetworkFootprintPortExclusions 57
kernel.NetworkFootprintPortKind 66
kernel.NetworkFootprintPortList 73
kernel.NetworkFootprintPortMode 66
kernel.NetworkFootprintPortRange 57
kernel.NetworkFootprintPortRangeList 73
kernel.NetworkFootprintPortValue 69
kernel.NetworkFootprintSelfCollision 57

kernel.NetworkFootprintSelfCollisionList 73
kernel.NumericType 70
kernel.OpFinished 57
kernel.OpNotFinished 57
kernel.OpState 70
kernel.OptionalTypeSpec 57
kernel.OptionalTypeSpecV4 58
kernel.OptionalTypeSpecV5 58
kernel.OsKind 66
kernel.PrecisionSleep 58
kernel.Priority 67
kernel.ProcessData 58
kernel.ProcessInfo 58
kernel.Processes 73
kernel.PropertyCategorySpec 67
kernel.PropertyRelationSpec 67
kernel.PropertySpec 58
kernel.PropertySpecList 73
kernel.PropertySpecListV4 74
kernel.PropertySpecListV5 74
kernel.PropertySpecV4 59
kernel.PropertySpecV5 59
kernel.QuantityTypeSpec 59
kernel.QuantityTypeSpecV4 59
kernel.QuantityTypeSpecV5 60
kernel.QueueConfig 60
kernel.QueueEvictionPolicy 67
kernel.RealType 67
kernel.RunMode 67
kernel.SenData 60
kernel.SequenceTypeSpec 60
kernel.SequenceTypeSpecV4 61
kernel.SequenceTypeSpecV5 61
kernel.SignalData 61
kernel.SleepPolicy 70
kernel.StringList 74
kernel.StructTypeFieldSpec 61
kernel.StructTypeFieldSpecList 74
kernel.StructTypeFieldSpecListV4 74
kernel.StructTypeFieldSpecListV5 74
kernel.StructTypeFieldSpecV4 61
kernel.StructTypeFieldSpecV5 61
kernel.StructTypeSpec 62
kernel.StructTypeSpecV4 62
kernel.StructTypeSpecV5 62
kernel.SystemSleep 62
kernel.ThreadCreateErr 68
kernel.TransportModeSpec 68
kernel.U32List 74
kernel.UncaughtException 62
kernel.UnitCat 68
kernel.UnitInfo 62
kernel.UnitList 74
kernel.VariantTypeFieldSpec 63
kernel.VariantTypeFieldSpecList 74
kernel.VariantTypeFieldSpecListV4 75
kernel.VariantTypeFieldSpecListV5 75
kernel.VariantTypeFieldSpecV4 63
kernel.VariantTypeFieldSpecV5 63
kernel.VariantTypeSpec 63
kernel.VariantTypeSpecV4 63
kernel.VariantTypeSpecV5 63
kernel.VirtualClock 46
kernel.VirtualKernelClock 46
kernel.VirtualMasterClock 46
kernel.WordSize 68
kernel.log.BasicFile 77
kernel.log.ColorStderr 77
kernel.log.ColorStdout 77
kernel.log.Config 77
kernel.log.LogLevel 79
kernel.log.LoggerConfig 77
kernel.log.LoggerConfigList 79
kernel.log.Null 78
kernel.log.RotatingFile 78
kernel.log.SinkConfig 78
kernel.log.SinkConfigList 79
kernel.log.SinkNameList 79
kernel.log.SinkType 79
kernel.log.Stderr 78
kernel.log.Stdout 78
kernel.log.Syslog 78