Weight-Native Computing Architecture: Design Report

Formal record of a voice design discussion

Date: 2026-10-16

Authors: Shivam Agarwal and Grok (Leo)

Context: Voice design discussion on 2026-10-16

Language: ASD-STE100-style controlled technical English (about 80% stringency)

भार-आधारित कंप्यूटिंग संरचना: डिज़ाइन रिपोर्ट

भार-आधारित ऑपरेटिंग सिस्टम पर चर्चा का औपचारिक अभिलेख

दिनांक: 2026-10-16

लेखक: शिवम अग्रवाल और ग्रोक (लियो)

संदर्भ: 2026-10-16 को हुई मौखिक डिज़ाइन चर्चा

Front Matter Notes

• Context: This report records a voice design discussion on 2026-10-16.

• Source: No transcript exists. The authors reconstructed this report from the discussion outline.

• The report contains no quotes or benchmarks from the discussion.

• Section 20 contains size estimates from the discussion. They are estimates, not measurements.

• The prior-work note cites published research. The authors added these citations after the discussion. The discussion did not cite them.

• Sections 17 to 31 record the later part of the same discussion. A quality pass added the assumptions, the prior-work note, the extended glossary, and Section 32.

• Numbering: Sections 9 to 12 are not used in this record. The section numbers follow the discussion outline.

• Style: The text uses ASD-STE100-style controlled technical English at about 80% stringency.

Abstract

This report records a design discussion about a weight-native computing architecture. In this architecture, model weights replace executable code as the primary artifact. The report translates software engineering invariants into weight space. It describes a neural operating system that detects devices from tokenized electrical signatures. It describes weight libraries that the designer trains in isolation and composes at runtime. It requires an external oracle for verification and a fail-closed gate at runtime. It specifies hash-driven versioning and a Merkle tree over weight clusters in a frozen read-only hash region. The later sections add an input gate, error-raising clusters, a frozen checker, size estimates, activation debugging, router-based composition, manifest headers, a delta store, capability tokens, shadow execution, and a dev and production test split. It lists the design decisions, the open issues, and the next steps.

Assumptions and Limitations

(a) This report is a design proposal. It is not an implemented system.

(b) No trained weight clusters exist yet. All cluster behavior in this report is hypothetical.

(c) Outputs are probabilistic. Thus zero-one loss cannot be used at runtime without an external oracle (Sections 6.1 and 6.4).

(d) Storage cost is 10-100x that of a code kernel (Section 20.4).

(e) The router and dispatch vocabulary is a fixed registry. The system does not learn it at runtime (Section 22.5).

How This Differs from Existing Work

Research has explored weight-based execution, neural networks that act as machines, and learned dispatch. Examples are neural program induction and differentiable interpreters. Neural Turing Machines couple a neural network to an external memory (Graves, Wayne, and Danihelka, 2014, arXiv:1410.5401). Neural Programmer-Interpreters learn to call and compose sub-programs (Reed and de Freitas, ICLR 2016, arXiv:1511.06279). A differentiable Forth interpreter lets a programmer write a program sketch with slots that training fills (Bošnjak, Rocktäschel, Naradowsky, and Riedel, ICML 2017, arXiv:1605.06640). Sparsely-gated mixture-of-experts layers use a learned gate to route each input to expert sub-networks

(Shazeer et al., ICLR 2017, arXiv:1701.06538). Capability-based security comes from operating systems such as seL4 (Klein et al., SOSP 2009) and Capsicum (Watson et al., USENIX Security 2010). This report combines isolated trained clusters, a frozen external checker, capability tokens, shadow execution, and a self-referencing hash into one full OS replacement. To the knowledge of the authors, no earlier work documents this combination as a coherent system design. The authors did not do a systematic literature search. This statement is therefore a limitation, not a proof of novelty.

Table of Contents

Front Matter Notes 3

Abstract 3

Assumptions and Limitations 3

How This Differs from Existing Work 3

Glossary 9

1. Motivation and Core Thesis 11

1.1 Core thesis . . . 11

1.2 Invariants in weight space . . . 11

2. From Code to Weights 11

2.1 Constrained decoding . . . 11

2.2 End-to-end trained code models . . . 11

2.3 Weights as data, not program . . . 11

2.4 VM-as-weights variant . . . 11

3. Neural OS Architecture 11

3.1 Weights as OS . . . 11

3.2 Device detection by electrical signatures . . . 12

3.3 Inference engine as boot-time loader . . . 12

3.4 Identity as a learned function . . . 12

4. Weight Libraries and Composition 12

4.1 Isolated training of function clusters . . . 12

4.2 Frozen contracts and named clusters . . . 13

4.3 Runtime composition . . . 13

4.4 Layer classification as design-time contract . . . 13

4.5 Variable-length inputs . . . 13

4.6 Learned type system . . . 13

5. FPGA Analogy 13

5.1 LUT configuration and weight swap . . . 13

5.2 Modularity . . . 13

5.3 Precision and generalization . . . 14

6. Verification and Error Handling 14

6.1 External oracle . . . 14

6.2 Self-verification . . . 14

6.3 Adversarial verifier model . . . 14

6.4 Zero-one loss limits . . . 14
6.5 Confidence thresholds . . . 14
6.6 Fail-closed runtime gates . . . 15
6.7 Input distribution monitors . . . 15
7. Versioning 15
7.1 Hash-driven auto-versioning . . . 15
7.2 Cluster-level granularity . . . 15
7.3 Loss of semantic meaning . . . 15
7.4 Cluster-level changelogs . . . 15
8. Self-Referencing Hash Layer 15
8.1 Embedded hash layer . . . 15
8.2 Atomic recompute race . . . 15
8.3 Fixed-point problem . . . 16
8.4 Resolution: the ROM verifies, the artifact carries its own seal . . . 16
8.5 Merkle tree over weight clusters . . . 16
13. Debugging 17
13.1 Activation probes . . . 17
13.2 Circuit tracing . . . 17
13.3 Hash-based rollback and diff . . . 17
13.4 Activation trace . . . 17
14. Remaining Open Issues 17
14.1 Security . . . 17
14.2 Testing . . . 17
14.3 Tooling ecosystem . . . 17
15. Design Decisions Log 18
16. Open Questions and Next Steps 20
17. Input Poisoning vs Weight Poisoning 21
17.1 What the hash protects . . . 21
17.2 Input poisoning with correct weights . . . 21
17.3 Defense . . . 21
17.4 Two separate layers . . . 21
18. Type-Confusion and Error-Raising Clusters 22
18.1 Type-confusion attack . . . 22
18.2 Error-raising clusters . . . 22
18.3 Confidence rule . . . 22

18.4 Drift of the error boundary . . . 22
19. Frozen Checker 23
19.1 Definition . . . 23
19.2 Location and boot order . . . 23
19.3 Build . . . 23
19.4 Runtime steps . . . 23
20. Weight-Native Kernel Size Estimate 24
20.1 Cluster sizes . . . 24
20.2 Full OS estimate . . . 24
20.3 Comparison with code kernels . . . 24
20.4 Trade-off . . . 24
20.5 Third dimension: debugging . . . 24
21. Activation Breakpoints and Debugging 25
21.1 Activation breakpoint . . . 25
21.2 Replay . . . 25
21.3 Binary search debugging . . . 25
21.4 Debugger cluster . . . 25
21.5 Parallel complexity . . . 25
22. Cluster Classes and Dynamic Composition 26
22.1 Functions and objects . . . 26
22.2 Instantiation . . . 26
22.3 Dispatch weights . . . 26
22.4 Call graph in weights . . . 26
22.5 Router output . . . 26
23. Weight Manifest Header 27
23.1 Header contents . . . 27
23.2 Registry lookup . . . 27
23.3 Self-verified header . . . 27
23.4 Self-referencing hash . . . 27
24. Updated Design Decisions Log 28
25. Open Questions (updated) 31
26. Delta Store and Weight Diffing as First-Class Operation 32
26.1 Store deltas, not copies . . . 32
26.2 Effects . . . 32
26.3 Hash the complete artifact . . . 32

26.4 Role of the delta . . . 32
27. Cluster Capability Tokens 33
27.1 Signed capability . . . 33
27.2 Check before dispatch . . . 33
27.3 Two separate questions . . . 33
27.4 Model . . . 33
28. Shadow Execution for Safe Updates 34
28.1 Parallel run . . . 34
28.2 Promote or reject . . . 34
28.3 Tolerance per cluster . . . 34
28.4 Effect . . . 34
29. Dev vs Production Testing Environments 35
29.1 Two environments . . . 35
29.2 Dev testing . . . 35
29.3 Production testing . . . 35
29.4 Three-level foundation . . . 35
29.5 Coverage . . . 35
30. Binary-Search Debugging Refinement and Dedicated Debugger Cluster 36
30.1 Relation to Section 21 . . . 36
30.2 Binary search at cluster boundaries . . . 36
30.3 Dedicated debugger cluster . . . 36
30.4 Context-aware logging . . . 36
30.5 Parallel complexity . . . 36
31. Self-Referencing Hash Trick and Header-in-Weight Corrections 37
31.1 Relation to Sections 8 and 23 . . . 37
31.2 Self-referencing hash trick . . . 37
31.3 Correction: header in the weight file . . . 37
31.4 Registry lookup . . . 37
31.5 Signed header . . . 37
32. Next Steps 38
Appendix A. Karpathy ASD-STE100 Reference 39
Appendix B. Idea Inventory 40

Glossary

Term	Definition
Cluster (weight cluster)	A named group of model weights that implements one function (Sections 4.1 and 4.2).
Primitive cluster	A cluster that implements one basic function, for example add or store. It is the analog of a function (Section 22.1).
Higher-order cluster	A function that the router makes from primitive clusters in sequence. The report also calls it a cluster class. It needs no new weights (Section 22.2).
Router	A small cluster that takes a task and outputs a sequence of primitive cluster IDs from the cluster registry (Sections 22.3 to 22.5).
Dispatch weights	The router weights that encode the call graph (Section 22.4).
Cluster registry	The fixed vocabulary of cluster IDs that the router can output. It is the analog of an opcode table (Section 22.5).
Capability token	A signed declaration that ships with a cluster. It declares the input types, the output types, the resource limits, and the shadow-execution tolerance (Section 27).
Delta store	A store that keeps only the differences between weight versions. The hash always covers the full assembled artifact (Section 26).
Shadow execution	A run of a new cluster version in parallel with the old version on the same inputs, before promotion (Section 28).
Frozen checker	A small handwritten deterministic C program in ROM or in a signed firmware image. It runs before the weights load and holds the hash-verification logic (Sections 8.4 and 19).
Manifest header	The part of the weight file that holds the weight name, the root hash, the layer count, and the per-layer hashes (Sections 23 and 31).
Self-referencing hash	A hash field inside the weight artifact. The system sets the field to zero, computes the hash, and stores it in the field (Section 31.2).
Weight ID	The identity of a weight artifact: its name and its root hash in the manifest header. The router uses it for registry lookup (Section 23.2).
Error boundary	The learned surface where a cluster changes from a result to an error code (Section 18.4).
Golden input set	A set of known input-output pairs that humans verify (Section 29.2).
Binary-search debugging	A method that halts the forward pass at a layer or cluster boundary and checks the output. Each check halves the region that contains the fault (Sections 21.3 and 30.2).
Weight library	A set of weight clusters with frozen contracts.
Frozen contract	The fixed input and output behavior of a weight cluster. Training does not change it.
Composition	The connection of weight clusters at runtime to make a larger function.
Inference engine	The program that runs the weights. In the neural OS, it is the boot-time loader.
Neural OS	An operating system that the weights implement, not executable code.
Electrical signature	The data that a device supplies to the host, for example PCIe configuration space or USB descriptors.
Token	One unit of input to the model.
Oracle	An external checker of output, for example a compiler, a test suite, or a formal specification.
Verifier model	A separate model with separate weights and a separate objective. It checks the output of the main model.
Fail-closed gate	A runtime check that blocks the output when a check fails.
Confidence threshold	The minimum confidence value that the gate accepts.
Input distribution monitor	A runtime check that detects input outside the training distribution.

Hash	A fixed-length digest of the weight bytes.
Frozen hash region	A read-only memory region that keeps the reference hashes. It follows the secure-boot ROM model.
Merkle tree	A tree of hashes. Each leaf is the hash of one weight cluster. Each parent is the hash of its children.
Activation probe	A read-only tap on the activations at a cluster boundary.
Activation trace	The recorded activations of one run. It is the analog of a stack trace.

1. Motivation and Core Thesis

1.1 Core thesis

Model weights replace executable code as the primary artifact. The designer does not write a program. The designer trains, composes, and verifies weights. The system runs weights in an inference engine.

1.2 Invariants in weight space

Software engineering has invariants. Examples are modularity, contracts, versioning, verification, and debugging. This report translates each invariant into weight space. Each later section treats one invariant.

2. From Code to Weights

2.1 Constrained decoding

The first step uses a model to generate code. Constrained decoding limits the output to valid tokens of a grammar. The output is still code. A compiler or an interpreter still runs it.

2.2 End-to-end trained code models

The next step trains a model end to end on code tasks. The model produces the result directly or through code. This step moves more of the behavior into the weights.

2.3 Weights as data, not program

In the target design, weights are data. The inference engine is the only general program. A change of behavior is a change of data. It is not a change of code. Section 19 adds one more small fixed program: the frozen checker.

2.4 VM-as-weights variant

A variant puts a virtual machine into the weights. The weights then interpret a program, as a VM interprets bytecode. This variant keeps a program layer inside the weight space.

3. Neural OS Architecture

3.1 Weights as OS

The weights implement the operating system functions. The inference engine is the only general executable code on the device. The frozen checker of Section 19 is a second, small, fixed program. It runs before the weights load.




Figure 1. Neural OS stack: hardware signatures to tokenizer to inference loader to weight clusters.

3.2 Device detection by electrical signatures

Each device supplies data to the host. Examples are PCIe configuration space and USB descriptors. A tokenizer converts this data into tokens. The model reads the tokens and identifies the device.

3.3 Inference engine as boot-time loader

At boot, the inference engine loads the weights. The inference engine then runs the weights as the OS.

3.4 Identity as a learned function

Today, a device stores its identity in EEPROM. In this design, device identity becomes a learned function of the signature. The model learns the map from signature to device class.

4. Weight Libraries and Composition

4.1 Isolated training of function clusters

The designer trains each function cluster in isolation. Examples are clusters for add, multiply, and divide. Isolated training keeps each cluster independent of the others.




Figure 2. Weight-library composition of frozen, named clusters.

4.2 Frozen contracts and named clusters

After training, the designer freezes the cluster. The frozen contract defines the input and output behavior. Each cluster has a name. The name identifies the cluster in the library.

4.3 Runtime composition

At runtime, the system connects clusters to make larger functions. Composition is the weight-space analog of a function call.

4.4 Layer classification as design-time contract

The designer assigns a role to each layer at design time. Mechanistic interpretability methods check that the layer performs that role. The role is part of the contract.

4.5 Variable-length inputs

Inputs can have different lengths. Attention masks and padding handle variable-length inputs.

4.6 Learned type system

The system does not declare types. The weights learn the types from the training data.

5. FPGA Analogy

5.1 LUT configuration and weight swap

An FPGA keeps its function in LUT configuration memory. A change of configuration changes the function. The hardware stays the same. In this design, a weight swap changes the function. The inference engine stays the same.

5.2 Modularity

FPGA designs use modules with fixed interfaces. Weight clusters with frozen contracts are the analog of these modules.

5.3 Precision and generalization

A LUT gives an exact result for each input. Weights generalize to new inputs, but they are not exact. The designer must select a point between precision and generalization.

6. Verification and Error Handling

6.1 External oracle

Verification requires an external oracle. Examples are a compiler, a test suite, and a formal specification.




Figure 3. Verifier and oracle loop with a fail-closed gate.

6.2 Self-verification

A model that checks its own output only confirms itself. Self-verification is self-confirmation. It is not verification.

6.3 Adversarial verifier model

A verifier model has separate weights. It also has a separate objective. Its objective is to find errors in the main model output.

6.4 Zero-one loss limits

Many functions have a correct answer or a wrong answer. Zero-one loss gives no gradient. Training on it directly is not possible. The training must use a surrogate loss. The surrogate does not guarantee exact results.

6.5 Confidence thresholds

Each output has a confidence value. The gate rejects output below the confidence threshold. Section 18.3 sets the threshold at 50% for error-raising clusters.

6.6 Fail-closed runtime gates

The gate blocks output when a check fails. The system does not pass unchecked output to the next stage.

6.7 Input distribution monitors

The monitor compares each input with the training distribution. The monitor flags input outside the distribution. The gate then blocks it. Section 17 makes this input gate a layer separate from the hash.

7. Versioning

7.1 Hash-driven auto-versioning

The system computes a hash of the weights. A change of weights changes the hash. The new hash creates a new version automatically. Section 26 stores versions as deltas. The hash always covers the full assembled artifact.




Figure 5. Versioning and rollback flow.

7.2 Cluster-level granularity

The system computes one hash for each weight cluster. A version then identifies which clusters changed.

7.3 Loss of semantic meaning

A hash shows that the weights changed. A hash does not show what the change means.

7.4 Cluster-level changelogs

Each cluster has a changelog. The changelog records the reason and the expected effect of each change.

8. Self-Referencing Hash Layer

8.1 Embedded hash layer

One proposal embeds a hash layer in the weights. The hash layer acts as an integrity seal. Sections 8.1 to 8.3 record this first proposal and its problems. Section 8.4 gives the resolution.

8.2 Atomic recompute race

A weight change and the hash recompute are two steps. Between the two steps, the seal is wrong. The update must be atomic to remove this race.

8.3 Fixed-point problem

The hash layer is part of the weights. The hash must therefore include its own value. This is a fixed-point problem. A normal hash function cannot solve it directly. Section 31.2 removes the problem: the system sets the hash field to zero before it computes the hash.

8.4 Resolution: the ROM verifies, the artifact carries its own seal

The frozen checker in ROM holds the hash-verification logic (Section 19). The self-referencing hash field lives inside the weight artifact, in the manifest header (Sections 23 and 31). The ROM verifies. The artifact carries its own seal. This follows the secure-boot ROM model. Zeroing the hash field before computation removes the fixed-point problem of Section 8.3. The atomic recompute race of Section 8.2 still applies. An update must write the weights and the seal in one atomic step. Limitation: a self-seal shows that the bytes are consistent. It does not show that an approved party made them. The signed header of Section 31.5 gives this proof. The location of the trusted reference, for example a public key or a Merkle root, is UNDECIDED (Section 25).




Figure 4. Merkle tree over weight clusters. The frozen checker in ROM verifies the seals. The seal lives in the artifact.

8.5 Merkle tree over weight clusters

A Merkle tree has one leaf for each weight cluster. The system can verify one cluster without a check of all weights. Git and blockchains use the same structure. The per-layer hashes in the manifest header (Section 23.1) are the leaves inside one cluster.

13. Debugging

13.1 Activation probes

The designer puts activation probes at cluster boundaries. A probe reads the activations. It does not change them.

13.2 Circuit tracing

Circuit tracing follows a computation through the model, in the style of Anthropic interpretability work. It shows which components produce an output.

13.3 Hash-based rollback and diff

Cluster hashes identify the changed clusters. The designer can roll back one cluster to a previous version. The designer can compare two versions cluster by cluster. Section 26 makes rollback a delta operation.

13.4 Activation trace

An activation trace records the activations of one run. It is the analog of a stack trace. Sections 21 and 30 refine debugging with activation breakpoints, binary search, and a debugger cluster.

14. Remaining Open Issues

14.1 Security

Adversarial inputs can cause wrong output. Training-data poisoning puts wrong behavior into the weights. A hash cannot catch poisoning. The hash seals the poisoned weights as valid. Section 17 treats input poisoning. Training-data poisoning stays open (Section 16).

14.2 Testing

Differential testing compares two implementations on the same inputs. Property-based testing checks properties on random inputs. For weights, the result is a probabilistic bound. Line coverage has no meaning for weights. Statistical coverage of the input space replaces it. Section 29 assigns these methods to the dev and production environments.

14.3 Tooling ecosystem

Code has an IDE, a debugger, and a profiler. Weight-native systems need analog tools. These tools do not exist yet in a complete form. Sections 21 and 30 define the debugger approach.

15. Design Decisions Log

Each entry records what was decided, why, the positives, the negatives, and the effect on the program.

D1	**Weights replace code as the primary artifact.**
Why	Behavior becomes data that training can change.
Positives	One artifact type. Composition and swap become data operations.
Negatives	Results are not exact. Verification becomes harder.
Effect on the program	All later sections follow from this decision.

D2	**The inference engine is the only general executable program and the boot-time loader.**
Why	It makes the trusted code base small.
Positives	Small code base to audit.
Negatives	The engine becomes a single point of failure.
Effect on the program	Security work concentrates on the engine and the weights. Decision (c) adds the frozen checker to the trusted code base.

D3	**Device detection uses tokenized electrical signatures.**
Why	Device data already exists in PCIe configuration space and USB descriptors.
Positives	No separate driver code for identification.
Negatives	Identification can be wrong for unknown devices.
Effect on the program	The OS needs an input distribution monitor for device data.

D4	**Function clusters are trained in isolation and frozen.**
Why	Isolation keeps contracts stable.
Positives	Clusters are reusable and independent.
Negatives	Isolated clusters can fail when composed.
Effect on the program	Composition needs its own verification.

D5	**Types are learned, not declared.**
Why	The weights learn the structure of the data.
Positives	No type declarations to maintain.
Negatives	No static type check exists.
Effect on the program	Type errors appear only at runtime or in tests.

D6	**Verification uses an external oracle and a separate verifier model.**
Why	Self-verification is only self-confirmation.
Positives	Independent checks catch errors that the main model hides.
Negatives	More models and more cost.
Effect on the program	Every release needs oracle results.

D7	**Runtime gates fail closed.**
Why	Unchecked output must not reach the next stage.
Positives	Errors stop at the gate.
Negatives	More rejected output. Lower availability.
Effect on the program	The program needs a fallback path for rejected output.

D8	**Versions are hash-driven at cluster level, with changelogs.**
Why	A hash detects every weight change.
Positives	Automatic and exact change detection.
Negatives	The hash has no semantic meaning.
Effect on the program	Changelogs are mandatory for each cluster change.

D9	**The frozen checker in ROM holds the hash-verification logic. Each artifact carries its own self-referencing seal. Cluster hashes form a Merkle tree.**
Why	Logic in ROM cannot change at runtime. Zeroing the hash field removes the fixed-point problem (Section 31.2).
Positives	Partial verification is possible. Each file verifies itself.
Negatives	The atomic recompute race remains. The ROM needs a separate update process. A self-seal alone does not prove authenticity.
Effect on the program	The boot process runs the frozen checker first. See Sections 8.4, 19, and 31. This entry replaces the earlier text that moved all hashes out of the weights.

D10	**Debugging uses activation probes, circuit tracing, and hash-based rollback.**
Why	No source code exists to step through.
Positives	Visibility at cluster boundaries.
Negatives	Probes show values, not reasons.
Effect on the program	The tooling work needs interpretability methods.

16. Open Questions and Next Steps

1. Define the tokenizer format for PCIe configuration space and USB descriptors.

2. Train a small cluster library for add, multiply, and divide. Freeze the contracts.

3. Measure the composition error when clusters connect at runtime.

4. Select an oracle for each cluster: a test suite or a formal specification.

5. Design the verifier model objective.

6. Specify the frozen hash region and the Merkle tree layout.

7. Specify the update process for the frozen hash region.

8. Define the changelog format for each cluster.

9. Open question: how can a design detect training-data poisoning that a hash cannot catch? Status: partly answered. Section 17 adds an input gate for input poisoning. Training-data poisoning is UNDECIDED. Why it matters: a hash seals poisoned weights as valid (Section 14.1).

10. Open question: which statistical coverage metric replaces line coverage? Status: UNDECIDED. Why it matters: without a metric, the program cannot say when testing is complete (Sections 14.2 and 29.5).

11. Open question: which point between precision and generalization suits each function? Status: partly answered. Section 18.3 sets a 50% error threshold. Section 28.3 sets tolerance for each cluster in its capability. The point for each function is UNDECIDED. Why it matters: it sets how exact each cluster must be.

12. Open question: which tools replace the IDE, the debugger, and the profiler? Status: partly answered. Sections 21 and 30 define the debugger approach. The IDE and profiler analogs are UNDECIDED. Why it matters: engineers cannot build or tune clusters without them.

17. Input Poisoning vs Weight Poisoning

17.1 What the hash protects

The hash protects weight integrity. If the bytes do not change, the hash matches. A hash match shows that the weights are correct.

17.2 Input poisoning with correct weights

Input poisoning is possible even with correct weights. An attacker crafts inputs outside the training distribution. These inputs cause wrong outputs. The system does not crash. The hash cannot detect this attack.

17.3 Defense

Runtime input distribution monitors are the defense. Confidence thresholds are also part of the defense.

17.4 Two separate layers

The design uses two separate layers. The hash guards the weights. The input gate guards the model.

18. Type-Confusion and Error-Raising Clusters

18.1 Type-confusion attack

Addition of a float and a string is a type-confusion attack.

18.2 Error-raising clusters

Train clusters to emit error tokens or machine code on incompatible inputs. Example: train the add cluster to reject string plus float.

18.3 Confidence rule

The model can show low confidence when it handles an input. If the confidence or probability drops below 50%, the cluster emits an error code. This rule is fail-closed. The cluster does not guess.

18.4 Drift of the error boundary

The error boundary itself is a learned surface. A learned surface can drift. Drift causes false rejects and false accepts. Thus the error boundary still needs pinning.

19. Frozen Checker

19.1 Definition

The frozen checker is a small, handwritten, deterministic program. It stays outside the weights. It is not weight-based. Weights are probabilistic. A safety gate cannot tolerate even 1% error.

19.2 Location and boot order

The frozen checker is hosted in ROM or in a signed firmware image. It executes before the weights load. This order is like BIOS or secure boot.

19.3 Build

The checker is written in C. The compiler compiles it at build time to a tiny binary. The source is about 20-30 lines. The binary is about 1-4 KB. No GCC exists at runtime.

19.4 Runtime steps

1. Read the input token.
2. Match the token against the expected type.
3. On mismatch, set the error flag.
4. On match, pass the token to the weights.

20. Weight-Native Kernel Size Estimate

20.1 Cluster sizes

The table gives the size of one cluster at four scales. Sizes are for FP16. Assumption: FP16 uses 2 bytes for each parameter, FP8 uses 1 byte, and 4-bit uses 0.5 byte. The stated sizes agree with this. Limitation: the discussion did not record how it derived the parameter counts, for example the vocabulary size or the embedding size. The numbers are estimates, not measurements.

Cluster	Layers	Model dim (d)	FF dim	Parameters	Size (FP16)
Tiny	2	256	512	17.4M	35 MB
Small	4	512	1024	41.2M	82 MB
Medium	8	768	2048	93.2M	186 MB
Large	12	1024	4096	216.5M	433 MB

20.2 Full OS estimate

The estimate uses 8 OS services. Each service is one tiny cluster.

Configuration	Parameters	FP16	FP8	4-bit
8 OS services x tiny cluster	139M	279 MB	139 MB	70 MB

20.3 Comparison with code kernels

System	Source size	Compiled size
Linux kernel v6.x	~30M LOC	10-20 MB
xv6-like minimal kernel	~10K LOC	~1 MB
Frozen checker	~20-30 lines	~1-4 KB

20.4 Trade-off

Storage is 10-100x heavier. Code complexity is near zero.

20.5 Third dimension: debugging

Debugging complexity does not disappear. It moves into the weights. Engineers read activation traces instead of stack traces.

21. Activation Breakpoints and Debugging

21.1 Activation breakpoint

An activation breakpoint halts the forward pass at a cluster. The granularity is coarse compared to instruction-level breakpoints. But the full state is visible: input, output, and weight values. This is like registers and locals in gdb.

21.2 Replay

The real difficulty is replay, not stepping. Randomness and accumulated state make replay hard.

21.3 Binary search debugging

Halt at a layer. If the output is correct, the bug is in the forward layers, after the halt point. If the output is wrong, the bug is in the backward layers, before the halt point. Repeat to narrow down the bug. Section 30 refines this method.

21.4 Debugger cluster

A dedicated debugger cluster receives the activation outputs. It does per-layer logging. It does context-aware logging. Context-aware logging records which context has which activation.

21.5 Parallel complexity

Debugging complexity becomes parallel, not sequential. This follows the microservices observability pattern. The pattern uses per-component logs, trace IDs, and narrow-down.

22. Cluster Classes and Dynamic Composition

22.1 Functions and objects

Primitive clusters are functions. Cluster classes are objects. The glossary also calls them higher-order clusters. A cluster class keeps state and behavior in weights. Its behavior is a routing pattern in the router weights (Section 22.3). The discussion does not state which weights keep the state of a class (Section 25).

22.2 Instantiation

Instantiation does NOT require new weight snapshots. A Fibonacci class is a routing pattern over the add and store clusters. It is not a set of new weights.

22.3 Dispatch weights

Dynamic composition uses dispatch weights, not weight swapping. A small router cluster takes a task, for example Fibonacci. The router outputs a sequence of primitive cluster IDs: add, add, store, loop. Each primitive runs. Its output returns to the router. The router decides the next step.

22.4 Call graph in weights

The call graph is encoded in weights. Today's branch instructions become router activations.

22.5 Router output

The router outputs structured IDs from a fixed vocabulary. The vocabulary is the cluster registry, like an opcode table. The router is trained on task-to-sequence pairs. The router does not do token generation.

23. Weight Manifest Header

23.1 Header contents

Today, bytecode is sent with a header. Weights also get a header. The header contains the weight name, the root hash, the layer count, and the per-layer hashes. The header is small: about hundreds of bytes per cluster.

23.2 Registry lookup

The router finds clusters by reading headers. It matches the hash or the name. This is a registry lookup. It is the analog of a bytecode import table. The hash enables a direct index. No linear scan is necessary.

23.3 Self-verified header

The header is PART of the weight file. A change to the header breaks the hash. Thus the header is self-verified. Section 8.4 explains how this seal relates to the frozen checker in ROM.

23.4 Self-referencing hash

1. Set the hash field to zero.

2. Compute the hash.

3. Store the result in the hash field.

To verify, repeat the steps and compare.

Use a length-extension-resistant hash, for example SHA-3.

24. Updated Design Decisions Log

This log records the decisions from the later part of the discussion. It extends Section 15. Items (a) to (g) record the decisions of Sections 17 to 23. Items (h) to (m) record the decisions of Sections 26 to 31. After the summary table, each item records what was decided, why, the positives, the negatives, and the effect on the program, as in Section 15. Where the discussion gives no content for a field, the field says: Not stated in discussion.

ID	Decision	Section
a	Input gate separate from hash layer	17
b	Error-raising as trained cluster behavior with 50% confidence threshold	18
c	Frozen checker in ROM/signed firmware, C-compiled, outside weights	19
d	Weight-native kernel size trade-off accepted (storage up, code down)	20
e	Activation breakpoints + binary search + debugger cluster for debugging	21
f	Dispatch weights for dynamic cluster composition	22
g	Weight manifest header with self-referencing hash	23
h	The store keeps deltas between weight versions, not full copies.	26
i	Every cluster ships with a signed capability token.	27
j	New cluster versions run in shadow execution before promotion.	28
k	Dev and production use separate test regimes.	29
l	Debugging uses binary search at cluster boundaries and a dedicated debugger cluster.	30
m	The weight file uses a self-referencing hash, and the header is part of the weight file.	31

(a)	Input gate separate from hash layer
Why	A hash cannot detect input poisoning. Correct weights can still give wrong output (Section 17.2).
Positives	Each layer has one job. The design defends against attacks on correct weights.
Negatives	Not stated in discussion.
Effect on the program	The runtime needs input distribution monitors and confidence thresholds (Section 17.3).

(b)	Error-raising as trained cluster behavior with 50% confidence threshold
Why	Type confusion, for example float plus string, is an attack (Section 18.1). Fail-closed means no guessing.
Positives	Incompatible input gives an error code, not a guess.
Negatives	The error boundary is learned and can drift. Drift causes false rejects and false accepts (Section 18.4).
Effect on the program	The error boundary needs pinning.

(c)	Frozen checker in ROM/signed firmware, C-compiled, outside weights
Why	Weights are probabilistic. A safety gate cannot tolerate even 1% error (Section 19.1).
Positives	Deterministic. Tiny: about 1-4 KB. Runs before the weights load, like secure boot.
Negatives	Not stated in discussion.
Effect on the program	The build needs a C compile step. The trusted code base is the inference engine and the frozen checker.

(d)	Weight-native kernel size trade-off accepted (storage up, code down)
Why	Code complexity becomes near zero (Section 20.4).
Positives	Near-zero code complexity.
Negatives	Storage is 10-100x heavier. Debugging complexity moves into the weights (Section 20.5).
Effect on the program	Debugging needs activation tooling (Section 21).

(e)	Activation breakpoints + binary search + debugger cluster for debugging
Why	Debugging complexity moves into the weights (Section 20.5).
Positives	Full state is visible at a breakpoint. Binary search narrows the fault. Complexity becomes parallel.
Negatives	Granularity is coarse. Replay is difficult (Sections 21.1 and 21.2).
Effect on the program	The program needs a debugger cluster and trace IDs. Section 30 refines this decision.

(f)	Dispatch weights for dynamic cluster composition
Why	A cluster class is a routing pattern, not new weights (Section 22.2).
Positives	No weight swapping. No new weight snapshot for each instance.
Negatives	Not stated in discussion.
Effect on the program	The router is trained on task-to-sequence pairs with a fixed cluster registry.

(g)	Weight manifest header with self-referencing hash
Why	The router must find clusters (Section 23.2).
Positives	Direct index lookup. The header verifies itself.
Negatives	Not stated in discussion.
Effect on the program	The header is part of the weight file. The hash uses SHA-3. Decision (m) refines this decision.

(h)	The store keeps deltas between weight versions, not full copies.
Why	This applies the Git object model to weights.
Positives	Updates are cheap. Rollback is trivial. Storage is saved.
Negatives	Each delta must reproduce a byte-identical full artifact.
Effect on the program	The hash covers the complete artifact, header included, never only the delta. See Section 26.

(i)	Every cluster ships with a signed capability token.
Why	The hash and the capability answer two separate questions.
Positives	The router can refuse a cluster that asks for more than it declares. The model is seL4 and Capsicum.
Negatives	Each cluster needs a capability and a signature. The router does two checks.
Effect on the program	The router checks the capability and the hash before dispatch. See Section 27.

(j)	New cluster versions run in shadow execution before promotion.
Why	Old and new outputs on the same inputs show the effect of the change.
Positives	Zero-downtime safe upgrade. Production weight changes become routine.
Negatives	Two versions run at the same time.
Effect on the program	Each cluster declares its tolerance metric and value in its capability token. The default is exact match. See Sections 27 and 28.

(k)	**Dev and production use separate test regimes.**
Why	Dev weights are mutable. Production weights are frozen.
Positives	Dev finds where the error boundary breaks. Production keeps a small regression check.
Negatives	Production testing uses no new inputs. It depends on the fail-closed gate.
Effect on the program	The program keeps a human-verified golden set. Statistical coverage replaces line coverage. See Section 29.

(l)	**Debugging uses binary search at cluster boundaries and a dedicated debugger cluster.**
Why	No source code exists to step through.
Positives	Fast narrow-down. Context-aware logs. Parallel complexity.
Negatives	The debugger cluster is one more cluster to train and verify.
Effect on the program	Debugging follows the microservices observability pattern. See Sections 21 and 30.

(m)	**The weight file uses a self-referencing hash, and the header is part of the weight file.**
Why	Zeroing the hash field removes the fixed-point problem. A header change breaks the hash.
Positives	The file verifies itself. The router uses a direct hash index.
Negatives	The atomic recompute race of Section 8.2 still needs an atomic update.
Effect on the program	The signed-header requirement stands. See Sections 23 and 31.

25. Open Questions (updated)

These questions add to the open questions in Section 16.

1. Does the frozen checker need its own hash or signing? Position recorded: the checker lives in ROM or in a signed firmware image (Section 19.2). Whether a ROM-hosted checker also needs its own hash is UNDECIDED. Why it matters: the ROM update process (D9) depends on it.

2. Can router dispatch weights themselves be versioned and hashed? The router is a cluster (Section 22.3). Sections 23, 26, and 31 give every weight artifact a header and a hash. The discussion states no exception for the router. An explicit decision is UNDECIDED. Why it matters: a router change changes every call graph.

3. How can training make error boundaries without false rejects? Status: UNDECIDED. Why it matters: false rejects lower availability (D7), and false accepts break the fail-closed rule.

4. Can cluster classes share primitive weights (parameter sharing) to reduce the 279 MB footprint? Position recorded: cluster classes reuse primitives through routing and need no new weights (Section 22.2). Sharing between the 8 OS services is UNDECIDED. Why it matters: it decides if the 279 MB FP16 estimate can become smaller.

5. How long can a delta chain grow before the store needs a full snapshot (Section 26)? Status: UNDECIDED. Why it matters: it sets the rollback cost and the storage cost.

6. Who signs the capability tokens, and with which key (Section 27)? Status: UNDECIDED. Why it matters: without a defined signer, the signature proves nothing.

7. Which resource limits does a capability declare, and how does the runtime enforce them (Section 27)? Status: UNDECIDED. Why it matters: the router cannot enforce limits that nobody defined.

8. How many inputs does shadow execution need before promotion (Section 28)? Status: UNDECIDED. Why it matters: too few inputs can promote a faulty cluster.

9. How large must the golden input set be, and who maintains it (Section 29)? Status: UNDECIDED. Why it matters: the golden set defines what the regression check can catch.

10. Is the golden-set tolerance band of Section 29.2 the capability tolerance of Section 28.3? Status: UNDECIDED. Why it matters: two different bands can give two different results for one update.

11. Who verifies the debugger cluster itself (Section 30)? Status: UNDECIDED. Why it matters: a wrong debugger cluster gives wrong logs.

12. Who signs the manifest header, and where is the trusted reference, for example a public key or a Merkle root (Sections 8.4 and 31)? Status: UNDECIDED. Why it matters: authenticity depends on it. A self-seal alone shows only consistency.

13. Which weights keep the state of a cluster class (Section 22.1)? Status: UNDECIDED. Why it matters: state location decides how instances stay separate.

26. Delta Store and Weight Diffing as First-Class Operation

26.1 Store deltas, not copies

The store keeps only the deltas between weight versions. It does not keep a full copy of each version. This applies the Git object model to weights.

26.2 Effects

An update is cheap. A rollback is trivial. The store uses less space.

26.3 Hash the complete artifact

The hash covers the COMPLETE weight artifact. The complete artifact is the full file, header included. The system never hashes only the delta. Version identity stays content-addressable through this hash. Section 7 defines hash-driven versioning.

26.4 Role of the delta

The delta is a storage and transfer optimization only. Integrity checks always run against the full assembled artifact. Version identity always runs against the full assembled artifact. Verification always runs against the full assembled artifact. A delta that cannot produce a byte-identical full artifact is invalid.

27. Cluster Capability Tokens

27.1 Signed capability

Every cluster ships with a signed capability. The capability declares the input types, the output types, and the resource limits of the cluster. The capability also declares the shadow-execution tolerance of the cluster (Section 28). The tolerance declaration gives a comparison metric and its value.

27.2 Check before dispatch

The router checks the capability before dispatch. The router also checks the hash, as in Section 23.

27.3 Two separate questions

The hash answers the question: is this the same cluster? The capability answers the question: what may this cluster do? These are two separate questions. Thus the design uses two separate checks.

27.4 Model

The model is capability-based security, as in seL4 and Capsicum.

28. Shadow Execution for Safe Updates

28.1 Parallel run

The new cluster version runs in parallel with the old version. Both versions receive the same inputs. The system compares the outputs.

28.2 Promote or reject

If the difference is within tolerance, the system promotes the new version. If the difference is outside tolerance, the system rejects the new version. The old version stays in service.




Figure 6. Shadow execution: old and new versions run on the same inputs; the system compares outputs and promotes or rejects.

28.3 Tolerance per cluster

No fixed numeric tolerance exists. Tolerance is set for each cluster. The signed capability token of the cluster declares the tolerance (Section 27). The capability states the comparison metric and its value. The metric is exact match, a relative error bound, or a statistical distribution bound. The shadow executor reads the capability at promotion time. It uses the declared metric. If the capability declares no tolerance, the default is exact match.

28.4 Effect

This gives a safe upgrade with zero downtime. A production weight change becomes a routine operation. Without shadow execution, it is the most dangerous operation.

29. Dev vs Production Testing Environments

29.1 Two environments

In dev, weights are mutable. Updates are permitted in dev. In production, weights are frozen.

29.2 Dev testing

Dev testing uses a golden input set. The golden input set contains known input-output pairs. Humans verify these pairs. The golden set runs on the old version and on the new version, with a tolerance band. The discussion does not state if this band is the capability tolerance of Section 28.3 (Section 25). Dev testing also uses adversarial fuzzing. Dev testing also uses distribution-shift simulation. These two methods find where the error boundary breaks.

29.3 Production testing

Production testing is a regression check only. It uses the same golden set. It uses no new inputs. The fail-closed gate already handles unseen input (Sections 6.6 and 18).

29.4 Three-level foundation

Level 1 is differential testing. Level 2 is property-based testing with probabilistic bounds. Level 3 is regression testing.

29.5 Coverage

Line coverage has no meaning for weights. Statistical coverage of the input space replaces it.

30. Binary-Search Debugging Refinement and Dedicated Debugger Cluster

30.1 Relation to Section 21

This section refines Section 21. It does not replace Section 21.

30.2 Binary search at cluster boundaries

Stop at a cluster boundary. If the output is correct, the fault is in a forward layer. Binary search then narrows the fault to one layer. Section 21.3 gives the same procedure at layer level.

30.3 Dedicated debugger cluster

A dedicated debugger cluster receives the activation outputs. It does its own logging. This extends Section 21.4.

30.4 Context-aware logging

Context-aware logging maps each context to its activation. This context maps to this activation. That context maps to that activation.

30.5 Parallel complexity

Complexity becomes parallel, not sequential. This is the same pattern as microservices observability. The pattern uses per-component logs, trace IDs, and narrow-down.

31. Self-Referencing Hash Trick and Header-in-Weight Corrections

31.1 Relation to Sections 8 and 23

This section refines Section 23. It removes the fixed-point problem of Section 8.3. Section 8.4 states the resolution: the frozen checker in ROM verifies, and the artifact carries its own seal.

31.2 Self-referencing hash trick

1. Set the hash field to zero.

2. Compute the hash.

3. Store the hash in the hash field.

To verify, repeat the same process: set to zero, compute, compare.

SHA-3 resists length extension.

Thus this method is clean.

31.3 Correction: header in the weight file

The manifest header is PART of the weight file. It is not a separate artifact. A change to the header breaks the hash. The hash layer catches this change.

31.4 Registry lookup

The router finds a cluster by a direct hash index. It does not do a linear scan of all headers.

31.5 Signed header

The signed-header requirement stands. The discussion does not say who signs the header or which key is used. Section 25 records this as an open question.

32. Next Steps

These milestones are ordered. Each milestone has a definition of done. They replace the earlier backlog of Section 16 as the plan of work.

1. Train one isolated primitive cluster with a frozen checker and a golden test set.

Done when an addition cluster passes its golden test set and the frozen checker rejects every type-mismatched input in that set.

2. Build the router and the cluster registry with manifest headers.

Done when the router finds each registered cluster by a direct hash index and rejects a cluster whose header hash does not verify.

3. Compose two primitives into a higher-order cluster.

Done when the router runs a task as a sequence of two primitive clusters and the result passes a golden test set for that task.

4. Implement shadow execution with capability-declared tolerance.

Done when a new cluster version is promoted or rejected by the metric in its capability token, with exact match as the default.

5. Implement the delta store and the self-referencing hash.

Done when every stored delta reproduces a byte-identical full artifact whose self-referencing hash verifies.

6. Run adversarial fuzzing against the error boundary.

Done when a fuzzing report lists the false-reject and false-accept rates of each cluster error boundary.

Appendix A. Karpathy ASD-STE100 Reference

Andrej Karpathy posted on X on 2026-10-02 at 00:37 UTC (06:07 IST). URL: https://x.com/karpathy/status/2105819303471976479.

The X connector returned the start of the post text. The returned text is: "Ask your LLM to explain something in ASD-STE100, it's a controlled language specification originally developed for". The connector truncated the remaining text. The authors did not verify the remaining text.

The user referenced the advice to aim for about 80% of full ASD-STE100 stringency. The authors did not verify this part against the full post text.

ASD-STE100 is Simplified Technical English. The aerospace industry developed it for maintenance documentation.

This report applies these rules: short sentences, active voice, one idea per sentence, and one term for one meaning.

The glossary defines each term. The text uses each term with the same meaning.

The report does not apply the full approved-word dictionary. This is the 20% that the report does not apply.

Appendix B. Idea Inventory

Each item records one distinct idea from the discussion outline.

B1. Model weights replace executable code as the primary artifact.

B2. Software engineering invariants translate into weight space.

B3. Constrained decoding limits model output to valid code.

B4. End-to-end trained code models move behavior into the weights.

B5. Weights are data, not program.

B6. A virtual machine can exist as weights (VM-as-weights).

B7. The weights implement the operating system.

B8. Device detection uses electrical signatures.

B9. PCIe configuration space becomes tokens.

B10. USB descriptors become tokens.

B11. The inference engine is the boot-time loader.

B12. EEPROM-stored identity becomes a learned function.

B13. Function clusters are trained in isolation.

B14. Example clusters are add, multiply, and divide.

B15. Clusters have frozen contracts.

B16. Clusters have names.

B17. Clusters compose at runtime.

B18. Layer classification is a design-time contract.

B19. Mechanistic interpretability checks layer roles.

B20. Attention masks and padding handle variable-length inputs.

B21. The type system is learned, not declared.

B22. FPGA LUT configuration memory is the analog of a weight swap.

B23. Modularity follows the FPGA module model.

B24. A tradeoff exists between precision and generalization.

B25. Verification requires an external oracle.

B26. Oracle examples are a compiler, a test suite, and a formal specification.

B27. Self-verification is self-confirmation.

B28. An adversarial verifier model has separate weights.

B29. The verifier model has a separate objective.

B30. Zero-one loss limits training for exact functions.

B31. Confidence thresholds control output acceptance.

B32. Runtime gates fail closed.

B33. Input distribution monitors detect out-of-distribution input.

B34. A weight change triggers hash-driven auto-versioning.

B35. Versioning has cluster-level granularity.

B36. Hash versions lose semantic meaning.

B37. Each cluster has a changelog.

B38. An embedded hash layer acts as an integrity seal.

B39. The embedded hash has an atomic recompute race.

B40. The embedded hash has a fixed-point problem.

B41. A separate frozen read-only hash region solves the problem (secure-boot ROM model).

B42. A Merkle tree over weight clusters gives partial verification.

B43. The Merkle tree is the analog of Git and blockchain structures.

B44. Activation probes sit at cluster boundaries.

B45. Circuit tracing in the Anthropic style shows the computation path.

B46. Hashes enable rollback and diff.

B47. An activation trace is the analog of a stack trace.

B48. Adversarial inputs are a security issue.

B49. A hash cannot catch training-data poisoning.

B50. Differential testing compares implementations.

B51. Property-based testing gives probabilistic bounds.

B52. Statistical coverage replaces line coverage.

B53. The ecosystem needs IDE, debugger, and profiler analogs.

B54. Each design decision records what, why, positives, negatives, and effect on the program.

B55. Input poisoning needs an input gate separate from the hash (Section 17).

B56. Clusters raise error codes below 50% confidence (Section 18).

B57. A frozen checker in ROM runs before the weights load (Section 19).

B58. A weight-native kernel trades storage for code complexity (Section 20).

B59. Activation breakpoints and binary search support debugging (Section 21).

B60. A router composes primitive clusters through dispatch weights (Section 22).

B61. Each weight file has a manifest header (Section 23).

B62. A delta store keeps weight versions (Section 26).

B63. Capability tokens declare what a cluster may do (Section 27).

B64. Shadow execution makes updates safe (Section 28).

B65. Dev and production use separate test regimes (Section 29).

B66. A debugger cluster does context-aware logging (Section 30).

B67. The self-referencing hash zeroes its field before computation (Section 31).