



Software Documentation for SnapTray

Table of Contents

- [Software Documentation for SnapTray](#)
 - [Table of Contents](#)
 - [1. Introduction](#)
 - [2. System Overview](#)
 - [3. Requirements Specification](#)
 - [4. System Architecture](#)
 - [4.1 Components/Modules](#)
 - [4.2 Data Flow](#)
 - [4.3 Technologies](#)
 - [5. Design](#)
 - [5.1 Design Principles](#)
 - [5.1.1 Modularity and Separation of Concerns](#)
 - [5.1.2 Security-First Approach](#)
 - [5.1.3 Scalability and Performance](#)
 - [5.1.4 User-Centric Design](#)

- 5.1.5 Reliability and Fault Tolerance
- 5.1.6 Maintainability and Extensibility
- 5.1.7 Data Integrity and Consistency
- 5.1.8 Cross-Platform Compatibility
- 5.2 Database Design
 - 5.2.1 Az adatbázis célja, funkciója és a benne tárolt információk összefoglalása
 - 5.2.2 Adatbázis-terv és séma
 - 5.2.2.1 Entitások és kapcsolatok (ER modell összefoglaló)
 - 5.2.2.2 Relációs séma (táblázatok részletei)
 - 5.2.2.2.1 User (Felhasználók)
 - 5.2.2.2.2 Payment (Kifizetések)
 - 5.2.2.2.3 MenuItems (Menüelemek)
 - 5.2.2.2.4 Order (Rendelések)
 - 5.2.2.2.5 OrderItems (Rendelés tételek)
 - 5.2.2.2.6 Review (Értékelések)
 - 5.2.2.2.7 DailyMenu (Napi menü)
 - 5.2.2.2.8 ParentStudent (Szülő-Diák kapcsolat)
 - 5.2.2.2.9 SecurityLogs (Biztonsági naplók)
 - 5.2.2.2.10 UserLoyalty (Hűségprogram)
 - 5.2.2.3 Fizikai és logikai szerkezet

- 5.2.2.4 Használati esetek (Use Cases) és forgatókönyvek
- 5.2.2.5 Biztonság és hozzáférés
- 5.2.2.6 Karbantartás és üzemeltetés
- 5.3 Algorithms and Data Structures
 - 5.3.1 Data Structures
 - 5.3.1.1 MongoDB Collections (NoSQL Documents)
 - 5.3.1.2 Redis Data Structures
 - 5.3.1.3 Redis Lua Scripting
 - 5.3.1.4 JavaScript Objects and Arrays
 - 5.3.2 Core Algorithms
 - 5.3.2.1 Authentication and Security Algorithms
 - 5.3.2.2 Payment Processing Algorithms
 - 5.3.2.3 Loyalty Point Calculation Algorithm
 - 5.3.2.4 Search and Filtering Algorithms
 - 5.3.2.5 Caching Algorithms
 - 5.3.2.6 Rate Limiting Algorithm
 - 5.3.2.7 Data Validation Algorithms
 - 5.3.3 Performance Optimization Algorithms
 - 5.3.3.1 Database Query Optimization
 - 5.3.3.2 Pagination Algorithm

- 5.3.3.3 Batch Processing Algorithm
 - 5.3.4 Security Algorithms
 - 5.3.4.1 reCAPTCHA Verification
 - 5.3.5 Algorithm Selection Rationale
- 5.4 Security Design
 - 5.4.1 Security Features
 - 5.4.2 Security Policies
 - 5.4.3 In depth Security Measures
 - 5.4.4 Security Testing and Validation
- 6. Implementation
 - 6.1 Directory Structure
 - 6.2 Backend Implementation
 - 6.2.1 Technology Stack
 - 6.2.3 Main Application Structure
 - 6.2.4 Authentication & Security
 - 6.2.5 Order & Payment Processing
 - 6.2.6 Caching & Performance
 - 6.2.7 Loyalty System
 - 6.2.8 Rate Limiting (Advanced)
 - 6.2.9 Extensibility & Maintainability

- 6.2.9.1 Modular Architecture and Separation of Concerns
- 6.2.9.2 Configuration Management and Environment Handling
- 6.2.9.3 Error Handling and Resilience
- 6.2.9.4 Logging and Monitoring
- 6.2.9.5 Testing and Quality Assurance
- 6.2.9.6 Code Quality and Development Practices
- 6.2.9.7 Scalability Considerations
- 6.2.9.8 Future Extensibility
- 6.2.9.9 Maintenance Procedures
- 6.3 Frontend Implementation
 - 6.3.1 Technology Stack
 - 6.3.2 Application Architecture
 - 6.3.3 Component Structure
 - 6.3.4 State Management
 - 6.3.5 Routing and Navigation
 - 6.3.6 API Integration Layer
 - 6.3.7 UI/UX Design Implementation
 - 6.3.8 Form Handling and Validation
 - 6.3.9 Authentication Handling (Frontend)
 - 6.3.10 Performance Optimization

- 6.3.11 Error Handling and User Feedback
 - 6.3.12 Accessibility (Optional but strong)
 - 6.3.13 Responsiveness (Mobile/Desktop)
 - Router Modules and API Endpoints
 - 7. Testing and Validation
 - 8. User Manual
 - 9. Deployment and Maintenance
 - 10. Conclusion and Future Work
 - 11. References
 - 12. Appendices
-

1. Introduction

A SnapTray egy webalapú menza-rendelőrendszer, amelynek célja, hogy egyszerűsítse az étkezési rendelések lebonyolítását iskolai környezetben. Fő célja, hogy a diákok, szülők és az étkeztető személyzet közötti interakció gyorsabbá és átláthatóbbá váljon az online rendelés, a valós idejű rendeléskövetés és a biztonságos fizetési lehetőségek révén.

A rendszer három fő felhasználói szerepet szolgál ki. A diákok böngészhetnek az étlapok között, rendelhetnek, kezelhetik a virtuális pénztárcájukat, és nyomon követhetik tranzakcióikat. A szülők figyelemmel kísérhetik gyermekeik rendeléseit, kezelhetik a fizetéseket és követhetik a költségeiket. Az adminisztrátorok számára dashboard biztosít lehetőséget az étlapok kezelésére, a rendelések nyomon követésére és statisztikák elemzésére.

A SnapTray modern biztonsági megoldásokat alkalmaz, beleértve a kétlépcsős azonosítást, az email-ellenőrzést, valamint a gyakori webes támadások elleni védelmet. A fizetési lehetőségek PayPal és Google Pay integráción keresztül biztosítottak, így a tranzakciók gyorsak és biztonságosak.

Az intuitív felhasználói felület, a megbízható háttérrendszer és a hatékony adatkezelés révén a SnapTray javítja a menzai élményt minden felhasználó számára, növelve a kényelmet, az átláthatóságot és az üzemeltetési hatékonyságot.

2. System Overview

A rendszer egy webalapú rendelési és fizetési platform oktatási intézmények számára. Célja, hogy a diákok biztonságosan tudjanak rendeléseket leadni, a szülők felügyelhessék a költségeket, az adminisztrátorok pedig kezelhessék a teljes rendszert.

Az alkalmazás kliens–szerver architektúrát követ. A backend Node.js alapú Express szerver, a frontend React komponensekből épül fel szerepkör-alapú dashboardokkal. A rendszer Redis-t használ gyorsítótárazásra, rate limitingre és Lua scriptek segítségével atomi műveletekhez. MongoDB adatbázis biztosítja az adatok perzisztens tárolását.

Megvalósított fő funkciók:

Felhasználókezelés és autentikáció:

- Többszerepkörű felhasználói rendszer (diák, szülő, adminisztrátor)
- Email alapú fiókellenőrzés és kétlépcsős azonosítás (2FA)

- JWT alapú munkamenet-kezelés Redis tárolással
- Jelszó biztonság bcrypt hasheléssel és erősség validációval

Rendelés és menü rendszer:

- Dinamikus menükezelés kategóriákkal és táplálkozási információkkal
- Valós idejű készletkövetés riasztásokkal
- Napi menü funkcionalitás menüelemek társításával
- QR kód integráció menüelemekhez
- Átfedhetetlen allergén és étrendi információk

Fizetés feldolgozás:

- PayPal és Google Pay API integráció
- Pénztárca egyenleg rendszer atomi műveletekkel
- Helyszín alapú pénznem támogatás
- Biztonságos tranzakció naplózás és audit trail

3. Requirements Specification

Fő célok

- Biztonságos és ellenőrzött rendelési folyamat

- Digitális pénztárca és hűségpont rendszer
- Skálázható és nagy teljesítményű backend
- Külső fizetési szolgáltatók integrálása (PayPal, Google Pay)

Felhasználókezelés

- A rendszernek lehetővé kell tennie a felhasználók regisztrációját.
- A rendszernek támogatnia kell az email alapú fiókellenőrzést.
- A rendszernek szerepkör-alapú hozzáférést kell biztosítania (diák, szülő, admin).

Hitelesítés és biztonság

- A rendszernek JWT alapú hitelesítést kell alkalmaznia.
- A rendszernek támogatnia kell a kétlépcsős azonosítást (2FA).
- A rendszernek védenie kell a brute-force támadások ellen rate limiting segítségével.

Rendelések és fizetések

- A rendszernek lehetővé kell tennie a diákok számára rendelés leadását.
- A rendszernek ki kell számítania a rendelés végösszegét.
- A rendszernek támogatnia kell PayPal és Google Pay fizetéseket.
- A rendszernek nyilván kell tartania a tranzakciókat.

Adminisztráció

- Az adminisztrátoroknak lehetőséget kell biztosítani felhasználók kezelésére.

- A rendszernek statisztikákat és riportokat kell biztosítania.
-

4. System Architecture

A rendszer három fő rétegből áll:

Megjelenítési réteg (Frontend)

- React.js komponensekből épülő felhasználói felület
- Szerepkör-alapú dashboardok (diák, szülő, admin)
- Tailwind CSS responsive design
- REST API-n keresztüli kommunikáció a backenddel
- Valós idejű frissítések Socket.IO-val


Alkalmazási réteg (Backend)

- Node.js és Express.js alapú szerver
- JWT alapú hitelesítés és jogosultságkezelés
- Üzleti logika szolgáltatásokban (order-service, payment services)
- Redis Lua scriptek atomi műveletekhez
- Rate limiting és security middleware

Adatréteg

- MongoDB perzisztens adatbázis Mongoose ODM-mel
 - Redis cache munkamenetekhez és rate limitinghez
 - Stratégiai indexek teljesítmény optimalizáláshoz
 - Tranzakciók adat konzisztencia biztosításához
-

MERN Stack with Redis + Lua Architecture
Repository: [bivorzk/iskolaprojekt](https://github.com/bivorzk/iskolaprojekt)



4.1 Components/Modules

The SnapTray system is organized into several key subsystems that work together to provide a cohesive cafeteria management solution:

- **Frontend/UI Layer:** Built with React.js, this layer handles user interactions, displays the interface, and manages client-side state. It includes components for authentication, menu browsing, ordering, and dashboard management.
- **API Layer:** Implemented using Node.js and Express.js, this layer provides RESTful endpoints for data access and business logic execution. It handles requests from the frontend, processes them, and returns appropriate responses.
- **Data Layer:** Comprises MongoDB for persistent data storage and Redis for caching and session management. This layer ensures data integrity, efficient retrieval, and temporary storage for performance optimization.
- **Authentication and Security Module:** Integrated across all layers, this module manages user authentication, authorization, rate limiting, and security logging.
- **Payment Processing Module:** Handles integration with external payment providers like PayPal and Google Pay, ensuring secure and reliable transaction processing.
- **Loyalty System Module:** Manages user points, tiers, and discounts, calculating rewards based on purchase history and applying appropriate benefits.

4.2 Data Flow

Data flows through the SnapTray system in a structured manner to ensure security, performance, and consistency:

1. **User Interaction:** Users interact with the React frontend, triggering API calls via HTTP requests.
2. **Request Processing:** The Express server receives requests, validates them through middleware (authentication, rate limiting, input sanitization), and routes them to appropriate handlers.

3. **Business Logic Execution:** Handlers execute business logic, often involving database queries to MongoDB or cache checks in Redis.
4. **Data Retrieval/Storage:** For read operations, data is fetched from Redis cache if available, otherwise from MongoDB. Write operations update both database and invalidate relevant cache entries.
5. **Response Generation:** Processed data is formatted and sent back to the frontend as JSON responses.
6. **Real-time Updates:** For certain operations (like wallet balance changes), Redis pub/sub is used to notify connected clients of updates.
7. **Logging and Monitoring:** All significant actions are logged to SecurityLogs collection for audit and monitoring purposes.

This flow ensures that sensitive operations are atomic, cached data remains consistent, and the system can handle concurrent users efficiently.

4.3 Technologies

The technology stack for SnapTray was chosen to balance development speed, performance, scalability, and maintainability:

- **MERN Stack (MongoDB, Express.js, React.js, Node.js):** Selected for its JavaScript full-stack consistency, reducing context switching and enabling shared code between frontend and backend. MongoDB's document-based structure aligns well with the flexible data requirements of a cafeteria system.
- **Redis:** Chosen for its high-performance in-memory data structure store, ideal for caching frequently accessed data (user sessions, menu items, statistics) and implementing features like rate limiting and real-time notifications. Its atomic operations ensure data consistency in high-concurrency scenarios.
- **Lua Scripting in Redis:** Utilized for executing complex, atomic operations on Redis data structures. Chosen because it allows multiple Redis commands to run as a single, uninterruptible transaction, ensuring data consistency, preventing race conditions, and improving performance by reducing network round trips between the application and Redis server.
- **Tailwind CSS:** Selected for rapid UI development with utility-first approach, ensuring responsive design and consistent styling across devices.

- **JWT for Authentication:** Provides stateless authentication, reducing server-side session storage needs and improving scalability.
- **bcrypt for Password Hashing:** Industry-standard for secure password storage, protecting against rainbow table and brute-force attacks.
- **reCAPTCHA:** Integrated to prevent automated abuse while maintaining user experience.
- **PayPal/Google Pay APIs:** Chosen for their robust security, global acceptance, and ease of integration for payment processing.
- **Socket.IO:** Implemented for real-time bidirectional communication between clients and server, enabling live chat and order status updates.
- **Express Validator:** Used for comprehensive server-side input validation and sanitization.
- **Helmet:** Security middleware for setting various HTTP headers to protect against common web vulnerabilities.
- **IPlocate.io:** Integrated for IP geolocation services to enhance security logging and fraud detection.
- **Nodemailer:** Used for email verification and notifications.
- **Artillery:** Implemented for load testing and performance validation.

The architecture follows a monolithic approach rather than microservices due to the project's scope and team size, allowing for simpler deployment, debugging, and data consistency. Horizontal scaling is achieved through MongoDB sharding and Redis clustering when needed.

5. Design

5.1 Design Principles

The SnapTray system follows several key design principles to ensure a robust, scalable, and user-friendly school cafeteria management solution. These principles guide the architecture, implementation, and maintenance of the system.

5.1.1 Modularity and Separation of Concerns

- **Component-based Architecture:** The system is built using React components for the frontend, ensuring reusable and maintainable UI elements.
- **Service Layer Abstraction:** Business logic is separated into dedicated service modules (order-service.js, paypal-service.js, etc.) to maintain clean separation between data access, business rules, and presentation layers.
- **Middleware Organization:** Security, authentication, and validation logic are implemented as Express middleware, allowing for clean request processing pipelines.

5.1.2 Security-First Approach

- **Defense in Depth:** Multiple layers of security including input validation, authentication, authorization, rate limiting, and data sanitization.
- **Principle of Least Privilege:** Users have access only to the minimum resources necessary for their role (student, parent, teacher, admin).
- **Secure by Default:** All endpoints require authentication by default, with explicit permissions granted for specific operations.
- **Data Protection:** Sensitive data (passwords, payment information) is encrypted and hashed appropriately.

5.1.3 Scalability and Performance

- **Horizontal Scaling:** The system uses MongoDB and Redis, which support horizontal scaling through sharding and clustering.
- **Caching Strategy:** Redis is employed for session management and data caching to reduce database load and improve response times.
- **Asynchronous Processing:** Non-blocking I/O operations and asynchronous programming patterns ensure the system can handle concurrent users efficiently.
- **Resource Optimization:** Database queries are optimized with proper indexing, and large datasets are paginated.

5.1.4 User-Centric Design

- **Intuitive User Interface:** Clean, responsive design using Tailwind CSS that works across devices (desktop, tablet, mobile).
- **Progressive Enhancement:** Core functionality works without JavaScript, with enhanced features for modern browsers.
- **Feedback Systems:** Clear error messages, loading states, and success confirmations to guide users through processes.

5.1.5 Reliability and Fault Tolerance

- **Error Handling:** Comprehensive error handling with graceful degradation - the system continues to function even when individual components fail.
- **Transaction Management:** Database operations use transactions where appropriate to maintain data consistency.
- **Logging and Monitoring:** Extensive logging for debugging and monitoring system health, with different log levels for different environments.
- **Backup and Recovery:** Regular database backups and recovery procedures to prevent data loss.

5.1.6 Maintainability and Extensibility

- **Clean Code Principles:** Following established coding standards, meaningful variable names, and comprehensive documentation.
- **Version Control:** Git-based development with feature branches and proper commit messages.
- **API Design:** RESTful API design with consistent naming conventions and response formats.
- **Configuration Management:** Environment-based configuration to support different deployment environments (development, staging, production).

5.1.7 Data Integrity and Consistency

- **Validation Layers:** Input validation at multiple levels (client-side, server-side, database-level).

- **Referential Integrity:** Proper use of MongoDB references and population to maintain relationships between entities.
- **Atomic Operations:** Critical operations (like payment processing and loyalty point updates) use atomic database operations.
- **Audit Trail:** Security logs track all important actions for compliance and debugging.

5.1.8 Cross-Platform Compatibility

- **Browser Support:** Compatible with modern browsers (Chrome, Firefox, Safari, Edge) with graceful degradation for older browsers.
- **Mobile Responsiveness:** Responsive design ensures usability on various screen sizes.
- **API Flexibility:** RESTful APIs that can be consumed by different clients (web, mobile apps, third-party integrations).

5.2 Database Design

5.2.1 Az adatbázis célja, funkciója és a benne tárolt információk összefoglalása

Ez az adatbázis egy iskolai büfék rendszer (MERN stack projekt) részét képezi, amely lehetővé teszi a felhasználók (diákok, szülők, tanárok) számára az étkezés megrendelését, kifizetését és értékelését. A rendszer támogatja a felhasználói autentikációt, a menükezelést, rendeléseket, kifizetéseket, hűségprogramokat, E2EE chatet és biztonsági naplózást. A fő cél az iskolai étkezés hatékony és biztonságos kezelése, beleértve a készletkezelést, értékeléseket és a pénzügyi tranzakciókat. Az adatbázis MongoDB-t használ Mongoose ODM-mel, amely egy NoSQL adatbázis, de sémákkal strukturált. Redis-t használ gyorsítótárazáshoz és ideiglenes adatokhoz.

Az adatbázis-modell típusa: NoSQL (MongoDB), lekérdezési nyelv: JavaScript (Mongoose queries). Redis in-memory adatbázis gyorsítótárazáshoz és session/ephemerális adatokhoz.

5.2.2 Adatbázis-terv és séma

Entitások és kapcsolatok (ER modell összefoglaló)


A rendszer fő entitásai és kapcsolataik:

- **User** (Felhasználó): Központi entitás, minden más entitáshoz kapcsolódik.
- **UserPersonalInfo**: Egy felhasználóhoz tartozó személyes adatok (alágyazott dokumentum).
- **MenuItems** (Menüelemek): Étkezési tételek.
- **Order** (Rendelés): Felhasználók rendelései.
- **OrderItems** (Rendelés tételek): Egy rendeléshez tartozó Menüelemek (Order-be ágyazva).
- **Payment** (Kifizetés): Pénzügyi tranzakciók.
- **Review** (Értékelés): Menüelemek értékelése (beágyazott MenuItems-ben).
- **DailyMenu** (Napi menü): Iskolai periódusok szerinti menük, több MenuItems-t tartalmaz (N:N kapcsolat linking table-lal).
- **ParentStudent** (Szülő-Diák kapcsolat): Szülők és diákok összekapcsolása.
- **SecurityLogs** (Biztonsági naplók): Események naplózása.
- **UserLoyalty** (Hűségprogram): Felhasználók pontjai, kedvezményei és hűség szintje.
- **DeviceSyncSession** (Eszköz szinkronizálási munkamenet): Eszközök közötti kulcs szinkronizálás (önálló, nem kapcsolódik más entitáshoz).
- **Message** (Üzenetek): E2EE chat üzenetek.
- **PreKey** (Előzetes kulcsok): ECDH előzetes kulcsok.
- **StorageBlob** (Tárolási blob): Titkosított üzenet/session történetek.

Kapcsolatok:

- User 1:N Payment, Order, SecurityLogs, UserLoyalty, Message (sender/recipient), PreKey, StorageBlob, ParentStudent (szülőként vagy diákként).
- MenuItem 1:N OrderItem (Order-be ágyazva), Review (beágyazott).
- Order 1:N OrderItem (beágyazott).
- DailyMenu N:M MenuItem (linking table: DailyMenuMenuItem).
- Message 1:1 PreKey (opcionális, X3DH-hez).
- StorageBlob 1:1 User (per blobType és partitionKey).
- DeviceSyncSession: önálló, nem kapcsolódik más entitáshoz.

Példa: DailyMenu és MenuItem kapcsolata



DeviceSyncSession

Ez a tábla önálló, nem kapcsolódik más entitáshoz, csak eszköz-azonosítókat és titkosított adatokat tárol. Ez teljesen rendben van, mivel ephemeralis, session típusú adatokat kezel.

E2EE Chat és Üzenetkezelés az Adatbázisban

A rendszer egyik legösszetettebb és legnagyobb része a végpontok közötti titkosított (E2EE) chat funkció, amely több adatbázis-entitást is érint. Az üzenetküldés a Double Ratchet protokollra és X3DH kulcscserére épül, így minden üzenet és kulcsmozgás külön dokumentumként jelenik meg a MongoDB-ben. A főbb komponensek:

- **Message:** Minden elküldött üzenet egy dokumentum, amely tartalmazza a küldő és címzett felhasználó és eszköz azonosítóját, a titkosított üzenettartalmat, státuszt, időbélyegeket, valamint a Double Ratchet és X3DH protokollhoz szükséges metaadatokat (header, x3dhHeader, encryptionMetadata stb.).
- **PreKey:** Az előzetes kulcsok (OPK, SPK) a kulcscsere protokollhoz, minden eszközre és felhasználóra külön dokumentumként tárolva. Ezek gyorsan cserélődnek, használat után törlődnek.
- **StorageBlob:** Titkosított üzenet- és session-történetek, amelyek lehetővé teszik a kliensoldali visszaállítást vagy szinkronizációt. A szerver nem lát bele a tartalomba (zero-knowledge).
- **DeviceSyncSession:** Ideiglenes, eszközök közötti kulcsszinkronizálási session-ök, amelyek automatikusan törlődnek (TTL index).

A chat rendszer minden komponense úgy van kialakítva, hogy a szerver ne férjen hozzá a titkosított tartalomhoz, csak a szükséges metaadatokat tárolja. Az üzenetek, kulcsok és session-ök közötti kapcsolatok referenciákon (ObjectId) és eszközazonosítókra alapulnak. A Message kollekció indexei optimalizálják a keresést felhasználó, eszköz és státusz szerint. A PreKey és StorageBlob kollekciók magas churn-t kezelnek, mivel a kulcsok és session-ök gyorsan cserélődnek. Ez a felépítés biztosítja a biztonságos, skálázható és auditálható chat-funkciót az iskolai rendszerben.

5.3 Algorithms and Data Structures

The SnapTray system employs various algorithms and data structures to ensure efficient data processing, security, and performance. This section documents the key algorithms and data structures used throughout the system.

5.3.1 Data Structures

5.3.1.1 MongoDB Collections (NoSQL Documents)

- **Document-based Storage:** MongoDB collections store data as BSON documents, allowing flexible schemas and nested structures.
- **Embedded Documents:** Order items are embedded within Order documents for atomic operations and better read performance.
- **References:** ObjectId references link related documents (e.g., User to Order, MenuItem to Review).
- **Arrays:** Used for storing multiple values like allergens, menu items in daily menus, and discount lists.

5.3.1.2 Redis Data Structures

- **Strings:** Session storage, cached user data, and simple key-value pairs.
- **Hashes:** Complex cached objects like user statistics and dashboard data.
- **Sorted Sets:** Rate limiting with score-based expiration.
- **Lists:** Queue structures for background processing (if implemented).

5.3.1.3 Redis Lua Scripting

Redis Lua scripts are used for atomic operations that require multiple Redis commands to execute as a single, uninterruptible transaction. This ensures data consistency in high-concurrency scenarios.

Key Lua Scripts in the System:

Rate Limiting Script (rate_limit.lua):

```

-- Sliding window rate limiting using Redis sorted sets
local key = KEYS[1]
local window = tonumber(ARGV[1])
local max_requests = tonumber(ARGV[2])
local now = tonumber(ARGV[3])

-- Remove old entries outside the window
redis.call('ZREMRANGEBYSCORE', key, 0, now - window)

-- Count current requests in window
local current_count = redis.call('ZCARD', key)

-- Check if limit exceeded
if current_count >= max_requests then
    return {0, current_count} -- 0 = blocked, current count
end

-- Add current request
redis.call('ZADD', key, now, now)

-- Set expiration on the key (cleanup)
redis.call('EXPIRE', key, window)

return {1, current_count + 1} -- 1 = allowed, new count

```

- **Purpose:** Distributed sliding window rate limiting
- **Algorithm:** Uses Redis sorted sets for precise time-based windows
- **Benefits:** More accurate than fixed windows, handles burst traffic better

Wallet Update Script (wallet_update.lua):


```
-- Atomic wallet balance updates with validation
local wallet_key = KEYS[1]
local amount = tonumber(ARGV[1])

local current_balance = tonumber(redis.call('GET', wallet_key) or '0')
local new_balance = current_balance + amount

if new_balance < 0 then
    return redis.error_reply('INSUFFICIENT_FUNDS')
end

redis.call('SET', wallet_key, new_balance)

return new_balance
```

- **Purpose:** Thread-safe wallet balance modifications
- **Validation:** Prevents negative balances
- **Atomicity:** Single operation ensures consistency

Order Processing Script (process_order.lua):

```

-- Atomic order processing with inventory and wallet validation
local inventory_key = KEYS[1]
local wallet_key = KEYS[2]
local order_key = KEYS[3]
local quantity = tonumber(ARGV[1])
local price = tonumber(ARGV[2])
local user_id = ARGV[3]

-- Check inventory
local current_stock = tonumber(redis.call('GET', inventory_key) or '0')
if current_stock < quantity then
    return redis.error_reply('INSUFFICIENT_STOCK')
end

-- Check wallet balance
local current_balance = tonumber(redis.call('GET', wallet_key) or '0')
local total_cost = quantity * price
if current_balance < total_cost then
    return redis.error_reply('INSUFFICIENT_FUNDS')
end

-- Atomic operations: deduct inventory and balance, create order
redis.call('DECRBY', inventory_key, quantity)
redis.call('DECRBY', wallet_key, total_cost)
redis.call('HMSET', order_key, 'user_id', user_id, 'quantity', quantity, 'total_cost', total_cost)

return {current_stock - quantity, current_balance - total_cost, order_key}

```

- **Purpose:** Atomic order processing with inventory and payment validation
- **Benefits:** Prevents overselling and ensures payment consistency
- **Error Handling:** Comprehensive validation before execution

Lua Script Benefits:

- **Atomicity:** Multiple Redis operations execute as one atomic unit
- **Performance:** Reduces network round trips between application and Redis
- **Consistency:** Eliminates race conditions in concurrent operations
- **Reusability:** Scripts are cached on Redis server for repeated execution

5.3.1.4 JavaScript Objects and Arrays

- **Plain Objects:** Configuration objects, API responses, and in-memory data manipulation.
- **Arrays:** Cart management, menu filtering, and batch operations.
- **Maps:** Efficient key-value storage for caching and lookups.
- **Sets:** Unique value collections for filtering and deduplication.

5.3.2 Core Algorithms

5.3.2.1 Authentication and Security Algorithms

Password Hashing Algorithm:

```
// bcrypt with salt rounds for secure password storage
const hashedPassword = await bcrypt.hash(password, 12);
const isValid = await bcrypt.compare(password, hashedPassword);
```

- **Algorithm:** bcrypt with adaptive cost factor
- **Purpose:** Prevent rainbow table attacks and brute force attacks

JWT Token Generation and Verification:

```
// HS256 algorithm for token signing
const token = jwt.sign(payload, secretKey, { expiresIn: '24h' });
const decoded = jwt.verify(token, secretKey);
```

- **Algorithm:** HMAC-SHA256 (HS256)
- **Purpose:** Stateless authentication and secure data transmission
- **Security Features:** Expiration, issuer validation, audience restriction

IP Hashing for Privacy:

```
// SHA-256 hashing for GDPR compliance
const hashedIP = crypto.createHash('sha256').update(ipAddress).digest('hex');
```

- **Algorithm:** SHA-256 cryptographic hash
- **Purpose:** Anonymize IP addresses in logs while maintaining uniqueness
- **Compliance:** GDPR Article 32 data protection requirements

5.3.2.2 Payment Processing Algorithms

Currency Conversion Algorithm:

```
// Simple multiplication-based conversion
const convertCurrency = (amount, fromRate, toRate) => {
  return (amount / fromRate) * toRate;
};
```

- **Algorithm:** Linear conversion with exchange rates
- **Purpose:** Convert between different currencies for international payments

- **Precision:** Uses floating-point arithmetic with rounding to 2 decimal places

Payment Validation Algorithm:

```
// Multi-step validation with checksums
const validatePayment = (paymentData) => {
  return validateAmount(paymentData.amount) &&
    validateCurrency(paymentData.currency) &&
    validateChecksum(paymentData);
};
```

- **Algorithm:** Multi-condition validation with early termination
- **Purpose:** Prevent fraudulent transactions and data corruption
- **Error Handling:** Comprehensive validation with specific error messages

5.3.2.3 Loyalty Point Calculation Algorithm

Point Calculation Based on Purchase Amount:

```
const calculatePoints = (amount, tier, healthLevel, date) => {
  const basePoints = amount * 4; // 4 points per dollar
  const tierMultiplier = getTierMultiplier(tier);
  const healthBonus = healthLevel === 'HIGH' ? 1.5 : 1.0;
  const holidayBonus = isHoliday(date) ? 1.2 : 1.0;

  return Math.floor(basePoints * tierMultiplier * healthBonus * holidayBonus);
};
```

- **Algorithm:** Multiplicative point calculation with tier bonuses
- **Factors:** Purchase amount, user tier, health score, holiday periods

- **Rounding:** Floor function to ensure integer points

Tier Determination Algorithm:

```
const determineTier = (totalPoints) => {  
  if (totalPoints >= 20000) return 'PLATINUM';  
  if (totalPoints >= 8000) return 'GOLD';  
  if (totalPoints >= 2500) return 'SILVER';  
  if (totalPoints >= 1200) return 'BRONZE';  
  return 'NONE';  
};
```

- **Algorithm:** Threshold-based classification
- **Purpose:** Automatic tier promotion based on accumulated points
- **Triggers:** Real-time updates on point changes

5.3.2.4 Search and Filtering Algorithms

Menu Item Filtering Algorithm:

```
const filterMenuItems = (items, filters) => {  
  return items.filter(item => {  
    return (!filters.category || item.category === filters.category) &&  
      (!filters.priceRange || isInRange(item.price, filters.priceRange)) &&  
      (!filters.allergens || !hasAllergens(item, filters.allergens)) &&  
      (!filters.searchTerm || matchesSearch(item, filters.searchTerm));  
  });  
};
```

- **Algorithm:** Multi-criteria filtering with short-circuit evaluation

- **Purpose:** Efficient menu browsing with multiple filter options

Text Search Algorithm:

```
const matchesSearch = (item, term) => {  
  const searchTerm = term.toLowerCase();  
  return item.name.toLowerCase().includes(searchTerm) ||  
    item.description.toLowerCase().includes(searchTerm);  
};
```

- **Algorithm:** Case-insensitive substring matching
- **Purpose:** Basic text search across menu items
- **Limitations:** Simple implementation, could be enhanced with fuzzy matching

5.3.2.5 Caching Algorithms

Cache Key Generation:

```
const generateCacheKey = (userId, resource, params) => {  
  return `${userId}:${resource}:${JSON.stringify(params)}`;  
};
```

- **Algorithm:** Structured key generation with JSON serialization
- **Purpose:** Unique cache keys for different user-resource combinations
- **Collision Prevention:** Includes all relevant parameters

Cache Invalidation Strategy:

```
const invalidateUserCache = async (userId) => {  
  const pattern = `${userId}:*`;   
  const keys = await redisClient.keys(pattern);  
  if (keys.length > 0) {  
    await redisClient.del(keys);  
  }  
};
```

- **Algorithm:** Pattern-based bulk invalidation
- **Purpose:** Clear all user-related cache entries on data changes
- **Performance:** Uses Redis pattern matching for efficiency

5.3.2.6 Rate Limiting Algorithm

Sliding Window Algorithm (Redis Lua Implementation):


```

-- Uses Redis sorted sets for precise sliding window rate limiting
local key = KEYS[1]
local window = tonumber(ARGV[1])
local max_requests = tonumber(ARGV[2])
local now = tonumber(ARGV[3])

-- Remove requests outside the current window
redis.call('ZREMRANGEBYSCORE', key, 0, now - window)

-- Count requests in current window
local current_count = redis.call('ZCARD', key)

if current_count >= max_requests then
    return {0, current_count} -- Rate limit exceeded
end

-- Add current request and set expiration
redis.call('ZADD', key, now, now)
redis.call('EXPIRE', key, window)

return {1, current_count + 1} -- Request allowed

```

- **Algorithm:** Sliding window using Redis sorted sets
- **Benefits:** More accurate than fixed windows, handles burst traffic better
- **Implementation:** Distributed across multiple server instances
- **Data Structure:** Sorted set with timestamps as scores
 - windowMs: 15 * 60 * 1000, // 15 minutes
 - max: 100, // limit each IP to 100 requests per windowMs
 - store: new RedisStore({ /* redis config */ })
 - });

- **Algorithm**: Token bucket with fixed window
- **Purpose**: Prevent abuse and ensure fair resource usage
- **Storage**: Redis-backed for distributed rate limiting

5.3.2.7 Data Validation Algorithms

Input Sanitization Algorithm:

```
```javascript
const sanitizeInput = (input) => {
 return input
 .trim()
 .replace(/[<>]/g, '') // Basic XSS prevention
 .substring(0, 1000); // Length limiting
};
```

- **Algorithm**: Multi-step sanitization with regex replacement
- **Purpose**: Prevent injection attacks and normalize input data
- **Layers**: Client-side, server-side, and database-level validation

#### Email Validation Algorithm:

```
const validateEmail = (email) => {
 const emailRegex = /^[^\s@]+@[^\s@]+\.[^\s@]+$/;
 return emailRegex.test(email) && email.length <= 254;
};
```

- **Algorithm**: Regular expression matching with length constraints
- **Purpose**: Ensure valid email format and prevent buffer overflow

## 5.3.3 Performance Optimization Algorithms

### 5.3.3.1 Database Query Optimization

#### Index Utilization:

```
// Compound indexes for common query patterns
User.collection.createIndex({ email: 1, isVerified: 1 });
Order.collection.createIndex({ userId: 1, orderDate: -1 });
```

- **Algorithm:** Strategic index creation based on query patterns
- **Purpose:** Reduce query execution time
- **Maintenance:** Automatic index updates on document changes

### 5.3.3.2 Pagination Algorithm

#### Cursor-based Pagination:

```
const getPaginatedResults = async (model, filter, page, limit) => {
 const skip = (page - 1) * limit;
 const results = await model.find(filter)
 .sort({ createdAt: -1 })
 .skip(skip)
 .limit(limit);
 const total = await model.countDocuments(filter);
 return { results, total, page, pages: Math.ceil(total / limit) };
};
```

- **Algorithm:** Skip-limit pagination with total count
- **Purpose:** Efficient handling of large datasets

### 5.3.3.3 Batch Processing Algorithm

#### Order Fulfillment Batch Processing:

```
const processOrderBatch = async (orders) => {
 const bulkOps = orders.map(order => ({
 updateOne: {
 filter: { _id: order._id },
 update: { status: 'Completed' }
 }
 }));
 return await Order.bulkWrite(bulkOps);
};
```

- **Algorithm:** Bulk database operations for multiple records
- **Purpose:** Reduce database round trips for batch updates

### 5.3.4 Security Algorithms

#### 5.3.4.1 reCAPTCHA Verification

#### Score-based Assessment:

```
const verifyRecaptcha = async (token) => {
 const response = await fetch('https://www.google.com/recaptcha/api/siteverify', {
 method: 'POST',
 body: new URLSearchParams({
 secret: process.env.RECAPTCHA_SECRET,
 response: token
 })
 });
 const result = await response.json();
 return result.score >= 0.5; // Threshold for human/bot determination
};
```

- **Algorithm:** Machine learning-based risk assessment
- **Purpose:** Distinguish between human users and automated bots
- **Accuracy:** Google's proprietary algorithm with score 0.0-1.0 (1 being the highest chance the user is a human and 0 being the lowest chance, 0.5 the default threshold for human detection )

### 5.3.4 Algorithm Selection Rationale

- **Security Algorithms:** Chosen for industry-standard security (bcrypt, JWT, AES)
- **Performance Algorithms:** Selected for scalability (Redis caching, pagination, indexing)
- **Business Logic Algorithms:** Designed for fairness and transparency (loyalty calculations, tier systems)
- **Data Processing Algorithms:** Optimized for common use cases (filtering, searching, validation)

The algorithms are chosen to balance security, performance, maintainability, and user experience while adhering to industry best practices and compliance requirements.

## 5.4 Security Design

### 5.4.1 Security Features

- **Authentication:** JWT-based authentication with role-based access control (RBAC).
- **Data Encryption:** Sensitive data encrypted at rest and in transit (TLS/SSL).
- **Input Validation:** Comprehensive validation and sanitization of all user inputs.
- **Rate Limiting:** Prevent brute-force attacks using express-rate-limit with Redis store and Redis Lua scripting for dashboard/admin routes.
- **Logging and Monitoring:** SecurityLogs collection for tracking user actions and potential security incidents.
- **Regular Audits:** Periodic security audits and vulnerability assessments.
- **Backup and Recovery:** Planned, not yet implemented (see Roadmap).
- **Compliance:** Adherence to GDPR and other relevant data protection regulations.
- **XSS Protection:** Use of libraries like *xss-clean* and *helmet* to mitigate XSS attacks.
- **HTTP Pollution Protection:** Use of *helmet* and *hpp* to set secure HTTP headers and prevent HTTP parameter pollution.
- **CSRF Protection:** Partial implementation; CSRF tokens are planned for all state-changing operations (see Roadmap).
- **Password Policies:** Strong password requirements enforced via *zxcvbn* and custom validation.
- **Two-Factor Authentication (2FA):** Basic 2FA endpoint implemented; full integration planned (see Roadmap).
- **Session Management:** Secure session handling with appropriate expiration and invalidation.
- **Location-based Security:** Implemented geolocation analysis with risk scoring for fraud detection.
- **reCAPTCHA Integration:** Google reCAPTCHA v3 is integrated into registration and login.
- **IP Hashing:** IP addresses are hashed using SHA-256 before storage in SecurityLogs.

- **NoSQL Injection Prevention:** Use of parameterized queries, Mongoose ODM, and express-mongo-sanitize.
- **Security Headers:** Helmet.js sets security headers, including CSP.
- **Content Security Policy (CSP):** Strict CSP enforced, no inline scripts except for specific nonces, eval() disabled.

### 5.4.2 Security Policies

- **Access Control:** Strict role-based access control (RBAC) to limit user permissions.
- **Data Retention:** Policies for data retention and deletion in compliance with regulations.
- **Incident Response:** Procedures for responding to security incidents and breaches.
- **User Education:** Informing users about security best practices.
- **Regular Updates:** Keeping software and dependencies up to date with security patches.

### 5.4.3 In depth Security Measures

- **Password Hashing:** All passwords are hashed using bcrypt with a salt of 10 rounds for both registration and password reset.
- **JWT Authentication:** JSON Web Tokens (JWT) are used for stateless authentication between the client and server. JWT signing secrets are generated using cryptographically secure random values stored in environment variables.
- **Payment Security:** Integration with PayPal's and Google Pay's secure payment gateways, ensuring PCI compliance and encrypted payment data.
- **XSS Protection:** Use of libraries like *xss-clean* and *helmet* to mitigate XSS attacks by sanitizing user inputs and setting secure HTTP headers.
- **CSRF Protection:** Partial; planned for all state-changing operations.
- **Rate Limiting:** Two methods: *express-rate-limit* with Redis store for general routes, and Redis Lua scripting for dashboard/admin routes.
- **IP Hashing:** IP addresses are hashed using SHA-256 before storage in SecurityLogs.

- **reCAPTCHA Integration:** Google reCAPTCHA v3 is integrated into registration and login, using a score-based assessment.
- **NoSQL Injection Prevention:** Parameterized queries, Mongoose ODM, and express-mongo-sanitize are used to prevent NoSQL injection attacks.
- **IP Detection:** Implemented integration with [iplocate.io](https://iplocate.io) for VPN/Proxy/Tor detection and geolocation-based risk analysis.
- **HTTP Parameter Pollution (HPP):** The *hpp* library middleware is used to protect against HTTP Parameter Pollution attacks.
- **CORS Policy:** Strict CORS policy using the *cors* middleware, only allowing requests from the official frontend domain.
- **Security Headers:** Helmet.js sets various HTTP headers for enhanced security.
- **Database Security:** MongoDB connections use authentication with credentials stored in environment variables. Connection pooling and timeouts prevent resource exhaustion. Mongoose ODM provides schema validation and type casting.
- **Error Handling Security:** Sensitive information is never exposed in error messages sent to clients.
- **API Security:** All API endpoints require authentication by default. Public endpoints are explicitly marked and protected with additional rate limiting and bot detection.
- **Environment Security:** All sensitive configuration is stored in environment variables and never committed to version control.

## 5.4.4 Security Testing and Validation

- **Automated Security Testing:** The project includes security-focused test suites that validate authentication flows, input sanitization, and rate limiting effectiveness.
- **Penetration Testing:** Periodic manual security assessments to identify vulnerabilities not caught by automated tools.



## 6.1 Directory Structure

```
|— code_analytics.json
|— package.json
|— postcss.config.js
|— readme.md
|— tailwind.config.js
|— todo.md
|— config/
| |— DATABASE_CONSTANTS.JS
| |— database_queries.js
| └─ hu.json
|— data/
| |— disposable_email_list.json
| |— Most_used_passwords.json
| |— password_characters.json
| └─ database_test/
| |— Food_Items.json
| └─ menu_items.json
|— docs/
| |— a.md
| |— DatabaseDoc.md
| |— Documentation.html
| |— Documentation.md
| |— E2EE_Chat_README.md
| |— Paypal_TestDetails.txt
| |— sourcefor_security_checks.txt
| └─ TODO.md
|— public/
| |— googlepay.js
| |— index.html
| |— password_reset.html
| |— pay.html
| |— paypal.js
| |— register.html
| └─ verify.html
```

```
| |─ 404/
| | |─ 404.html
| | |─ 404.jsx
| |─ 429/
| | |─ 429.html
| | |─ 429.jsx
| |─ chat/
| | |─ chat-styles.css
| | |─ chat.jsx
| | |─ index.html
| | |─ api/
| | |─ components/
| | |─ config/
| | |─ utils/
| |─ css/
| | |─ mobile-enhancements.css
| |─ dashboard/
| | |─ TODO.txt
| | |─ admin/
| | |─ editor/
| | |─ parent/
| | |─ student/
| |─ home_page/
| | |─ home_page.html
| | |─ home_page.jsx
| |─ information/
| | |─ index.html
| | |─ information.jsx
| |─ js/
| | |─ e2ee-crypto.js
| | |─ mobile-utils.js
| |─ no_perm/
| | |─ index.html
| | |─ no_perm.jsx
| |─ Order/
```

```
| |─ Cart.jsx
| |─ Header.jsx
| |─ index.html
| |─ LoyaltyStatus.jsx
| |─ MenuItem.jsx
| |─ MobileCart.jsx
| |─ MobileToast.jsx
| |─ notifications.js
| |─ order.jsx
| |─ paymentHandlers.js
| |─ useCart.js
| |─ useMobileCart.js
|─ src/
| |─ api.js
| |─ database.js
| |─ logout.js
| |─ main.js
| |─ redis-lua.js
| |─ redis.js
| |─ Register.jsx
| |─ script-loader.js
| |─ verificationStore.js
| |─ auth/
| | |─ 2fa.js
| | |─ email_verification.js
| | |─ index.js
| | |─ login.js
| | |─ middleware.js
| | |─ password_reset.js
| | |─ passwordhash.js
| | |─ register.js
| | | |─ security.js
| | └─ validation.js
| |─ cache/
| | |─ ChangeStreamManager.js
```

```
| | └─ KeyRegistry.js
| └─ dashboard/
| | └─ dashboard.js
| | └─ admin/
| | └─ editor/
| | └─ middleware/
| | └─ parent/
| | └─ services/
| | └─ statistics/
| | └─ student/
| └─ examples/
| | └─ lua-demo.js
| └─ locationRiskAnalyzer/
| | └─ locationRiskAnalyzer.js
| └─ LoyaltySystem/
| | └─ loyalty-service.js
| └─ middleware/
| | └─ ...
| └─ models/
| | └─ ...
| └─ Orders/
| └─ payments/
| └─ scripts/
| └─ services/
└─ tests/
 └─ code_analytic.py
 └─ code_analytics.json
 └─ creating_test_users.js
 └─ database_testing.js
 └─ fake_data.py
 └─ menu_items.json
 └─ Paypal_TestConfig.txt
 └─ query_security_logs.js
```

```
├─ register_testing.py
├─ seed_rewards.js
└─ performance_tests/
```

## 6.2 Backend Implementation

### 6.2.1 Technology Stack

The SnapTray backend is built for scalability, security, and maintainability. The main technologies are:

- **Node.js** (runtime)
  - **Express.js** (web framework)
  - **MongoDB** (NoSQL database)
  - **Redis** (in-memory cache, rate limiting, atomic ops)
  - **JWT** (authentication)
  - **PayPal & Google Pay** (payment gateways)
- 

### 6.2.3 Main Application Structure

- **src/main.js**: Entry point, sets up Express, middleware, routers, and rate limiting.
- **Routers**: Modularized for authentication, dashboard, orders, payments, chat, etc.
- **Database Models**: Defined with Mongoose (see `src/models/` ).
- **Services**: Business logic (loyalty, caching, Redis Lua, payments, etc.).

Example: Express app setup and initialization (src/main.js)

```
const express = require('express');
const app = express();

// Trust proxy for correct IP extraction
app.set('trust proxy', 1);

const rateLimit = require('express-rate-limit');
const session = require('express-session');
const database = require('./database');
const path = require('path');
const emailverification = require('./auth/email_verification');
const api = require('./api');
const { RedisStore } = require('rate-limit-redis');
const favicon = require('serve-favicon');
const googlepayRouter = require('./payments/googlepay');
const paypalRouter = require('./payments/paypal');
const password_reset = require('./auth/password_reset');
const database_queries = require('./config/database_queries');
const TwoFA = require('./auth/2fa');
const dashboardRouter = require('./dashboard/dashboard');
const logoutRouter = require('./logout');
const Order = require('./Orders/Order');
const redisLuaService = require('./services/redis-lua-service');
const chatService = require('./services/chat-service');
const geosecurityService = require('./services/Geosecurity-service');
const cors = require('cors');
const { startChangeStreams, stopChangeStreams } = require('./dashboard/services/cache-service');
const { Server } = require('socket.io');

require('dotenv').config({ path: path.join(__dirname, '../.env') });

const port = process.env.PORT;

let redisAvailable = false;
```



```
const { redisClient, isRedisAvailable } = require('./redis');

redisClient.on('connect', async () => {
 console.log('Redis connected in main.js');
 redisAvailable = true;

 // Initialize Redis Lua service
 try {
 await redisLuaService.initialize();
 } catch (error) {
 console.error('Failed to initialize Redis Lua service:', error);
 }
});

// Start MongoDB change streams once the connection is open
```

---

## 6.2.4 Authentication & Security

- **Registration:** Validates input, hashes passwords (bcrypt), uses reCAPTCHA, sends verification email, logs security events.
- **Login:** Verifies password, issues JWT, logs IP/location, rate limits by IP.
- **Session:** Stores user info and JWT in session.

Example registration route (src/auth/register.js):

```
router.post('/register', async (req, res) => {
 try {
 const { username, password, email } = req.body;
 const clientIp = req.clientIp || req.ip || 'unknown';

 // Rate limiting
 if (isRedisAvailable) {
 const rateLimitKey = `reg_attempts:${clientIp}`;
 const attempts = await redisClient.get(rateLimitKey);
 const attemptCount = attempts ? parseInt(attempts) : 0;

 if (attemptCount >= 5) {
 return res.status(429).send('Too many registration attempts. Please try again later.'); }

 await redisClient.setEx(rateLimitKey, 3600, (attemptCount + 1).toString());
 }

 // reCAPTCHA verification
 const captchaResponse = req.body['g-recaptcha-response'];
 const captchaResult = await verifyCaptcha(captchaResponse, secretKey);
 if (!captchaResult.success) {
 return res.status(400).json({ error: captchaResult.error, details: captchaResult.details });
 }

 // Validation
 const usernameError = validateUsername(username, password);
 if (usernameError) return res.status(400).send(usernameError);

 const passwordError = validatePassword(password);
 if (passwordError) return res.status(400).send(passwordError);

 const emailError = validateEmail(email);
 if (emailError) return res.status(400).send(emailError);
 }
});
```

```
// Check existing users
const existingUser = await User.findOne({ username });
const existingEmail = await User.findOne({ email });

let shouldCreateUser = !existingUser && !existingEmail;
let shouldSendEmail = shouldCreateUser || (existingEmail && !existingEmail.isVerified);

// Send verification email
if (shouldSendEmail) {
 const verificationCode = crypto.randomBytes(3).toString('hex').toUpperCase();
 await setVerificationCode(email, verificationCode);
 await sendVerificationEmail.sendVerificationEmail(email, verificationCode);
}

// Create user if not exists
if (shouldCreateUser) {
 const hashedPassword = await bcrypt.hash(password, 10);
 const user = new User({ username, password: hashedPassword, email });
 await user.save();
 await createSecurityLog('USER_REGISTER', { username, email }, clientIp);
}

res.status(200).json({ message: 'Registration successful! Please check your email for verification.' });
} catch (error) {
 console.error('Registration error:', error);
 res.status(500).send('Internal server error');
}
});
```

---

## 6.2.5 Order & Payment Processing

- **Order API:** Validates cart, checks stock, creates order in DB, integrates with PayPal/Google Pay.
- **Order Completion:** Updates order status, deducts stock, awards loyalty points, logs payment.

Example PayPal order creation (src/api.js):

```
router.post('/orders', async (req, res) => {
 // ...validate user, stock...
 const { jsonResponse, httpStatusCode } = await paypalService.createOrder(cart, currency, amount);
 // ...save order to DB...
 res.status(httpStatusCode).json(jsonResponse);
});
```

---

## 6.2.6 Caching & Performance

- **Redis:** Used for caching (menu items, sessions), atomic wallet/stock updates, and rate limiting.
- **Cache Middleware:** Wraps API endpoints to serve cached data when available.

Example cache middleware (src/dashboard/services/cache-service.js):

```
function cacheResult(cacheKey, ttl = 300) {
 return async (req, res, next) => {
 if (!isRedisAvailable()) return next();
 const key = typeof cacheKey === 'function' ? cacheKey(req) : cacheKey;
 const cached = await redisClient.get(key);
 if (cached) return res.status(200).json(JSON.parse(cached));
 const originalJson = res.json;
 res.json = function(data) {
 redisClient.setEx(key, ttl, JSON.stringify(data));
 return originalJson.call(this, data);
 };
 next();
 };
}
```

---

## 6.2.7 Loyalty System

- **Points Calculation:** Points per order, with bonuses for holidays, healthy choices, and user tier.
- **Awarding:** On order completion, points are calculated and added atomically.

Example (src/LoyaltySystem/loyalty-service.js):

```
function ConvertPoints(dollarAmount, tier, healthLevel, date) {
 let total = 0;
 for (let i = 0; i < Math.floor(dollarAmount); i++) {
 total += Math.floor(Math.random() * 6) + 4; // 4-9 points per dollar
 }
 if (isHoliday(date)) total *= 1.5;
 else if (isHolidaySeason(date)) total *= 1.2;
 total *= 1 + (healthLevel * 0.2);
 const tierBonus = DISCOUNT_RATES[tier] || 0;
 total *= 1 + tierBonus;
 return Math.floor(total);
}
```

---

## 6.2.8 Rate Limiting (Advanced)

- **Express Middleware:** For general API routes.
- **Redis Lua Script:** For dashboard/admin, implements sliding window algorithm for fair, distributed rate limiting.

Example Lua script (used via redis-lua-service):

```
-- KEYS[1]: rate_limit_key
-- ARGV[1]: window_size_seconds, ARGV[2]: max_requests, ARGV[3]: current_timestamp
local key = KEYS[1]
local window = tonumber(ARGV[1])
local max_requests = tonumber(ARGV[2])
local now = tonumber(ARGV[3])
redis.call('ZREMRANGEBYSCORE', key, 0, now - window)
local current_count = redis.call('ZCARD', key)
if current_count >= max_requests then
 return {0, current_count}
end
redis.call('ZADD', key, now, now)
redis.call('EXPIRE', key, window)
return {1, current_count + 1}
```

---

## 6.2.9 Extensibility & Maintainability

The SnapTray backend is designed with extensibility and maintainability as core principles, ensuring the system can evolve with changing requirements while remaining easy to understand, modify, and scale. This section details the architectural decisions, patterns, and practices that support long-term software sustainability.

### 6.2.9.1 Modular Architecture and Separation of Concerns

The backend follows a modular architecture that separates concerns into distinct layers and modules, promoting high cohesion within modules and loose coupling between them. This design allows for independent development, testing, and deployment of components.

- **Layered Architecture:** The system is organized into presentation (routes), business logic (services), data access (models), and infrastructure (middleware, utilities) layers. This separation enables changes in one layer without affecting others.
- **Module Organization:** Code is structured into logical modules (e.g., `src/auth/`, `src/dashboard/`, `src/services/`, `src/payments/`), each

responsible for a specific domain. This organization facilitates:

- Easier navigation and understanding of the codebase
- Parallel development by multiple team members
- Selective testing and deployment of features
- **Service-Oriented Design:** Business logic is encapsulated in service modules (e.g., `loyalty-service.js` , `paypal-service.js` ), which provide clean APIs for controllers. This abstraction allows for:
  - Reusable business logic across different endpoints
  - Easier unit testing of individual services
  - Potential future migration to microservices

Example service structure (`src/services/order-service.js`):



```
class OrderService {
 async validateOrderStock(cart) {
 // Validate inventory levels
 for (const item of cart) {
 const menuItem = await MenuItems.findById(item.id);
 if (!menuItem || menuItem.stock < item.quantity) {
 throw new Error(`Insufficient stock for ${menuItem.name}`);
 }
 }
 }

 async convertCartToDbFormat(cart) {
 // Convert frontend cart format to database format
 const dbOrderItems = [];
 let totalAmount = 0;
 for (const item of cart) {
 const menuItem = await MenuItems.findById(item.id);
 dbOrderItems.push({
 menuItem: item.id,
 quantity: item.quantity,
 price: menuItem.price
 });
 totalAmount += menuItem.price * item.quantity;
 }
 return { dbOrderItems, totalAmount };
 }

 async createOrderRecord(userId, dbOrderItems, totalAmount, paypalOrderId) {
 // Create order record in database
 const newOrder = new Order({
 user: userId,
 items: dbOrderItems,
 totalAmount,
 paypalOrderId,
 });
 }
}
```

```
 status: 'pending'
 });
 return await newOrder.save();
}
}

module.exports = new OrderService();
```

### 6.2.9.2 Configuration Management and Environment Handling

The system uses environment-based configuration to support multiple deployment environments (development, staging, production) without code changes.

- **Environment Variables:** Sensitive data (database credentials, API keys, JWT secrets) are stored in environment variables, loaded via `dotenv`. This approach:
  - Prevents hardcoding of secrets in source code
  - Enables different configurations per environment
  - Supports secure deployment practices
- **Configuration Modules:** Centralized configuration in modules like `config/database_queries.js` and `config/DATABASE_CONSTANTS.JS` allows for easy tuning of system parameters.

Example environment configuration:

```
// .env file structure
MONGODB_URI=example
DB_NAME=example
PORT=300 // example port

Recaptcha configuration {#recaptcha-configuration }
Client_Side_Captha=example
Server_Side_Captha=example

SENDGRID_API_KEY=SG.example.com
Email configuration {#email-configuration }
EMAIL_USER=example@example.com
EMAIL_PASS=examplePassword1;
SMTP_HOST=example
SMTP_PORT=464 // example

PAYPAL_CLIENT_ID=example
PAYPAL_CLIENT_SECRET=example

IP_HASH_SECRET=examplehash
JWT_SECRET=examplehash
JWT_EMAIL_SECRET=examplehash
JWT_LOGIN_SECRET=examplehash
SESSION_SECRET=examplehash
ARTILLERY_API_KEY=examplehash

REDIS_HOST=127.0.0.1:6379 //example

GEOIP=exampleAPI_key
```

### 6.2.9.3 Error Handling and Resilience

Comprehensive error handling ensures system stability and provides meaningful feedback to users and developers.

- **Centralized Error Handling:** Express error middleware catches and processes errors uniformly, logging details while exposing safe messages to clients.
- **Graceful Degradation:** The system continues operating even when non-critical components fail (e.g., Redis unavailability falls back to database-only operations).
- **Retry Mechanisms:** Critical operations (e.g., payment processing) include retry logic with exponential backoff.

Example error handling middleware:

```
// src/middleware/errorHandler.js
const errorHandler = (err, req, res, next) => {
 console.error('Error:', err);

 // Log security-related errors
 if (err.name === 'ValidationError' || err.name === 'CastError') {
 createSecurityLog('VALIDATION_ERROR', { error: err.message, path: req.path }, req.ip);
 }

 // Determine error response
 let statusCode = 500;
 let message = 'Internal server error';

 if (err.name === 'ValidationError') {
 statusCode = 400;
 message = 'Invalid input data';
 } else if (err.message.includes('Insufficient stock')) {
 statusCode = 409;
 message = err.message;
 }

 res.status(statusCode).json({
 error: message,
 timestamp: new Date().toISOString()
 });
};

module.exports = errorHandler;
```

#### 6.2.9.4 Logging and Monitoring

Comprehensive logging supports debugging, auditing, and monitoring system health.

- **Structured Logging:** All critical operations are logged with consistent formats, including user actions, errors, and performance metrics.

- **Security Logging:** Sensitive operations (authentication, payments) are logged to the SecurityLogs collection for audit trails.
- **Performance Monitoring:** Response times and error rates are tracked to identify bottlenecks.

Example logging in authentication:

```
// src/auth/login.js
const loginAttempt = await User.findOne({ username });
if (!loginAttempt) {
 await createSecurityLog('LOGIN_FAILED', { username, reason: 'User not found' }, clientId);
 return res.status(401).json({ error: 'Invalid credentials' });
}

// Successful login
await createSecurityLog('LOGIN_SUCCESS', { userId: loginAttempt._id, username }, clientId);
```

#### 6.2.9.5 Testing and Quality Assurance

The system includes automated testing to ensure reliability and facilitate maintenance.

- **Unit Testing:** Individual functions and modules are tested in isolation using Jest or Mocha.
- **Integration Testing:** API endpoints and database interactions are tested end-to-end.
- **Security Testing:** Automated tests validate authentication flows, input sanitization, and rate limiting.
- **Performance Testing:** Load testing with Artillery ensures the system handles expected traffic.

Example unit test (tests/auth.test.js):

```

const request = require('supertest');
const app = require('../src/main');

describe('Authentication', () => {
 test('should register a new user', async () => {
 const response = await request(app)
 .post('/register')
 .send({
 username: 'testuser',
 password: 'TestPass123!',
 email: 'test@example.com',
 'g-recaptcha-response': 'mock-captcha-token'
 });

 expect(response.status).toBe(200);
 expect(response.body.message).toContain('Registration successful');
 });
});

```

#### 6.2.9.6 Code Quality and Development Practices

Maintaining code quality ensures long-term maintainability.

- **Linting and Formatting:** ESLint and Prettier enforce consistent code style and catch potential issues.
- **Version Control:** Git is used with feature branches, pull requests, and code reviews to maintain code quality.
- **Documentation:** Inline comments, JSDoc, and this comprehensive documentation support knowledge transfer.
- **Dependency Management:** `package.json` and `package-lock.json` ensure reproducible builds and security updates.

#### 6.2.9.7 Scalability Considerations

The architecture supports horizontal scaling and performance optimization.

- **Stateless Design:** JWT-based authentication and external session storage allow for load balancing across multiple server instances.
- **Caching Strategy:** Redis caching reduces database load and improves response times.
- **Database Optimization:** Indexes, query optimization, and connection pooling support growing data volumes.
- **Microservices Readiness:** Modular design allows for future decomposition into microservices if needed.

#### 6.2.9.8 Future Extensibility

The system is designed to accommodate future enhancements:

- **Plugin Architecture:** Service modules can be extended or replaced without core changes.
- **API Versioning:** RESTful API design supports versioning for backward compatibility.
- **Feature Flags:** Configuration-driven feature toggles allow for gradual rollouts.
- **Third-Party Integrations:** Modular payment and authentication services support adding new providers.

#### 6.2.9.9 Maintenance Procedures


Regular maintenance ensures system health:

- **Dependency Updates:** Regular security audits and dependency updates using tools like `npm audit`.
- **Database Maintenance:** Index optimization, backup verification, and data archiving.
- **Performance Tuning:** Monitoring and optimizing slow queries and endpoints.
- **Security Patches:** Prompt application of security updates to dependencies and infrastructure.

This comprehensive approach to extensibility and maintainability ensures that SnapTray can evolve with the school's needs while remaining reliable, secure, and cost-effective to maintain.

---





# Router Modules and API Endpoints

---

-- Set expiration on the key (cleanup)

```
redis.call('EXPIRE', key, window)
```

```
return {1, current_count + 1} -- 1 = allowed, new count
```

- The Lua script implements a sliding window rate limiting algorithm using Redis sorted sets to track request timestamps. (The sliding window algorithm provides a more accurate rate limiting mechanism compared to fixed window algorithms by allowing requests to be counted over a rolling time frame, reducing the chances of burst traffic exceeding limits at the edges of fixed windows.) This is particularly useful for dashboard routes where users may perform multiple actions in a short period.
- The script uses Redis commands like `ZREMRANGEBYSCORE` to remove old entries, `ZCARD` to count current requests, and `ZADD` to add new request timestamps.
- It returns a status indicating whether the request is allowed or blocked, along with the current request count.
- The script is executed atomically, ensuring consistent rate limiting even under high concurrency.
- There is a line called `@diagnostic disable: undefined-global` which is used to disable warnings from code analysis tools about undefined global variables, specifically for the Redis commands used in the script. This helps to keep the code clean and focused on its functionality without being cluttered by unnecessary warnings. This does not affect the execution of the script itself nor the performance of the site.

## Router Modules and API Endpoints:

# Router Modules and API Endpoints

---

## Main Application Routes

Method	Endpoint	Description
GET	/login	Login page
GET	/register	Registration page
GET	/password-reset/:token	Password reset page
GET	/pay	Payment page
GET	/chat	Chat frontend (E2EE chat UI)

### GET /login

**Authentication:** None required (public page)

**Sample Request:** GET /login

**Sample Response:** HTML page content

**Error Codes:** None

### GET /register

**Authentication:** None required (public page)

**Sample Request:** GET /register

**Sample Response:** HTML page content

**Error Codes:** None

## GET /password-reset/:token

**Authentication:** None required (token-based access)

**Sample Request:** GET /password-reset/abc123token

**Sample Response:** HTML form for password reset

**Error Codes:** None

## GET /pay

**Authentication:** Session required

**Sample Request:** GET /pay (with valid session)

**Sample Response:** HTML payment page

**Error Codes:** 401 Unauthorized (if not logged in)

## GET /chat

**Authentication:** Session required

**Sample Request:** GET /chat (with valid session)

**Sample Response:** HTML chat interface

**Error Codes:** 401 Unauthorized (if not logged in)

# Authentication Routes

Method	Endpoint	Description
POST	/register	User registration
POST	/login	User login
POST	/logout	User logout
GET	/logout	Logout confirmation
POST	/2fa	Two-factor authentication

## POST /register

**Authentication:** None required

**Sample Request:**

```
{
 "username": "johndoe",
 "password": "SecurePass123!",
 "email": "john@example.com",
 "isParent": "false",
 "g-recaptcha-response": "recaptcha_token_here"
}
```

**Sample Response:**

```
{
 "message": "Registration successful! Check your email for verification code."
}
```

### Error Codes:

- 400 Bad Request (missing fields, invalid input, CAPTCHA failed)
- 429 Too Many Requests (rate limited)
- 500 Internal Server Error

## POST /login

**Authentication:** None required

### Sample Request:

```
{
 "username": "johndoe",
 "password": "SecurePass123!"
}
```

**Sample Response:** Welcome, johndoe (text/plain)

### Error Codes:

- 400 Bad Request (missing username/password)
- 401 Unauthorized (invalid credentials)
- 429 Too Many Requests (rate limited)
- 500 Internal Server Error

## POST /logout

**Authentication:** Session required

**Sample Request:** POST /logout (with valid session)

**Sample Response:**

```
{
 "message": "Logged out successfully"
}
```

**Error Codes:**

- 401 Unauthorized (no active session)
- 500 Internal Server Error

## GET /logout

**Authentication:** Session required

**Sample Request:** GET /logout (with valid session)

**Sample Response:** Redirect to /login

**Error Codes:**

- 401 Unauthorized (no active session)
- 500 Internal Server Error

## POST /2fa

**Authentication:** None required

**Sample Request:**

```
{
 "email": "john@example.com"
}
```

### Sample Response:

```
{
 "token": "jwt_token_here"
}
```

### Error Codes:

- 404 Not Found (user not found)
- 500 Internal Server Error

## Email Verification Routes

Method	Endpoint	Description
POST	/email-verification/verify-code	Verify email code
GET	/email-verification/verify/:token	Verify email with token

### POST /email-verification/verify-code

**Authentication:** None required

#### Sample Request:



```
{
 "email": "john@example.com",
 "code": "ABC123"
}
```

### Sample Response:

```
{
 "message": "Email verified successfully"
}
```

### Error Codes:

- 400 Bad Request (missing email/code, invalid/expired code)
- 500 Internal Server Error

## GET /email-verification/verify/:token

**Authentication:** None required

**Sample Request:** GET /email-verification/verify/jwt\_token\_here

**Sample Response:** Email verified successfully (text/plain)

### Error Codes:

- 400 Bad Request (invalid/expired token)
- 500 Internal Server Error

# Password Reset Routes

Method	Endpoint	Description
POST	/password-reset/	Request password reset
GET	/password-reset/:token	Password reset form
POST	/password-reset/:token	Submit new password
POST	/forgot-password/	Forgot password request

## POST /password-reset/

**Authentication:** None required

**Sample Request:**

```
{
 "email": "john@example.com"
}
```

**Sample Response:**

```
{
 "message": "If an account with that email exists, a password reset link has been sent"
}
```

**Error Codes:**

- 400 Bad Request (missing email)

- 500 Internal Server Error

## GET /password-reset/:token

**Authentication:** None required

**Sample Request:** GET /password-reset/jwt\_token\_here

**Sample Response:** Token is valid. You may now reset your password. (text/plain)

**Error Codes:**

- 400 Bad Request (invalid/expired token)
- 500 Internal Server Error

## POST /password-reset/:token

**Authentication:** None required

**Sample Request:**

```
{
 "newPassword": "NewSecurePass123!",
 "confirmPassword": "NewSecurePass123!"
}
```

**Sample Response:**

```
{
 "message": "Password has been reset successfully"
}
```

**Error Codes:**

- 400 Bad Request (missing fields, passwords don't match, weak password, invalid token)
- 500 Internal Server Error

## POST /forgot-password/

**Authentication:** None required

**Sample Request:**

```
{
 "email": "john@example.com"
}
```

**Sample Response:**

```
{
 "message": "If an account with that email exists, a password reset link has been sent"
}
```

**Error Codes:**

- 400 Bad Request (missing email)
- 500 Internal Server Error

## Dashboard Routes

Method	Endpoint	Description
GET	/dashboard/	Main dashboard
GET	/dashboard/admin	Admin dashboard page
GET	/dashboard/student	Student dashboard page

### GET /dashboard/

**Authentication:** Session required

**Sample Request:** GET /dashboard/ (with valid session)

**Sample Response:** HTML dashboard page

**Error Codes:** 401 Unauthorized (if not logged in)

### GET /dashboard/admin

**Authentication:** Session required (admin role)

**Sample Request:** GET /dashboard/admin (with admin session)

**Sample Response:** HTML admin dashboard page

**Error Codes:**

- 401 Unauthorized (if not logged in)
- 403 Forbidden (if not admin)

### GET /dashboard/student

**Authentication:** Session required (student/parent role)

**Sample Request:** GET /dashboard/student (with student session)

**Sample Response:** HTML student dashboard page

**Error Codes:**

- 401 Unauthorized (if not logged in)
- 403 Forbidden (if not student/parent)

# Admin Dashboard API Routes

Method	Endpoint	Description
GET	/dashboard/admin/usercount	Get user count
GET	/dashboard/admin/userlist	Get list of users
GET	/dashboard/admin/stats	Get admin statistics
GET	/dashboard/admin/signup-stats	Get signup statistics
GET	/dashboard/admin/orders	Get orders data
GET	/dashboard/admin/soldout	Get sold out items
GET	/dashboard/admin/itemcount	Get item count
GET	/dashboard/admin/menulist	Get menu items list
GET	/dashboard/admin/stockalerts	Get stock alerts
GET	/dashboard/admin/paymentstats	Get payment statistics
GET	/dashboard/admin/welcome-message	Get welcome message
GET	/dashboard/admin/health	System health check
GET	/dashboard/admin/menuitem_export	Export menu items
GET	/dashboard/admin/delete_menuitem/:id	Delete menu item
POST	/dashboard/admin/create_menuitem	Create new menu item
PUT	/dashboard/admin/menuitem/:id	Update menu item

## GET /dashboard/admin/usercount

**Authentication:** Session required (admin role)

**Sample Request:** GET /dashboard/admin/usercount

**Sample Response:**

```
{
 "total": 150
}
```

### Error Codes:

- 401 Unauthorized (if not logged in)
- 403 Forbidden (if not admin)
- 500 Internal Server Error

## GET /dashboard/admin/userlist

**Authentication:** Session required (admin role)

**Sample Request:** GET /dashboard/admin/userlist

**Sample Response:**



```
{
 "users": [
 {
 "username": "johndoe",
 "email": "john@example.com",
 "usertype": "student",
 "createdAt": "2023-01-15T10:30:00.000Z"
 }
]
}
```

### Error Codes:

- 401 Unauthorized (if not logged in)
- 403 Forbidden (if not admin)
- 500 Internal Server Error

## GET /dashboard/admin/health

**Authentication:** Session required (admin role)

**Sample Request:** GET /dashboard/admin/health

**Sample Response:**

```
{
 "overall": "ok",
 "timestamp": "2023-01-15T10:30:00.000Z",
 "services": {
 "database": "healthy",
 "redis": "healthy",
 "userModel": "healthy",
 "menuModel": "healthy",
 "orderModel": "healthy",
 "paymentModel": "healthy",
 "loyaltyModel": "healthy",
 "adminEndpoints": "healthy",
 "redisLua": "healthy",
 "sessions": "healthy",
 "caching": "healthy",
 "externalServices": {
 "paypal": "configured",
 "googlepay": "configured"
 }
 },
 "details": {
 "database": "MongoDB connection established and responding",
 "redis": "Redis connection established and responding"
 }
}
```

### Error Codes:

- 401 Unauthorized (if not logged in)
- 403 Forbidden (if not admin)
- 500 Internal Server Error

## POST /dashboard/admin/create\_menuitem

**Authentication:** Session required (admin role)

### Sample Request:

```
{
 "name": "Cheeseburger",
 "description": "Delicious cheeseburger with fries",
 "stock": 50,
 "price": 8.99,
 "category": "Main Course",
 "allergens": ["gluten", "dairy"],
 "nutritionalInfo": {
 "calories": 650,
 "protein": 25
 },
 "healthScore": 75
}
```

### Sample Response:

```
{
 "message": "Menu item created"
}
```

### Error Codes:

- 400 Bad Request (validation errors)
- 401 Unauthorized (if not logged in)
- 403 Forbidden (if not admin)

- 500 Internal Server Error

## PUT /dashboard/admin/menuitem/:id

**Authentication:** Session required (admin role)

### Sample Request:

```
{
 "name": "Cheeseburger Deluxe",
 "stock": 45,
 "price": 9.49,
 "available": true
}
```

### Sample Response:

```
{
 "message": "Menu item updated",
 "item": {
 "_id": "menu_item_id",
 "name": "Cheeseburger Deluxe",
 "stock": 45,
 "price": 9.49,
 "available": true
 }
}
```

### Error Codes:

- 401 Unauthorized (if not logged in)
- 403 Forbidden (if not admin)

- 404 Not Found (item not found)
- 500 Internal Server Error

## Student Dashboard Routes

Method	Endpoint	Description
GET	/dashboard/student/freeze_account	Freeze student account
POST	/dashboard/student/parent/link	Link parent account

### GET /dashboard/student/freeze\_account

**Authentication:** Session required (student role)

**Sample Request:** GET /dashboard/student/freeze\_account

**Sample Response:** HTML page for account freezing

**Error Codes:**

- 401 Unauthorized (if not logged in)
- 403 Forbidden (if not student)

### POST /dashboard/student/parent/link

**Authentication:** Session required (student role)

**Sample Request:**

```
{
 "parentEmail": "parent@example.com"
}
```

### Sample Response:

```
{
 "message": "Parent link request sent"
}
```

### Error Codes:

- 401 Unauthorized (if not logged in)
- 403 Forbidden (if not student)
- 400 Bad Request (invalid email)
- 500 Internal Server Error

# Order Management Routes

Method	Endpoint	Description
GET	/Order/	Order page
GET	/Order/menu_items	Get menu items for ordering
GET	/Order/:orderID	Get specific order details
POST	/Order/Order	Create new order
PUT	/Order/:orderID/status	Update order status
POST	/Order/:orderID/capture	Capture order payment

## GET /Order/

**Authentication:** Session required

**Sample Request:** GET /Order/

**Sample Response:** HTML order page

**Error Codes:** 401 Unauthorized (if not logged in)

## GET /Order/menu\_items

**Authentication:** Session required

**Sample Request:** GET /Order/menu\_items

**Sample Response:**

```
[
 {
 "_id": "item_id",
 "name": "Cheeseburger",
 "description": "Delicious cheeseburger",
 "price": 8.99,
 "available": true,
 "stock": 50
 }
]
```

### Error Codes:

- 401 Unauthorized (if not logged in)
- 500 Internal Server Error

## POST /Order/Order

**Authentication:** Session required

**Sample Request:**



```
{
 "cart": [
 {
 "id": "item_id",
 "quantity": 2,
 "price": 8.99
 }
],
 "currency": "USD",
 "amount": 17.98
}
```

**Sample Response:** PayPal order JSON (varies by PayPal API)

**Error Codes:**

- 400 Bad Request (invalid cart, insufficient stock)
- 401 Unauthorized (if not logged in)
- 500 Internal Server Error

## POST /Order/:orderID/capture

**Authentication:** Session required

**Sample Request:** POST /Order/ABC123/capture

**Sample Response:** PayPal capture JSON (varies by PayPal API)

**Error Codes:**

- 400 Bad Request (invalid order ID, already captured)
- 401 Unauthorized (if not logged in)
- 404 Not Found (order not found)

- 500 Internal Server Error

## Admin Management Routes

Method	Endpoint	Description
GET	/admin/changeuser	Change user permissions

### GET /admin/changeuser

**Authentication:** Session required (admin role)

**Sample Request:** GET /admin/changeuser

**Sample Response:** HTML page for user management

**Error Codes:**

- 401 Unauthorized (if not logged in)
  - 403 Forbidden (if not admin)
-

# API Routes

---

## General API Routes

Method	Endpoint	Description
GET	/api/test	API test endpoint
GET	/api/current_user	Get current logged-in user
GET	/api/menu-items	Get available menu items

### GET /api/test

**Authentication:** None required

**Sample Request:** GET /api/test

**Sample Response:** Test route working! (text/plain)

**Error Codes:** None

### GET /api/current\_user

**Authentication:** Session required

**Sample Request:** GET /api/current\_user

**Sample Response:**

```
{
 "loggedIn": true,
 "user": {
 "id": "user_id",
 "username": "johndoe",
 "usertype": "student",
 "email": "john@example.com"
 }
}
```

**Error Codes:** None (returns loggedIn: false if not authenticated)

## GET /api/menu-items

**Authentication:** Session required

**Sample Request:** GET /api/menu-items

**Sample Response:**

```
[
 {
 "_id": "item_id",
 "name": "Cheeseburger",
 "description": "Delicious cheeseburger",
 "price": 8.99,
 "available": true,
 "stock": 50,
 "category": "Main Course",
 "allergens": ["gluten", "dairy"]
 }
]
```

**Error Codes:**

- 401 Unauthorized (if not logged in)
- 500 Internal Server Error

## Order API Routes

Method	Endpoint	Description
POST	<code>/api/orders</code>	Create PayPal order
POST	<code>/api/orders/:orderId/capture</code>	Capture PayPal payment

### POST `/api/orders`

**Authentication:** Session required

**Sample Request:**

```
{
 "cart": [
 {
 "id": "item_id",
 "quantity": 2,
 "price": 8.99
 }
],
 "currency": "USD",
 "amount": 17.98
}
```

**Sample Response:** PayPal order JSON (includes order ID, status, links, etc.)

**Error Codes:**

- 400 Bad Request (invalid cart, insufficient stock)
- 401 Unauthorized (if not logged in)
- 500 Internal Server Error

## POST /api/orders/:orderId/capture

**Authentication:** Session required

**Sample Request:** POST /api/orders/ABC123/capture

**Sample Response:** PayPal capture JSON (includes transaction details)

**Error Codes:**

- 400 Bad Request (invalid order ID, already captured)
- 401 Unauthorized (if not logged in)
- 404 Not Found (order not found)
- 500 Internal Server Error

## Google Pay API Routes

Method	Endpoint	Description
POST	/api/orders/googlepay	Create Google Pay order
POST	/api/orders/googlepay/complete	Complete Google Pay transaction

## POST /api/orders/googlepay

**Authentication:** Session required

### Sample Request:

```
{
 "cart": [
 {
 "id": "item_id",
 "quantity": 1,
 "price": 8.99
 }
],
 "currency": "USD",
 "amount": 8.99
}
```

### Sample Response:

```
{
 "success": true,
 "orderId": "order_123",
 "totalAmount": 8.99,
 "currency": "USD"
}
```

### Error Codes:

- 400 Bad Request (invalid cart, insufficient stock)
- 401 Unauthorized (if not logged in)
- 500 Internal Server Error

## POST /api/orders/googlepay/complete

**Authentication:** Session required

### Sample Request:

```
{
 "orderId": "order_123",
 "paymentMethodData": { /* Google Pay payment data */ },
 "transactionId": "txn_456"
}
```

### Sample Response:

```
{
 "success": true,
 "orderId": "order_123",
 "transactionId": "txn_456",
 "loyaltyPointsAwarded": 8
}
```

### Error Codes:

- 400 Bad Request (invalid data)
- 401 Unauthorized (if not logged in)
- 404 Not Found (order not found)
- 500 Internal Server Error



# Payment Integration Routes

Method	Endpoint	Description
POST	/api/payments/paypal	PayPal payment processing
POST	/api/payments/googlepay	Google Pay payment processing

## POST /api/payments/paypal

**Authentication:** Session required

**Sample Request:** Similar to /api/orders (PayPal order creation)

**Sample Response:** PayPal payment JSON

**Error Codes:**

- 400 Bad Request (invalid payment data)
- 401 Unauthorized (if not logged in)
- 500 Internal Server Error

## POST /api/payments/googlepay

**Authentication:** Session required

**Sample Request:** Similar to /api/orders/googlepay/complete

**Sample Response:** Google Pay payment JSON

**Error Codes:**

- 400 Bad Request (invalid payment data)
- 401 Unauthorized (if not logged in)

- 500 Internal Server Error

---

## Chat API & WebSocket Routes

Method	Endpoint	Description
GET	/chat	Chat frontend (serves chat UI)
WS	/chat	WebSocket endpoint for real-time chat
POST	/chat/setup-e2ee	Setup E2EE public key for user
GET	/chat/public-key/:userId	Get E2EE public key for a user
POST	/chat/send-message	Send encrypted message (E2EE)
GET	/chat/messages/:otherUserId	Get messages for a conversation
GET	/chat/message/:messageId	Fetch a single message
POST	/chat/message/:messageId/replace	Mark a message as replaced (auto-resend)
PUT	/chat/messages/read/:otherUserId	Mark messages as read
GET	/chat/conversations	Get conversation list
GET	/chat/search-users	Search users for chat
GET	/chat/e2ee-status	Get E2EE status for current user
POST	/chat/reset-e2ee	Reset E2EE keys for user
POST	/chat/backup-keys	Backup encrypted private key to server
GET	/chat/has-key-backup	Check if user has a key backup
GET	/chat/restore-keys	Restore encrypted private key from server
<b>POST</b>	/chat/admin/clear-all-e2ee	<b>Admin: clear all E2EE data/messages (admin only)</b>

Method	Endpoint	Description
POST	/chat/request-sender-recovery	Mark messages as needing sender-key recovery

## GET /chat

**Authentication:** Session required

**Sample Request:** GET /chat

**Sample Response:** HTML chat interface

**Error Codes:** 401 Unauthorized (if not logged in)

## WS /chat

**Authentication:** Session required (WebSocket upgrade)

**Sample Message (send):**

```
{
 "type": "send_message",
 "to": "user_id",
 "encryptedContent": "encrypted_message_data"
}
```

**Sample Message (receive):**

```
{
 "type": "new_message",
 "from": "user_id",
 "encryptedContent": "encrypted_message_data",
 "timestamp": "2023-01-15T10:30:00.000Z"
}
```

**Error Codes:** WebSocket connection errors

## POST /chat/send-message

**Authentication:** Session required

**Sample Request:**

```
{
 "to": "recipient_user_id",
 "encryptedContent": "e2ee_encrypted_message",
 "messageType": "text"
}
```

**Sample Response:**

```
{
 "success": true,
 "messageId": "msg_123",
 "timestamp": "2023-01-15T10:30:00.000Z"
}
```

**Error Codes:**

- 400 Bad Request (invalid data)
- 401 Unauthorized (if not logged in)
- 404 Not Found (recipient not found)
- 500 Internal Server Error

## GET /chat/messages/:otherUserId

**Authentication:** Session required

**Sample Request:** GET /chat/messages/user\_456

**Sample Response:**

```
[
 {
 "id": "msg_123",
 "from": "user_123",
 "to": "user_456",
 "encryptedContent": "e2ee_data",
 "timestamp": "2023-01-15T10:30:00.000Z",
 "status": "sent"
 }
]
```

### Error Codes:

- 401 Unauthorized (if not logged in)
  - 403 Forbidden (if not authorized to view conversation)
  - 500 Internal Server Error
- | GET | /chat/pending-recovery | Get messages needing sender-key recovery |

### WebSocket events:

- `newMessage` (real-time message delivery)
- `messageReplaced` (auto-resend notification)
- `processPendingRecovery` (sender-key recovery)

**Admin-only routes are shown in red and are not accessible to normal users.**

**Notes:**

- All chat API endpoints require authentication.
- E2EE = End-to-End Encryption (all messages are encrypted client-side).
- WebSocket endpoint is used for real-time chat updates and notifications.



## 6.2.3 Database Integration and Models

---

The backend uses MongoDB as the primary database for storing user data, orders, menu items, and security logs. Mongoose is used as the ODM (Object Data Modeling) library to define schemas and interact with the database.

### User Model

---

- **username**: String, required, unique
- **password**: String, required, hashed with bcrypt (10 rounds)
- **email**: String, required, unique, validated
- **isVerified**: Boolean, default false
- **usertype**: String, enum: ['admin', 'student', 'parent', 'teacher', 'frozen', 'editor'], default: 'student'
- **createdAt**: Date, default now
- **balance**: Number, default 0
- **isBanned**: Boolean, default false
- **banReason**: String, default ""
- **userPersonalInfo**: Subdocument for personal info (firstName, lastName, etc.)
- **identity**: E2EE identity fields
- **devices**: Registered device info
- **recoveryBlob**: For encrypted recovery data

- **encryption:** Legacy E2EE fields

## Loyalty System

---

- Points are awarded per order using a random value (4-9 points per dollar spent), with bonuses for holidays and healthy choices.
- Tiers: NONE, BRONZE, SILVER, GOLD, PLATINUM (see config/DATABASE\_CONSTANTS.JS for rates and names)
- Tier bonuses and discounts are applied automatically.
- See `src/LoyaltySystem/loyalty-service.js` for calculation details.

## Admin Dashboard Features

---

- Advanced rate limiting for all admin routes (30 requests/minute, Redis Lua-based)
- User management: list, count, ban, change roles
- Menu and order management: view, update, export
- Statistics and analytics endpoints
- All endpoints are protected by admin permission middleware

## Caching Strategy

---

The backend employs Redis as an in-memory data store to cache frequently accessed data, such as menu items and user sessions. This reduces database load and improves response times for read-heavy operations. Caching is implemented in

`src/dashboard/services/cache-service.js` and used throughout the dashboard and API routes. Redis Lua scripting is used for atomic operations (rate limiting, wallet updates).

- The project uses the following redis keys as seen in: `src/cache/KeyRegistry.js`

```
const keyRegistry = {

 /*
 These are the keys that are in a MongoDB database collection (tables)
 */

 users: (userId) => [
 `user:username:${userId}`,
 `student:userinfo:${userId}`,
 'admin:usercount',
 'admin:userlist',
 'admin:activeusers',
 'admin:signup-stats',
 'admin:stats',
 'editor:usercount',
 'editor:activeusers',
],

 menuitems: (itemName) => [
 `menu_item:${itemName}`,
 'admin:menulist',
 'admin:itemcount',
 'admin:stockalerts',
 'admin:soldout',
 'admin:menuitem_export',
 'editor:menulist',
 'editor:itemcount',
],

 dailymenus: () => [
 'daily_menu:available',
 'admin:menulist',
 'editor:menulist',
],
}
```

```
orders: (orderId) => [
 `order:${orderId}`,
 'admin:orders',
 'editor:orders',
 'admin:most_bought_items_alltime',
 'admin:most_bought_items_lastweek',
 'admin:average_order_value',
],
```

```
orderitems: (userId) => [
 `student:order_history:${userId}`,
 `parent:orders:${userId}`,
],
```

```
payments: (userId) => [
 `student:transactions:${userId}`,
 `parent:transactions:${userId}`,
 'admin:paymentstats',
 'admin:revenue_lastmonth',
 'admin:total_revenue',
 'admin:stats',
],
```

```
userloyalties: (userId) => [
 `student:loyalty:${userId}`,
 `loyalty:rewards:${userId}`,
 `wallet:user:${userId}`,
 `student:wallet_balance:${userId}`,
 `student:wallet:${userId}`,
 'admin:totalpoints',
 'editor:totalpoints',
 `parent:stats:${userId}`,
],
```

```
rewards: () => [
 'admin:rewards_list',
 'admin:reward_stats',
 'editor:rewards_list',
 'editor:reward_stats',
],

redemptions: (userId) => [
 `student:loyalty:${userId}`,
 `loyalty:rewards:${userId}`,
 'admin:reward_stats',
 'editor:reward_stats',
],

parentstudents: (userId) => [
 `parent:studentlist:${userId}`,
 `parent:welcome:${userId}`,
 `parent:link-requests:${userId}`,
 `parent:stats:${userId}`,
],

prekeys: (userId) => [
 `e2ee:pubkey:${userId}`,
],

// ————— Does not fit into any collection, but still requires caching ————— //

verification: (email) => [
 `verification:${email}`,
],

loginAttempts: (ip) => [
 `login_attempts:${ip}`,
],
```

```
regAttempts: (ip) => [
 `reg_attempts:${ip}`,
],

rateLimit: (role, identifier) => [
 `ratelimit:${role}:${identifier}`,
],

chatRateLimit: (userId) => [
 `rate_limit:user:${userId}`,
],

system: () => [
 'system:health',
],

};
```

## **6.3 Frontend Implementation**

### **6.3.1 Technology Stack**

### **6.3.2 Application Architecture**

### **6.3.3 Component Structure**

### **6.3.4 State Management**

### **6.3.5 Routing and Navigation**

### **6.3.6 API Integration Layer**

### **6.3.7 UI/UX Design Implementation**

### **6.3.8 Form Handling and Validation**

### **6.3.9 Authentication Handling (Frontend)**

### **6.3.10 Performance Optimization**

### **6.3.11 Error Handling and User Feedback**

### **6.3.12 Accessibility (Optional but strong)**

### **6.3.13 Responsiveness (Mobile/Desktop)**

## **7. Testing and Validation**

---



## **8. User Manual**

---

## **9. Deployment and Maintenance**

---

## **10. Conclusion and Future Work**

---

## **11. References**

---

## **12. Appendices**

---